VerifyHub B2B KYC Platform — Completed API Report

Complete REST API Reference for Frontend Developers · Authentication, KYC Verification Engine, Wallet & Admin Suite

> **Base Headers Required for All Requests:** `Accept: application/json` | `Content-Type: application/json`
> **Protected Endpoints (Sanctum Auth):** Pass Bearer token in header: `Authorization: Bearer <token>`
> **Standard Success Response Envelope:** `{"success": true, "message": "...", "data": {...}}`

---

1. AUTHENTICATION & SESSION APIS

1. Super Admin Login

`POST` **`/api/auth/admin/login`**

Where used in Frontend: Admin Portal Login Screen (`/admin/login`)

Why used: Authenticates platform administrator, verifies admin privileges, logs security audit trail, and returns Sanctum Bearer access token.

REQUEST FORMAT:

```
{
  "email": "admin@verifyhub.in",
  "password": "password123"
}
```

RESPONSE FORMAT:

```
{
  "success": true,
  "message": "Super Admin authenticated successfully.",
  "data": {
    "token_type": "Bearer",
    "access_token": "1|adminAccessTokenExampleXYZ123456",
    "role": "admin",
    "user": {
      "id": 1,
      "name": "Super Administrator",
      "email": "admin@verifyhub.in",
      "role": "admin",
      "status": "active"
    }
  }
}
```

2. Retailer Merchant Login

`POST` **`/api/auth/retailer/login`**

Where used in Frontend: Retailer Portal Login Screen (`/retailer/login`)

Why used: Authenticates merchant using either 10-digit mobile or registered email. Returns access token, active wallet balance, and merchant profile.

REQUEST FORMAT:

```
{
  "identifier": "9876543210",
  "password": "password123"
}
```

RESPONSE FORMAT:

```
{
  "success": true,
  "message": "Retailer authenticated successfully.",
  "data": {
    "token_type": "Bearer",
    "access_token": "2|retailerTokenExampleABC987654",
    "role": "retailer",
    "user": {
      "id": "RT1001",
      "name": "Rajesh Sharma",
      "shop": "Sharma Communication",
      "email": "rajesh@sharmakyc.in",
      "mobile": "9876543210",
      "city": "Vadodara",
      "state": "Gujarat",
      "pan": "ABCDE1234F",
      "gst": "24ABCDE1234F1Z5",
      "status": "active",
      "wallet": 4850.00
    }
  }
}
```

3. Current User Profile (/me)

`GET` **`/api/auth/me`**

Where used in Frontend: App initialization / Refresh / Header user badge

Why used: Validates stored session token on page load, fetches updated role, permissions, and live wallet balance. Requires Bearer token.

REQUEST FORMAT:

```
No body
```

RESPONSE FORMAT:

```
{
  "success": true,
  "message": "User profile retrieved successfully.",
  "data": {
    "id": "RT1001",
    "name": "Rajesh Sharma",
    "shop": "Sharma Communication",
    "email": "rajesh@sharmakyc.in",
    "mobile": "9876543210",
    "role": "retailer",
    "status": "active",
    "wallet": 4850.00
  }
}
```

4. User Logout

`POST` **`/api/auth/logout`**

Where used in Frontend: Top Navbar / Sidebar "Sign Out" action

Why used: Revokes active Sanctum Bearer token and records security audit trail.

REQUEST FORMAT:

```
No body
```

RESPONSE FORMAT:

```
{
  "success": true,
  "message": "Successfully logged out.",
  "data": null
}
```

2. KYC VERIFICATION SERVICES (CORE ENGINE)

5. Execute Instant KYC Verification

`POST` **`/api/verifications/verify`**

Where used in Frontend: Retailer Portal → "New Verification" Modal / Quick Verify form

Why used: The core verification engine. Verifies citizen identity, atomically debits service charge from retailer wallet, records immutable verification record.

A. PAN CARD VERIFICATION REQUEST:

```
{
  "retailer_id": "RT1001",
  "service_type": "pan",
  "payload": {
    "pan": "ABCDE1234F",
    "name": "Priya Kapoor"
  }
}
```

PAN VERIFICATION SUCCESS RESPONSE:

```
{
  "success": true,
  "message": "Verification processed successfully.",
  "data": {
    "id": "VRF261024A1B2C",
    "retailer_id": "RT1001",
    "type": "pan",
    "doc": "ABXXXXX34F",
    "name": "Priya Kapoor",
    "status": "verified",
    "amount": 2.25,
    "response": "200 · VALID · Record found",
    "details": {
      "Holder name": "Priya Kapoor",
      "Holder category": "Individual",
      "Aadhaar seeding": "Linked",
      "Name match": "Match · 100%",
      "Source": "Income Tax Department (Sandbox)"
    },
    "channel": "Web dashboard",
    "created_at": "2026-10-24T10:15:00.000000Z"
  }
}
```

B. AADHAAR OTP VERIFICATION REQUEST:

```
{
  "retailer_id": "RT1001",
  "service_type": "aadhaar",
  "payload": {
    "aadhaar": "987654321012",
    "name": "Amit Kumar Verma",
    "gender": "Male"
  }
}
```

C. BANK ACCOUNT PENNY DROP REQUEST:

```
{
  "retailer_id": "RT1001",
  "service_type": "bank",
```

```
  "payload": {
    "account": "12345678901",
    "ifsc": "HDFC0001234",
    "name": "Rahul Choudhary"
  }
}
```

D. CONSENT LETTER WITH E-SIGN REQUEST:

```
{
  "retailer_id": "RT1001",
  "service_type": "esign",
  "payload": {
    "name": "Priya Kapoor",
    "mobile": "9876543210",
    "purpose": "KYC verification for account opening"
  }
}
```

INSUFFICIENT BALANCE ERROR RESPONSE (422 UNPROCESSABLE):

```
{
  "success": false,
  "message": "Insufficient wallet balance. Please top up your wallet to proceed."
}
```

6. Verification Records & Audit Trail

`GET` `/api/verifications/records`

Where used in Frontend: Admin Verification Audit Trail (`/admin/records`) & Retailer History (`/retailer/history`)

Why used: Returns paginated, searchable verification transactions with real-time stats (verified count, failed count, total amount deducted).

Query Parameters: page, per_page, `retailer_id`, type (pan/aadhaar/bank/esign), `status` (verified/failed), `search`, `start_date`, `end_date`

REQUEST FORMAT:

```
GET /api/verifications/records?type=pan&status=verified&per_page=10&page=1
```

RESPONSE FORMAT:


```
{
  "success": true,
  "message": "Verification records retrieved successfully.",
  "data": {
    "current_page": 1,
    "data": [
      {
        "id": "VRF261024A1B2C",
        "retailer_id": "RT1001",
        "type": "pan",
        "doc": "ABXXXXX34F",
        "name": "Priya Kapoor",
        "status": "verified",
        "amount": "2.25",
        "response": "200 · VALID · Record found",
        "channel": "Web dashboard",
        "created_at": "2026-10-24T10:15:00.000000Z",
        "retailer": {
          "id": "RT1001",
          "shop": "Sharma Communication",
          "owner": "Rajesh Sharma"
        }
      }
    ],
    "total": 142,
    "per_page": 10,
    "last_page": 15,
    "stats": {
      "total": 142,
      "verified": 136,
      "failed": 6,
      "deducted": 354.50
    }
  }
}
```


3. RETAILER PORTAL & DASHBOARD APIS

7. Retailer Dashboard Overview

`GET` **`/api/retailer/overview`**

Where used in Frontend: Retailer Home Screen (`/retailer/dashboard`)

Why used: Delivers full dashboard snapshot: available wallet float, last top-up amount, pending fund requests, verification success stats, and active rate card.

REQUEST FORMAT:

```
No body (Bearer token required)
```

RESPONSE FORMAT:


```
{
  "success": true,
  "message": "Retailer overview retrieved successfully.",
  "data": {
    "retailer": {
      "id": "RT1001",
      "shop": "Sharma Communication",
      "owner": "Rajesh Sharma",
      "email": "rajesh@sharmakyc.in",
      "mobile": "9876543210",
      "city": "Vadodara",
      "status": "active"
    },
    "wallet": {
      "balance": 4850.00,
      "last_topup_amount": 2000.00,
      "pending_request_amount": 0.00,
      "pending_request_count": 0
    },
    "kpis": {
      "total_verifications": 142,
      "verified_count": 136,
      "failed_count": 6,
      "success_rate": 95.8,
      "todays_verifications": 14,
      "todays_spent": 38.50,
      "total_spent": 354.50
    },
    "services": [
      { "id": "aadhaar", "name": "Aadhaar OTP", "price": 3.50, "status": "active" },
      { "id": "pan", "name": "PAN Verification", "price": 2.25, "status": "active" },
      { "id": "bank", "name": "Bank Penny Drop", "price": 2.50, "status": "active" },
      { "id": "esign", "name": "e-Sign Consent", "price": 6.00, "status": "active" }
    ],
    "recent_verifications": []
  }
}
```

8. Retailer Profile & Password Settings

`GET` `PUT` **`/api/retailer/profile`** | **`/api/retailer/password`**

Where used in Frontend: Retailer Profile & Account Settings (`/retailer/settings`)

Why used: Updates retailer contact information, business address, and security password.

UPDATE PROFILE REQUEST FORMAT:

```
{
  "shop": "Sharma Communication & Tech",
  "owner": "Rajesh Kumar Sharma",
  "address": "Shop 4, Station Road, Vadodara",
  "city": "Vadodara",
  "state": "Gujarat"
}
```

CHANGE PASSWORD REQUEST FORMAT:

```
{
  "current_password": "OldPassword123",
  "new_password": "NewSecretPassword456",
  "new_password_confirmation": "NewSecretPassword456"
}
```

4. WALLET & TOP-UP APIS

9. Retailer Wallet Top-Up Request

`POST` **`/api/wallet/fund-requests`**

Where used in Frontend: Retailer Wallet → "Request Wallet Top-Up" Modal

Why used: Retailer submits online transfer proof (UTR reference, payment mode, amount) after transferring money to the company bank account.

REQUEST FORMAT:

```
{
  "amount": 2500,
  "mode": "UPI",
  "utr": "UTR61024889912",
  "transfer_date": "2026-10-24",
  "remarks": "GooglePay transfer for weekend verifications"
}
```

RESPONSE FORMAT (201 CREATED):

```
{
  "success": true,
  "message": "Fund request of ₹2,500 submitted successfully.",
  "data": {
    "id": "FRQ261024K9L2P",
    "retailer_id": "RT1001",
    "amount": "2500.00",
    "mode": "UPI",
    "utr": "UTR61024889912",
    "status": "pending",
    "created_at": "2026-10-24T11:00:00.000000Z"
  }
}
```

10. Wallet Transactions (Passbook)

`GET` **`/api/wallet/transactions`**

Where used in Frontend: Retailer Wallet Passbook (`/retailer/wallet`) & Admin Ledger (`/admin/wallet`)

Why used: Comprehensive financial ledger displaying every credit (top-up) and debit (KYC verification charges) with opening and closing balances.

RESPONSE FORMAT:


```
{
  "success": true,
  "message": "Wallet transactions retrieved successfully.",
  "data": {
    "current_page": 1,
    "data": [
      {
        "id": "TXN261024001",
        "retailer_id": "RT1001",
        "type": "credit",
        "amount": "2500.00",
        "balance_before": "2350.00",
        "balance_after": "4850.00",
        "note": "Top-up approved by Super Admin",
        "ref": "FRQ261024K9L2P",
        "mode": "UPI",
        "created_at": "2026-10-24T11:05:00.000000Z"
      },
      {
        "id": "TXN261024002",
        "retailer_id": "RT1001",
        "type": "debit",
        "amount": "2.25",
        "balance_before": "4850.00",
        "balance_after": "4847.75",
        "note": "PAN verification charge",
        "ref": "VRF261024A1B2C",
        "mode": "Auto Debit",
        "created_at": "2026-10-24T11:10:00.000000Z"
      }
    ]
  }
}
```


11. Admin Approve / Reject Top-Up Request

`PUT` **`/api/admin/wallet/fund-requests/{id}/approve`** | **`/api/admin/wallet/fund-requests/{id}/reject`**

Where used in Frontend: Admin Portal → Wallet Approvals Tab (`/admin/wallet`)

Why used: Admin verifies the bank statement against the UTR. Approving automatically credits the retailer's wallet and notifies the merchant.

REJECT REQUEST FORMAT:


```
{
  "reason": "UTR number does not match bank statement"
}
```

12. Admin Manual Wallet Adjustment

`POST` **`/api/admin/wallet/adjust`**

Where used in Frontend: Admin Portal → "Manual Credit / Debit" Drawer

Why used: Direct manual correction or promotional credit to a merchant's wallet.

REQUEST FORMAT:

```
{
  "retailer_id": "RT1001",
  "type": "credit",
  "amount": 1000,
  "mode": "NEFT",
  "ref": "BANK-REF-9921",
  "note": "Promotional bonus credit"
}
```

5. SUPER ADMIN MANAGEMENT SUITE

13. Admin Dashboard Overview & Analytics

`GET` **`/api/admin/overview`**

Where used in Frontend: Admin Home Screen (`/admin/dashboard`)

Why used: Delivers platform-level KPIs: Active retailers, 30d new retailers, total verifications, success rate %, total platform revenue, total floating float, and service distribution chart data.

RESPONSE FORMAT:

```
{
  "success": true,
  "message": "Admin dashboard overview retrieved successfully.",
  "data": {
    "kpis": {
      "total_retailers": 28,
      "active_retailers": 26,
      "total_verifications": 4820,
      "success_rate": 97.4,
      "total_revenue": 14850.75,
      "total_floating_wallet": 62400.00,
      "todays_verifications": 182,
      "todays_billed": 560.25
    },
    "category_distribution": {
      "total": 4820,
      "items": [
        { "id": "aadhaar", "name": "Aadhaar OTP", "count": 2100, "percentage": 43.6, "color": "#3b82f6" },
        { "id": "pan", "name": "PAN Verification", "count": 1850, "percentage": 38.4, "color": "#10b981" },
        { "id": "bank", "name": "Bank Penny Drop", "count": 620, "percentage": 12.9, "color": "#06b6d4" },
        { "id": "esign", "name": "e-Sign Consent", "count": 250, "percentage": 5.1, "color": "#8b5cf6" }
      ]
    }
  }
}
```

14. Retailers Management (CRUD)

GET POST PUT **/api/admin/retailers** | **/api/admin/retailers/{id}/status**

Where used in Frontend: Admin Portal → Retailers List & Modal (`/admin/retailers`)

Why used: List all onboarded merchants, create new retailer account, edit retailer, or toggle status between active and inactive.

CREATE RETAILER REQUEST:

```
{
  "shop": "National Digital Services",
  "owner": "Vikram Mehta",
  "mobile": "9825012345",
  "email": "vikram@nationaldigital.in",
  "address": "101 City Center, Station Road",
  "city": "Ahmedabad",
  "state": "Gujarat",
  "pan": "ABCDE1234F",
  "gst": "24ABCDE1234F1Z5",
  "password": "SecurePassword123",
  "status": "active"
}
```

15. Pricing Switchboard & Custom Rate Cards

GET POST **/api/admin/pricing** | **/api/admin/pricing/override**

Where used in Frontend: Admin Portal → Pricing & Rates (`/admin/pricing`)

Why used: View provider cost vs. selling price margins, update default rates, and set custom rate cards per retailer.

SET CUSTOM RETAILER PRICE OVERRIDE REQUEST:

```
{
  "retailer_id": "RT1001",
  "pricing": {
    "pan": 2.00,
    "aadhaar": 3.00,
    "bank": 2.20,
    "esign": 5.50
  }
}
```

6. NOTIFICATIONS & FRONTEND INTEGRATION GUIDE

16. In-App Notifications Stream

GET PUT `/api/notifications` | `/api/notifications/{id}/read`

Where used in Frontend: Top Navbar Notification Bell Icon & Dropdown

Why used: Shows real-time alerts: pending top-up requests, low wallet balance warning (< ₹1,500), and system updates.

RESPONSE FORMAT:


```
{
  "success": true,
  "data": {
    "unread_count": 2,
    "notifications": [
      {
        "id": "NTF_FRQ_102",
        "title": "New fund request",
        "text": "Sharma Communication requested a ₹2,500 wallet top-up.",
        "type": "info",
        "read": false,
        "link": "/admin/wallet",
        "created_at": "2026-10-24T11:00:00.000000Z"
      }
    ]
  }
}
```

Frontend Setup Quick-Start (Axios / Fetch)

Setting	Value	Note
Base URL	`http://127.0.0.1:8000/api`	Configure in frontend `.env` as `VITE_API_URL`
Default Headers	`Accept: application/json` `Content-Type: application/json`	Ensures Laravel returns JSON responses on errors instead of HTML
Auth Header	`Authorization: Bearer <token>`	Add to Axios request interceptor using stored token

SAMPLE AXIOS CLIENT SETUP:

```
import axios from 'axios';

const api = axios.create({
  baseURL: import.meta.env.VITE_API_URL || 'http://127.0.0.1:8000/api',
  headers: {
    'Accept': 'application/json',
    'Content-Type': 'application/json',
  },
});

api.interceptors.request.use((config) => {
  const token = localStorage.getItem('access_token');
  if (token) {
    config.headers.Authorization = `Bearer ${token}`;
  }
  return config;
});

export default api;
```