Implementation of an Alternate Chemistry Library into OpenFOAM™

Bernhard F.W. Gschaider[1] Markus Rehm[2] Peter Seifert[2]
Bernd Meyer[2]

[1]ICE Strömungsforschung
Leoben, Austria

[2]Institute of Energy Process Enineering and Chemical Engineering,
TU Bergakademie Freiberg, Germany

Open Source CFD International Conference
4th/5th December

Outline

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

The `chemistryModel`-class

- Part of the OPENFOAM™-distribution
  - Solves a set of chemical reactions and returns a **reaction-rate**
  - Used in the solvers `dieselFoam` and `reactingFoam`
- Chemical reactions can be specified in two formats:
  - A generic OPENFOAM™-format (allows the inclusion of non-standard reaction rates)
  - The CHEMKIN™-format which is very "FORTRAN"
- Both formats are converted to the same internal representation
- ... and are solved using a number of different solvers

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Cantera

Cantera [1] is a open-source chemical kinetics package

- Very **flexible** and easy to handle
- Important functions for chemical species, (heterogeneous) kinetics, equilibrium, transport, diffusion, heat conduction are available and efficiently implemented
- Kernel written in C++; accessible via Python, Matlab, Fortran and of course C/C++
- Good Chemkin^{TM}-Lexer
- A set of ideal reactors is available
- Uses the CVODE-Solver of the Sundials Suite [2] for integration of the ODEs.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Goals of this work

As mentioned in the Milan presentation [3], CANTERA would be benefitial for the development of solvers for reacting flows:

- Flexible exchange of **chemistry engines** without the necessity to change the solver
- Easy access to **thermochemical functions**
- Better **stability** (JANAF-error)
- Stationary chemistry solver

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

The Alternate Chemistry Library

- A Library that provides a **framework** for adding **further chemistry solvers**
- Should require only **minimal changes** to existing solvers
  - Solvers should be implementation-agnostic (by using the RunTime-selection mechanism)
- This is achieved by replacing the `chemistryModel` object (usually called `chemistry`) in the solvers with a `autoPtr<alternateChemistryModel>`
  - Direct subclassing of `chemistryModel` is not possible because necessary properties are `private`
  - Usually every call `chemistry.xxxx()` is replaced by a `chemistry().xxxx()`

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Interface

- Only a **small part** of the original `chemistryModel`-interface is needed by the solvers:

  solve Solve the reaction system
  RR Access the reaction rates
  tc Access the chemical time-scale

- Only these have to be implemented by a new chemical solver class
- In addition to these the methods

  calcDQ for the calculation of `dQ`
  tf Access the flow time-scale (described later)

  were added to the interface

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

chemistryModelProxy

- Provides access to the functionality of the original `chemistryModel`-class
- Has a private `chemistryModel`-object
- Calls are passed through to the `chemistryModel`-object
  - `solve()` and `tc()`
  - `calcDQ()` implemented after example from original solvers
- With this chemistry model implementation the solver is equivalent to the original `reactingFoam`

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

The CANTERA-model

- Implements interface to the CANTERA-package
- Requires the `thermoType` to be a `hMixtureThermo<CanteraMixture>`
  - Instead of the usual `hMixtureThermo<reactingMixture>`
  - Currently required to have consistent calculations of the mixture and the chemistry
  - Calculation of thermophysical properties is done in `CanteraThermo` a wrapper to the CANTERA-class `IdealGasMix`
- Reactions are read from a `cti`-file (CANTERA Input)
  - Also the thermophysical data of the species. Thus the requirement on the `thermoType`
- Calculations in `solve()` are done via the `Reactor`/`ReactorNet`-classes of CANTERA
  - Solution of the ODEs is done via CVODE

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Class overwiew



alternateReactingFoam

Solver almost unchanged. Basis: reactingFoam. Remember the Chalmers **PaSR-Model** for turbulent combustion:

$$\kappa = \frac{dT + tc}{dT + tc + tk} \tag{1}$$

Where *tc* is the **chemical time scale** and *tk* is the **turbulent time scale**.

- Implementation of tc()-method for the CANTERA calculation necessary.
- For the CANTERA solver no ODE solver from OF necessary (choice of the ODE solver in chemistryProperties doesn't have any effect).

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

alternateSteadyReactingFoam

Steady solvers are a must when simulating **large-scale chemical reactors** or **burners**.
Necessary changes from the transient case:

- Usage of the SIMPLE-algorithm for p-U-coupling
- Coupling of chemistry to the flow-time
- **Stabilization** of the solution by reduction of κ if $|Y_i^{old} - Y_i^{new}|$ is too large (only at start-up!)

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Flow time scale

In **unsteady** calculations Co<1 and integration time equals dT.
For **steady-state** solvers Co$>>1$. So we limit the integration time by the residence time in the cell i:

$$tf_i = \frac{D_i}{U_i} \tag{2}$$

and hence we substitute dT in (1) by df:

$$\kappa = \frac{tf + tc}{tf + tc + tk} \tag{3}$$

We define the **flow time scale** tf.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

CVODE

An OF library that makes use of the CVODE-Solver of the Sundials Suite [2] was written.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Plug flow reactor (PFR) test case

Simple test case, which is easily comparable to ideal PFR models as available in CHEMKIN^{TM} or CANTERA:

- Ignitable premixed composition at inlet: $Y_{H2} = 0.009$, $Y_{O2} = 0.026$, $Y_{Ar} = 0.965$, $T = 1600$ K, $p = 1$ bar
- Tube idealized as 2D-domain $x_{max} = 1$ m, $y_{max} = 0.1$ m, 10x100 cells, inlet left patch, outlet right patch, upper and lower patch symmetry
- $H_2 - O_2$ mechanism with 9 species and 27 reactions



PFR alternateReactingFoam

For the **transient simulations** we were interested in

- Behaviour of the CANTERA chemistry library
- Choice of ODE solvers and their performance

All plots were done along the **x direction**. The ideal Solution was obtained by calculating the time into a position with U and ρ.

PFR alternateReactingFoam ODE-solvers (T)

ODESIBS: ODE SIBS; EI: Euler Implicit; CV: CVODE



PFR alternateReactingFoam ODE CPUTime



PFR alternateReactingFoam Summary

Transient PFR results:

- With implementation of CANTERA chemistry and tc() results for both chemistry engines give **identical results** for PFR.
- ODE SIBS results deviate sligtly from the others (EI, CV) (due to semi-impliciteness?)
- CVODE more stable than SIBS, EI but sometimes slower
- CVODE benefits from **larger integration steps** (internal time-stepping). $\rightarrow$ So use higher Co, if results aren't affected.
- Compared to ideal reactor solvers are 'faster' and there is a temperature difference of 5 K. Possibly induced by discretisation errors or idealisation.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

PFR alternateSteadyReactingFoam

The following aspects for the runs of the **steady-state simulations** are of particular interest:

- **A** Performance and stability of the steady-state implementation in relation to transient case and the ideal case.
- **B** Influence of the implementation of κ
- **C** Influence of Cmix

Plots are similar to the transient ones but scaling was changed.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

PFR alternateSteadyReactingFoam (T)

A Transient vs. steady



PFR alternateSteadyReactingFoam (H2)

A Transient vs. steady



PFR alternateSteadyReactingFoam (T)

B Influence of κ



PFR alternateSteadyReactingFoam (H2)

B Influence of κ



PFR alternateSteadyReactingFoam (T)

C Influence of Cmix



PFR alternateSteadyReactingFoam (H2)

C Influence of Cmix



PFR alternateSteadyReactingFoam (OH)

C Influence of Cmix



PFR Steady Summary

A:

- Transient/Steady solutions do **not agree totally** but **refinement reduces deviation**

B+C:

- Definition of new κ according to (3) brings no changes for small values of Cmix. But for Cmix=1 the solution seems closer to ideal solution.
- However, no clear conclusion could be drawn.

Sydney Bluff-body Flame (HM1)



Data from Sandia bluff-body flame HM1 conducted at Sydney university [4].

HM1 case set-up



HM1 set-up

Boundary Conditions:

- Diameters: $D_{jet} = 3.6$mm; $D_{channel} = 150$mm (300mm), $D_{bluffbody} = 50$mm
- Turbulence:8.5 % (2.5%) turbulence intensity , 0.135 mm (5.625 mm) mixing length for jet (co-flow)
- Mesh: from blockMesh with 1095

Inlet conditions:

- HM1: $U_{jet} = 118$m/s $U_{coflow} = 40$m/s

Other models:

- $k - \epsilon$ turbulence model, ATRMech (reduced GRI 3.0)
- OF used KRR4 ODE solver for chemistry

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

HM1 Plots & Points of Measurement

- Plots of **radius** against measurement **values** (**Exp HM1**) at different **x-positions** are shown together with simulation results.
- **EDC** referes to the EDCSimpleFoam solver [3].
- **CAN** and **OF** mark CANTERA- and OPENFOAM™-solution
- **K1** and **K2** stands for κ_1 and κ_2

HM1 Plots & Points of Measurement



HM1 results T



HM1 results H2



HM1 results H2O



HM1 results CO



HM1 results CO2



HM1 results OH



Discussion HM1

Why are all the resuls **so similar**? (No influence of κ-implementation or Cmix (not shown))

- In case Cmix=0.005 no difference in κ notable - too fast mixing as in PFR case.
- Furthermore, in the domain **close to the inlets** $\kappa \approx 1$ in every case and influence of Cmix can only be seen **further downstream** where no measurements are available.
- Comparison with **transient simulation** of HM1 indicates that κ_2 seems more appropriate (see next slide)
- Still, further testing is needed

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

HM1 comparison κ_1, κ_2 for Cmix=1



Conclusion HM1

- Flame was rendered with **acceptable quality** by the new solvers
- Steady solvers are **very robust** if the right ODE solvers are used (CVODE for CANTERA, KRR4 for OF)
- Checking of dY_i provides further stability and and prevents composition from being driven to unphysical states.
- Solutions for a finer grid (20000 cells) are still not available - flame **blows off** very easily.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Summary

The implementation of the CANTERA chemistry into OPENFOAM™ can be considered successful and provides:

- A **flexible interface** to access a wide range of thermophysical data,and chemistry functions
- Robust **solvers** for transient and steady-state calculations
- Valuable **test-cases** for validation and further investigation
- **Collaborators** are welcome to test the code and contribute own developments.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

How to get the library

- The libraries and solvers presented here will be made available on the openfoam-extend-SVN on sourceforge.net
  - **Libraries** Two independent libraries:
    - **alternateChemistryModel** The general framework an the OpenFOAM™-interface
    - **canteraChemistryModel** The interface to Cantera
  - **Solvers** The steady and the transient solver with the test-cases PFR and HM1
- URL will be given on the Wiki
- Interfaces to other **chemistry libraries**, more **solvers**, critique, and improvements are encouraged

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Future Work

There is always room for improvement:

- Both chemistry solvers read the same input files
  - Converter between CANTERA and OPENFOAM™-format
- Make the CANTERACHEMISTRYMODEL indepentent of `canteraMixture`
- Implementation of reduction/tabulation techniques for more time-efficient solution.
- More combustion models.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Acknowledgements

A part of the development and implementation work was done by the IEC in the context of the research project "Grosstechnisch bertragbare Untersuchungen zur Weiterentwicklung der IGCC-Kohlekraftwerkstechnik mit CO2-Abtrennung - **COORAMENT**". This project is supported by the **German Federal Ministry of Economics and Technology** (Project ID 0327113B).
Furthermore we thank N. Nordin for a valuable posting regarding the tc()- implementation, all developers who contributed to OpenFOAM™, and people who inspired that work.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering

Bibliography

[1] DG Goodwin. Cantera: Object-oriented software for reacting flows. Technical report, California Institute of Technology, 2002.

[2] A.C. Hindmarsh, P.N. Brown, K.E. Grant, S.L. Lee, R. Serban, D.E. Shumaker, and C.S. Woodward. SUNDIALS: Suite of nonlinear and differential/algebraic equation solvers. *ACM Transactions on Mathematical Software (TOMS)*, 31(3):363–396, 2005.

[3] M. Rehm, P. Seifert, and B. Meyer. Towards a CFD Model for Industrial Scale Gasification Processes. In *OpenFOAM Workshop 2008, Milan*, 2008.

[4] BB Dally, AR Masri, RS Barlow, and GJ Fiechtner. Instantaneous and Mean Compositional Structure of Bluff-Body Stabilized Nonpremixed Flames. *Combustion and Flame*, 114(1-2):119–148, 1998.

Strömungsforschung GmbH
ICE
Innovative Computational Engineering