Drilling Mechanics - APWD Time Based

Real Time, Recorded Mode, Composite

Schlumberger

Company:	Equinor
Well:	31/5-7
Field:	Eos
Rig Name:	West Hercules
Country:	Norway

Latitude:	60° 34' 35.14" N	UWID:	
Longitude:	3° 26' 36.13" E	Rig Name:	West Hercules
Block:	31/5	Rig Type:	Semi-Submersible

FL: Norwegian North Sea
FL1: Section: 8 1/2 in.
FL2: Job no.: 19SCA0085

Log Measured From: - Drill Floor: 31.00 m
Permanent Datum: - Mean Sea Level
Ground Level: 307.00 m

Acquisition Dates:	29-Dec-2019 -- 15-Jan-2020
Log Interval:	12/29/2019 8:00:00 AM -- 1/15/2020 4:00:00 AM
Index Types:	Time
Index Scales:	5 cm / 3600 secs
Depth Source:	Driller's Depth
Depth Sensor:	3rd Party Depth
Print Type:	Final
Spud Date:	02-Dec-2019

Other Services:
Direction & Inclination (Surveys)
Directional Drilling
geoVISION Bit Resistivity
VISION Resistivity

Disclaimer

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents

1. Header
2. Disclaimer
3. Contents
4. Well Sketch
5. Borehole Size/Casing/Tubing Record
6. Operational Run Summary
7. Borehole Fluids
8. Remarks and Equipment Summary
9. Run 9 Drilling Mechanics - APWD - Time Based
   9.1 Integration Summary
   9.2 Composite Summary
   9.3 Log (Drilling Mechanics Light)
10. Run 10 Drilling Mechanics - APWD - Time Based
   10.1 Integration Summary
   10.2 Composite Summary
   10.3 Log (Drilling Mechanics Light)
11. Run 12 Drilling Mechanics - APWD - Time Based
13. Tail

11.1 Integration Summary
11.2 Composite Summary
11.3 Log (Drilling Mechanics Light)
12. Run 13 Drilling Mechanics - APWD - Time Based
12.1 Integration Summary
12.2 Composite Summary
12.3 Log (Drilling Mechanics Light)

Well Sketch





Borehole Size/Casing Record

Bit						
Bit Size (in)	36	26	17.5	12.25	8.5	
Top Driller (m)	338	441.5	931	1904	2584	
Bottom Driller (m)	441.5	931	1904	2584	2915	
Casing						
Size (in)	30	20	13.625	9.625		
Weight (lbm/ft)	457	133	88.2	53.5		
Inner Diameter (in)	27.067	18.73	12.375	8.535		
Grade	X56	N80	P110	P110		
Top Driller (m)	335.1	334.1	335.3	1840.4		
Bottom Driller (m)	406.6	925.1	1896.7	2583		

Operational Run Summary

Parameter (unit)	Run 9	Run 10	Run 12	Run 13		
Date Log Started	29-Dec-2019	31-Dec-2019	07-Jan-2020	13-Jan-2020		
Time Log Started	05:27:58	17:32:56	05:04:30	19:44:45		
Date Log Finished	30-Dec-2019	01-Jan-2020	07-Jan-2020	15-Jan-2020		
Time Log Finished	06:36:04	07:38:34	18:44:39	10:55:23		
Bit Size (in)	8.500	8.500	8.500	8.500		
Bit Start Depth (m)	2584.00	2596.00	2697.00	2784.00		
Bit Stop Depth (m)	2592.00	2643.00	2710.00	2915.00		
Top Log Interval (m)	2584.70	2585.90	2630.90	2699.00		
Bottom Log Interval (m)	2591.22	2642.28	2709.03	2914.28		
Max Hole Deviation (deg)	1.10	1.12	1.12	1.12		
Azimuth of Max Deviation (deg)	133.27	120.28	120.28	120.28		
Logging Unit Number	A615	A615	A615	A615		
Logging Unit Location	Service Office	Service Office	Service Office	Service Office		
Recorded By	S.Kroevel	M.Martter	M.Martter	M.Bergenkull		
Witnessed By	J.Eikenes	J.Eikenes	R.Nordstokke	R.Nordstokke		
Service Order Number	19SCA0085	19SCA0085	19SCA0085	19SCA0085		

Borehole Fluids

Parameter(unit)	Run 9	Run 10	Run 12	Run 13		
Fluid Type	Water	Water	Water	Water		
Fluid Name	Glydril	Glydril	Glydril	Glydril		
Max Recorded Temperatures (degC)	38	43	44	51		
Source of Sample	Active Tank	Active Tank	Active Tank	Active Tank		
Salinity (ppm)	93984	93984	97140	79402		
Density (g/cm3)	1.15	1.15	1.15	1.15		
Funnel Viscosity (s)						
Fluid Loss (cm3)						
PH						
Source RMF						
RMC	Pressed	Pressed	Pressed	Pressed		
RM @ Meas Temp (ohm.m@degC)	0.07 @ 18	0.07 @ 15	0.08 @ 14.8	0.09 @ 18.9		
RMF @ Meas Temp (ohm.m@degC)	0.06 @ 18	0.06 @ 20	0.07 @ 14.8	0.07 @ 17.9		
RMC @ Meas Temp (ohm.m@degC)	0.1 @ 20	0.09 @ 15	0.09 @ 20	0.1 @ 20		
RM @ BHT (ohm.m@degC)	0.05 @ 38	0.04 @ 43	0.04 @ 44	0.05 @ 51		
RMF @ BHT (ohm.m@degC)	0.04 @ 38	0.04 @ 43	0.04 @ 44	0.04 @ 51		
RMC @ BHT (ohm.m@degC)	0.07 @ 38	0.05 @ 43	0.06 @ 44	0.06 @ 51		
Total Solid (%)						
High Gravity Solids (%)						

Remarks and Equipment Summary

All depths referenced to driller's depth. See EOWR for depth tracking details.

APWD data from tool memory. All other data is Real Time.

Gamma Ray measurement is environmentally corrected for mud weight, bit size, collar thickness and Potassium content.

Run 9: Remarks	Run 10: Remarks	Run 12: Remarks
Run 9 POOH at 2592 m to perform coring.	Data acquired while reaming down over cored interval from 2592 to 2596 m bit depth.	Data acquired while reaming down over cored interval from 2643 to 2697 m bit depth.
	Run 10 POOH at 2643 m to perform coring.	Run 12 POOH at 2710 m to perform coring.

Run 9: Toolstring



Run 10: Toolstring



Run 12: Toolstring





ROP 11.76

ARC6:H0143-1 **9.88**
ARDC:H0143-1
Upper Extender:07/
018
CDJA
AREA:618
APWD:283006
ARSS:915804-2
Lower Extender:14
/045

arcVISION

ROP 7.58
GR 6.51
Resistivity 6.46
Pressure 5.75

RAB6:42913 **4.08**
RBDC:42913
Buttons:022
Stabilizer:81110D
Upper Extender:285
3
RBBC
RBEC:216
Lower Extender

geoVISION

Buttons 2.3
Ring 2.13
ROP 1.99
Bit Res, WBM 0.63
Bit Res, OBM 0.00
GR 1.77

Bit: 8 1/2":RH57
84 **0.24**

Smith Milltooth XR+

TOOL_ZERO

Lengths are in m
Maximum Outer Diameter = 8.500 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO



ROP 11.79

ARC6:H0143-1 **9.91**
ARDC:H0143-1
Upper Extender:07/01
8
CDJA
AREA:618
APWD:283006
ARSS:915804-2
Lower Extender:14/04
5

arcVISION

ROP 7.61
GR 6.54
Resistivity 6.49
Pressure 5.78

RAB6:42913 **4.11**
RBDC:42913
Buttons:022
Stabilizer:81110D
Upper Extender:2853
RBBC
RBEC:216
Lower Extender

geoVISION

Buttons 2.33
Ring 2.16
ROP 2.02
Bit Res, WBM 0.64
Bit Res, OBM 0.00
GR 1.8

Bit: 8 1/2":NE0217 **0.27**

Smith PDC XZ616

TOOL_ZERO

Lengths are in m
Maximum Outer Diameter = 8.500 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO



ROP 11.79

ARC6:H0143-1 **9.91**
ARDC:H0143-1
Upper Extender:07/01
8
CDJA
AREA:618
APWD:283006
ARSS:915804-2
Lower Extender:14/04
5

arcVISION

ROP 7.61
GR 6.54
Resistivity 6.49
Pressure 5.78

RAB6:42913 **4.11**
RBDC:42913
Buttons:022
Stabilizer:81110D
Upper Extender:2853
RBBC
RBEC:216
Lower Extender

geoVISION

Buttons 2.33
Ring 2.16
ROP 2.02
Bit Res, WBM 0.64
Bit Res, OBM 0.00
GR 1.8

Bit: 8 1/2":NE0217 **0.27**

Smith PDC XZ616

TOOL_ZERO

Lengths are in m
Maximum Outer Diameter = 8.500 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO

Run 13: Remarks
Data acquired while reaming down over cored interval from 2710 to 2784 m bit depth.
Run 13, 8 1/2 in. section and well TD at 2915 m.

Run 13: Toolstring

Equip name **Length** **MP name** **Offset**

TELE675:E4388 **18.37** TeleScope
MSSU675:30848
Upper Extender
MDC675:E4388
MMA:2507
MDI:3666
PMVC:236
PMEA:803
MTA:2162
MTK675:004
MSSD675:1005482-1
Lower Extender, Long





Lengths are in m
Maximum Outer Diameter = 8.500 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO

Run 9

Drilling Mechanics - APWD - Time Based

Pass Summary

Run Name	Pass Objective	Direction	Start	Stop	Include Parallel Data

Run 9	TimeLogicalAcq	Down	29-Dec-2019 5:27:58 AM	30-Dec-2019 6:36:04 AM	Yes

Log

Company:Equinor Well:31/5-7

Run 9: TimeLogicalAcq:S054

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:32

Gamma Ray (GR_ARC_RT) ARC6 RT — 0 gAPI 150

Height of block above rig floor (BPOS) RT — 0 m 45

Stick Slip Indicator (STICK_RT) TELE675 RT — 0 c/min 500

Collar Rotational Speed (CRPM_RT) TELE675 RT — 0 c/min 250

Depth Index (DEPTH) RT — m

Shock Risk (SHKRSK_RT) TELE675 RT — 5 0

Shock Peak (SHKPK_RT) TELE675 RT — 0 gn 250

Equivalent Circulating Density (ECD_ARC) ARC6 RM — 1 g/cm3 2

Downhole Annulus Temperature (ATMP) ARC6 RM — 0 degC 200

Downhole Annulus Pressure (APRS_ARC) ARC6 RM — 0 bar 1000





Dec,29
12:00
2553.16
2553.21
2553.61
2553.52
2553.62
12:30:00
2553.81
2553.35
2554.40
2554.64
2555.80
13:00:00
2559.34
2561.13
2559.12
2557.62
2555.22
13:30:00
2552.25
2556.48
2556.25
2558.79
2554.66
14:00:00
2552.32
2554.16
2558.53
2562.02
2563.75
14:30:00
2567.83
2570.02
2572.05
2574.17
2576.49
15:00:00
2580.47
2582.24
Start Drilling
2583.45
15:30:00
2584.65
2584.96
2574.43
2570.33
2580.72
16:00:00
2574.19
2583.75
2585.68
2582.65
2585.94
16:30:00
2586.70
2583.14
2578.54
2577.00
2574.61
17:00:00
APRS_ARC
2574.24
2577.76
ATMP
2582.13
2578.29



ECD_ARC
BPOS
17:30:00
2571.92
2571.92
2575.02
2569.41
Dec,29
18:00
2569.51
2569.33
2569.14
2569.23
2569.23
18:30:00
2569.88
2569.42
2569.23
2569.79
2569.33
19:00:00
2569.23
2569.61
2569.61
2569.33
2569.42
19:30:00
2569.70
2569.42
2569.61
2569.42
2569.61
20:00:00
2569.79
2569.14
2569.23
2569.42
2569.33
20:30:00
2569.79
2569.61
2569.14
2569.79
2569.42
21:00:00
2569.50
2569.41
2568.74
2568.74
2568.74
21:30:00
2586.68
2587.16
2587.70
2588.20
2588.97
22:00:00
2590.98
2591.96
Stop Drilling
2586.76
22:30:00
2581.68
2578.91
2576.33
2573.75
2571.18
23:00:00



Gamma Ray (GR_ARC_RT) ARC6 RT
0 gAPI 150

Height of block above rig floor (BPOS) RT
0 m 45

Stick Slip Indicator (STICK_RT) TELE675 RT
0 c/min 500

Collar Rotational Speed (CRPM_RT) TELE675 RT
0 c/min 250

Depth Index (DEPTH) RT
m

Shock Risk (SHKRSK_RT) TELE675 RT
5 0

Shock Peak (SHKPK_RT) TELE675 RT
0 gn 250

Equivalent Circulating Density (ECD_ARC) ARC6 RM
1 g/cm3 2

Downhole Annulus Temperature (ATMP) ARC6 RM
0 degC 200

Downhole Annulus Pressure (APRS_ARC) ARC6 RM
0 bar 1000

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:32

Run 10

Drilling Mechanics - APWD - Time Based

Pass Summary

Run Name	Pass Objective	Direction	Start	Stop	Include Parallel Data
Run 10	TimeLogicalAcq	Down	31-Dec-2019 5:32:56 PM	01-Jan-2020 7:38:34 AM	Yes

Log

Company:Equinor Well:31/5-7

Run 10: TimeLogicalAcq:S054

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:34

Track	Curve	Scale left	Unit	Scale right
1	Gamma Ray (GR_ARC_RT) ARC6 RT	0	gAPI	150
1	Height of block above rig floor (BPOS) RT	0	m	45
2	Stick Slip Indicator (STICK_RT) TELE675 RT	0	c/min	500
2	Collar Rotational Speed (CRPM_RT) TELE675 RT	0	c/min	250
Depth	Depth Index (DEPTH) RT		m	
Depth	Shock Risk (SHKRSK_RT) TELE675 RT	5		0
Depth	Shock Peak (SHKPK_RT) TELE675 RT	0	gn	250
3	Equivalent Circulating Density (ECD_ARC) ARC6 RM	1	g/cm3	2
3	Downhole Annulus Temperature (ATMP) ARC6 RM	0	degC	200
3	Downhole Annulus Pressure (APRS_ARC) ARC6 RM	0	bar	1000




22:00:00
2611.33
2613.44
2615.36
2617.25
2619.37
22:30:00
2622.08
2623.16
2624.19
2625.04
2626.52
23:00:00
2628.19
2629.11
2631.16
2632.94
2635.24
23:30:00
2636.13
2639.32
2637.74
2636.35
Jan, 01
00:00
2641.74
Stop Drilling
2635.84
2635.84
2630.94
00:30:00
2625.38
2622.61
2619.82
2617.05
2614.28
01:00:00
2608.73
2605.96
2603.19
2600.43
2601.28
01:30:00
2608.02
2611.60
2615.17
2619.61
2635.53
02:00:00
2639.85
2639.74
2639.74
2639.74
2639.74
02:30:00
2639.74
2635.10
2595.87
2595.96
2556.69
03:00:00
2556.24
2556.27
2556.33
2556.33
2517.75
03:30:00



Gamma Ray (GR_ARC_RT) ARC6 RT
0 gAPI 150

Height of block above rig floor (BPOS) RT
0 m 45

Stick Slip Indicator (STICK_RT) TELE675 RT
0 c/min 500

Collar Rotational Speed (CRPM_RT) TELE675 RT
0 c/min 250

Depth Index (DEPTH) RT
m

Shock Risk (SHKRSK_RT) TELE675 RT
5 0

Shock Peak (SHKPK_RT) TELE675 RT
0 gn 250

Equivalent Circulating Density (ECD_ARC) ARC6 RM
1 g/cm3 2

Downhole Annulus Temperature (ATMP) ARC6 RM
0 degC 200

Downhole Annulus Pressure (APRS_ARC) ARC6 RM
0 bar 1000

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:34

Run 12

Drilling Mechanics - APWD - Time Based

Pass Summary

Run Name	Pass Objective	Direction	Start	Stop	Include Parallel Data
Run 12	TimeLogicalAcq	Down	07-Jan-2020 5:04:30 AM	07-Jan-2020 6:44:39 PM	Yes

Log

Company:Equinor Well:31/5-7

Run 12: TimeLogicalAcq:S054

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:36

Depth Index (DEPTH) RT
m

Shock Risk (SHKRSK_RT) TELE675 RT
5 0

Gamma Ray (GR_ARC_RT) ARC6 RT
0 gAPI 150

Stick Slip Indicator (STICK_RT) TELE675 RT
0 c/min 500

Equivalent Circulating Density (ECD_ARC) ARC6 RM
1 g/cm3 2

Height of block above rig floor (BPOS) RT
0 m 45

Collar Rotational Speed (CRPM_RT) TELE675 RT
0 c/min 250

Shock Peak (SHKPK_RT) TELE675 RT
0 gn 250

Downhole Annulus Temperature (ATMP) ARC6 RM
0 degC 200

Downhole Annulus Pressure (APRS_ARC) ARC6 RM
0 bar 1000


714.12
791.32
906.61
984.07
1022.53
Jan, 07
06:00
1253.54
1290.10
1290.12
1290.12
1292.07
06:30:00
1369.30
1446.45
1522.68
1600.51
1677.63
1754.18
07:00:00
1836.67
1908.55
2024.93
2115.74
2210.00
2305.19
07:30:00
2402.51
2489.06
2581.09
2633.31
2633.31
2633.31
08:00:00
2633.31
2634.58
2637.61
2637.61
2637.61
2638.53
08:30:00
2642.55
2645.76
2649.51
2653.93
2657.91
2662.14
09:00:00
2666.21
2670.62
2673.14
2675.88
2675.94
2675.54
09:30:00
2674.91
2675.28
2679.71
2683.77
2687.65
Start Drilling
10:00:00
2695.14
2697.26
2698.63
2699.59
2701.61
2702.81
10:30:00
2704.27
2706.28
2708.73
2708.70
2707.97
Stop Drilling
11:00:00
2706.45



2707.76
2708.26
2708.45
2689.46
2674.28
11:30:00
2674.28
2654.46
2635.22
2634.81
2618.64
Jan,07
12:00
2590.40
2576.77
2572.45
2572.39
2566.68
12:30:00
2564.59
2564.02
2564.02
2564.02
2564.02
2564.02
13:00:00
2564.02
2563.75
2556.89
2556.89
2556.89
2556.89
13:30:00
2556.89
2556.48
2556.48
2556.48
2556.48
2556.48
14:00:00
2556.35
2556.35
2526.43
2499.24
2473.43
2435.70
14:30:00
2396.73
2360.59
2307.48
2259.07
2206.73
2165.46
15:00:00
2114.25
2048.36
1970.24
1931.26
1853.22
1759.66
15:30:00
1658.07
1580.37
1464.46
1385.58
1307.57
1229.99
16:00:00
1113.93
1036.43
923.51
841.71
753.97
647.85
Gamma Ray
(GR_ARC_RT) ARC6
Stick Slip Indicator
(STICK_RT) TELE675
Depth Index
(DEPTH) RT
Equivalent Circulating Density (ECD_ARC) ARC6 RM

(GR_ARC_RT) ARC6 RT | (STICK_RT) TELE675 RT | (DEPTH) RT m | 1 g/cm3 2
0 gAPI 150 | 0 c/min 500 | | Downhole Annulus Temperature (ATMP) ARC6 RM 0 degC 200

Height of block above rig floor (BPOS) RT 0 m 45

Collar Rotational Speed (CRPM_RT) TELE675 RT 0 c/min 250

Shock Risk (SHKRSK_RT) TELE675 RT 5 0

Shock Peak (SHKPK_RT) TELE675 RT 0 gn 250

Downhole Annulus Pressure (APRS_ARC) ARC6 RM 0 bar 1000

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:36

Run 13

Drilling Mechanics - APWD - Time Based

Pass Summary

Run Name	Pass Objective	Direction	Start	Stop	Include Parallel Data
Run 13	TimeLogicalAcq	Down	13-Jan-2020 7:44:45 PM	15-Jan-2020 10:55:23 AM	Yes

Log

Company:Equinor Well:31/5-7

Run 13: TimeLogicalAcq:S054

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:38

Gamma Ray (GR_ARC_RT) ARC6 RT 0 gAPI 150

Height of block above rig floor (BPOS) RT 0 m 45

Stick Slip Indicator (STICK_RT) TELE675 RT 0 c/min 500

Collar Rotational Speed (CRPM_RT) TELE675 RT 0 c/min 250

Depth Index (DEPTH) RT m

Shock Risk (SHKRSK_RT) TELE675 RT 5 0

Shock Peak (SHKPK_RT) TELE675 RT 0 gn 250

Equivalent Circulating Density (ECD_ARC) ARC6 RM 1 g/cm3 2

Downhole Annulus Temperature (ATMP) ARC6 RM 0 degC 200

Downhole Annulus Pressure (APRS_ARC) ARC6 RM 0 bar 1000





1986.85
2092.47
2169.79
2208.61
Jan, 14
12:00
2478.27
2555.68
2568.60
2569.78
2580.11
12:30:00
2605.24
2621.39
2684.51
2684.51
2684.51
2706.10
13:00:00
2705.84
2713.22
2713.23
2713.23
2712.61
2716.28
13:30:00
2721.98
2726.69
2731.68
2736.21
2741.37
2745.99
14:00:00
2751.34
2753.94
2751.72
2751.91
2756.92
2761.18
14:30:00
2766.33
2771.41
2776.21
2780.20
2782.86
15:00:00
2784.42
2792.23
2790.03
2791.75
15:30:00
2794.19
2796.96
2799.10
2802.83
2805.58
2808.08
16:00:00
2810.89
2813.44
2816.97
2818.31
2822.31
2824.75
16:30:00
2828.62
2830.48
2828.47
2828.15
2831.10
2832.88
17:00:00
2834.53
2837.77
APRS_ARC
ATMP
CD_ARC
BPOS
CRPM_RT
SHKPK_RT
GR_ARC_RT
STICK_RT
Start Drilling
SHKRSK_RT


2841.08
2844.97
2847.09
2847.55
17:30:00
2842.35
2846.01
2848.72
2849.28
2852.70
Jan, 14
18:00
2859.35
2860.79
2862.73
2866.33
2861.93
18:30:00
2862.66
2862.30
2862.84
2865.76
2868.98
2866.72
19:00:00
2868.88
2870.27
2872.43
2874.12
2876.11
2878.41
19:30:00
2881.56
2883.19
2886.26
2888.78
2891.17
2893.65
20:00:00
2896.36
2897.76
2901.17
2904.15
2905.93
2905.51
20:30:00
2907.10
Stop Drilling
2915.59
2913.04
2913.04
21:00:00
2913.07
2912.89
2912.71
2908.09
2905.11
2904.81
21:30:00
2902.38
2890.96
2889.02
2888.93
2886.97
2878.25
22:00:00
2889.13
2890.55
2876.92
2888.95
2889.32
2878.73
22:30:00
2868.44
2874.76
2884.55



Gamma Ray (GR_ARC_RT) ARC6 RT	Stick Slip Indicator (STICK_RT) TELE675 RT	Depth Index (DEPTH) RT m	Equivalent Circulating Density (ECD_ARC) ARC6 RM 1 g/cm3 2 Downhole Annulus Temperature (ATMP) ARC6 RM

0 gAPI 150	0 c/min 500	Shock Risk (SHKRSK_RT) TELE675 RT 5 0	Downhole Annulus Temperature (ATMP) ARC6 RM 0 degC 200
Height of block above rig floor (BPOS) RT 0 m 45	Collar Rotational Speed (CRPM_RT) TELE675 RT 0 c/min 250	Shock Peak (SHKPK_RT) TELE675 RT 0 gn 250	Downhole Annulus Pressure (APRS_ARC) ARC6 RM 0 bar 1000

Description: Format: Log (Drilling Mechanics Light) Index Scale: 5 cm per 3600 s Index Type: Time Creation Date: 21-Jan-2020 12:50:38

Company:	Equinor
Well:	31/5-7
Field:	Eos
Rig Name:	West Hercules
Country:	Norway

Schlumberger

Drilling Mechanics - APWD

Time Based

Real Time, Recorded Mode, Composite