



KSI Geo-Pressure Daily Evaluation Report Bilabri DX1 Prospect

Peak Equator Wellsite Geo-Pressure Report – Job # 1050402(W)

Date: Saturday, January 20

Time: 06:00

KSI Geopressure Analyst:

Chris H. Fletcher

Last shoe depth:

2770m MD (2630m TVD)

Current MD(TVD):

3203m MD (2976m TVD)

Current Pore Pressure:

12.5 ppg

Max Pore Pressure in OPEN HOLE:

12.5 ppg

Current Fracture Gradient:

15.8 ppg

LOT:

14.8 ppg

Mud Weight in:

12.9 ppg

ECD

no data

06:00 Depth/PP

3203m (2976m TVD)/12.0ppg

Midnight depth/PP

3203m (2976m TVD)/10.9ppg

6 hr footage drilled

no footage drilled

Pore Pressure change

no footage drilled

Analyst Confidence Level: **90%** based on all observations

LWD Sensor Offsets From Bit (m) Res: 5.48m, D&I: 10.60m, Gamma: 5.09m, PWD: 13.06, Sonic: N/A, Density: 10.96m, Neutron: 17.11m

Cutting Morphology: mostly PDC common, approximately ½ to ¾ inch long, abundant 1 inch. Abundant platy mfrn elliptical plates. First occurrence of moderately firm shale.

Caving Morphology: platy moderately firm elliptical shale plates. First occurrence of moderately firm shale.

Hole Fill/ Tight Hole: none

Previous Rig Activity (last – 24hrs): Well control procedures.

Current Rig Activity: Waiting on mud.

Rig plan activity (ahead - 24hrs): Take on barite and drill to casing liner point.

PP monitoring

Pore pressure is assessed at 12.5ppg at 3203m MD (2976m TVD.) All functions within specification

Drilling / LWD Performance:

Logging GR, Res, Den, Nphi and ECD with Autotrak.

Additional note/Comments:

Pore pressure increased 1.5ppg in the last 100m vertical of the hole section to 12.5ppg.

ALERT

Pore pressure has increased to 12.5ppg, and is on an increasing trend. MW is 12.9ppg. I anticipate a pore pressure increase of 1.2ppg, to 13.7ppg, over the next 60m measured (50m vertical) drilled. Because there may be gas in the sand we are currently drilling, the pressure in the sand will be more a function of the pressure at the water contact below the gas than the pore pressure of the shale above. Anticipating the pore pressure below this sand member, the recommended safe drilling mud density for this sand member is 13.1ppg.

