



**BAKER  
HUGHES**

|                                            |         |                                  |                                         |           |                |                                    |                       |         |                                  |                           |  |                   |           |                    |                          |              |                     |               |  |
|--------------------------------------------|---------|----------------------------------|-----------------------------------------|-----------|----------------|------------------------------------|-----------------------|---------|----------------------------------|---------------------------|--|-------------------|-----------|--------------------|--------------------------|--------------|---------------------|---------------|--|
| Rpt Date 12/13/2005                        |         |                                  | Well Name/No Bilabri DX1                |           |                | Section Name/No 17 1/2" section #3 |                       |         | Mud System AQUA-DRILL            |                           |  |                   |           |                    |                          |              |                     |               |  |
| Job# 1                                     |         | Spud Date 11/25/2005             |                                         |           | MD 1178.00 m   |                                    | Progress 111.00 m     |         | Present Activity Back Reaming    |                           |  |                   |           |                    |                          |              |                     |               |  |
| Operator Peak Petroleum Industries Limited |         |                                  | Company Rep Steve Green /Texas Richards |           |                | Contractor Dolphin Drilling Ltd    |                       |         | Contractor Rep Troy Nolan/ Blair |                           |  |                   |           |                    |                          |              |                     |               |  |
| Field/Lease Bilabri                        |         | Blk/Co/Parish OML -122, /Nigeria |                                         |           | Area OML - 122 |                                    | Country/State Nigeria |         |                                  | Rig Bulford Dolphin       |  |                   |           |                    |                          |              |                     |               |  |
| Drilling Assembly                          |         |                                  |                                         |           |                | Casing                             |                       | Volumes | Pump Information                 |                           |  |                   |           |                    |                          |              |                     |               |  |
| Bit Gauge in                               |         | Mfr                              |                                         | Bit Model |                | OD in                              | ID in                 | Depth m | bbl                              | Model                     |  | Liner in          | Stroke in | Eff %              | Vol/Stk bbl              | Stk Rate SPM | Circ Rate USgal/min |               |  |
| 17 1/2                                     |         | Reed Tool Company                |                                         | MS51A     |                |                                    | 18 3/4                | 156.96  | Total Hole 1161.34               | Continental Ensco FA-1600 |  | 6 1/2             | 12.00     | 93.00              | 0.1145                   | 64           | 308                 |               |  |
| Drill Collars                              |         |                                  | Drill Pipe                              |           |                | 20                                 | 18.542                | 453.00  |                                  | Continental Ensco FA-1600 |  | 6 1/2             | 12.00     | 93.00              | 0.1145                   | 77           | 370                 |               |  |
| OD in                                      | ID in   | Length m                         | OD in                                   | ID in     | Length m       |                                    | 17 1/2                | 1178.00 | Active Pits 340                  | Continental Ensco FA-1600 |  | 6 1/2             | 12.00     | 93.00              | 0.1145                   | 0            |                     |               |  |
| 9 1/2                                      | 2 13/16 | 17.56                            | 5                                       | 4.276     | 918.43         |                                    |                       |         |                                  |                           |  |                   |           |                    |                          |              |                     |               |  |
| 8 1/2                                      | 2 3/4   | 46.69                            | 5                                       | 3 1/2     | 166.88         |                                    |                       |         | Tot Active 1501.34               |                           |  |                   |           |                    |                          |              |                     |               |  |
|                                            |         |                                  |                                         |           |                |                                    |                       |         | In Storage 720                   | Surface to Bit            |  | 3.9 min/545stks   |           |                    | Total System 93.0 min/13 |              |                     |               |  |
|                                            |         |                                  |                                         |           |                |                                    |                       |         |                                  | Bottoms Up                |  | 68.1 min/9597stks |           |                    |                          |              |                     |               |  |
| Mud Properties                             |         |                                  |                                         |           |                | Max Ann Velocity                   |                       |         | Hole Information                 |                           |  |                   |           |                    |                          |              |                     |               |  |
| Property                                   |         | Fluid Spec                       |                                         | 1         | 2              | 3                                  | AV Riser              |         | 50.90 ft/min                     | Standpipe Pressure        |  | 1758 psi          |           | Water Depth        |                          |              |                     | 14            |  |
| Sample From                                |         |                                  |                                         | Flow Line | Active Pit     |                                    | AV Casing             |         | 52.13 ft/min                     | Hole Flow                 |  | 678 USgal/min     |           | Riser Booster Rate |                          |              |                     | US            |  |
| Check Time                                 |         |                                  |                                         | 03:45     | 23:30          |                                    | AV Open Hole          |         | 77.81 ft/min                     | Solids Analysis           |  |                   |           |                    |                          |              |                     |               |  |
| MD m                                       |         |                                  |                                         | 1100.00   | 1174.00        |                                    | Vc Open Hole          |         | 217.86 ft/min                    | Property                  |  | 1                 |           | 2                  |                          | 3            | 4                   |               |  |
| TVD m                                      |         |                                  |                                         | 1100.00   | 1174.00        |                                    | Vc Drill Pipe         |         | 189.41 ft/min                    | LGS %                     |  | 5.91              |           | 5.77               |                          |              |                     |               |  |
| Bit Depth m                                |         |                                  |                                         | 1100.00   | 1174.00        |                                    | Min Ann Velocity      |         |                                  | LGS g/cc                  |  | 0.2               |           | 0.2                |                          |              |                     |               |  |
| Density ppg                                |         |                                  |                                         | 9.60      | 9.60           |                                    | AV Riser              |         | 50.90 ft/min                     | HGS %                     |  | 0.00              |           | 0.00               |                          |              |                     |               |  |
| Funnel Visc. sec/quart                     |         | 0.0                              |                                         | 39.0      | 42.0           |                                    | AV Casing             |         | 52.13 ft/min                     | HGS g/cc                  |  | 0.0               |           | 0.0                |                          |              |                     |               |  |
| Flow Line Temp degF                        |         |                                  |                                         | 96.0      | 101.0          |                                    | AV Open Hole          |         | 59.10 ft/min                     | Bentonite %               |  | 0.00              |           | 0.00               |                          |              |                     |               |  |
| Test Temp degF                             |         |                                  |                                         | 80.0      | 96.0           |                                    | Bit Information       |         |                                  | Bentonite g/cc            |  | 0.0               |           | 0.0                |                          |              |                     |               |  |
| Rheol Temp degF                            |         |                                  |                                         | 80.0      | 96.0           |                                    | Size                  |         | 17 1/2 in                        | Drill Sol %               |  | 5.91              |           | 5.77               |                          |              |                     |               |  |
| PV cP                                      |         |                                  |                                         | 8         | 11             |                                    | Hours On Bit          |         |                                  | Drill Sol g/cc            |  | 0.2               |           | 0.2                |                          |              |                     |               |  |
| YP lbf/100ft^2                             |         | 0                                |                                         | 20        | 20             |                                    | Bit Number            |         |                                  | Avg Dens Sol sg           |  | 2.9048            |           | 2.7208             |                          |              |                     |               |  |
| 10sec Gel lbf/100ft^2                      |         |                                  |                                         | 4         | 4              |                                    | BHA Number            |         | 2                                | Rheology                  |  |                   |           |                    |                          |              |                     |               |  |
| 10min Gel lbf/100ft^2                      |         |                                  |                                         | 8         | 8              |                                    | Depth In              |         | 459.00 m                         | 600 RPM                   |  | 36                |           | 42                 |                          |              |                     |               |  |
| API Filtrate cc                            |         |                                  |                                         | 7.0       | 7.0            |                                    | Bit RPM               |         |                                  | 300 RPM                   |  | 28                |           | 31                 |                          |              |                     |               |  |
| API Cake in/32                             |         |                                  |                                         | 1.0       | 1.0            |                                    | WOB                   |         | klbf                             | 200 RPM                   |  | 22                |           | 24                 |                          |              |                     |               |  |
| pH                                         |         |                                  |                                         | 9         | 8.7            |                                    | Nozzles               |         | 26:3x22                          | 100 RPM                   |  | 15                |           | 16                 |                          |              |                     |               |  |
| Pm                                         |         |                                  |                                         | 0.1       | 0.1            |                                    | Bit Hydraulics        |         |                                  | 6 RPM                     |  | 7                 |           | 4                  |                          |              |                     |               |  |
| PF                                         |         |                                  |                                         | 0.1       | 0.1            |                                    | TFA                   |         | 1.6322 in^2                      | 3 RPM                     |  | 4                 |           | 3                  |                          |              |                     |               |  |
| Excess Lime lb/bbl                         |         |                                  |                                         | 0.0       | 0.0            |                                    | Nozzle Vel            |         | 133.3 ft/sec                     |                           |  |                   |           |                    |                          |              |                     |               |  |
| Hardness mg/l                              |         |                                  |                                         | 200.0     | 240.0          |                                    | Bit Press Loss        |         | 153 psi                          |                           |  |                   |           |                    |                          |              |                     |               |  |
| Chlorides mg/l                             |         |                                  |                                         | 58000.0   | 60000.0        |                                    | HHP / Area            |         | 0.25 HP/in^2                     | Hydraulic Analysis        |  |                   |           |                    |                          |              |                     |               |  |
| K mg/l                                     |         |                                  |                                         | 44340.0   | 46546.0        |                                    | HHP                   |         | 8.70 %                           | Behavior Index (n)        |  |                   |           |                    |                          |              |                     | 0.477         |  |
| NaCl mg/l                                  |         |                                  |                                         | 29588.1   | 29598.9        |                                    |                       |         |                                  | Consistency Index (k)     |  |                   |           |                    |                          |              |                     | 1.470 #sec^n/ |  |
| KCl mg/l                                   |         |                                  |                                         | 84543.1   | 88749.3        |                                    |                       |         |                                  | ECD @ Bit Depth           |  |                   |           |                    |                          |              |                     | 9.63 pp       |  |
| MBT lb/bbl                                 |         |                                  |                                         | 5.0       | 5.0            |                                    |                       |         |                                  | ECD @ Casing Shoe         |  |                   |           |                    |                          |              |                     | 9.62 pp       |  |
| Retort Water %                             |         |                                  |                                         | 91.00     | 90.5           |                                    |                       |         |                                  |                           |  |                   |           |                    |                          |              |                     |               |  |

|  |  |  |  |  |
|--|--|--|--|--|
|  |  |  |  |  |
|  |  |  |  |  |
|  |  |  |  |  |

| BHDF Fluids Rep               | BHDF Rep Phone       | Warehouse           | Warehouse Phone   | Coordinator   | Daily Cost   | Cumulative Cost | Inventory Value |
|-------------------------------|----------------------|---------------------|-------------------|---------------|--------------|-----------------|-----------------|
| Maisonneuve J/Billy O./Wobo C | 009-234-803-4020-440 | Onne, Port Harcourt | 009-234-84-462609 | Ogaree Lawson | 25201.11 USD | 415250.19 USD   | 302306.69 USD   |

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

# ADVANTAGE Daily Drilling Fluids Report - 22



INTEQ

|                                            |                                         |                                    |                                      |
|--------------------------------------------|-----------------------------------------|------------------------------------|--------------------------------------|
| Rpt Date 12/13/2005                        | Well Name/No Bilabri DX1                | Section Name/No 17 1/2" section #3 | Mud System AQUA-DRILL                |
| Job# 1                                     | Spud Date 11/25/2005                    | MD 1178.00 m                       | Progress 111.00 m                    |
| Operator Peak Petroleum Industries Limited | Company Rep Steve Green /Texas Richards | Contractor Dolphin Drilling Ltd    | Contractor Rep Troy Nolan/ Blair Don |
| Field/Lease Bilabri                        | Blk/Co/Parish OML -122, /Nigeria        | Area OML - 122                     | Country/State Nigeria                |
|                                            |                                         |                                    | Rig Bulford Dolphin                  |

## Solids Control Equipment

| Name              | # | Mfr                   | Hours hours | Screen Sizes | Act Volume Lost bbl | Res Volume Lost bbl | Comments |
|-------------------|---|-----------------------|-------------|--------------|---------------------|---------------------|----------|
| CENTRIFUGE        | 1 | SWACO                 | 0.0         |              | 20.00               | 0.00                |          |
| CENTRIFUGE        | 2 | SWACO                 | 0.0         |              | 0.00                | 0.00                |          |
| DEGASSER          | 1 | Derrick Equipments Co | 0.0         |              | 0.00                | 0.00                |          |
| DESANDER          | 1 | SWACO                 | 0.0         |              |                     | 0.00                |          |
| DESILTER          | 1 | SWACO                 | 0.0         |              | 0.00                | 0.00                |          |
| MUD CLEANER       | 1 | SWACO                 | 0.0         | 2 X 175      | 0.00                | 0.00                |          |
| SHALE SHAKER      | 1 | Brandt                | 0.0         | 20/40        | 0.00                | 0.00                |          |
| SHALE SHAKER      | 2 | Brandt                | 0.0         | 20/40        | 0.00                | 0.00                |          |
| SHALE SHAKER      | 3 | Brandt                | 0.0         | 20/40        | 0.00                | 0.00                |          |
| SHALE SHAKER      | 4 | Derrick Equipments Co | 0.0         | 3 X 150      | 5.00                | 0.00                |          |
| SHALE SHAKER      | 5 | Derrick Equipments Co | 0.0         | 3 X 150      | 5.00                | 0.00                |          |
| SHALE SHAKER      | 6 | Derrick Equipments Co | 0.0         | 3 X 150      | 4.00                | 0.00                |          |
| Total Volume Lost |   |                       |             |              | 34                  | 0                   |          |

## Volumes

| Additions bbl |                  |         | Losses bbl |              |                      | Total Volumes bbl |            |                     |
|---------------|------------------|---------|------------|--------------|----------------------|-------------------|------------|---------------------|
| Mud Added     | Weight Materials |         | Downhole   | Left In Pit  |                      | Starting Volume   | 2022.29    | Riser w/o Pipe      |
| Brine         | 187              | Water   | 123        | Cased Off    | Trip Losses          | Daily Additions   | 322.53     | Casing w/o Pipe     |
| Base Fluid    |                  | Product | 12.53      | Left In Hole | Injected             | Daily Losses      | 124        | Open Hole w/o Pipe  |
| Recycled      |                  | Other   |            | Discharged   | Spill To Environment | Ending Volume     | 2220.82    | String Displacement |
|               |                  |         |            | SCE          | 34                   | Onshore Disposal  | Net Change | 198.53              |
|               |                  |         |            | Evaporation  | Returned             |                   |            | String Capacity     |
|               |                  |         |            | Other Losses |                      |                   |            | Total Hole w/ Pipe  |
|               |                  |         |            |              |                      |                   |            | Total Active        |
|               |                  |         |            |              |                      |                   |            | Total Reserve       |

## IADC Hours

|               |     |                    |   |           |     |          |    |
|---------------|-----|--------------------|---|-----------|-----|----------|----|
| Miscellaneous | 1.5 | Drilling Formation | 8 | Circulate | 3.5 | Tripping | 11 |
|---------------|-----|--------------------|---|-----------|-----|----------|----|

## Primary Currency USD

## Secondary Currency

## Totals USD

|                        |           |                        |      |                       |           |
|------------------------|-----------|------------------------|------|-----------------------|-----------|
| Daily Product Cost     | 23176.11  | Daily Product Cost     | 0.00 | Primary Product       | 318644.79 |
| Daily Tax              | 0.00      | Daily Tax              | 0.00 | Secondary Product     | 0.00      |
| Debit/Credit           | 0.00      | Debit/Credit           | 0.00 | Primary Engineering   | 36450.00  |
| Daily Engineering Cost | 2025.00   | Daily Engineering Cost |      | Secondary Engineering | 0.00      |
| Total Daily Cost       | 25201.11  | Total Daily Cost       | 0.00 | Primary Total         | 415250.19 |
| Total Inventory Value  | 302306.69 | Total Inventory Value  | 0.00 | Secondary Total       | 0.00      |
|                        |           |                        |      | Deck Load             | 585756 lb |

## Products and Services

| Product                  | Units    | Start | Transferred In | Received | Returned | Lost | Daily Use | Final | Unit Price USD | Daily Cost USD | Active Ending Concentrations lb/bbl | Reserve Ending Concentrations lb/bbl |
|--------------------------|----------|-------|----------------|----------|----------|------|-----------|-------|----------------|----------------|-------------------------------------|--------------------------------------|
| Bulk                     |          |       |                |          |          |      |           |       |                |                |                                     |                                      |
| BARITE - Imported        | 1000 kg  | 207   |                |          |          |      |           | 207   | 540.00         |                |                                     |                                      |
| Water Based Product      |          |       |                |          |          |      |           |       |                |                |                                     |                                      |
| AQUA-COL D               | 1 m^3    | 7     |                |          |          |      | 1         | 6     | 3589.90        | 3589.90        | 6.68                                | 3.51                                 |
| AQUA-COL D               | 55 USgal |       |                |          |          |      |           |       | 746.70         |                |                                     |                                      |
| BENTONITE                | 50 kg    | 5     |                |          |          |      |           | 5     | 35.53          |                |                                     |                                      |
| CaCO3 F                  | 50 kg    | 200   |                |          |          |      |           | 200   | 45.36          |                | 0.78                                |                                      |
| CAUSTIC SODA             | 25 kg    | 25    |                |          |          |      | 6         | 19    | 37.89          | 227.34         | 0.70                                | 0.12                                 |
| LD-8                     | 55 USgal | 1     |                |          |          |      |           | 1     | 1580.41        |                |                                     |                                      |
| LIME                     | 25 kg    | 80    |                |          |          |      |           | 80    | 34.25          |                |                                     |                                      |
| MIL-GUAR                 | 25 kg    | 76    |                |          |          |      |           | 76    | 135.00         |                | 0.08                                |                                      |
| MIL-PAC LV               | 25 kg    | 93    |                |          |          |      | 10        | 83    | 155.00         | 1550.00        | 1.33                                | 0.50                                 |
| MIL-PAC R                | 25 kg    | 118   |                |          |          |      | 14        | 104   | 155.00         | 2170.00        | 1.39                                | 0.51                                 |
| ML 1013 (BIOCIDE)        | 55 USgal | 2     |                |          |          |      |           | 2     | 2508.30        |                |                                     |                                      |
| NEW-DRILL PLUS           | 25 kg    | 168   |                |          |          |      | 6         | 162   | 110.66         | 663.96         | 0.39                                | 0.07                                 |
| NUT PLUG F               | 25 kg    | 40    |                |          |          |      |           | 40    | 27.01          |                |                                     |                                      |
| POTASSIUM CHLORIDE       | 50 kg    | 63    |                |          |          |      |           | 63    | 48.00          |                | 2.28                                |                                      |
| POTASSIUM CHLORIDE       | tonne    | 16    |                |          |          |      |           | 16    | 960.00         |                |                                     |                                      |
| POTASSIUM CHLORIDE BRINE | 1 bbl    |       |                | 187      |          |      | 187       |       | 46.85          | 8760.95        | 32.94                               | 151.33                               |
| SODA ASH                 | 50 kg    | 20    |                |          |          |      |           | 20    | 73.40          |                |                                     |                                      |
| SOLETEX                  | 50 lb    | 160   |                |          |          |      |           | 160   | 125.73         |                |                                     |                                      |

|                                                            |                                                   |                                            |                                                     |                                        |                                      |                                             |                                             |                   |                                                                                                                                                                                                                                                                                                                                               |      |      |
|------------------------------------------------------------|---------------------------------------------------|--------------------------------------------|-----------------------------------------------------|----------------------------------------|--------------------------------------|---------------------------------------------|---------------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|
| X-CIDE 102                                                 | 55<br>USgal                                       | 4                                          |                                                     |                                        |                                      |                                             | 4                                           | 2508.30           |                                                                                                                                                                                                                                                                                                                                               |      |      |
| XANTHAN GUM D                                              | 25 kg                                             | 138                                        |                                                     |                                        |                                      | 18                                          | 120                                         | 345.22            | 6213.96                                                                                                                                                                                                                                                                                                                                       | 1.69 | 0.63 |
| <b>BHDF Fluids Rep</b><br>Maisonneuve J/Billy O./Wobo<br>C | <b>BHDF Rep Phone</b><br>009-234-803-4020-<br>440 | <b>Warehouse</b><br>Onne, Port<br>Harcourt | <b>Warehouse<br/>Phone</b><br>009-234-84-<br>462609 | <b>Coordinator</b><br>Ogaree<br>Lawson | <b>Daily Cost</b><br>25201.11<br>USD | <b>Cumulative<br/>Cost</b><br>415250.19 USD | <b>Inventory<br/>Value</b><br>302306.69 USD | <b>Page<br/>2</b> | <b>Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.</b> |      |      |