

ADVANTAGE Daily Drilling Fluids Report - 50



INTEQ

Rpt Date 10/Jan/2006		Well Name/No Bilabri DX 1		Section Name/No 12-1/4" Section #4		Mud System SYN-TEQ (PARA)	
Job# 1		Spud Date 22/Nov/2005		MD 2779.00 m		Progress 0.00 m	
Operator Peak Petroleum Indust. Limited		Company Rep Tex Richards		Contractor Dolphin Drilling Ltd		Contractor Rep Troy Nolan / Blair Don	
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria	
						Rig BULFORD DOLPHIN	

Drilling Assembly						Casing		Volumes	Pump Information						
Bit Gauge in	Mfr		Bit Model		OD in	ID in	Depth m	bbl	Model	Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min
0						19	168.00	Total Hole	Continental Ensco FA-1600	5 1/2	12.00	97.00	0.0855	0	
Drill Collars			Drill Pipe			20	18.700	453.00	1342.77	Continental Ensco FA-1600	5 1/2	12.00	97.00	0.0855	0
OD in	ID in	Length m	OD in	ID in	Length m	13 3/8	12 3/8	1536.00	Active Pits	Continental Ensco FA-1600	5 1/2	12.00	97.00	0.0855	0
							12 1/4	2779.00	455						
								Tot Active							
								1797.77							
								In Storage							
								399							
								Circulation Times							
								Surface to Bit	min/stks				Total System		min/stks
								Bottoms Up	min/stks						

Mud Properties					Max Ann Velocity		Hole Information			
Property	Fluid Spec	1	2	3	AV Riser	ft/min	Standpipe Pressure	psi	Water Depth	168.25 m
Sample From		Active Pit	Active Pit		AV Casing	ft/min	Hole Flow	USgal/min	Riser Booster Rate	USgal/min
Check Time		06:00	21:30		AV Open Hole	ft/min	Solids Analysis			
MD m		2779.00	2779.00		Vc Open Hole	ft/min	Property	1	2	3
TVD m		2620.00	2620.00		Vc Drill Pipe	ft/min	LGS %	6.64	6.73	
Bit Depth m		0.00	2046.00		Min Ann Velocity		LGS lb/bbl	60.50	61.37	
Inc deg		32.90	32.90		AV Riser	ft/min	HGS %	7.11	7.50	
Density ppg	0.0	10.6	10.7		AV Casing	ft/min	HGS lb/bbl	104.68	110.39	
Funnel Visc. sec/quart	0.0	102.0	97.0		AV Open Hole	ft/min	Avg Dens Sol sg	3.4275	3.4429	
Flow Line Temp degF			120.0		Bit Information					
Test Temp degF		105.0	120.0		Size					
Rheol Temp degF		130.0	120.0		Hours On Bit					
PV cP		47	40		Bit Number					
YP lbf/100ft^2	0	32	38		BHA Number		Rheology			
10sec Gel lbf/100ft^2		15	15		Depth In		600 RPM	126	118	
10min Gel lbf/100ft^2		30	32		Bit RPM		300 RPM	79	78	
HTHP Filtrate cc		2.8	2.8		WOB		200 RPM	58	62	
HTHP Cake in/32		2.0	2.0		Nozzles		100 RPM	41	41	
HTHP Temp degF		250.0	250.0		Bit Hydraulics		6 RPM	12	14	
HTHP Pressure psi		500	500		TFA		3 RPM	9	12	
Retort Water %		21.50	20.00		Nozzle Vel	ft/sec				
Retort Base Fluid %		63.00	64.00		Bit Press Loss	psi				
Retort Solids %		15.50	16.00		HHP / Area	HP/in^2	Hydraulic Analysis			
Corrected Solids %		13.75	14.23		HHP	%	Behavior Index (n)			
Oil:Water Ratio		75:25	76:24				Consistency Index (k)			
Alk (Whole Mud-POM) cc/cc		1.3	1.4				ECD @ Bit Depth			
Cl (Whole Mud-Clom) cc/cc		43000	43000				ECD @ Casing Shoe			
Ca (Whole Mud-Caom) cc/cc		0	0		Fluid Comments/ Recommendations					
Excess Lime lb/bbl		1.7	1.8		Treated mud system with Base oil while circulation at 1500m and 2000m. Mixed 50 bbls sweep to be spot at bottom. Increase mud weight to 10.7ppg.					
Brine Density sg		1.21	1.23							
NaCl % wt		0	0							
CaCl2 % wt		24	25							
Elect. Stab.V		500.0	543.0							
Sand %		0.90								
					Drilling Comments					
					Finished to pick up samples on log No 4. P.O.O.H the same and recovered samples. Rig down Baker Atlas, Make up slick BHA and trip in hole, @ 1500m Circulated bottoms up while conditioning Mud system. Continue tripping to 2000m. Circ. and condition Mud. Max Gas = 3100 Unit. T.I.H. To TD @ 2779m. Circ. While conditioning Mud, observed Max gas @ 7010 Units. Continue to circulate and raise mud weight to 10.7 ppg. Check for flow. O.K pumped and spotted 50 bbls sweep on bottom. P.O.O.H. To run 9 5/8" casing.					

BHDF Fluids Rep	BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost	Inventory Value	Page 1
Jose Rodriguez / Wobo Chimeka	234-803-4020440	Onne Port Harcourt	234-84-462609	Ogaree Lawson	1717.40 USD	1815155.33 USD	398563.29 USD	

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

ADVANTAGE Daily Drilling Fluids Report - 50



INTEQ

Rpt Date 10/Jan/2006		Well Name/No Bilabri DX 1		Section Name/No 12-1/4" Section #4		Mud System SYN-TEQ (PARA)	
Job# 1		Spud Date 22/Nov/2005		MD 2779.00 m		Progress 0.00 m	
Operator Peak Petroleum Indust. Limited		Company Rep Tex Richards		Contractor Dolphin Drilling Ltd		Present Activity Tripping	
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria	
						Rig BULFORD DOLPHIN	

Solids Control Equipment							
Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments
CENTRIFUGE	1	SWACO	0.0		0.00	0.00	
CENTRIFUGE	2	SWACO	0.0		0.00	0.00	
DESANDER	1	SWACO	0.0		0.00	0.00	
DESILTER	1	SWACO	0.0		0.00	0.00	
MUD CLEANER	1	SWACO	0.0	2 x 210	0.00	0.00	
SHALE SHAKER	1	Brandt	0.0		0.00	0.00	
SHALE SHAKER	1	SWACO	0.0		0.00	0.00	
SHALE SHAKER	2	Brandt	0.0		0.00	0.00	
SHALE SHAKER	3	Brandt	0.0		0.00	0.00	
SHALE SHAKER	4	Derrick Equipments Co	0.0	3 x 200	0.00	0.00	
SHALE SHAKER	5	Derrick Equipments Co	0.0	200, 2 x 175	0.00	0.00	
SHALE SHAKER	6	Derrick Equipments Co	0.0	3 x 175	0.00	0.00	
				Total Volume Lost	0	0	

Volumes							
Additions bbl			Losses bbl		Total Volumes bbl		
Mud Added	Weight Materials		Downhole	Left In Pit	Starting Volume	2196.46	Riser w/o Pipe
Brine	Water		Cased Off	Trip Losses	Daily Additions	0.38	Casing w/o Pipe
Base Fluid	Product	0.38	Left In Hole	Injected	Daily Losses		Open Hole w/o Pipe
Recycled	Other		Discharged	Spill To Environment	Ending Volume	2196.84	String Displacement
			SCE	Onshore Disposal	Net Change	0.38	String Capacity
			Evaporation	Returned			Total Hole w/ Pipe
			Other Losses				Total Active
							Total Reserve

IADC Hours							
Wireline Logs	3	Circulate	8	Tripping	12	Surface String Handling	
BHDF Fluids Rep	BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost	Inventory Value
Jose Rodriguez / Wobo Chimeka	234-803-4020440	Onne Port Harcourt	234-84-462609	Ogaree Lawson	1717.40 USD	1815155.33 USD	398563.29 USD

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

ADVANTAGE Daily Drilling Fluids Report - 50



INTEQ

Rpt Date 10/Jan/2006		Well Name/No Bilabri DX 1		Section Name/No 12-1/4" Section #4		Mud System SYN-TEQ (PARA)											
Job# 1	Spud Date 22/Nov/2005	MD 2779.00 m		Progress 0.00 m		Present Activity Tripping											
Operator Peak Petroleum Indust. Limited		Company Rep Tex Richards		Contractor Dolphin Drilling Ltd		Contractor Rep Troy Nolan / Blair Don											
Field/Lease Bilabri	Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN										
Primary Currency USD		Secondary Currency		Totals USD													
Daily Product Cost	367.40	Daily Product Cost	0.00	Primary Product	1730633.65												
Daily Tax	0.00	Daily Tax	0.00	Secondary Product	0.00												
Debit/Credit	0.00	Debit/Credit	0.00	Primary Engineering	74925.00												
Daily Engineering Cost	1350.00	Daily Engineering Cost		Secondary Engineering	0.00												
Total Daily Cost	1717.40	Total Daily Cost	0.00	Primary Total	1815155.33												
Total Inventory Value	398563.29	Total Inventory Value	0.00	Secondary Total	0.00												
				Deck Load	932664 lb												
Products and Services																	
Product	Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl							
Bulk																	
BARITE - Imported	1000 kg	184						184	52.82	10.59							
Oil Based Product																	
CALCIUM CHLORIDE (97%)	1000 kg																
CALCIUM CHLORIDE (97%)	25 kg	280						280	4.82	0.54							
CARBO-GEL	25 kg																
CARBO-GEL 2	25 kg	164					4	160	0.48	0.04							
CARBO-TROL HT	25 kg	100						100	1.84	0.21							
OMNI-COTE	55 USgal	8						8									
OMNI-MUL	55 USgal	24						24	3.50	0.85							
OMNI-PLEX	55 USgal	12						12	1.34	0.17							
OMNI-TEC	55 USgal	22						22	1.11	0.59							
PARA-TEQ BASE FLUID	1 bbl	357						357	57.14	48.06							
SA-58	50 lb																
Water Based Product																	
AQUA-COL D	1 m^3																
AQUA-COL D	1 m^3																
BENTONITE	50 kg	5						5									
CALCIUM CARBONATE - FINE	50 kg	174						174	4.93	4.34							
CALCIUM CARBONATE - MED	50 kg	80						80									
CAUSTIC SODA	25 kg	4						4									
LD-8	55 USgal																
LIME	25 kg	150						150	5.50	0.62							
MIL-GUAR	25 kg	19						19									
MIL-PAC R	25 kg	20						20									
MIL-PAC LV	25 kg	59						59									
ML 1013 (BIOCID)	55 USgal	1						1									
NEW-DRILL PLUS	25 kg	29						29									
NUT PLUG F	25 lb	40						40									
POTASSIUM CHLORIDE	1000 kg																
POTASSIUM CHLORIDE	50 kg	4						4									
POTASSIUM CHLORIDE BRINE	1 bbl	790						790									
SODA ASH	25 kg	20						20									
SOLTEX	50 lb																
XANTHANGUM D	25 kg	24						24									
XCIDE 102	55 USgal																
LCM																	
SOLUFLAKE F	25 kg	40						40									
Other																	
BLACK MAGIC SF T	50 lb																
QM SEAL	25 lb	52						52									
BHDF Fluids Rep		BHDF Rep Phone		Warehouse		Warehouse Phone		Coordinator		Daily Cost		Cumulative Cost		Inventory Value		Page 3	
Jose Rodriguez / Wobo Chimeka		234-803-4020440		Onne Port Harcourt		234-84-462609		Ogaree Lawson		1717.40 USD		1815155.33 USD		398563.29 USD			
Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.																	