

ADVANTAGE Daily Drilling Fluids Report - 87



INTEQ

Rpt Date 16/Feb/2006		Well Name/No Bilabri DX 1		Section Name/No 6" Section #6		Mud System SYN-TEQ (PARA)	
Job# 1		Spud Date 22/Nov/2005		MD 3545.00 m		Progress 0.00 m	
Operator Peak Petroleum Indust. Limited		Company Rep Texas Richards / Jerry Perczyk		Contractor Dolphin Drilling Ltd		Contractor Rep Troy Nolan / Paul Shepard	
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria	
						Rig BULFORD DOLPHIN	

Drilling Assembly						Casing		Volumes	Pump Information						
Bit Gauge in	Mfr	Bit Model	OD in	ID in	Depth m	bbl		Model	Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min	
6	HCC	STR382DG3K		19	168.00	Total Hole		Continental Ensco FA-1600	5 1/2	12.00	94.0	0.0829	0		
Drill Collars						20	18.700	453.00	Continental Ensco FA-1600	5 1/2	12.00	94.0	0.0829	0	
OD in	ID in	Length m	OD in	ID in	Length m	13 3/8	12 3/8	1536.00	Active Pits	Continental Ensco FA-1600	5 1/2	12.00	94.0	0.0829	0
4 3/4	2 3/16	9.35	5	4.726	614.01	9 5/8	8.681	2770.00	410						
4 3/4	2 3/16	73.72	3 1/2	2 1/2	836.00	7	6.184	3061.00	Tot Active						
4 3/4	2 3/16	18.68					8 1/2	3200.00	1300.59	Circulation Times					
							6	3545.00	In Storage	Surface to Bit		min/stks		Total System min/stks	
									320	Bottoms Up		min/stks			

Mud Properties				Max Ann Velocity		Hole Information				
Property	Fluid Spec	1	2	3	AV Riser	ft/min	Standpipe Pressure	0 psi	Water Depth	168.25 m
Sample From		Active Pit	Active Pit		AV Casing	ft/min	Hole Flow	USgal/min	Riser Booster Rate	USgal/min
Check Time		09:55	23:45		AV Open Hole	ft/min	Solids Analysis			
MD m		3545.00	3545.00		Vc Open Hole	ft/min	Property	1	2	3
TVD m		3348.00	3348.00		Vc Drill Pipe	ft/min	LGS %	5.84	5.84	
Bit Depth m		1565.70	1565.70		Min Ann Velocity		LGS lb/bbl	53.22	53.22	
Inc deg		32.00	32.00		AV Riser	ft/min	HGS %	23.72	23.72	
Density ppg		15.0	15.0		AV Casing	ft/min	HGS lb/bbl	349.16	349.16	
Funnel Visc. sec/quart		86.0	84.0		AV Open Hole	ft/min	Avg Dens Sol sg	3.8839	3.8839	
Test Temp degF		105.0	105.0		Bit Information					
Rheol Temp degF		140.0	140.0		Size	6 in				
PV cP		53	53		Hours On Bit					
YP lbf/100ft^2		24	22		Bit Number					
10sec Gel lbf/100ft^2		9	10		BHA Number	17	Rheology			
10min Gel lbf/100ft^2		17	18		Depth In	3200.00 m	600 RPM	130	128	
30min Gel lbf/100ft^2		23	25		Bit RPM		300 RPM	77	75	
HTHP Filtrate cc		2.2	2.2		WOB	2.00 klbf	200 RPM	55	57	
HTHP Cake in/32		2.0	2.0		Nozzles	2x32:12	100 RPM	33	34	
HTHP Temp degF		250.0	250.0		Bit Hydraulics		6 RPM	9	9	
HTHP Pressure psi		500	500		TFA	0.7854 in^2	3 RPM	7	7	
Retort Water %		16.0	16.0		Nozzle Vel	ft/sec				
Retort Base Fluid %		53.0	53.0		Bit Press Loss	psi				
Retort Solids %		31.0	31.0		HHP / Area	HP/in^2	Hydraulic Analysis			
Corrected Solids %		29.6	29.6		HHP	%	Behavior Index (n)			
Oil:Water Ratio		77:23	77:23				Consistency Index (k) #sec^n/100ft^2			
Alk (Whole Mud-POM) cc/cc		1.4	1.2				ECD @ Bit Depth ppg			
Cl (Whole Mud-Clom) cc/cc		35000	35000				ECD @ Casing Shoe ppg			
Ca (Whole Mud-Caom) cc/cc		0	0		Fluid Comments/ Recommendations					
Excess Lime lb/bbl		1.8	1.6		Received 520 bbls of average 14.8 ppg SBM, backloaded 241 bbls of SBM weight 11.5 ppg and later received 373 bbls of SBM from MV Northern Crusader. Adjusted rheology with Omniplex and wt up with barite to 15.0 ppg. Received 100MT barite from the N. Crusader.					
Brine Density sg		1.23	1.23							
NaCl % wt		0	0							
CaCl2 % wt		26	26							
Elect. Stab.V		557.0	569.0							
Sand %		0.50	0.50							
					Drilling Comments					
					Cont POOH t/2434, F/C, observe gain. CBU @ 30 SPM. Stop short of 200 stks to btms up due to observed pit gain. Shut in well, SIDPP - 480, SICP - 380 psi. Circ @ 20 SPM. Shut on choke, SIDPP - 1140, SICP - 1830 psi. Close upper pipe rams, space out & commence bullheading. Pump #1 - 11 SPM down string, Pump #3 - 11 SPM down choke. Total strks 7564, 620 bbls. Sut down pumps & monitor press. SIDPP - 600, SICP - 890 psi. Bullhead a further 250 bbls of 15.0 ppg mud. Pump #1 - 12 SPM down string, Pump #3 - 24 SPM down choke. Stop pumps, shut in with SIDPP - 380, SICP - 380 psi. & monitor well.					

BHDF Fluids Rep	BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost	Inventory Value	Page 1
Waboso P / Uwakwe M /Opara.C	234-803-4020440	Onne Port Harcourt	234-84-462609	Ogaree Lawson/Jim Hosey	31437.90 USD	4109987.46 USD	562509.24 USD	

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

ADVANTAGE Daily Drilling Fluids Report - 87



INTEQ

Rpt Date 16/Feb/2006		Well Name/No Bilabri DX 1		Section Name/No 6" Section #6		Mud System SYN-TEQ (PARA)				
Job# 1		Spud Date 22/Nov/2005		MD 3545.00 m		Progress 0.00 m		Present Activity Well Control		
Operator Peak Petroleum Indust. Limited		Company Rep Texas Richards / Jerry Perczyk		Contractor Dolphin Drilling Ltd		Contractor Rep Troy Nolan / Paul Shepard				
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN		
Solids Control Equipment										
Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments			
CENTRIFUGE	1	SWACO	0.0		0.00	0.00				
CENTRIFUGE	2	SWACO	0.0		0.00	0.00				
DESANDER	1	SWACO	0.0		0.00	0.00				
DESILTER	1	SWACO	0.0		0.00	0.00				
MUD CLEANER	1	SWACO	0.0	2 x 210	0.00	0.00				
SHALE SHAKER	1	SWACO	0.0		0.00	0.00				
SHALE SHAKER	1	Derrick Equipments Co	24.0	175, 200, 200	0.00	0.00				
SHALE SHAKER	2	Derrick Equipments Co	24.0	175, 2 x 210	0.00	0.00				
SHALE SHAKER	3	Derrick Equipments Co	24.0	175, 2 x 200	0.00	0.00				
SHALE SHAKER	4	Brandt	0.0		0.00	0.00				
SHALE SHAKER	5	Brandt	0.0		0.00	0.00				
SHALE SHAKER	6	Brandt	0.0		0.00	0.00				
				Total Volume Lost	0	0				
Volumes										
Additions bbl				Losses bbl			Total Volumes bbl			
Mud Added	893	Weight Materials	52.52	Downhole	835	Left In Pit	Starting Volume	1623.1	Riser w/o Pipe	193.29
Brine		Water		Cased Off		Trip Losses	Daily Additions	1073.14	Casing w/o Pipe	653.43
Base Fluid	30	Product	2.62	Left In Hole		Injected	Daily Losses	1076	Open Hole w/o Pipe	71.59
Recycled		Other	95	Discharged		Spill To Environment	Ending Volume	1620.24	String Displacement	27.73
				SCE		Onshore Disposal	Net Change	-2.86	String Capacity	62.17
				Evaporation		Returned			Total Hole w/ Pipe	890.59
				Other Losses					Total Active	1300.59
									Total Reserve	320.00
IADC Hours										
Well Control						24				
BHDF Fluids Rep		BHDF Rep Phone		Warehouse		Warehouse Phone		Coordinator		Daily Cost
Waboso P / Uwakwe M /Opara.C		234-803-4020440		Onne Port Harcourt		234-84-462609		Ogaree Lawson/Jim Hosey		31437.90 USD
										Cumulative Cost
										4109987.46 USD
										Inventory Value
										562509.24 USD
Page 2										

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

ADVANTAGE Daily Drilling Fluids Report - 87



INTEQ

Rpt Date 16/Feb/2006	Well Name/No Bilabri DX 1	Section Name/No 6" Section #6	Mud System SYN-TEQ (PARA)
Job# 1	Spud Date 22/Nov/2005	MD 3545.00 m	Progress 0.00 m
Operator Peak Petroleum Indust. Limited	Company Rep Texas Richards / Jerry Perczyk	Contractor Dolphin Drilling Ltd	Contractor Rep Troy Nolan / Paul Shepard
Field/Lease Bilabri	Blk/Co/Parish OML - 122 / Nigeria	Area Offshore	Country/State Nigeria
Rig BULFORD DOLPHIN			
Primary Currency USD		Secondary Currency	Totals USD
Daily Product Cost	30537.90	Daily Product Cost	0.00
Daily Tax	0.00	Daily Tax	0.00
Debit/Credit	0.00	Debit/Credit	0.00
Daily Engineering Cost	900.00	Daily Engineering Cost	0.00
Total Daily Cost	31437.90	Total Daily Cost	0.00
Total Inventory Value	562509.24	Total Inventory Value	0.00
		Deck Load	416.69 UK ton

Products and Services										
Product	Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl
Bulk										
BARITE - Imported	1000 kg	18		100			35	83	279.13	221.92
Oil Based Product										
CALCIUM CHLORIDE (97%)	1000 kg									
CALCIUM CHLORIDE (97%)	25 kg	360						360	10.16	12.21
CARBO-GEL 2	25 kg	120						120	3.11	3.56
CARBO-TROL HT	25 kg	110						110	3.19	3.09
OMNI-COTE	55 USgal	7						7	0.85	0.06
OMNI-MUL	55 USgal	20						20	5.94	5.14
OMNI-PLEX	55 USgal	12					2	10	3.16	2.93
OMNI-TEC	55 USgal	8						8	4.14	4.28
PARA-TEQ BASE FLUID	1 bbl	1156					30	1126	125.31	141.45
SA-58	50 lb									
Water Based Product										
BENTONITE	50 kg									
CALCIUM CARBONATE - FINE	50 kg	50						50	5.00	1.91
CALCIUM CARBONATE - MED	50 kg	60						60	2.30	0.40
CAUSTIC SODA	25 kg									
LIME	25 kg	320						320	7.74	5.07
MIL-GUAR	25 kg	19						19		
MIL-PAC R	25 kg									
MIL-PAC LV	25 kg									
ML 1013 (BIOCIDE)	55 USgal									
NEW-DRILL PLUS	25 kg									
NUT PLUG F	25 lb									
POTASSIUM CHLORIDE	50 kg									
POTASSIUM CHLORIDE BRINE	1 bbl	790						790		
SODA ASH	25 kg									
XANTHANGUM D	25 kg	24						24		
LCM										
CALCIUM CARBONATE COARSE	50 kg	100						100		
CHEK-LOSS	25 lb	120						120		
SOLUFLAKE C	25 kg	40						40	0.30	0.22
SOLUFLAKE F	25 kg	120						120	1.76	0.45
SOLUFLAKE M	25 kg	225						225	0.84	0.51
X-LINK	40 lb									
X-LINK RTR	5 USgal									
Other										
BLACK MAGIC SF T	50 lb	200						200		
OM SEAL	25 lb									

BHDF Fluids Rep	BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost	Inventory Value	Page 3
Waboso P / Uwakwe M /Opara.C	234-803-4020440	Onne Port Harcourt	234-84-462609	Ogaree Lawson/Jim Hosey	31437.90 USD	4109987.46 USD	562509.24 USD	

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.