

ADVANTAGE Daily Drilling Fluids Report - 61

INTEQ

Rpt Date 06/Sep/2006				Well Name/No Bilabri D 2				Section Name/No 12 1/4" pilot hole - 2 #5				Mud System SYN-TEQ (PARA)							
Job# 1		Spud Date 05/Jul/2006				MD 3116.00 m				Progress 289.00 m				Present Activity Drilling Formation					
Operator Peak Petroleum Indust. Limited				Company Rep James Blackmon/Peter Vermeulen				Contractor Dolphin Drilling Ltd				Contractor Rep Stephen Milne /Harvey Ketchion							
Field/Lease Bilabri				Blk/Co/Parish OML - 122 / Nigeria				Area Offshore				Country/State Nigeria				Rig BULFORD DOLPHIN			
Drilling Assembly						Casing			Volumes		Pump Information								
Bit Gauge in		Mfr		Bit Model		OD in	ID in	Depth m	bbl	Model		Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min		
12 1/4		HCC		PDC			19 1/2	178.00	Total Hole	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	80	401		
Drill Collars			Drill Pipe			13 3/8	12.415	1622.00	1558	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	80	401		
OD in	ID in	Length m	OD in	ID in	Length m		12 1/4	3116.00	Active Pits	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	0			
9 1/2	2.800	18.26	5	4.276	2901.44				342										
8 1/2	2.800	29.09	5	3	166.87				Tot Active										
									1900	Circulation Times									
									In Storage	Surface to Bit		9.2 min/1466stks		Total System		99.4 min/15909stks			
									300	Bottoms Up		72.4 min/11580stks							
Mud Properties								Max Ann Velocity		Hole Information									
Property		1	2	3	4	AV Riser		55.37 ft/min		Standpipe Pressure		3380 psi		Water Depth 152.00 m					
Sample From		Reserve	Flow Line	Active Pit	Flow Line	AV Casing		152.34 ft/min		Hole Flow		803 USgal/min		Riser Booster Rate USgal/min					
Check Time		05:24	05:36	11:20	23:10	AV Open Hole		328.89 ft/min		Solids Analysis									
MD m		2904.00	2910.00	2980.00	3111.00	Vc Open Hole		476.70 ft/min		Property		1	2	3	4				
TVD m		2305.42	2305.42	2324.55	2359.00	Vc Drill Pipe		400.32 ft/min		LGS %		8.85	8.46	8.48	8.51				
Bit Depth m		2904.00	2910.00	2980.00	3111.00	Min Ann Velocity				LGS lb/bbl		80.65	77.07	77.31	77.54				
Inc deg		76.86	76.86	76.98	76.80	AV Riser		55.37 ft/min		HGS %		5.39	5.72	5.74	5.76				
Density ppg		10.10	10.10	10.10	10.10	AV Casing		152.34 ft/min		HGS lb/bbl		79.42	84.16	84.47	84.78				
Funnel Visc. sec/quart		76.0	72.0	73.0	70.0	AV Open Hole		157.29 ft/min		Avg Dens Sol sg		3.2060	3.2453	3.2455	3.2458				
Circ BHTdegF			187.1	187.1	193.1	Bit Information													
Flow Line Temp degF			158.0	157.0	160.0	Size		12 1/4 in											
Test Temp degF		90.0	118.0	115.0	111.0	Hours On Bit													
Rheol Temp degF		120.0	120.0	120.0	120.0	Bit Number													
PV cP		27	34	32	35	BHA Number		9		Rheology									
YP lbf/100ft^2		29	28	33	30	Depth In		m		600 RPM		83	96	97	100				
10sec Gel lbf/100ft^2		10	13	13	14	Bit RPM				300 RPM		56	62	65	65				
10min Gel lbf/100ft^2		18	22	24	26	WOB		klbf		200 RPM		44	48	50	51				
HTHP Filtrate cc		3.8	3.2	3.0	3.0	Nozzles		7x16		100 RPM		31	33	35	35				
HTHP Cake in/32		2.0	2.0	2.0	2.0	Bit Hydraulics				6 RPM		11	13	14	13				
HTHP Temp degF		250.0	250.0	250.0	250.0	TFA		1.3744 in^2		3 RPM		9	12	12	12				
HTHP Pressure psi		500	500	500	500	Nozzle Vel		187.3 ft/sec											
Retort Water %		21.0	19.0	19.0	19.0	Bit Press Loss		317 psi											
Retort Base Fluid %		63.0	65.0	65.0	65.0	HHP / Area		1.28 HP/in^2		Hydraulic Analysis									
Retort Solids %		16.0	16.0	16.0	16.0	HHP		11.5 %		Behavior Index (n)		0.305							
Corrected Solids %		14.2	14.2	14.2	14.3					Consistency Index (k)		7.784 #sec^n/100ft^2							
Oil:Water Ratio		75:25	77:23	77:23	77:23					ECD @ Bit Depth		10.39 ppg							
Alk (Whole Mud-POM) cc/cc		1.40	2.20	2.00	1.50					ECD @ Casing Shoe		10.35 ppg							
Cl (Whole Mud-Clom) cc/cc		43000	44000	43000	42000	Fluid Comments/ Recommendations													
Ca (Whole Mud-Caom) cc/cc		0	0	0	0	Connditioned active and run centrifuge at intervals to maintain mud specs and wt at 10.1 while drilling ahead. Gathered up all reserve mud in one pit in anticipation of mud delivery from town. Reserve volume as at report time - 160 bbls. Used 1 New 200, 1 new 175 & 2 new 180 mesh Skaker screens.													
Excess Lime lb/bbl		1.8	2.8	2.6	1.9														
Brine Density sg		1.22	1.24	1.24	1.23														
NaCl % wt		0	0	0	0														
CaCl2 % wt		24	27	26	26														
Elect. Stab.V		391.0	512.0	536.0	518.0														
Sand %			0.25	0.20	0.20														

ADVANTAGE Daily Drilling Fluids Report - 61

INTEQ

Rpt Date 06/Sep/2006	Well Name/No Bilabri D 2	Section Name/No 12 1/4" pilot hole - 2 #5	Mud System SYN-TEQ (PARA)
Job# 1	Spud Date 05/Jul/2006	MD 3116.00 m	Progress 289.00 m
Operator Peak Petroleum Indust. Limited	Company Rep James Blackmon/Peter Vermeulen	Contractor Dolphin Drilling Ltd	Contractor Rep Stephen Milne /Harvey Ketchion
Field/Lease Bilabri	Blk/Co/Parish OML - 122 / Nigeria	Area Offshore	Country/State Nigeria
			Rig BULFORD DOLPHIN

Solids Control Equipment

Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments
CENTRIFUGE	1	SWACO	6.0		8.0	0.0	
CENTRIFUGE	2	SWACO	0.0		0.0	0.0	
DESANDER	1	SWACO	0.0		0.0	0.0	
DESILTER	1	SWACO	0.0		0.0	0.0	
MUD CLEANER	1	SWACO	1.0	2 x 210	0.0	0.0	
SHALE SHAKER	1	Brandt	0.0		0.0	0.0	
SHALE SHAKER	1	Derrick Equipments Co	24.0	3 x 175	4.0	0.0	
SHALE SHAKER	2	Brandt	0.0		0.0	0.0	
SHALE SHAKER	2	Derrick Equipments Co	24.0	180, 2 x 175	4.0	0.0	
SHALE SHAKER	3	Derrick Equipments Co	24.0	200. 2 x 175	4.0	0.0	
SHALE SHAKER	3	Brandt	0.0		0.0	0.0	
				Total Volume Lost	20	0	

Volumes

Additions bbl		Losses bbl		Total Volumes bbl			
Mud Added	Weight Materials	Downhole	25	Left In Pit	Starting Volume	2302	Riser w/o Pipe
Brine	Water	Cased Off		Trip Losses	Daily Additions	8	Casing w/o Pipe
Base Fluid	Product	8	Left In Hole	Injected	Daily Losses	110	Open Hole w/o Pipe
Recycled	Other		Discharged	Spill To Environment	Ending Volume	2200.0	String Displacement
			SCE	20	Onshore Disposal	Net Change	-102.0
			Evaporation	32	Returned		Total Hole w/ Pipe
			Other Losses	33			Total Active
							Total Reserve

IADC Hours

Drilling Formation	24								
--------------------	----	--	--	--	--	--	--	--	--

Primary Currency USD		Secondary Currency		Totals USD	
Daily Product Cost	4056.00	Daily Product Cost	0.00	Primary Product	1484645.12
Daily Tax	0.00	Daily Tax	0.00	Secondary Product	0.00
Debit/Credit	0.00	Debit/Credit	0.00	Primary Engineering	59850.00
Daily Engineering Cost	900.00	Daily Engineering Cost		Secondary Engineering	0.00
Total Daily Cost	4956.00	Total Daily Cost	0.00	Primary Total	1544495.12
Total Inventory Value	497322.11	Total Inventory Value	0.00	Secondary Total	0.00
				Deck Load	362.27 UK ton

Products and Services

Product	Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl
Bulk										
BARITE - Imported	1000 kg	192						192	6.00	30.11
Oil Based Product										
CARBO-GEL	25 kg	137						137	5.16	6.10
MIL-LIME	25 kg	120					40	80	8.98	5.23
OMNI-COTE	55 USgal	7						7	0.20	
OMNI-MUL	55 USgal	16						16	3.35	2.20
OMNI-PLEX	55 USgal	11						11	4.15	2.85
OMNI-TEC	55 USgal	20					2	18	1.85	1.31
PARA-TEQ	1 bbl	831						831		
SA 58	50 lb									
Water Based Product										
CALCIUM CHLORIDE (97%)	50 lb	240					40	200	10.19	6.88
CAUSTIC SODA	25 kg	17						17	0.03	0.03
POTASSIUM CHLORIDE BRINE	1 bbl	189						189	38.15	45.90
XANTHANGUM D	25 kg	36						36	0.19	0.23
LCM										
CALCIUM CARBONATE - FINE	25 kg	160						160	0.95	0.11
CALCIUM CARBONATE - MED	25 kg	220						220	0.03	0.03
KWIKSEAL - MEDIUM	50 lb	39						39	0.02	0.03
MIL-PLUG FINE	50 lb	84						84		
MIL-SEAL MEDIUM	50 lb	90						90		
SOLUFLAKE F	50 lb	158						158		
SOLUFLAKE M	50 lb	80						80		
Other										
SAW DUST	25 kg	30						30		

BHDF Fluids Rep Peter Waboso / Kunle Olayinka	BHDF Rep Phone 234-803-402-0440	Warehouse Onne	Warehouse Phone 234-84-462609	Coordinator Lawson Ogaree	Daily Cost 4956.00 USD	Cumulative Cost 1544495.12 USD	Inventory Value 497322.11 USD	Page 2
--	------------------------------------	-------------------	----------------------------------	------------------------------	---------------------------	-----------------------------------	----------------------------------	--------

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.