

ADVANTAGE Field Survey Listing



INTEQ

Operator PEAK PETROLEUM				Field BILABRI		API No						
Well BILABRI D2				Wellbore Original Path Hole				Rig B. DOLPHIN		Job 8JLUJ25		
Well Origin												
Latitude				4.65 deg				Longitude				5.08 deg
North Reference				True				Drill Depth Zero				Kelly Bushing
Vertical Datum is				Mean Sea Level				Vertical Datum to DDZ				25.00 m
Vertical Section North				0.00 m				Vertical Section East				0.00 m
Vertical Section Azimuth				0.00 deg				Vertical Section Depth				0.00 m
Grid Convergence				0.00 deg				Magnetic Declination				-3.48 deg
Total Correction				-3.48 deg				TVD Calculation Method				Minimum Curvature
D-Raw Calculation				Magcorr1				Local Magnetic Field				32.4964 uT
Local Magnetic Dip Angle				-17.40 deg				Local Gravity Field				0.997305 gravity
Tie In	MD m	Incl deg	Azim deg	North m	East m	TVD m	VS m	Incr VS m	CRS LEN m	DLS deg/30m	Build deg/30m	Turn deg/30m
	462.00	0.44	43.70	1.28	1.23	462.00	1.28	1.78	462.00	0.03	0.03	2.84
	492.00	0.23	352.35	1.43	1.30	491.99	1.43	1.94	30.00	0.35	-0.21	-51.35
	520.00	0.25	55.37	1.52	1.34	519.99	1.52	2.04	28.00	0.27	0.01	67.52
	548.00	0.60	4.78	1.70	1.40	547.99	1.70	2.23	28.00	0.52	0.38	-54.21
	577.00	0.53	39.67	1.95	1.50	576.99	1.95	2.50	29.00	0.36	-0.08	36.10
	605.00	0.15	24.71	2.09	1.60	604.99	2.09	2.66	28.00	0.41	-0.40	-16.03
	634.00	0.20	335.94	2.17	1.59	633.99	2.17	2.75	29.00	0.16	0.05	-50.45
	663.00	0.31	346.37	2.29	1.55	662.99	2.29	2.87	29.00	0.12	0.11	10.79
	691.00	0.61	21.80	2.50	1.59	690.99	2.50	3.09	28.00	0.43	0.32	37.97
	720.00	0.45	24.36	2.75	1.69	719.99	2.75	3.35	29.00	0.16	-0.16	2.65
	748.00	0.40	346.33	2.94	1.72	747.99	2.94	3.55	28.00	0.30	-0.05	-40.75
	777.00	0.17	99.41	3.03	1.73	776.99	3.03	3.64	29.00	0.51	-0.24	116.98
	805.00	0.16	30.45	3.06	1.80	804.99	3.06	3.71	28.00	0.20	-0.01	-73.88
	836.00	0.27	43.62	3.15	1.87	835.99	3.15	3.83	31.00	0.12	0.11	12.74
	865.00	0.20	353.42	3.25	1.91	864.99	3.25	3.93	29.00	0.22	-0.07	-51.94
	893.00	0.30	54.57	3.34	1.96	892.99	3.34	4.04	28.00	0.29	0.10	65.52
	922.00	0.18	19.52	3.42	2.04	921.99	3.42	4.15	29.00	0.19	-0.13	-36.26
	950.00	0.55	32.28	3.58	2.13	949.99	3.58	4.33	28.00	0.41	0.40	13.67
	979.00	0.48	359.38	3.82	2.20	978.99	3.82	4.58	29.00	0.31	-0.07	-34.03
	1007.00	0.69	352.45	4.10	2.17	1006.98	4.10	4.86	28.00	0.23	0.22	-7.43
	1036.00	1.01	8.94	4.52	2.19	1035.98	4.52	5.29	29.00	0.41	0.33	17.06
	1064.00	0.95	338.12	4.98	2.14	1063.98	4.98	5.75	28.00	0.56	-0.06	-33.02
	1093.00	0.96	336.00	5.43	1.95	1092.97	5.43	6.23	29.00	0.04	0.01	-2.19
	1122.00	0.85	338.38	5.85	1.78	1121.97	5.85	6.69	29.00	0.11	-0.11	2.47
	1150.00	1.25	343.71	6.34	1.61	1149.97	6.34	7.20	28.00	0.44	0.43	5.70
	1179.00	1.18	336.86	6.92	1.41	1178.96	6.92	7.82	29.00	0.17	-0.08	-7.09
	1207.00	1.16	340.32	7.45	1.20	1206.95	7.45	8.39	28.00	0.08	-0.02	3.71
	1235.00	1.25	350.10	8.02	1.05	1234.95	8.02	8.98	28.00	0.24	0.09	10.48
	1264.00	0.96	359.72	8.57	1.00	1263.94	8.57	9.53	29.00	0.35	-0.30	9.95
	1293.00	1.03	346.33	9.07	0.93	1292.94	9.07	10.03	29.00	0.25	0.07	-13.85
	1321.00	0.81	342.03	9.50	0.81	1320.93	9.50	10.48	28.00	0.25	-0.24	-4.61
	1349.00	0.72	344.30	9.86	0.70	1348.93	9.86	10.86	28.00	0.10	-0.09	2.44
	1377.00	0.73	345.85	10.20	0.61	1376.93	10.20	11.21	28.00	0.02	0.00	1.65
	1405.00	0.70	304.05	10.47	0.43	1404.93	10.47	11.54	28.00	0.55	-0.03	-44.78
	1462.00	0.28	292.62	10.72	0.01	1461.92	10.72	12.02	57.00	0.22	-0.22	-6.02
	1519.00	0.37	307.83	10.88	-0.27	1518.92	10.88	12.35	57.00	0.07	0.05	8.01
	1548.00	0.88	319.97	11.11	-0.49	1547.92	11.11	12.67	29.00	0.54	0.53	12.55
	1577.00	1.12	312.25	11.47	-0.84	1576.92	11.47	13.17	29.00	0.28	0.24	-7.99
Tie Column Legend: I - interpolated tie-point, S - survey station, U - user-defined, T - Surface												
Notice: Field Copy Only. Certified results will be provided after submission to the Baker Hughes INTEQ office.												
Page 1												