



Buford Dolphin

Bottom Hole Assembly

Client Peak Petroleum Well No. GULF 1 D3 Date 8.10.06

Assembly Number 2 Bit Number 2 RR

Jar Hours 5.25

Type HTC

Connections

Qty	Description	Length	Accum	Outside Diameter	Inside Diameter	O.D.	Length	Serial	Box	Pin
1	1 7/8 Bit	4.2	4.2	1 7/8	1 7/8	—	—	6048671		7 5/8 R
1	Bit Sub	8.6	1.28	9 7/16	3"	9 7/16	Sub	TB1 001	7 5/8 R	7 5/8 R 60X
1	9 5/8 DC	8.61	9.89	9 5/8	3 3/4	9 3/8	.48	102 903	7 5/8 R	7 5/8 R
1	1 7/8 Sub	3.48	12.31	1 7/8	3"	9 3/8	.89	3286	7 5/8 R	7 5/8 R
1	9 5/8 DC	2.23	21.14	9 5/8	3 3/4	9 5/16	.42	TOD 902	7 5/8 R	7 5/8 R
1	1 7/8 Sub	2.50	23.64	1 7/8	3"	1 7/8	.90	3284	7 5/8 R	7 5/8 R
1	1 7/8 Sub	8.8	24.52	9 5/8	3 3/4	9 5/8	Sub	1002	7 5/8 R	7 5/8 R
1	X 10	1.03	25.55	9 5/8	3	8	.64	TD1 025	6 5/8 R	7 5/8 R
1	Flex Pipe	.79	26.34	7 3/16	2 3/8	7 3/16	Sub	FC2A	6 5/8 R	6 5/8 R
1	1 7/8 MWD	19.61	38.95	8 1/4	3	8 1/4	Sub	1886	6 5/8 R	6 5/8 R
1	8 1/4 MWD	6.57	45.52	8"	3 3/4	2"	Sub	804087	6 5/8 R	6 5/8 R
1	8" DC	9.35	54.87	8"	2 3/8	7 7/8	.51	85D 808	6 5/8 R	6 5/8 R
1	8" DC	9.15	64.02	8"	2 3/4	8	.41	T-1	6 5/8 R	6 5/8 R
1	8" DC	9.14	73.16	8"	2 3/4	7 5/16	.58	CP3442	6 5/8 R	6 5/8 R
1	8" DC	9.00	82.16	8"	2 3/4	7 7/8	.50	Q10	6 5/8 R	6 5/8 R
1	7 3/4 Sub	9.52	91.68	7 3/4	3"	7 5/8	.37	1417-1035	6 5/8 R	6 5/8 R
1	8" DC	9.05	100.73	8	2 13/16	7 5/8	.61	CP3442-17	6 5/8 R	6 5/8 R
1	X Over	1.02	101.75	8	2 1/8	8 1/2	.64	26644A	4 5/8 R	4 5/8 R
1	4 5/8 R	158.56	260.31	DETA 5 IN	DETA 5 IN	DETA 5 IN	DETA 5 IN	DETA 5 IN	4 5/8 R	4 5/8 R

Bha Total Length 260.31 Mud Weight 5/M
Bha Total Weight 65,000 Below Jar Weight 49,000

Totco ring No. Float YES Wall Brace

275