

**BAKER
HUGHES**

Rpt Date 18/Nov/2006			Well Name/No Bilabri D4			Section Name/No 12-1/4" Section #3			Mud System SYN-TEQ (PARA)											
Job# 1		Spud Date		MD 815.00 m			Progress 0.00 m			Present Activity Test BOP										
Operator Peak Petroleum Indust. Limited				Company Rep Thomas G. May / Chris Newton			Contractor Dolphin Drilling Ltd			Contractor Rep Stephen Milne / Troy Nolan										
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria			Area Offshore		Country/State Nigeria			Rig BULFORD DOLPHIN										
Drilling Assembly						Casing			Volumes		Pump Information									
Bit Gauge in		Mfr		Bit Model		OD in	ID in	Depth m	bbl	Model		Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min			
0							19 1/2	172.50	Total Hole	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	0				
Drill Collars		Drill Pipe		36	31 3/4	262.00	0			Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	0				
OD in	ID in	Length m	OD in	ID in	Length m	20	18 3/4	291.60	Active Pits	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	0				
						13 3/8	12.415	800.00	0											
							12 1/4	815.00	Tot Active											
									0	Circulation Times										
									In Storage	Surface to Bit		min/stks		Total System		min/stks				
									855	Bottoms Up		min/stks								
Mud Properties						Max Ann Velocity				Hole Information										
Property			Fluid Spec			1	2	3	AV Riser		ft/min		Standpipe Pressure		psi		Water Depth		146.00 m	
Sample From						Reserve			AV Casing		ft/min		Hole Flow		USgal/min		Riser Booster Rate		USgal/min	
Check Time						12:30			AV Open Hole		ft/min		Solids Analysis							
MD m						815.00			Vc Open Hole		ft/min		Property		1	2		3	4	
TVD m						815.00			Vc Drill Pipe		ft/min		LGS %		9.17					
Bit Depth m						0.00			Min Ann Velocity				LGS lb/bbl		83.55					
Density ppg			10.00-10.50			10.30			AV Riser		ft/min		HGS %		4.10					
Funnel Visc. sec/quart						78.0			AV Casing		ft/min		HGS lb/bbl		60.42					
Test Temp degF						85.0			AV Open Hole		ft/min		Avg Dens Sol sg		3.0948					
Rheol Temp degF						120.0			Bit Information											
PV cP						41			Size											
YP lbf/100ft^2						23			Hours On Bit											
10sec Gel lbf/100ft^2						11			Bit Number											
10min Gel lbf/100ft^2						20			BHA Number				Rheology							
HTHP Temp degF						250.0			Depth In				600 RPM		105					
HTHP Pressure psi						500			Bit RPM				300 RPM		64					
Retort Water %						32.0			WOB				200 RPM		48					
Retort Base Fluid %						53.0			Nozzles				100 RPM		35					
Retort Solids %						15.0			Bit Hydraulics				6 RPM		15					
Corrected Solids %						13.3			TFA				3 RPM		13					
Oil:Water Ratio						62:38			Nozzle Vel		ft/sec									
Alk (Whole Mud-POM) cc/cc						1.30			Bit Press Loss		psi									
Cl (Whole Mud-Clom) cc/cc						44000			HHP / Area		HP/in^2		Hydraulic Analysis							
Ca (Whole Mud-Caom) cc/cc						0			HHP		%		Behavior Index (n)							
Excess Lime lb/bbl						1.7							Consistency Index (k)						#sec^n/100ft^2	
Brine Density sg						1.15							ECD @ Bit Depth						ppg	
NaCl % wt						0														

ADVANTAGE Daily Drilling Fluids Report - 13



INTEQ

Rpt Date 18/Nov/2006		Well Name/No Bilabri D4		Section Name/No 12-1/4" Section #3		Mud System SYN-TEQ (PARA)	
Job# 1		Spud Date		MD 815.00 m		Progress 0.00 m	
Operator Peak Petroleum Indust. Limited		Company Rep Thomas G. May / Chris Newton		Contractor Dolphin Drilling Ltd		Contractor Rep Stephen Milne / Troy Nolan	
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria	
						Rig BULFORD DOLPHIN	

Solids Control Equipment							
Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments
CENTRIFUGE	1		0.0		0.0	0.0	
CENTRIFUGE	2		0.0		0.0	0.0	
DESANDER	1		0.0		0.0	0.0	
DESILTER	1		0.0		0.0	0.0	
MUD CLEANER	1		0.0	175, 210	0.0	0.0	
SHALE SHAKER	1		0.0		0.0	0.0	
SHALE SHAKER	1		0.0	3 x 110	0.0	0.0	
SHALE SHAKER	2		0.0		0.0	0.0	
SHALE SHAKER	2		0.0	3 x 110	0.0	0.0	
SHALE SHAKER	3		0.0	3 x 110	0.0	0.0	
SHALE SHAKER	3		0.0		0.0	0.0	
Total Volume Lost					0	0	

Volumes							
Additions bbl		Losses bbl		Total Volumes bbl			
Mud Added	Weight Materials	Downhole	Left In Pit	Starting Volume	855	Riser w/o Pipe	
Brine	Water	Cased Off	Trip Losses	Daily Additions		Casing w/o Pipe	
Base Fluid	Product	Left In Hole	Injected	Daily Losses		Open Hole w/o Pipe	
Recycled	Other	Discharged	Spill To Environment	Ending Volume	855.0	String Displacement	
		SCE	Onshore Disposal	Net Change		String Capacity	
		Evaporation	Returned			Total Hole w/ Pipe	
		Other Losses				Total Active	
						Total Reserve	855.0

IADC Hours							
Wait	24	Test BOP	0	Run/Pull Riser	0		

BHDF Fluids Rep	BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost	Inventory Value	Page 2
Jerry Laydoo / Kunle Olayinka	234-803-402-0440	Onne	234-84-462609	Lawson Ogaree	1350.00 USD	136772.27 USD	612017.70 USD	

Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.

ADVANTAGE Daily Drilling Fluids Report - 13



INTEQ

Rpt Date 18/Nov/2006			Well Name/No Bilabri D4			Section Name/No 12-1/4" Section #3				Mud System SYN-TEQ (PARA)					
Job# 1		Spud Date		MD 815.00 m			Progress 0.00 m			Present Activity Test BOP					
Operator Peak Petroleum Indust. Limited				Company Rep Thomas G. May / Chris Newton			Contractor Dolphin Drilling Ltd			Contractor Rep Stephen Milne / Troy Nolan					
Field/Lease Bilabri			Blk/Co/Parish OML - 122 / Nigeria				Area Offshore		Country/State Nigeria			Rig BULFORD DOLPHIN			
Primary Currency USD				Secondary Currency				Totals USD							
Daily Product Cost				0.00		Daily Product Cost				0.00		Primary Product		124116.02	
Daily Tax				0.00		Daily Tax				0.00		Secondary Product		0.00	
Debit/Credit				0.00		Debit/Credit				0.00		Primary Engineering		12656.25	
Daily Engineering Cost				1350.00		Daily Engineering Cost						Secondary Engineering		0.00	
Total Daily Cost				1350.00		Total Daily Cost				0.00		Primary Total		136772.27	
Total Inventory Value				612017.70		Total Inventory Value				0.00		Secondary Total		0.00	
											Deck Load		788880 lb		
Products and Services															
Product		Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Unit Price USD	Daily Cost USD	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl		
Bulk															
MIL-BAR		1000 kg	152						152	540.00			108.47		
Oil Based Product															
CARBO-GEL		25 kg	80						80	264.28					
MIL-LIME		25 kg	40						40	34.25					
MIL-LIME		25 kg	80						80	34.25					
OMNI-COTE		55 USgal	4						4	2150.00					
OMNI-MUL		55 USgal	12						12	995.06					
OMNI-PLEX		55 USgal	8						8	1618.95					
OMNI-TEC		55 USgal	8						8	925.00					
PARA-TEQ		1 bbl	1469						1469	280.00					
Water Based Product															
CAUSTIC SODA		25 kg	32						32	37.89					
MIL-GUAR		25 kg	50						50	135.00			0.69		
MIL-PAC R		25 kg								155.00			0.40		
MIL-PAC LV		25 kg								155.00			2.26		
NEW-DRILL PLUS		25 kg								110.66			1.31		
POTASSIUM CHLORIDE BRINE		1 bbl								46.85			265.81		
SODA ASH		50 kg								146.80			1.07		
Xanthan Gum		25 kg	47						47	345.22			1.19		
XCIDE 102		55 USgal	1						1	2508.30			0.01		
LCM															
CALCIUM CARBONATE - FINE		25 kg								22.68			4.52		
CALCIUM CARBONATE - FINE		25 kg	80						80	22.68					
CALCIUM CARBONATE - MED		25 kg	40						40	22.68			2.26		
KWIKSEAL - MEDIUM		25 kg	35						35	70.52					
MIL-PLUG FINE		25 kg	56						56	27.01					
Other															
BLACK MAGIC SF T		25 kg	120						120	117.25					
CALCIUM CHLORIDE (97%)		25 kg	200						200	23.21					
SAW DUST		25 kg	29						29	12.50					
BHDF Fluids Rep		BHDF Rep Phone		Warehouse		Warehouse Phone		Coordinator		Daily Cost		Cumulative Cost			
Jerry Laydoo / Kunle Olayinka		234-803-402-0440		Onne		234-84-462609		Lawson Ogaree		1350.00 USD		136772.27 USD			
												Inventory Value			
												612017.70 USD			
Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.															