

**BAKER
HUGHES**

Rpt Date 07/Jan/2007			Well Name/No Bilabri D4			Section Name/No 12-1/4" Section #3			Mud System SYN-TEQ (PARA)											
Job# 1		Spud Date 09/Nov/2006			MD 2591.00 m			Progress 0.00 m		Present Activity Miscellaneous										
Operator Peak Petroleum Indust. Limited			Company Rep Tom G.May / Peter Vermeulen			Contractor Dolphin Drilling Ltd			Contractor Rep Steve Milne / Terry Nanidis											
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria			Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN											
Drilling Assembly						Casing		Volumes	Pump Information											
Bit Gauge in		Mfr		Bit Model		OD in	ID in	Depth m	bbl	Model		Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min			
12 1/4		HCC		PDC			19 1/2	172.50	Total Hole	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	60	301			
Drill Collars			Drill Pipe			20	18 3/4	291.60	1376.1	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	60	301			
OD in	ID in	Length m	OD in	ID in	Length m	13 3/8	12.415	800.00	Active Pits	Continental Ensco FA-1600		6 1/2	12.00	97.0	0.1194	0				
8	3 1/4	6.57	5	4.276	2348.34		12 1/4	2591.00	424											
8	2 5/8	9.35	5	3	158.56				Tot Active											
8	2 3/4	27.29							1800.1	Circulation Times										
8	2 13/16	9.05							In Storage	Surface to Bit		min/stks		Total System		min/stks				
									1011	Bottoms Up		min/stks								
Mud Properties						Max Ann Velocity			Hole Information											
Property			Fluid Spec		1	2	3	AV Riser	ft/min	Standpipe Pressure		640 psi		Water Depth		146.00 m				
Sample From					Active Pit	Active Pit		AV Casing	ft/min	Hole Flow		USgal/min		Riser Booster Rate		USgal/min				
Check Time					10:00	23:15		AV Open Hole	ft/min	Solids Analysis										
MD m					2591.00	2591.00		Vc Open Hole	ft/min	Property		1	2	3	4					
TVD m					2449.98	2449.98		Vc Drill Pipe	ft/min	LGS %		5.50		5.55						
Bit Depth m					2588.00	2588.00		Min Ann Velocity		LGS lb/bbl		50.11		50.56						
Inc deg					1.46	1.46		AV Riser	ft/min	HGS %		4.32		4.36						
Density ppg					9.30	9.30		AV Casing	ft/min	HGS lb/bbl		63.54		64.19						
Funnel Visc. sec/quart					87.0	88.0		AV Open Hole	ft/min	Avg Dens Sol sg		3.3036		3.3041						
Test Temp degF					95.0	95.0		Bit Information												
Rheol Temp degF					120.0	120.0		Size	12 1/4 in											
PV cP					31	30		Hours On Bit												
YP lbf/100ft^2					20	20		Bit Number												
10sec Gel lbf/100ft^2					7	8		BHA Number	10	Rheology										
10min Gel lbf/100ft^2					13	13		Depth In	2385.00 m	600 RPM		82		80						
HTHP Filtrate cc					2.4	2.6		Bit RPM		300 RPM		51		50						
HTHP Cake in/32					2.0	2.0		WOB	klbf	200 RPM		39		38						
HTHP Temp degF					250.0	250.0		Nozzles	4x16:4x12	100 RPM		27		27						
HTHP Pressure psi					500	500		Bit Hydraulics		6 RPM		8		9						
Retort Water %					24.0	24.0		TFA	1.2272 in^2	3 RPM		6		7						
Retort Base Fluid %					64.0	64.0		Nozzle Vel	ft/sec											
Retort Solids %					12.0	12.0		Bit Press Loss	psi											
Corrected Solids %					9.8	9.9		HHP / Area	HP/in^2	Hydraulic Analysis										
Oil:Water Ratio					73:27	73:27		HHP	%	Behavior Index (n)										
Alk (Whole Mud-POM) cc/cc					1.80	2.00				Consistency Index (k)								#sec^n/100ft^2		
Cl (Whole Mud-Clom) cc/cc					53000	51000				ECD @ Bit Depth								ppg		
Ca (Whole Mud-Caom) cc/cc					0	0				ECD @ Casing Shoe								ppg		
Excess Lime lb/bbl					2.3	2.6		Fluid Comments/ Recommendations												
Brine Density sg					1.23	1.23		SURFACE ACTIVE VOL (9.3ppg) = (Act Pit #2 - 236 bbls + S/Traps - 150bb) = 386 bbls. RESERVE VOL(9.3 ppg) =												

**BAKER
HUGHES**

Rpt Date 07/Jan/2007		Well Name/No Bilabri D4		Section Name/No 12-1/4" Section #3		Mud System SYN-TEQ (PARA)					
Job# 1	Spud Date 09/Nov/2006		MD 2591.00 m		Progress 0.00 m		Present Activity Miscellaneous				
Operator Peak Petroleum Indust. Limited		Company Rep Tom G.May / Peter Vermeulen		Contractor Dolphin Drilling Ltd		Contractor Rep Steve Milne / Terry Nanidis					
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN			
Solids Control Equipment											
Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments				
CENTRIFUGE	1		0.0		0.0	0.0					
CENTRIFUGE	2		0.0		0.0	0.0					
DESANDER	1		0.0		0.0	0.0					
DESILTER	1		0.0		0.0	0.0					
MUD CLEANER	1		0.0	175, 210	0.0	0.0					
SHALE SHAKER	1		0.0		0.0	0.0					
SHALE SHAKER	1		0.0	210, 2 x 175	0.0	0.0					
SHALE SHAKER	2		0.0		0.0	0.0					
SHALE SHAKER	2		0.0	3 x 175	0.0	0.0					
SHALE SHAKER	3		0.0	3 x 175	0.0	0.0					
SHALE SHAKER	3		0.0		0.0	0.0					
				Total Volume Lost	0	0					
Volumes											
Additions bbl			Losses bbl			Total Volumes bbl					
Mud Added	Weight Materials		Downhole	25	Left In Pit	Starting Volume	2842.1	Riser w/o Pipe	209.1		
Brine	Water		Cased Off		Trip Losses	Daily Additions	3.5	Casing w/o Pipe	383.2		
Base Fluid	Product	3.5	Left In Hole		Injected	Daily Losses	35	Open Hole w/o Pipe	856.6		
Recycled	Other		Discharged		Spill To Environment	Ending Volume	2810.6	String Displacement	72.7		
			SCE		Onshore Disposal	Net Change	-31.5	String Capacity	143.6		
			Evaporation		Returned			Total Hole w/ Pipe	1376.1		
			Other Losses	10				Total Active	1800.1		
								Total Reserve	1011.0		
IADC Hours											
Fishing				24							
Primary Currency USD			Secondary Currency			Totals USD					
Daily Product Cost		4140.91	Daily Product Cost		0.00	Primary Product		1676474.41			
Daily Tax		0.00	Daily Tax		0.00	Secondary Product		0.00			
Debit/Credit		0.00	Debit/Credit		0.00	Primary Engineering		68906.25			
Daily Engineering Cost		900.00	Daily Engineering Cost			Secondary Engineering		0.00			
Total Daily Cost		5040.91	Total Daily Cost		0.00	Primary Total		1745380.66			
Total Inventory Value		561151.39	Total Inventory Value		0.00	Secondary Total		0.00			
						Deck Load		622569 lb			
Products and Services											
Product		Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl
Bulk											
MIL-BAR		1000 kg	109						109	133.73	106.16
Oil Based Product											
CARBO-GEL		25 kg	288					5	283	5.60	7.09
MIL-LIME		25 kg	275					6	269	5.98	3.45
OMNI-COTE		55 USgal	10						10	0.30	0.16
OMNI-MUL		55 USgal	24					1	23	5.75	4.30
OMNI-PLEX		55 USgal	21					1	20	4.42	5.68
OMNI-TEC		55 USgal	20						20	3.00	2.45
PARA-TEQ		1 bbl	930						930		
SA 58		50 lb									
Water Based Product											
CAUSTIC SODA		25 kg	32						32		
MIL-GUAR		25 kg									