

ADVANTAGE Daily Drilling Fluids Report - 67

INTEQ

Rpt Date 11/Jan/2007			Well Name/No Bilabri D4			Section Name/No 12-1/4" Section #3			Mud System SYN-TEQ (PARA)						
Job# 1		Spud Date 09/Nov/2006			MD 2591.00 m		Progress 0.00 m		Present Activity Well Control						
Operator Peak Petroleum Indust. Limited			Company Rep Tom G.May / Peter Vermeulen			Contractor Dolphin Drilling Ltd			Contractor Rep Steve Milne / Terry Nanidis						
Field/Lease Bilabri			Blk/Co/Parish OML - 122 / Nigeria			Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN					
Drilling Assembly			Casing			Volumes	Pump Information								
Bit Gauge in	Mfr	Bit Model	OD in	ID in	Depth m	bbl	Model	Liner in	Stroke in	Eff %	Vol/Stk bbl	Stk Rate SPM	Circ Rate USgal/min		
12 1/4	HCC	PDC		19 1/2	172.50	Total Hole 1376.1	Continental Ensco FA-1600	6 1/2	12.00	97.0	0.1194	32	161		
Drill Collars		Drill Pipe		20	18 3/4	291.60	Continental Ensco FA-1600	6 1/2	12.00	97.0	0.1194	0			
OD in	ID in	Length m	OD in	ID in	Length m	13 3/8	12.415	800.00	Active Pits 494	Continental Ensco FA-1600	6 1/2	12.00	97.0	0.1194	0
8	3 1/4	6.57	5	4.276	2348.34		12 1/4	2591.00							
8	2 5/8	9.35	5	3	158.56				Tot Active 1870.1						
8	2 3/4	27.29							Circulation Times						
8	2 13/16	9.05							In Storage 966	Surface to Bit	min/stks		Total System	min/stks	
										Bottoms Up	min/stks				
Mud Properties					Max Ann Velocity			Hole Information							
Property		Fluid Spec	1	2	3	AV Riser	ft/min	Standpipe Pressure 40 psi		Water Depth 146.00 m					
Sample From			Flow Line	Active Pit		AV Casing	ft/min	Hole Flow USgal/min		Riser Booster Rate USgal/min					
Check Time			09:30	23:00		AV Open Hole	ft/min	Solids Analysis							
MD m			2591.00	2591.00		Vc Open Hole	ft/min	Property	1	2	3	4			
TVD m			2449.98	2449.98		Vc Drill Pipe	ft/min	LGS %	5.57	5.72					
Bit Depth m			2588.00	2588.00		Min Ann Velocity		LGS lb/bbl	50.77	52.15					
Inc deg			1.46	1.46		AV Riser	ft/min	HGS %	4.38	4.15					
Density ppg			9.30	9.30		AV Casing	ft/min	HGS lb/bbl	64.52	61.10					
Funnel Visc. sec/quart			85.0	88.0		AV Open Hole	ft/min	Avg Dens Sol sg	3.3045	3.2727					
Flow Line Temp degF			100.0	100.0		Bit Information									
Test Temp degF			98.0	95.0		Size	12 1/4 in								
Rheol Temp degF			120.0	120.0		Hours On Bit									
PV cP			30	32		Bit Number									
YP lbf/100ft^2			20	20		BHA Number	10	Rheology							
10sec Gel lbf/100ft^2			9	9		Depth In	2385.00 m	600 RPM	80	84					
10min Gel lbf/100ft^2			17	19		Bit RPM		300 RPM	50	52					
HTHP Filtrate cc			3.2	2.8		WOB	klbf	200 RPM	38	40					
HTHP Cake in/32			2.0	2.0		Nozzles	4x16:4x12	100 RPM	27	28					
HTHP Temp degF			250.0	250.0		Bit Hydraulics		6 RPM	10	10					
HTHP Pressure psi			500	500		TFA	1.2272 in^2	3 RPM	8	8					
Retort Water %			24.0	25.0		Nozzle Vel	ft/sec								
Retort Base Fluid %			64.0	63.0		Bit Press Loss	psi								
Retort Solids %			12.0	12.0		HHP / Area	HP/in^2	Hydraulic Analysis							
Corrected Solids %			10.0	9.9		HHP	%	Behavior Index (n)							
Oil:Water Ratio			73:27	72:28				Consistency Index (k) #sec^n/100ft^2							
Alk (Whole Mud-POM) cc/cc			1.90	1.80				ECD @ Bit Depth ppg							
Cl (Whole Mud-Clom) cc/cc			50000	52000				ECD @ Casing Shoe ppg							
Ca (Whole Mud-Caom) cc/cc			0	0		Fluid Comments/ Recommendations									
Excess Lime lb/bbl			2.5	2.3		Continue monitoring volumes while circulating. Monitor & maintain mud wt in/out the active at 9.3 ppg while continously utilising the degasser. Conditioned surface reserve volume at 9.3 ppg of mud received from Comrade. Inventory correctionfor Xcide-102. SURFACE ACTIVE VOL (9.3ppg) = (Act Pit #2 - 313 bbls + S/Traps - 150bb) = 463 bbls. RESERVE VOL(9.3 ppg) = (Pit #1 - 114bbls + pit #3 - 353bbls + pit 4 - 387bbls) = 854bbls. TOTAL USEABLE(9.3 ppg) = (Act Pit #2 - 313bbls + Res Pits 1,3, 4 - 854bbls) = 1167bbls. OTHER FLUIDS - Base Oil in Chemical pit - 55 bbls & Slug piit (9.2 ppg) - 59 bbls									
Brine Density sg			1.22	1.22											
NaCl % wt			0	0											
CaCl2 % wt			25	25											
Elect. Stab.V			511.0	521.0											
Sand %			0.50	0.50											
Drilling Comments															
Continue circ riser volume. F/C, open P/rams, F/C, circ down string f/693m. Max gas 2410 units. Reduce pumps. F/C, ok. RIH t/835m. CBU @ 30 spm, no losses. Close UPR, circ up C/K lines @ 15 spm, 6 bbls losses. F/C well, ok. Open U/ram, F/C on T/tank. CBU conventionally f/835 @ 35 spm. F/C, RIH f/835 t/978m. Circ conventionally down string @ 20 spm. Close UPR, circ remainder btms up through C/K, 25bbls losses @ 20 spm. CBU conventionally @ 20 spm, max gax 456 units. F/C, RIH t/TOF @ 1130m. CBU conventionally @ 20 spm. Max gas 1850 units.															
BHDF Fluids Rep Waboso Peter / Ifeanyi Nwosu		BHDF Rep Phone 234-803-402-0440		Warehouse Onne	Warehouse Phone 234-84-462609	Coordinator Lawson Ogaree	Daily Cost 16594.12 USD	Cumulative Cost 1795701.18 USD	Inventory Value 562676.99 USD	Page 1					
Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.															

ADVANTAGE Daily Drilling Fluids Report - 67



INTEQ

Rpt Date 11/Jan/2007		Well Name/No Bilabri D4		Section Name/No 12-1/4" Section #3		Mud System SYN-TEQ (PARA)	
Job# 1	Spud Date 09/Nov/2006		MD 2591.00 m		Progress 0.00 m		Present Activity Well Control
Operator Peak Petroleum Indust. Limited		Company Rep Tom G.May / Peter Vermeulen		Contractor Dolphin Drilling Ltd		Contractor Rep Steve Milne / Terry Nanidis	
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria		Area Offshore		Country/State Nigeria	
Rig BULFORD DOLPHIN							
Solids Control Equipment							
Name	#	Mfr	Hours hours	Screen Sizes	Act Volume Lost bbl	Res Volume Lost bbl	Comments
CENTRIFUGE	1		0.0		0.0	0.0	
CENTRIFUGE	2		0.0		0.0	0.0	
DESANDER	1		0.0		0.0	0.0	
DESILTER	1		0.0		0.0	0.0	
MUD CLEANER	1		0.0	175, 210	0.0	0.0	
SHALE SHAKER	1		0.0		0.0	0.0	
SHALE SHAKER	1		24.0	210, 2 x 175	2.0	0.0	
SHALE SHAKER	2		0.0		0.0	0.0	
SHALE SHAKER	2		24.0	3 x 175	2.0	0.0	
SHALE SHAKER	3		24.0	3 x 175	2.0	0.0	
SHALE SHAKER	3		0.0		0.0	0.0	
Total Volume Lost					6	0	
Volumes							
Additions bbl			Losses bbl			Total Volumes bbl	
Mud Added	Weight Materials		Downhole	97	Left In Pit	Starting Volume	2917.1
Brine	Water		Cased Off		Trip Losses	6	Riser w/o Pipe
Base Fluid	35	Product	7.5	Left In Hole	Injected	Daily Additions	42.5
Recycled		Other		Discharged	Spill To Environment	Daily Losses	124
				SCE	6	Ending Volume	2835.6
				Evaporation	Onshore Disposal	Net Change	-81.5
				Other Losses	15	Returned	
						String Displacement	72.7
						String Capacity	143.6
						Total Hole w/ Pipe	1376.1
						Total Active	1870.1
						Total Reserve	966.0
IADC Hours							
Well Control					24		
BHDF Fluids Rep		BHDF Rep Phone	Warehouse	Warehouse Phone	Coordinator	Daily Cost	Cumulative Cost
Waboso Peter / Ifeanyi Nwosu		234-803-402-0440	Onne	234-84-462609	Lawson Ogaree	16594.12 USD	1795701.18 USD
						Inventory Value	Page 2
Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.							

**BAKER
HUGHES**

Rpt Date 11/Jan/2007		Well Name/No Bilabri D4		Section Name/No 12-1/4" Section #3			Mud System SYN-TEQ (PARA)				
Job# 1	Spud Date 09/Nov/2006			MD 2591.00 m		Progress 0.00 m		Present Activity Well Control			
Operator Peak Petroleum Indust. Limited			Company Rep Tom G.May / Peter Vermeulen			Contractor Dolphin Drilling Ltd		Contractor Rep Steve Milne / Terry Nanidis			
Field/Lease Bilabri		Blk/Co/Parish OML - 122 / Nigeria			Area Offshore		Country/State Nigeria		Rig BULFORD DOLPHIN		
Primary Currency USD				Secondary Currency			Totals USD				
Daily Product Cost		15694.12		Daily Product Cost		0.00		Primary Product		1723194.93	
Daily Tax		0.00		Daily Tax		0.00		Secondary Product		0.00	
Debit/Credit		0.00		Debit/Credit		0.00		Primary Engineering		72506.25	
Daily Engineering Cost		900.00		Daily Engineering Cost				Secondary Engineering		0.00	
Total Daily Cost		16594.12		Total Daily Cost		0.00		Primary Total		1795701.18	
Total Inventory Value		562676.99		Total Inventory Value		0.00		Secondary Total		0.00	
								Deck Load		619922 lb	
Products and Services											
Product		Units	Start	Transferred In	Received	Returned	Lost	Daily Use	Final	Active Ending Concentrations lb/bbl	Reserve Ending Concentrations lb/bbl
Bulk											
MIL-BAR		1000 kg	100						100	129.25	114.15
Oil Based Product											
CARBO-GEL		25 kg	273					3	270	5.97	6.92
MIL-LIME		25 kg	269					29	240	5.32	4.61
OMNI-COTE		55 USgal	10						10	0.26	0.14
OMNI-MUL		55 USgal	22					2	20	5.38	4.97
OMNI-PLEX		55 USgal	17					1	16	4.76	6.42
OMNI-TEC		55 USgal	20						20	2.85	2.21
PARA-TEQ		1 bbl	879					35	844		
Water Based Product											
CAUSTIC SODA		25 kg	32						32		
MIL-GUAR		25 kg	50						50	0.26	0.11
OX-BAN		5 USgal	11						11		
Xanthan Gum		25 kg	39						39	0.44	0.19
XCIDE 102		55 USgal	8	-3					5	0.01	
LCM											
CALCIUM CARBONATE - FINE		25 kg	212					12	200	6.70	3.71
CALCIUM CARBONATE - MED		25 kg	490					10	480	6.96	2.96
MIL-PLUG - MEDIUM		25 kg	71						71	0.03	0.51
MIL-PLUG-COARSE		25 kg	168						168		
MIL-SEAL-COARSE		25 kg	180						180		
MIL-SEAL-FINE		25 kg	107						107	0.03	0.51
SOLUFLAKE C		50 lb	27						27	0.02	0.47
SOLUFLAKE F		50 lb	147						147	0.02	0.47
SOLUFLAKE M		50 lb	147						147	0.02	0.47
Other											
BLACK MAGIC SF T		25 kg	120						120		
CALCIUM CHLORIDE (97%)		25 kg	360						360	11.40	11.98
BHDF Fluids Rep		BHDF Rep Phone		Warehouse	Warehouse Phone		Coordinator	Daily Cost		Cumulative Cost	Inventory Value
Waboso Peter / Ifeanyi Nwosu		234-803-402-0440		Onne	234-84-462609		Lawson Ogaree	16594.12 USD		1795701.18 USD	562676.99 USD
Page 3											
Any opinion and/or recommendation, expressed orally or written herein, has been prepared carefully and may be used if the user so elects, however, no representative or warranty is made by ourselves or our agents as to the correctness or completeness, and no liability is assumed for any damages resulting from the use of same.											