

TECHNICAL SPECIFICATIONS

PRODUCT DETAILS.

Dimension (mm)	Weight (kg)	Unit Weight (kg/m²)	Surface Finish	Sheet/m²
8x1,200x2,400	41.3	14.3	Flat, Straight Grain	0.347
10x1,200x2,400	51.6	17.9		
12x1,200x2,400	61.9	21.5		

PROPERTY	SPECIFICATION	STANDARDS
FIRE RESISTANCE PROPERTY		
Fire Classification of Construction Products and Building Elements	Class A1	EN 13501-1:2018
DURABILITY PROPERTY		
Freeze/ Thaw Resistance	Pass	EN12467:2012
Warm Water Resistance	Pass	EN12467:2012
Heat/ Rain Resistance	Pass	EN12467:2012
Soak/ Dry Resistance	Pass	EN12467:2012

Remarks: EMC Stands for Equilibrium Moisture Content

PROPERTY		UNIT	SPECIFICATION	STANDARDS
PHYSICAL PROPERTY				
Tolerance	Thickness	mm.	± 0.20	EN12467:2012
	Width	mm.	± 1.0	
	Length	mm.	± 1.0	
	Straightness of Edge	mm./ m.	≤ 0.1%	
Density		Kg/m3	1,600 ≤ 50	EN12467:2012
MOR Average Both MD And CD (Wet Condition)		MPa	≤ 18	EN12467:2012
MOR OF MD (Wet Condition)		MPa	≤ 23	EN12467:2012
MOR OF CD (Wet Condition)		MPa	≤ 13	EN12467:2012
MOE OF MD (Wet Condition)		MPa	≤ 11,000	EN12467:2012
Moisture Content		%	≤ 12.0	EN12467:2012
Water Absorption		%	≤25	EN12467:2012
Water Permeability			Pass	EN12467:2012
Thermal Conductivity(k)		W/ m-K	0.162	ASTM C 518-10



MOISTURE RESISTANT



FIRE RESISTANT



TERMITE PROOF