

REG NO: 22TD0053 NAME: MOHAMED B SIRAJUDEEN

YEAR/SEM/SEC: Y3/S6/B

ONLINE SHOPPING CART

SOURCE CODE :

ProductBean.java

```
package lab.wt.cart.bean; public
class ProductBean
{
private String brand; private String hardDisk; private String gCard; private String ram;
//Go To Source -> Generate getters and setters public
String getBrand()
{
return brand;
}
public void setBrand(String brand)
{
this.brand = brand;
}
public String getHardDisk()
```

```
{
return hardDisk;
}

public void setHardDisk(String hardDisk)
{
this.hardDisk = hardDisk;
}

public String getgCard()
{
return gCard;
}

public void setgCard(String gCard)
{
this.gCard = gCard;
}

public String getRam()
{
return ram;
}

public void setRam(String ram)
{
this.ram = ram;
}

//Go To Source -> Generate toString @Override public
String toString()
{
```

```
return "ProductBean [brand=" + brand + ", gCard=" + gCard + ", hardDisk="+  
hardDisk + ", ram=" + ram + "];"
```

```
}
```

```
}
```

```
ShoppingCartServlet.java package lab.wt.cart.controller; import java.io.IOException;  
import java.util.Vector;
```

```
import javax.servlet.RequestDispatcher; import javax.servlet.ServletContext; import  
javax.servlet.ServletException; import javax.servlet.http.HttpServlet;
```

```
import javax.servlet.http.HttpServletRequest; import  
javax.servlet.http.HttpServletResponse; import javax.servlet.http.HttpSession;
```

```
import lab.wt.cart.bean.ProductBean;
```

```
public class ShoppingCartServlet extends HttpServlet
```

```
{
```

```
private static final long serialVersionUID = 1L; Vector<ProductBean>list=new  
Vector<ProductBean>(); public ShoppingCartServlet()
```

```
{
```

```
super();
```

```
}
```

```
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws  
ServletException, IOException
```

```
{
```

```
}
```

```
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws  
ServletException, IOException
```

```
{
```

```
HttpSession ses = request.getSession(true); ServletContext sc = getServletContext();
```

```
ProductBean pb=new ProductBean();
```

```
int choice=Integer.parseInt(request.getParameter("h1")); System.out.println(choice);  
switch(choice)  
{  
    //in this case when the entries are made it gets added in the list
```

case 1:

```
String brand=request.getParameter("brand"); String hardDisk=request.getParameter("hd");  
String gCard=request.getParameter("gCard");  
  
String ram=request.getParameter("ram"); pb.setBrand(brand);  
pb.setHardDisk(hardDisk); pb.setgCard(gCard);  
  
pb.setRam(ram); list.add(pb); ses.setAttribute("manageOrder",list);  
System.out.println(list);  
  
RequestDispatcher rDispatch=request.getRequestDispatcher("/Cart.jsp");  
if(rDispatch!=null)  
{  
    rDispatch.forward(request, response);  
}  
  
break;
```

case 2:

```
list.clear(); ses.setAttribute("manageOrder", "list"); System.out.println(list);  
  
RequestDispatcher rDispatch2=request.getRequestDispatcher("/Cart.jsp");  
if(rDispatch2!=null)  
{  
    rDispatch2.forward(request, response);  
}  
  
break;  
  
} // switch ends
```

```
}// doPost ends
```

```
}// ShoppingCartServlet ends
```

Cart.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Shopping Cart</title>
</head>
<body>
<h1 align="center">Shopping Cart</h1>
<form action="ShoppingCartServlet" method="post">
<br></br>
<h3 align="center"><b>ORDER PRODUCTS</b></h3>
<table align="center">
<tr>
<td>BRAND</td>
<td><select name="brand">
<option value="hp">hp-2000-2116TU</option>
<option value="dell">DELL-Vostro 2420</option>
<option value="sony">SONY-VAIO E14125</option>
<option value="acer">ACER-Aspire V5-471P</option>
</select>
</td>
```

```
</tr>
.<tr><td> </td></tr>
<tr>

<td>HARD DISK</td>

<td>

<select name="hd">

<option value="500GB">500 GB</option>

<option value="750GB">750 GB</option>

<option value="1TB">1 TB</option>

</select>

</td>

</tr>

<tr><td> </td></tr>

<tr>

<td>GRAPHICS CARD</td>

<td><select name="gCard">

<option value="nVIDIA">nVIDIA</option>

<option value="Radeon">Radeon</option>

<option value="Intel">Intel</option>

</select>

</td>

</tr>

<tr></tr>

<tr>

<td>RAM</td>

<td>

<select name="ram">

<option value="2GB">2GB</option>
```

```

<option value="4GB">4GB</option>
<option value="6GB">6GB</option>
</select>
</td>
</tr>
<tr><td> </td></tr>
<tr><td> </td> </tr>
</table>
<table align="center">
<tr>
<td><input type="submit" name="save" value="Add To Cart"/></td>
<td><input type="hidden" name="h1" value="1"/></td>
</tr>
</table>
</form>
<form action="ShoppingCartServlet" method="post">
<table align="center">
<tr>
<td><input type="hidden" name="h1" value="2"/></td>
<td><input type="submit" name="cancel" value="CANCEL"/></td>
</tr>
</table>
</form>
<form>
<table align="center">
<tr align="center">
<td WIDTH="500"><a href="DisplayOrder.jsp">Display Order</a></td>

```

```
</tr>
</table>
</form>
</body>
</html>
```

DisplayOrder.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<%@page import="java.util.Vector"%>
<%@page import="lab.wt.cart.bean.*" %>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Display Order</title>
</head>
<body background="Image.jpg">
<h1 align="center">Display Order</h1>
<br></br>
<br></br>
<center><h3>The Products you have added into the cart are displayed
below</h3></center>
<%
if(session.getAttribute("manageOrder")!=null)
{
%>
```



```

<form action="ShoppingCartServlet" method="post">
<h3 align="center" >Ordered Products</h3>
<table align="center" border="2">
<tr>
<th>BRAND</th>
<th>HARD DISK</th>
<th>GRAPHICS CARD</th>
<th>RAM</th>
</tr>
<% Vector<ProductBean>list2=new Vector<ProductBean>();
list2=(Vector<ProductBean>)request.getSession().getAttribute("manageOrder");
for(ProductBean pb1:list2)
{
%>
<tr>
<td><%=pb1.getBrand()%></td>
<td><%=pb1.getHardDisk()%></td>
<td><%=pb1.getgCard()%></td>
<td><%=pb1.getRam()%></td>
</tr>
<%
}
}
%>
</table>
</form>
</body>
</html>

```

OUTPUT:



