

**Original Manuscript ID:** Access-2025-40211

**Original Article Title:** “Landfill Site Allocation Multi-Objective Optimization with NSGA-II: A Case Study on Fogo Island, Cape Verde”

**To:** IEEE Access Editor

**Re:** Response to reviewers

Dear Editor and Reviewers,

We sincerely thank you for the thorough and constructive evaluation of our manuscript. The reviewers' comments have led to substantial improvements, and we are grateful for the opportunity to revise and resubmit our work.

We have carefully addressed all concerns raised by both reviewers. The key enhancements in this revised version include: (1) a dedicated sensitivity analysis section rigorously justifying  $k=3$  across  $k \in \{2, \dots, 10\}$  with a 6-panel figure and quantitative table; (2) an explicit discussion of operational limitations specific to Small Island Developing States, with spatial proxies formally connected to transport and construction costs; (3) comprehensive convergence and robustness documentation, including 30 independent runs with fixed seeds 1–30, explicit stopping criteria, and HV convergence curves; (4) complete AHP transparency, including the full  $11 \times 11$  pairwise comparison matrix, the exact Consistency Ratio ( $CR = 0.0564 < 0.10$ ), and a new figure illustrating the dual role of AHP in the framework; and (5) a verified public reproducibility package (Zenodo DOI + GitHub) with all data, code, and documented library versions.

All reported results are validated against a complete deterministic Exhaustive Search over the 2.90 million feasible configurations of the constrained combinatorial space, providing mathematical proof that the NSGA-II Pareto front captures 99.50% of the true hypervolume with a 4.0-fold computational speedup.

We are submitting: (a) this point-by-point response document; (b) a highlighted revised manuscript (PDF); (c) a clean final manuscript (LaTeX + PDF); and (d) the public data and code repository (Zenodo/GitHub).

We believe the revised manuscript fully addresses all reviewer concerns and meets IEEE Access publication standards.

Respectfully submitted on behalf of all authors,

MSc. Julio Leite Azancort Neto

Ph.D. Candidate in Applied Computing

Main and Corresponding Author

**Reviewer #1, Concern #1 (Justification of k):** The manuscript fixes  $k=3$  (number of facilities) without providing a rationale or evidence that conclusions are stable across nearby  $k$  values.

**Author response:**

We sincerely thank the reviewer for this critical observation. We acknowledge that the original manuscript lacked a comprehensive justification for fixing the cardinality constraint at  $k=3$ , and we have substantially revised the manuscript to address this concern with a rigorous, multi-faceted rationale that is now formally validated through a comprehensive sensitivity analysis.

The decision to set  $k=3$  is not an arbitrary parameter choice but rather a deliberate modeling constraint dictated by the unique geomorphological, administrative, and logistical realities of Fogo Island. This constraint is grounded in established regional planning strategies and is essential for ensuring both operational efficiency and resilience in this Small Island Developing State (SIDS) context. The detailed justification is now explicitly integrated throughout the revised manuscript and is supported by the following key arguments:

1. **Geomorphological and Infrastructural Constraints.** Fogo Island's topography is dominated by a central volcanic cone (Pico do Fogo) rising to 2,829 meters, which imposes a peripheral road network that prevents efficient cross-island transportation. This geographical constraint naturally partitions the island into distinct coastal sectors, making a decentralized waste management approach the only logistically viable option. A centralized system ( $k=1$  or  $k=2$ ) would impose extreme transport distances and would be vulnerable to complete operational failure if the single road network were disrupted by volcanic activity or landslides.
2. **Administrative and Municipal Alignment.** Fogo Island is administratively divided into three primary municipal sectors: Sao Filipe, Santa Catarina, and Mosteiros. Each sector has distinct population distributions and waste generation patterns. A  $k=3$  configuration allows for one landfill facility to be strategically placed to service each municipal sector independently, ensuring comprehensive island-wide coverage while minimizing intra-sector transport distances. This approach forms a spatial triangulation that is both geometrically optimal and administratively coherent.
3. **Operational Resilience and Disaster Risk Mitigation.** As an active volcanic island, Fogo is highly susceptible to natural hazards including volcanic eruptions, landslides, and seismic activity, which can sever sections of the peripheral road network. A  $k=3$  configuration provides essential operational redundancy: if a natural disaster isolates one sector by blocking road access, the other two facilities can continue to operate independently, preventing a complete collapse of waste management services. This resilience is a critical design requirement for SIDS, where infrastructure vulnerability is a primary concern [49].
4. **Alignment with Regional Planning Strategy.** The  $k=3$  constraint aligns directly with the regional planning framework established by Andrade and Barbosa (2015) [23], who conducted the foundational multi-criteria analysis for landfill siting on Fogo Island. Our optimization model formalizes and extends their strategic recommendations within a robust computational framework.

Regarding the stability of conclusions for alternative  $k$  values, we have now conducted a formal sensitivity analysis for  $k$  in the set  $\{2, 3, 4, 5, 6, 7, 8, 10\}$ , the results of which are presented in the new subsection "Sensitivity Analysis: Justification of the Cardinality Constraint" (Section II-E) and summarized in Table 7 of the revised manuscript. This analysis operates on two complementary levels.

From a purely algorithmic perspective, the normalized hypervolume (HV\_norm) peaks at  $k=3$ , which constitutes the elbow point of the performance curve [43]. Beyond  $k=3$ , diminishing returns are observed, as additional facilities yield progressively smaller quality gains relative to the theoretical maximum volume of the objective space. Panel (a) of Figure 4, a six-panel comprehensive visualization, clearly marks  $k=3$  as the

point at which the normalized hypervolume is maximized. Panel (b) further confirms that per-facility efficiency ( $HV\_norm/k$ ) declines monotonically from  $k=2$ , demonstrating that each additional facility beyond  $k=3$  yields progressively smaller algorithmic returns per unit of investment.

From an operational perspective, the selection of  $k$  must be governed by the hard resource limitations of Fogo Island, which define a feasible range of  $k \leq 3$  due to four hard constraints: (i) Municipal Budget Constraints: Cape Verde's municipal waste management budgets, constrained by limited tax revenue and dependency on international development aid, cannot sustain more than three facilities simultaneously [46]; (ii) Administrative Capacity Limitations: operating multiple waste management facilities requires trained personnel in environmental engineering and regulatory compliance, professions scarce in SIDS contexts [47]. Fogo Island's municipal administration has demonstrated capacity to manage up to three decentralized facilities, and configurations with  $k > 3$  would exceed available human resources; (iii) Waste Generation Scale: with a population of approximately 37,000 inhabitants generating an estimated 18,500 tons/year of municipal solid waste,  $k=3$  provides facilities serving approximately 12,300 inhabitants each. Configurations with  $k > 3$  would result in underutilized facilities serving fewer than 10,000 inhabitants per facility, violating minimum economic viability thresholds established in waste management planning guidelines for island communities [23], [48]; and (iv) Alignment with Regional Planning Policy: the  $k=3$  configuration aligns with established regional planning frameworks and municipal development plans already approved by Cape Verde's Ministry of Environment [23].

Within the operationally feasible range ( $k \leq 3$ ), the sensitivity analysis provides definitive quantitative evidence supporting the selection of  $k=3$  over  $k=2$ . As detailed in Table 7, the  $k=3$  configuration achieves a 249% improvement in Hypervolume (0.022 versus 0.006) and generates 59% more Pareto-optimal solutions (150 versus 95) compared to the  $k=2$  alternative. Furthermore, the three-site configuration provides essential operational redundancy and backup capacity, effectively mitigating the critical single-point-of-failure risk that a  $k=2$  system would create in the event of road network disruption due to natural disasters. Panel (e) of Figure 4 also confirms that Pareto front diversity saturates at the population size limit of 150 solutions for  $k \geq 3$ , indicating that the full diversity of the trade-off space is being captured at  $k=3$  without any loss of solution breadth.

Therefore,  $k=3$  is simultaneously the elbow point of the normalized hypervolume curve and the upper bound of the operationally feasible range, making it the natural constrained optimum for this SIDS context. The sensitivity analysis confirms that  $k=3$  is not merely a tunable optimization parameter but rather a hard, problem-defining constraint derived from the island's inherent geographical, administrative, and economic characteristics.

#### **Author action:**

We have comprehensively updated the manuscript by incorporating rigorous justifications for the fixed cardinality constraint ( $k=3$ ) throughout multiple sections, including a new dedicated subsection presenting formal sensitivity analysis results. The specific additions and modifications are detailed below:

1. New Sensitivity Analysis Subsection (Section II-E, Pages 8-9). We added a new subsection entitled "Sensitivity Analysis: Justification of the Cardinality Constraint" that provides a formal quantitative validation for the  $k=3$  selection. This subsection presents a systematic sensitivity analysis conducted for  $k$  in the set  $\{2, 3, 4, 5, 6, 7, 8, 10\}$ , evaluating the trade-offs between algorithmic performance and the operational constraints characteristic of Small Island Developing States. The analysis demonstrates that while the normalized hypervolume ( $HV\_norm$ ) peaks at  $k=3$  from a purely algorithmic perspective, the operationally feasible range is constrained to  $k \leq 3$  due to four hard

constraints: municipal budget limitations, administrative capacity, waste generation scale, and regional planning alignment. The added text includes:

"From a purely algorithmic perspective (Figure 4), the analysis reveals that the normalized hypervolume (HV\_norm) peaks at  $k=3$ , which constitutes the elbow point of the performance curve [43]. Beyond  $k=3$ , diminishing returns are observed, with HV\_norm declining monotonically as additional facilities yield progressively smaller quality gains relative to the theoretical maximum volume of the objective space."

2. Quantitative Results Table (Table 7, Page 9). We incorporated a comprehensive "K-Value Sensitivity Analysis Results" table presenting the quantitative metrics for each tested  $k$  value, including Hypervolume (HV), Efficiency (HV/ $k$ ), Growth percentage, Geographic Spread (km), and Viability Assessment. This table explicitly highlights  $k=3$  as simultaneously the elbow point of the performance curve (peak HV\_norm) and the maximum feasible configuration for SIDS contexts, while demonstrating that configurations for  $k=4$  through  $k=10$  exceed the operational constraints of Fogo Island (budget exceeded, administrative capacity exceeded, or overprovisioned).
3. Six-Panel Visualization (Figure 4, Pages 9-10). We added a comprehensive multi-panel figure that visually communicates the sensitivity analysis results from six analytical perspectives: (a) normalized hypervolume progression versus  $k$ , clearly identifying  $k=3$  as the elbow point; (b) per-facility efficiency (HV\_norm/ $k$ ) declining monotonically, confirming diminishing returns beyond the elbow; (c) average inter-facility distance of the best-compromise solution at each  $k$ ; (d) HV growth rate (%) revealing that incremental quality gains become marginal or negative beyond  $k=3$ ; (e) solution diversity confirming Pareto front saturation at the population size limit of 150 solutions for  $k \geq 3$ ; and (f) a normalized multi-criteria heatmap comparing HV Quality, Geographic Spread, and Efficiency dimensions across all tested  $k$  values.
4. Introduction Section (Section I, Pages 1-2). We added a new paragraph establishing the rationale for  $k=3$  at the outset of the paper, ensuring that readers understand the constraint from the very beginning:

"A pivotal modeling decision in this research is the rigorous justification of the fixed cardinality constraint of three facilities ( $k=3$ ). This parameter is dictated by the unique geomorphological structure of Fogo Island, where a central volcanic cone rising to 2829 meters imposes a peripheral road network that prevents cross-island transport. A three-site configuration provides essential operational redundancy: multiple facilities prevent single-point-of-failure scenarios, ensuring that if one facility becomes inaccessible due to road blockages (landslides, volcanic activity), the remaining facilities can maintain waste management services for the island population."

5. Problem Formulation (Section II-D, Page 7). We expanded the technical description of the cardinality constraint to explicitly link  $k=3$  to administrative divisions, regional planning strategies, and SIDS-specific operational constraints:

"In this study, the cardinality constraint is strictly set to  $k=3$ . This choice is strategically driven by operational constraints specific to Small Island Developing States (SIDS), where  $k=3$  represents the maximum viable configuration given municipal budget limitations, administrative capacity constraints, and waste generation scale, as validated through comprehensive sensitivity analysis. A three-site configuration ensures a decentralized waste management system providing operational redundancy, minimizing average transport distances over the island's restrictive conical topology in accordance with regional planning strategies [23]."

6. Conclusion Section (Section IV, Pages 20-21). We reinforced the operational resilience argument and connected it to the broader SIDS context:

"Furthermore, the multi-site configuration ( $k=3$ ) provides essential operational resilience, a priority for waste management in Small Island Developing States (SIDS) [9]. While the selected sites are geographically proximate, this redundancy ensures that if one facility becomes temporarily inaccessible due to natural hazards, the remaining facilities can maintain waste management services. Fogo Island is susceptible to natural hazards, including landslides and volcanic activity, which can sever sections of the single peripheral road. The proposed decentralized configuration ensures that in the event of a road blockade in one sector, the remaining two facilities can absorb the operational load, preventing complete service disruption."

These comprehensive revisions ensure that the  $k=3$  constraint is now rigorously justified through both qualitative argumentations grounded in real-world geographical, administrative, and operational requirements, and quantitative sensitivity analysis demonstrating its optimality within the feasible operational range for Small Island Developing States.

---

**Reviewer #1, Concern #2 (Operational Realism): The model formulation omits capacity, coverage/service reach, and transport cost components that connect siting choices to system performance.**

**Author response:**

We thank the reviewer for this valuable observation regarding the operational realism of the proposed model. We acknowledge that the original manuscript did not sufficiently address the absence of explicit capacity constraints, service coverage modeling, and detailed transportation cost calculations. These are indeed critical components for a fully operational waste management system. However, we must clarify that the scope of this study is deliberately focused on strategic locational suitability rather than dynamic operational logistics. This decision is not an oversight but a methodologically justified response to the severe data limitations inherent to Small Island Developing States (SIDS), where granular operational data is often unavailable or unreliable. We address each missing component in detail below:

1. Capacity Constraints and Landfill Lifespan. Modeling facility capacity and lifespan projections requires detailed, time-series data on daily waste generation rates per municipality, waste density and composition, population growth projections, and seasonal variations in waste production. For Fogo Island, this granular data is not publicly available. National-level estimates exist, but disaggregated municipal data with the temporal resolution necessary for capacity planning does not. Without this foundational data, any capacity constraint modeling would rely on assumptions that could introduce more uncertainty than insight, undermining rather than strengthening the scientific validity of the results.
2. Service Coverage Areas. Defining formal service coverage zones would require detailed waste generation distribution maps, municipal service boundaries and collection zones, and household-level waste production estimates. This level of spatial disaggregation is not available for Fogo Island. The centroid-based representation used in our study, where each 1 km by 1 km spatial unit is represented by its geometric centroid, is the highest spatial resolution feasible given available data sources. This limitation is acknowledged in the revised manuscript and positioned as a direction for future research.

3. **Transportation Costs.** Calculating precise vehicle routing costs would require municipal fleet composition (vehicle types, capacities, fuel consumption), road network topology with speed limits and conditions, current fuel prices and maintenance costs, and labor costs for collection crews. This operational data is not documented in publicly accessible sources for Cape Verde municipalities. Therefore, explicit monetary cost accounting was not feasible within the scope of this study.

**Our Methodological Approach to Operational Proxies.** While we could not model these operational components explicitly, the revised manuscript now makes explicit how robust spatial proxies within the optimization framework indirectly capture operational considerations:

Regarding transport and access costs: in the absence of granular vehicle routing data, a common limitation in Small Island Developing States [9], the distance to the road network serves as a spatial proxy for transport and access infrastructure costs, a practice widely adopted in macro-regional landfill siting studies [16], [36]. This sentence was explicitly added to Section II-C of the revised manuscript. Sites closer to existing roads minimize the need for new access infrastructure, reducing both construction and ongoing transportation costs. The permeability criterion within the Implementation Cost objective (f1) captures the additional capital investment required for hydraulic containment systems in high-permeability zones [42], functioning as a proxy for long-term operational containment costs. Slope within f1 captures earthwork and construction costs that directly influence the economic feasibility of facility implementation.

Regarding service coverage: the triangular network configuration enforced by the  $k=3$  cardinality constraint and the 10 km geographic dispersion constraint inherently addresses service coverage by ensuring that each of the three municipal sectors has access to a dedicated landfill facility, minimizing average transport distances across the island's restrictive conical topology. The geographic assessment conducted in Section II-H quantifies this coverage explicitly through the triangulation analysis, confirming that the Best Compromise Solution achieves a triangular coverage area of 52.82 km<sup>2</sup> and an average inter-facility spread of 13.41 km, representing a 50.3% improvement in geographic distribution relative to the unconstrained baseline.

Regarding capacity considerations: the selection of exactly  $k=3$  facilities, as rigorously justified in Section II-E, was itself calibrated against the island's waste generation scale of approximately 18,500 tons/year for 37,000 inhabitants. This configuration provides facilities serving approximately 12,300 inhabitants each, a scale that balances operational efficiency with service coverage within the economic viability thresholds documented in waste management planning guidelines for island communities [23], [48].

It is also important to note that these operational proxies are not a limitation unique to this study but rather reflect standard practice in strategic landfill siting frameworks at a regional scale. Studies by Karimi et al. [36] and Feizi et al. [16], among others cited in the revised manuscript, similarly employ spatial distance proxies for transport and access costs when detailed vehicle routing data is unavailable, precisely because this methodological approach is appropriate for the strategic planning stage that precedes operational logistics modeling.

We fully acknowledge that integrating explicit operational logistics would significantly enhance the practical applicability of this framework and represents an important direction for future research. The revised manuscript now includes a dedicated discussion of these limitations in the Conclusion section and proposes concrete directions for future work, including: (1) implementation of field monitoring systems to collect granular waste generation data; (2) parameterization of Vehicle Routing Problems (VRP) with volumetric capacity constraints [27]; and (3) dynamic modeling of landfill lifespan based on local waste composition data. These enhancements would transform the current strategic siting framework into a fully operational decision support system.

## Author action:

We updated the manuscript by explicitly acknowledging the operational limitations of the study, formally connecting the spatial proxies to their operational counterparts, and positioning the omitted components as a clear roadmap for future research. The specific additions and modifications are detailed below:

1. Spatial Proxy Connection for Transport Costs (Section II-C, Page 6). We added a sentence explicitly connecting the road network accessibility criterion to transport cost proxies, providing the operational realism link that was absent in the original manuscript:

"In the absence of granular vehicle routing data, a common limitation in Small Island Developing States [9], the distance to the road network serves as a spatial proxy for transport and access infrastructure costs, a practice widely adopted in macro-regional landfill siting studies [16], [36]."

This addition appears in the paragraph describing accessibility criteria, immediately after the sentence explaining that distance to the road network was calculated as the minimum Euclidean distance from each candidate centroid to the nearest road segment geometry. The explicit reference to vehicle routing data limitations [9] and the two supporting citations [16], [36] ground this proxy approach in established methodological practice.

2. Operational Scope Clarification (Section II-D, Page 7). We added language in the Problem Formulation subsection emphasizing that the study addresses strategic locational suitability as a foundational step, explicitly acknowledging that operational logistics modeling would be a natural extension requiring additional data collection efforts. The cardinality constraint justification now explicitly links  $k=3$  to waste generation scale, noting that this configuration provides facilities serving approximately 12,300 inhabitants each, calibrating the solution to operational viability thresholds [23], [48].
3. Limitations Section (Section IV, Page 20-21). We added a comprehensive paragraph in the Conclusion section explicitly detailing the operational constraints and data limitations that prevented the inclusion of capacity, coverage, and transport cost modeling:

"Despite these advances, the study operates under specific constraints typical of Small Island Developing States (SIDS). First, the analysis utilized a centroid-based representation, which may reduce spatial precision relative to actual polygon footprints. Second, the optimization focused on strategic locational suitability rather than dynamic operational logistics. Specifically, capacity constraints and landfill lifespan projections were not modeled due to the absence of granular, publicly available data on daily waste generation rates and specific waste density for the municipality. Furthermore, precise vehicle routing costs were not explicitly calculated due to the lack of documented data on the municipal fleet composition. Consequently, the Implementation Cost objective relied on robust spatial proxies rather than monetary accounting."

4. Future Work Proposal (Section IV, Page 21). We added explicit recommendations for addressing these operational gaps in subsequent research:

"Future research should address these gaps by implementing field monitoring systems to parameterize local Vehicle Routing Problems (VRP), allowing for the inclusion of volumetric capacity constraints. Additionally, comparative studies with other metaheuristics such as SPEA2 [52] or MOPSO [53], coupled with participatory methods to capture stakeholder preferences directly within the optimization loop, would further refine the applicability of this framework."

These additions ensure transparency regarding the study's scope and limitations while demonstrating methodological awareness of the operational components that lie beyond the current data constraints. The revised manuscript now presents a clear progression from the current strategic siting framework to a fully operational decision support system, with the intermediate steps explicitly documented.

---

**Reviewer #1, Concern #3 (Convergence and Robustness Evidence): No report of random seeds, explicit stopping criteria, or convergence indicators/curves (e.g., hypervolume,  $\epsilon$ /IGD), nor a parameter sensitivity summary.**

We sincerely thank the reviewer for this critical comment. We acknowledge that the original manuscript lacked comprehensive evidence of the algorithm's convergence behavior and robustness. The revised manuscript now provides a multi-layered validation framework that goes significantly beyond standard practice in applied optimization research, addressing each component of the reviewer's concern in detail.

1. **Algorithmic Parameters and Explicit Stopping Criteria.** The revised manuscript includes Table 8: NSGA-II Configuration Parameters (Section II-F), which fully documents all algorithmic settings used in this study. The stopping criterion is explicitly set to a fixed budget of 200 generations, a value selected based on preliminary convergence tests that demonstrated stable asymptotic behavior well before this limit. The complete parameter set documented in Table 8 includes Population Size (150), Max. Generations (200), Crossover Operator (Two-Point Crossover), Mutation Probability ( $1/N$ , where  $N=473$  is the chromosome length, yielding approximately 0.002), Selection Method (Binary Tournament), Selection Criteria (Feasibility + Rank + Crowding), Cardinality Constraint (Repair Operator,  $k=3$ ), Distance Constraint (Inequality,  $d_{\min}=10$  km), HV Reference Point (Dynamic, Nadir + epsilon), Objective Evaluation (Vectorised, population-level), and Parallel Execution (30 runs, process-based, 11 workers). To ensure full statistical reproducibility, the 30 independent runs were executed with fixed random seeds 1 through 30 (GLOBAL\_SEED = 1 for the reference run), enabling exact replication of all reported results, as documented in both Table 8 and the publicly archived code repository (Appendix A).
2. **Convergence Indicators: Hypervolume Evolution Analysis.** The revised manuscript includes Figure 5: Hypervolume Convergence History (Section III-B), which provides rigorous quantitative evidence of the algorithm's convergence dynamics across all 30 independent runs. The Hypervolume (HV) indicator is widely recognized as the most comprehensive performance metric for multi-objective optimization, as it simultaneously captures both convergence toward the Pareto front (accuracy) and the diversity of solutions along the trade-off surface (spread) [61]. The convergence analysis reveals two distinct and clearly identifiable phases. In the exploration phase, spanning approximately the first 18% of the evolutionary timeline, a steep ascent in solution quality was observed, with the mean hypervolume reaching 90% of its final value by generation 36, achieving a net performance gain of 182.5% relative to the initialization at generation 1 (from  $HV = 0.00758$  to  $HV = 0.02141$  at generation 200). In the stabilization phase spanning generations 37 to 200, the metric stabilized asymptotically. Statistical analysis of the final 50 generations revealed a standard deviation of  $\sigma = 8.31 \times 10^{-5}$  to the power of -5 across mean hypervolume values, with generation-to-generation increments averaging  $8.10 \times 10^{-6}$  to the power of -6, providing empirical evidence that the algorithm reached a robust approximation of the Pareto front without stagnation or genetic drift. Across the 30 independent runs, the final hypervolume ranged from 0.02021 to 0.02184, with a mean of  $0.02141 \pm 0.000408$ , confirming consistent convergence behavior regardless of the initial random seed.



3. Custom Repair Operator for Feasibility Enforcement. A critical methodological feature of this study is the custom Repair Operator (Algorithm 1, Section II-F), which enforces the cardinality constraint ( $k=3$ ) deterministically after each crossover and mutation step. This ensures that 100% of solutions entering fitness evaluation are feasible, enabling genuine multi-objective search across the full constrained solution space. Unlike penalty functions, which distort the fitness landscape and require parameter tuning, and unlike death penalty strategies, which discard infeasible solutions and reduce population diversity, repair operators systematically correct constraint violations while preserving genetic diversity [59]. The repair mechanism operates as follows: if an offspring vector has more than  $k$  sites selected, it randomly removes the excess selections until exactly  $k$  remain; if fewer than  $k$  are selected, it randomly adds selections from the unselected pool until exactly  $k$  are present. Algorithm 1 formally documents this procedure. The Distance-Aware Sampling operator (Algorithm 2) further complements the repair operator by generating initial populations that already satisfy the 10 km geographic dispersion constraint, significantly reducing the proportion of infeasible solutions in the first generation and accelerating convergence toward the feasible region.
4. Multiple Independent Runs and Statistical Robustness. Since NSGA-II is a stochastic algorithm, the validation analysis reports statistical indicators (mean and standard deviation) over 30 independent runs with distinct fixed seeds, as documented in Section II-G-3. This approach ensures that the reported results are not artifacts of a single fortunate random initialization but rather represent the algorithm's consistent performance across different stochastic realizations. The per-run HV statistics are provided in the results summary, documenting the individual performance of each of the 30 runs, from which the consistency of convergence can be directly verified.
5. Formal Validation Metrics: HV Gap, Optimality Gap, GD, and IGD. The revised manuscript defines and applies four complementary validation metrics in Section II-G-2, formally quantifying the reliability of the NSGA-II against the True Pareto Front obtained via exhaustive enumeration: (1) the Hypervolume Gap ( $\delta_{HV}$ , Eq. 15), which measures the relative HV difference between the heuristic approximation and the True Pareto Front; (2) the Optimality Gap ( $\delta_m$ , Eq. 16), which measures the absolute deviation between NSGA-II's extreme solutions and the global optima for each isolated objective; (3) the Generational Distance (GD, Eq. 17), which quantifies convergence accuracy by measuring the average Euclidean distance from solutions in the approximation set to the nearest member of the True Pareto Front [62]; and (4) the Inverted Generational Distance (IGD, Eq. 18), which assesses how well the approximation set covers the full extent of the True Pareto Front, capturing both convergence and diversity simultaneously.
6. Deterministic Validation: Exhaustive Search Benchmark. The most significant contribution to convergence validation in this study is the deterministic benchmarking framework (Section II-G), which provides mathematical proof of the algorithm's convergence to the true global optima. This goes far beyond standard convergence indicators by comparing the NSGA-II results against the complete set of exact solutions obtained through full combinatorial enumeration. The combinatorial solution space contains  $|\Omega| = C(473, 3) = 17,525,596$  possible configurations. After applying the geographic dispersion constraint ( $d_{min} = 10$  km), the pre-filtering procedure identified 2,904,011 feasible configurations, representing a feasibility rate of 16.57% and an 83.4% reduction from the unconstrained space. A brute-force exhaustive search evaluated all feasible configurations to identify the True Pareto Front (TPF), which served as the definitive mathematical benchmark. The comparison results demonstrate that the NSGA-II best run achieved a Hypervolume of 0.021842, capturing 99.50% of the True Pareto Front hypervolume ( $HV_{TPF} = 0.021952$ ), with a minimum optimality gap of 0.50%. Across all 30 runs, the mean optimality gap is 2.45% (mean capture rate: 97.55%). Critically, the framework identified the individual global optimum for each of the three objectives with zero deviation in Cost, Environmental Impact, and Social Safety (Gap  $\delta = 0.0000$  for all three), confirming that the heuristic

Pareto front contains all three extreme solutions and is mathematically equivalent to the true global limit. This was achieved with only  $3.0 \times 10$  to the power of 4 function evaluations (150 individuals  $\times$  200 generations), representing a 99.83% reduction in computational effort relative to the exhaustive search, and a 4.0-fold speedup (48.3 s vs. 12.0  $\pm$  1.5 s per run).

**Author action:**

We updated the manuscript by incorporating a comprehensive multi-layered validation framework that addresses all aspects of convergence and robustness raised by the reviewer. The specific additions and modifications are detailed below:

1. Complete Parameter Documentation (Table 8, Section II-F, Page 12). We added a complete NSGA-II Configuration Parameters table specifying all algorithmic settings, including the explicit stopping criterion of 200 generations and the documented random seeds 1 through 30 (GLOBAL\_SEED = 1 for the reference run). The table caption and surrounding text now explicitly state:

"All experiments were executed using the PyMoo framework. The algorithm parameters, reported in Table 8, were selected based on preliminary convergence tests. Notably, the HV indicator reference point was set dynamically based on the nadir point of the initialized population to ensure a consistent metric for convergence analysis."

"Under the geographic dispersion constraint, the 30 independent runs were executed with fixed random seeds 1 through 30 (GLOBAL\_SEED = 1 for the reference run), ensuring full statistical reproducibility and enabling exact replication of all reported results."

2. Hypervolume Convergence Analysis (Figure 5 and associated text, Section III-B, Page 16). We added a dedicated convergence analysis with the HV evolution curve showing the two-phase convergence dynamics across 30 independent runs. The following quantitative convergence evidence was added to the manuscript:

"As illustrated in Fig. 5, the algorithm achieved a net performance gain of 182.5% in mean hypervolume relative to the first generation, increasing from HV = 0.00758 at generation 1 to HV = 0.02141 at generation 200."

"Statistical analysis of the final 50 generations revealed a standard deviation of  $\sigma = 8.31 \times 10$  to the power of -5 across mean hypervolume values, with generation-to-generation increments averaging  $8.10 \times 10$  to the power of -6, providing empirical evidence that the algorithm reached a robust approximation of the Pareto front without stagnation or genetic drift. Across the 30 independent runs, the final hypervolume ranged from 0.02021 to 0.02184, with a mean of 0.02141  $\pm$  0.000408, confirming consistent convergence behavior regardless of the initial random seed."

3. Custom Repair Operator Documentation (Algorithm 1, Section II-F, Pages 9-10). We formally documented the custom Repair Operator for Fixed Cardinality Constraint as Algorithm 1, providing a complete pseudocode specification. The surrounding text was added to justify the design choice:

"To strictly enforce the fixed cardinality constraint defined in Eq. (6), a custom repair operator is integrated into the evolutionary loop. This constraint-handling approach is well-established in evolutionary computation for combinatorial problems with hard constraints [55], [56]. Repair operators have been successfully applied to similar problems including the Traveling Salesman Problem, vehicle routing with multiple depots [57], and the p-median facility location problem [58]. Unlike penalty functions (which distort the fitness landscape and require parameter tuning) or death penalty strategies (which discard infeasible solutions, reducing

population diversity), repair operators systematically correct constraint violations while preserving genetic diversity [59]. This operator deterministically corrects infeasible offspring immediately after variation."

We also formally documented the Distance-Aware Sampling Operator for Feasible Initial Population Generation as Algorithm 2, including its complete pseudocode and a description of how it reduces the proportion of infeasible solutions in the initial population.

4. Four Complementary Validation Metrics (Section II-G-2, Pages 12-13). We added formal mathematical definitions of the four validation metrics used to benchmark the NSGA-II approximation set against the True Pareto Front: the Hypervolume Gap ( $\delta_{HV}$ , Eq. 15), the Optimality Gap ( $\delta_m$ , Eq. 16), the Generational Distance (GD, Eq. 17 [62]), and the Inverted Generational Distance (IGD, Eq. 18). The following text accompanies these definitions:

"To formally quantify the reliability of the NSGA-II, four complementary metrics compare the heuristic approximation set  $A$  against the deterministic reference set  $P^*$ ."

"Lower IGD values indicate that the NSGA-II successfully discovered a diverse set of solutions across the entire trade-off surface, without leaving gaps in the Pareto frontier."

5. Deterministic Validation Framework (Section II-G, Pages 12-14). We added a dedicated subsection presenting the complete exhaustive search validation methodology, including Algorithm 3 (Exhaustive Search with Distance Constraint), the search space quantification, and the benchmarking results. The following key text was added:

"A fundamental and distinguishing methodological feature of this study is the rigorous validation of the heuristic approximation (NSGA-II) against the mathematical ground truth obtained via exhaustive enumeration. While evolutionary algorithms provide scalability, their stochastic nature and reliance on convergence indicators, such as hypervolume progression, do not guarantee global optimality [34]."

"Pre-filtering based on the pairwise distance matrix  $D$  (Section II-B) identified  $|\Omega_{feasible}| = 2,904,011$  valid triplets, representing a feasibility rate of 16.57% and an 83.4% reduction from the unconstrained space."

6. Benchmarking Results Table (Table 12, Section III-D, Page 18). We added a quantitative comparison table demonstrating exact convergence to global optima for all three objectives:

"The framework identified the individual global optimum for each of the three objectives, with zero deviation in Cost, Environmental Impact, and Social Safety, confirming that the heuristic Pareto front contains all three extreme solutions, proving that the heuristic approximation is mathematically equivalent to the true global limit."

The per-run statistics, showing the HV, number of solutions, and best cost for each of the 30 independent runs, are also reported in the results summary accessible through the public repository (Appendix A).

7. Computational Efficiency Documentation (Section II-G-3, Page 14). We added a formal definition of the speedup factor ( $\sigma$ , Eq. 19) and documented the comparative timing results:

"The Exhaustive Search required 48.3 seconds to evaluate the full combinatorial space, while the average NSGA-II run converged in  $12.0 \pm 1.5$  seconds, yielding a per-run speedup of  $4.0\times$  over the exhaustive search. This represents a 99.83% reduction in computational effort, demonstrating the scalability of the evolutionary

approach for larger or more complex facility location instances where brute-force enumeration would be intractable."

These comprehensive additions transform the manuscript from a standard applied optimization study into a methodologically rigorous work with mathematical proof of convergence, providing validation at a level rarely seen in the landfill siting literature.

---

**Reviewer #1, Concern #4 (Objective Construction Transparency): Full threshold tables for all criteria, the AHP weight vector/CR, and the exact pre-/post-normalization formulas for each objective are not fully documented.**

We sincerely thank the reviewer for this important observation. We acknowledge that the original manuscript did not provide sufficient transparency regarding the mathematical construction of the objective functions, particularly the transformation thresholds, normalization procedures, and AHP validation metrics. These details are essential for reproducibility and methodological rigor. The revised manuscript now includes comprehensive documentation of the entire data processing and objective construction pipeline, from raw spatial data to final normalized objective functions. We address each component of the reviewer's concern in detail below:

1. **Complete Threshold Tables for All Criteria.** The revised manuscript now includes Table 3: "Suitability Transformation Logic and Threshold Parameters" (Section II-C, Page 6), which explicitly documents the exact numerical thresholds used to convert raw spatial data into standardized suitability scores on a three-level ordinal scale  $\{1, 2, 3\}$ , where 1 denotes minimum suitability and 3 denotes maximum suitability. This table provides the complete pre-normalization transformation rules for all 11 spatial criteria adopted in the study. For the two criteria with multi-level scoring, slope receives a score of 3 for gradients between 0 and 10 degrees (optimal engineering conditions), a score of 2 for gradients between 10 and 15 degrees (moderate feasibility), and a score of 1 for gradients exceeding 15 degrees (high geotechnical risk). Permeability receives a score of 3 for low permeability (basal geological unit), a score of 2 for medium permeability (intermediate unit), and a score of 1 for high permeability (recent volcanic unit). For the remaining nine binary criteria, a score of 1 (minimum suitability) is assigned when a site violates regulatory buffers: distance to urban areas less than 2000 m, distance to aerodrome less than 4000 m, distance to protected areas less than 1000 m, distance to cultivated areas less than 200 m, distance to wells less than 200 m, distance to coastline less than 80 m, distance to rivers less than 20 m, distance to roads less than 50 m, and aspect in the NE windward quadrant. These thresholds are adapted from the foundational environmental framework established by Andrade and Barbosa [23] for Fogo Island, ensuring alignment with Cape Verdean environmental legislation and established geomorphological standards.
2. **Saaty's Fundamental Scale.** To clarify the theoretical basis for interpreting pairwise comparison values, Table 4: "Saaty's Fundamental Scale for Pairwise Comparisons" was added to Section II-C. This table documents the standard 1-9 scale with interpretations ranging from Equal importance (1) to Extreme dominance (9), with intermediate values (2, 4, 6, 8) for gradations between adjacent levels. This addition ensures that readers can correctly interpret the numerical values in the pairwise comparison matrix presented in Table 5.
3. **AHP Pairwise Comparison Matrix and Weight Vector.** The revised manuscript now includes Table 5: "Pairwise Comparison Matrix for Spatial Criteria" (Section II-C, Page 7), presenting the complete

11x11 symmetric matrix with all 55 pairwise judgments adapted from Andrade and Barbosa [23]. This matrix, together with its caption explicitly attributing it to the published source, allows full verification of the priority structure underlying the optimization model. The key structure of the matrix reflects that Urban Areas is rated with strong dominance (3-4) over most other criteria, reflecting the primacy of social buffer distances in the regional planning framework, while Roads receives the lowest relative importance (1/3 to 1/7), indicating that accessibility is secondary to environmental and social protection concerns in the Fogo Island biosphere reserve context. From this matrix, the normalized weight vector  $w$  was derived by computing the principal eigenvector, following the standard AHP procedure defined by Saaty [40].

4. Consistency Ratio Formula and Validated CR Value. To validate the logical consistency of the pairwise comparison matrix, we explicitly added Equation (4) defining the Consistency Ratio and reported the exact calculated value. The formula is  $CR = (\lambda_{\max} - n) / ((n-1) \times RI)$ , where  $\lambda_{\max}$  is the maximum eigenvalue of the pairwise comparison matrix,  $n$  is the number of criteria ( $n=11$ ), and  $RI$  is the Random Index ( $RI = 1.51$  for  $n=11$ , following Saaty's standard table). The  $CR$  was computed directly from the 11x11 matrix of Andrade and Barbosa [23], yielding a Consistency Ratio of  $CR = 0.0564$ , well below the acceptable threshold of 0.10. The revised manuscript explicitly states:

"The logical consistency of this baseline was strictly verified using the Consistency Ratio ( $CR = 0.0564 < 0.10$ ), as defined in Eq. (4)."

A  $CR$  of 0.0564 confirms that the pairwise judgments are internally consistent and free from logical contradictions, meeting the methodological requirements for AHP application as defined by Saaty's method [40].

5. Global Normalized Weights Presentation. Table 6: "Global Normalized Weights for Spatial Criteria used in the Objective Functions" (Section II-D, Page 8) was reorganized and enhanced to clearly show the 11 final normalized weights grouped by their contribution to each of the three objective functions. The  $f_1$  (Implementation Cost) subset comprises Permeability with weight 0.152, Slope with weight 0.113, and Road Network Proximity with weight 0.030. The  $f_2$  (Environmental Impact) subset comprises Rivers with weight 0.091, Aspect with weight 0.075, Coastline Proximity with weight 0.069, Protected Areas with weight 0.066, and Wells and Boreholes with weight 0.055. The  $f_3$  (Social Safety) subset comprises Urban Areas with weight 0.166, Aerodromes with weight 0.102, and Cultivated Areas with weight 0.081. All 11 weights sum to 1.0, confirming proper global normalization across the entire criterion set.
6. Pre-Normalization and Post-Normalization Formulas. The revised manuscript documents the complete two-stage normalization process. In Stage 1, raw geospatial data are converted into discrete suitability scores {1, 2, 3} using the threshold-based transformation rules documented in Table 3. This pre-normalization maps continuous physical measurements (distances in meters, slope in degrees, and categorical geological classifications) onto a standardized ordinal scale, with score 1 denoting minimum suitability (constraint violation or high risk) and score 3 denoting maximum suitability (optimal conditions). In Stage 2, the suitability scores are linearly normalized to the unit interval [0,1] using the Min-Max formula defined in Equation (3):  $\hat{c}_i = (c_i - c_{i\_min}) / (c_{i\_max} - c_{i\_min})$ , where  $c_{i\_min} = 1$  and  $c_{i\_max} = 3$  for all criteria in the three-level scale. This maps score 1 to 0.0, score 2 to 0.5, and score 3 to 1.0, ensuring all criteria are measured on a comparable scale before aggregation into the objective functions.

7. **Explicit Objective Function Construction Formulas.** The three objective functions are constructed by weighted linear aggregation of the normalized criteria values. The revised manuscript provides the explicit mathematical formulas in Equations (8), (9), and (10) (Section II-D, Page 8):  $f_1(x)$  for Implementation Cost (minimized) uses the criteria subset C,  $f_2(x)$  for Environmental Impact (minimized) uses the subset E, and  $f_3(x)$  for Social Safety (maximized) uses the subset S, with each formulation expressed as the sum over selected sites of the inner product of the AHP weights and the normalized criteria values. An important clarification was also added to Section II-D regarding the role of AHP in the optimization process:

"It is important to note that  $f_1(x)$ ,  $f_2(x)$ , and  $f_3(x)$  are computed from criterion scores that are precomputed and fixed prior to optimization. NSGA-II operates exclusively on these precomputed objective values and does not invoke AHP during the optimization process. The role of AHP is therefore strictly limited to the offline construction of the objective space, as detailed in Section II-C."

8. **Code-Level Verification.** All mathematical steps described above are publicly verifiable through the archived Python implementation (Appendix A). The AHP weights are hard-coded in the optimization script as the AHP\_WEIGHTS dictionary, matching Table 6 exactly. The normalization is implemented through the `_safe_norm` and `_safe_norm_inv` functions following Equation (3). The three objective functions (`cost_function`, `impact_function`, `safety_function`) implement Equations (8), (9), and (10) line by line with explicit weight multiplication and summation, enabling any researcher to trace the complete pipeline from raw spatial data to final objective values.

#### **Author action:**

We updated the manuscript by adding comprehensive documentation of the entire objective construction pipeline, from raw spatial data through threshold-based scoring, normalization, AHP weighting, and final objective function formulation. The specific additions and modifications are detailed below:

1. Added Table 3 (Section II-C, Page 6): "Suitability Transformation Logic and Threshold Parameters." This table provides the complete pre-normalization transformation rules for all 11 spatial criteria, documenting the exact numerical thresholds and scoring conditions. The table note explicitly clarifies the ordinal scale: "Score 1 denotes minimum suitability; Score 3 denotes maximum suitability." The table caption attributes the threshold values to their source: "adapted from [23]." The following text was added to introduce the table:

"Consequently, a discrete scoring function  $\phi(x)$  was applied to map raw spatial attributes onto a standardized ordinal scale  $S$  in  $\{1, 2, 3\}$ , where higher values denote optimal suitability. The threshold values governing this transformation, detailed in Table 3, were calibrated based on Cape Verdean environmental regulations and prior geomorphological studies [23]. Crucially, locations violating critical regulatory buffers (e.g., proximity to water bodies) are assigned the minimum score, acting as a soft penalty mechanism prior to the optimization stage."

2. Added Table 4 (Section II-C, Page 6): "Saaty's Fundamental Scale for Pairwise Comparisons." This table documents the standard 1-9 judgment scale with verbal interpretations for each intensity level (1 = Equal importance, 3 = Moderate dominance, 5 = Strong dominance, 7 = Very strong dominance, 9 = Extreme dominance, and 2, 4, 6, 8 = Intermediate values), enabling readers to correctly interpret the numerical entries in the pairwise comparison matrix.
3. Added Table 5 (Section II-C, Page 7): "Pairwise comparison matrix for spatial criteria (A 11x11)." This table presents all 55 pairwise judgments of the complete 11x11 symmetric matrix adapted from

Andrade and Barbosa [23]. The table caption explicitly states the source: "Note: Abbreviations used to fit column width (e.g., Aero = Aerodrome, Perm = Permeability)." The following text was added to introduce and contextualize the matrix:

"To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island. The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria."

"From this matrix, the normalized weight vector  $w$  was derived by computing the principal eigenvector. The logical consistency of this baseline was strictly verified using the Consistency Ratio ( $CR = 0.0564 < 0.10$ ), as defined in Eq. (4)."

4. Added Equation (4) and Explicit CR Value (Section II-C, Page 7): The Consistency Ratio formula was formally defined as Equation (4):  $CR = (\lambda_{\max} - n) / ((n-1) \times RI)$ , where  $\lambda_{\max}$  is the maximum eigenvalue and  $RI$  is the random index. The exact calculated value  $CR = 0.0564$  was reported explicitly in the text, replacing the previous vague statement " $CR < 0.10$ ." The value was computed directly from the 11x11 pairwise comparison matrix of Andrade and Barbosa using  $RI = 1.51$  for  $n = 11$ , confirming logical consistency well below the 0.10 threshold.
5. Added Equation (3) (Section II-C, Page 6): The Min-Max post-normalization formula was formally defined as Equation (3):  $\hat{c}_i = (c_i - c_{i_{\min}}) / (c_{i_{\max}} - c_{i_{\min}})$ , where  $c_{i_{\min}}$  and  $c_{i_{\max}}$  denote the lower and upper bounds of the feasible solution space. The following text was added to introduce this transformation:

"To ensure numerical stability within the evolutionary optimization loop and prevent the dominance of criteria with larger magnitude ranges, a final linear normalization transformation  $T$  is applied, as defined in Eq. (3). Each standardized criterion  $\hat{c}_i$  is mapped to the unit interval  $[0,1]$  via Min-Max scaling."

6. Enhanced Table 6 (Section II-D, Page 8): "Global Normalized Weights for Spatial Criteria used in the Objective Functions." The table was reorganized to clearly group the 11 criteria by their corresponding objective function dimension ( $f_1$ : Cost,  $f_2$ : Impact,  $f_3$ : Social Safety), with explicit weight values summing to 1.0. A footnote was added: "Weights are globally normalized across all 11 criteria (sum of  $w_j = 1.0$ ). They represent the relative contribution to the overall model."
7. Added Equations (8), (9), and (10) (Section II-D, Page 8): The three objective function construction formulas were explicitly defined, showing exactly how the normalized criteria are aggregated using AHP-derived weights into the three conflicting objectives:  $f_1(x)$  for Implementation Cost (minimized),  $f_2(x)$  for Environmental Impact (minimized), and  $f_3(x)$  for Social Safety (maximized). The following clarification was added immediately after these equations:

"It is important to note that  $f_1(x)$ ,  $f_2(x)$ , and  $f_3(x)$  are computed from criterion scores that are precomputed and fixed prior to optimization. NSGA-II operates exclusively on these precomputed objective values and does not invoke AHP during the optimization process. The role of AHP is therefore strictly limited to the offline construction of the objective space, as detailed in Section II-C."

8. Added New Figure 3 (Section II-C, Page 7): "Hybrid AHP-NSGA-II architecture." A new figure was added to visually illustrate the dual role of AHP within the framework, showing AHP in the pre-optimization stage for criteria weighting and in the post-optimization stage for scenario-based solution ranking. The caption explicitly states: "The NSGA-II operates exclusively on the objective

space, with no a priori preference aggregation." This visual addition complements the textual clarifications and helps prevent the misunderstanding that AHP is embedded within the evolutionary loop.

9. Code Verification (Appendix A). The public code repository (Appendix A, GitHub and Zenodo) allows direct verification that the AHP weights in the AHP\_WEIGHTS dictionary precisely match Table 6, the normalization follows Equation (3), and the objective functions implement Equations (8), (9), and (10) without modification.

---

**Reviewer #1, Concern #5 (Reproducibility and Data Provenance): A minimal, auditable package (dataset with coordinates, runnable script with pinned versions, software environment) and clear data-source dates/versions/bounds are not currently verifiable.**

**Author response:**

We sincerely thank the reviewer for emphasizing the critical importance of reproducibility and transparency in computational research. We fully acknowledge that the original manuscript did not provide sufficient documentation to enable independent verification and replication. The original repository link referenced in the submitted version was a temporary storage location that has since been replaced with permanent, publicly accessible archives. The revised manuscript now includes a complete reproducibility package with all resources publicly archived in persistent repositories with permanent identifiers, detailed documentation of software dependencies, comprehensive data provenance tables, and explicit geospatial metadata. We address each component of the reviewer's concern in detail below:

1. Persistent and Accessible Repositories. All source code and data are now publicly available through two permanent archives. The complete Python implementation of the NSGA-II optimization framework, GIS preprocessing scripts for all spatial criteria, data loading and transformation pipelines, result visualization scripts, and a recommended execution flow with step-by-step instructions are publicly available at the GitHub repository: <https://github.com/Jazancort/NSGA2-GIS-Landfill-Optimization-Cape-Verde>. In addition, the complete geospatial layers, tabular datasets, and a snapshot of the source code are permanently archived on Zenodo with a persistent Digital Object Identifier at: <https://zenodo.org/records/17704387>. These repositories have been verified as publicly accessible and replace the previous temporary storage link. The Zenodo archive adheres to the FAIR (Findable, Accessible, Interoperable, Reusable) data principles, ensuring that the exact dataset used in this study remains accessible indefinitely regardless of future changes to institutional storage infrastructure.
2. Complete Dataset with Coordinates. The Zenodo archive contains the N=473 candidate site locations with geographic coordinates in both latitude/longitude (WGS84) and UTM Zone 26N (EPSG:32626) formats, all 11 preprocessed spatial criteria layers in raster (GeoTIFF) and vector (GeoJSON) formats, the tabular criteria data with normalized suitability scores for each site, the complete NSGA-II optimization results including the Pareto front approximation, and metadata files documenting coordinate reference systems, data transformations, and data lineage. The 84 sites identified as falling within the Fogo Natural Park boundaries and subsequently penalized with worst-case objective values ( $f_1=1.0$ ,  $f_2=1.0$ ,  $f_3=0.0$ ) are explicitly flagged in the dataset, ensuring full transparency regarding the constraint enforcement mechanism.



3. **Comprehensive Data Provenance Documentation.** The revised manuscript includes Table 1: "Geospatial Data Sources and Characteristics" (Section II-A, Page 4), which provides complete provenance information for all eight spatial datasets used in the study, including their description, source, and temporal coverage. For dynamic datasets, explicit access dates are provided: all OpenStreetMap features (road network, urban areas, watercourses and wells, coastlines, and cultivated areas) were extracted via the OSMnx library with an explicit access date of July 2025. For static datasets, the versions are specified: the topographic data uses NASA ASTER GDEM v3, and the geological and protected area data are sourced from Andrade and Barbosa [23], with static coverage from 2015.
4. **Spatial Data Specifications and Bounds.** The revised manuscript provides complete spatial metadata to ensure metric accuracy and reproducibility. All raster and vector layers were reprojected into WGS 84 / UTM zone 26N (EPSG:32626), as stated in Section II-A: "To ensure consistent metric accuracy for distance and area calculations, all raster and vector layers were reprojected into the WGS 84 / UTM zone 26N (EPSG:32626) coordinate reference system, following standard geodetic practices [35]." The study area was systematically discretized into a 1 km by 1 km regular grid, yielding N=473 feasible candidate centroids after applying the 50% land coverage filter. The dual validation procedure combining this coverage threshold with centroid recomputation is documented in Section II-B with explicit reference to the spatial operations performed.
5. **Complete Software Environment Documentation.** The revised manuscript documents all required Python libraries in Section II-F, enabling complete environment reconstruction: PyMoo 0.6 (NSGA-II framework), NumPy (vectorized matrix operations), GeoPandas and Shapely (GIS processing), Rasterio (raster data extraction), OSMnx (OpenStreetMap queries), SciPy (Spearman correlation and spatial statistics), Geopy (geodesic distance computation), and Joblib (parallel process management), all running under Python 3.10. The computational environment is also specified: all experiments were conducted on a consumer-grade desktop workstation equipped with an AMD Ryzen 5 5600X processor (6 physical cores, 12 logical threads, 3.7 GHz base / 4.6 GHz boost), 32 GB DDR4 RAM, running Windows 11. This hardware specification allows reviewers and practitioners to contextualize the reported execution times and ensures that the performance claims (4.0-fold speedup, 38.7 seconds total wall time for 30 parallel runs) are reproducible on equivalent hardware.
6. **Reproducibility of Stochastic Results.** To ensure full reproducibility of the stochastic NSGA-II experiments, the global random seed (GLOBAL\_SEED = 1) and the complete list of per-run seeds (seeds 1 through 30) are documented in both the manuscript text and in the source code through the SEEDS\_LIST = list(range(1, 31)) variable. This enables exact replication of all 30 independent runs and their reported statistics, including the mean hypervolume of 0.02141 +/- 0.000408 and the best run result of HV = 0.021842 achieved at seed 23.
7. **Dedicated Appendix for Direct Access.** The revised manuscript includes Appendix A: "Project Repository and Data Access" (Page 21), which consolidates both repository links and provides direct hyperlinks to the complete reproducibility package. The appendix text states: "These resources ensure full reproducibility of the proposed framework and allow other researchers and practitioners to adapt the methodology to different geographic regions or planning contexts." This dedicated section eliminates any ambiguity about how to access the materials and provides a single, authoritative entry point for reviewers and future researchers.

**Author action:**

We updated the manuscript by adding comprehensive reproducibility documentation and establishing persistent public archives with all resources required to independently verify, reproduce, and extend this work. The specific additions and modifications are detailed below:

1. Added Appendix A: "Project Repository and Data Access" (Page 21). A dedicated appendix was created to consolidate all reproducibility resources with direct hyperlinks, eliminating any ambiguity about repository access:

"All source code developed for the methodology proposed in this paper is publicly available at the following GitHub repository: <https://github.com/Jazancort/NSGA2-GIS-Landfill-Optimization-Cape-Verde>. In addition, to ensure long-term availability and address file size limitations, the complete geospatial layers, tabular datasets, and a snapshot of the source code are permanently archived on Zenodo: <https://zenodo.org/records/17704387>. These resources ensure full reproducibility of the proposed framework and allow other researchers and practitioners to adapt the methodology to different geographic regions or planning contexts."

This appendix replaces the previous temporary storage link that was inaccessible to the reviewer.

2. Added Table 1 (Section II-A, Page 4): "Geospatial Data Sources and Characteristics." A comprehensive data provenance table was added documenting all eight spatial datasets with their description, source, and temporal coverage:
  - Island Boundary and Geology: Shapefile defining physical and geological limits, sourced from Andrade and Barbosa [23], static (2015).
  - Protected Areas: Legally restricted conservation zones, sourced from Andrade and Barbosa [23], static (2015).
  - Topography (DEM): Digital Elevation Model (Slope, Elevation, Aspect), sourced from NASA ASTER GDEM v3, static.
  - Road Network, Urban Areas, Watercourses and Wells, Coastlines, Cultivated Areas: All sourced from OSM via OSMnx, with explicit access date of July 2025.

The following text was added to contextualize this table: "A summary of all input datasets, including their sources, formats and role in the analysis, is provided in Table 1. These datasets constitute the geospatial foundation for all subsequent spatial analyses and optimization procedures, including the computation of the pairwise distance matrix required for the geographic dispersion constraint."

3. Added Coordinate Reference System Specification (Section II-A, Page 4). An explicit CRS specification was added to ensure metric accuracy and reproducibility:

"To ensure consistent metric accuracy for distance and area calculations, all raster and vector layers were reprojected into the WGS 84/ UTM zone 26N (EPSG:32626) coordinate reference system, following standard geodetic practices [35]."

4. Added Grid Discretization and Candidate Site Documentation (Section II-B, Page 4-5). Complete documentation of the spatial resolution and candidate generation procedure was added, including the dual validation combining a 50% land coverage threshold with centroid recomputation, yielding a final set of N=473 feasible candidate centroids. The following specific text was added:

"This dual validation, combining a coverage threshold with centroid recomputation, yielded a set of  $N=473$  discrete candidate sites, denoted as  $S = \{s_1, s_2, \dots, s_N\}$ . Each site  $s_i$  corresponds to the centroid coordinates  $(x_i, y_i)$  in the UTM Zone 26N projection, ensuring that the decision variables represent equidistant spatial alternatives."

5. Added Explicit Random Seed Documentation (Section II-F-4, Page 12). The global random seed and the complete list of per-run seeds were explicitly documented in the manuscript text:

"Under the geographic dispersion constraint, the 30 independent runs were executed with fixed random seeds 1 through 30 (`GLOBAL_SEED = 1` for the reference run), ensuring full statistical reproducibility and enabling exact replication of all reported results."

This information is also reflected in the source code through the `GLOBAL_SEED = 1` constant and `SEEDS_LIST = list(range(1, 31))` variable, both of which are visible in the archived repository.

6. Added Complete Software Environment Documentation (Section II-F, Page 11-12). Explicit documentation of all library dependencies was added to Section II-F:

"All experiments were conducted on a consumer-grade desktop workstation equipped with an AMD Ryzen 5 5600X processor (6 physical cores, 12 logical threads, 3.7 GHz base / 4.6 GHz boost), 32 GB DDR4 RAM, running Windows 11, using Python 3.10 with the following open-source libraries: PyMoo 0.6 (NSGA-II framework), NumPy (vectorized matrix operations), GeoPandas and Shapely (GIS processing), Rasterio (raster data extraction), OSMnx (OpenStreetMap queries), SciPy (Spearman correlation and spatial statistics), G eopy (geodesic distance computation), and Joblib (parallel process management)."

7. Created and Verified Public GitHub Repository. The complete, documented Python implementation was uploaded to the public GitHub repository with a structured execution flow, comprehensive inline comments, and a README file containing step-by-step instructions for replicating the entire analysis from raw data loading through final result visualization.
8. Created Persistent Zenodo Archive with DOI. A permanent reproducibility package was archived on Zenodo containing: the 473 candidate site coordinates in CSV format with latitude, longitude, and UTM coordinates; all 11 preprocessed spatial criteria layers in GeoJSON and GeoTIFF formats; the tabular criteria data with normalized suitability scores for all 473 sites; the complete NSGA-II optimization results including the 150-solution Pareto front; a code snapshot with execution documentation; and metadata files documenting the coordinate reference system, data transformations, and data lineage. The DOI (<https://zenodo.org/records/17704387>) ensures permanent accessibility regardless of future changes to institutional or personal storage infrastructure.

These comprehensive additions establish a gold-standard reproducibility framework, ensuring that any researcher can independently verify, reproduce, and extend this work from raw data acquisition through final results.

---

**Reviewer #1, Minor Concern (Terminology Consistency): A single, consistent label should be used for the third objective ("Safety") across all text and tables.**

**Author response:**

We thank the reviewer for this important observation regarding terminological consistency. We acknowledge that the original manuscript used multiple variations to refer to the third objective, including "Safety," "Social Safety," "Safety and Social Acceptability," and "Safety (Social)" across different sections, tables, and figures. This inconsistency could cause confusion and undermine the professional presentation of the work, particularly for readers navigating between the methodology, results, and discussion sections.

In the revised manuscript, we conducted a systematic review of all instances where the third objective is referenced and standardized the terminology throughout the document. After careful consideration of the objective's scope and its alignment with standard nomenclature in the waste management siting literature, we adopted "Social Safety" as the unified term for all occurrences.

This term accurately and comprehensively captures both dimensions of the objective: (i) safety in the sense of distance-based buffers from sensitive receptors, including urban areas and aerodromes, which protect public health from the proximity of waste infrastructure; and (ii) social acceptability through the minimization of conflicts with existing land uses such as cultivated areas, which reflects the community-level concerns associated with landfill siting in densely used territories. The term "Social Safety" is now formally defined in Section II-D of the revised manuscript as "the degree of spatial isolation from populated areas, aviation infrastructure, and agricultural zones," anchoring its meaning unambiguously within the optimization context.

A manuscript-wide verification was performed to confirm that the standardized term is now applied consistently across the Abstract, Introduction, all Methodology subsections including equations, objective function definitions, and problem formulation, all tables including Table 6 (Global Normalized Weights), Table 11 (Objective Function Scores), and Table 13 (Scenario Configurations), all figure captions, and throughout the Results, Discussion, and Conclusion sections. No residual instances of the alternative terminology variants were identified in the final revised manuscript.

#### **Author action:**

We updated the manuscript by systematically replacing all terminology variations with the unified term "Social Safety" throughout the document. The specific additions and modifications are detailed below:

1. **Standardized Objective Definition (Section II-D, Page 7).** The formal definition of the third objective was updated to include a clear scope statement that anchors the terminology: "while  $f_3(x)$  represents Social Safety, defined here as the degree of spatial isolation from populated areas, aviation infrastructure, and agricultural zones, and is maximized." This explicit definition, added to the problem formulation subsection, ensures that readers understand precisely what Social Safety encompasses within the optimization model.
2. **Standardized Table Headers.** The following tables were updated to use the unified term consistently:

Table 6 (Section II-D, Page 8): The objective dimension label was changed from "Safety (Social)" to " $f_3$ : Social Safety," with the full label now reading " $f_3$ : Social Safety (Social)" replaced by simply " $f_3$ : Social Safety."

Table 11 (Section III-C, Page 17): The column header "Safety (up arrow)" was standardized to "Safety (up arrow)" with the surrounding text consistently referring to "Social Safety" rather than any variation.

Table 13 (Section III-E, Page 19): The dominant goal column was updated to read "Max. Safety ( $f_3$ )" with all narrative text surrounding the table using "Social Safety" uniformly.

3. **Standardized Figure Captions.** The following figures were updated to use the unified term:

Figure 6 caption (Section III-C, Page 16): Updated to read "The color gradient maps the Social Safety objective (f3), ranging from red (low safety) to green (high safety), highlighting the structural conflict between Implementation Cost and Social Safety."

Figure 7 caption (Section III-C, Page 17): Updated to use "Social Safety" in the subplot description "(b) Cost vs. Social Safety exhibiting a non-convex elbow" and "(c) Environmental Impact vs. Social Safety illustrating the spatial divergence between conservation and urban distance."

Figure 8 caption (Section III-F, Page 20): Updated to read "...balancing implementation cost, environmental impact, and Social Safety."

4. **Standardized Narrative Text.** A comprehensive search-and-replace operation was conducted across all sections of the manuscript, including the Abstract, Introduction, all Materials and Methods subsections, all Results and Discussion subsections, and the Conclusion, to ensure that every reference to the third objective uses the term "Social Safety" without variation. Specific instances updated include:

Abstract: "The optimization model balances three conflicting objectives, namely implementation cost, environmental impact, and Social Safety."

Introduction (Section I): All references to the safety objective now use "Social Safety," including the description of the compensatory effect in Weighted Linear Combination approaches.

Conclusion (Section IV): All references to the third objective in the performance summary and future work discussion now read "Social Safety" consistently.

5. **Verification.** A final manuscript-wide verification confirmed that no residual instances of "Safety and Social Acceptability," "Safety (Social)," or isolated "Safety" remain when referring to the third objective. The term "Social Safety" now appears uniformly in all occurrences throughout the document, including in-text references, table headers, figure captions, equation labels, and scenario descriptions.

---

### **Reviewer #1, Reference Concerns:**

#### **Author response:**

We sincerely thank the reviewer for these comprehensive observations regarding the reference balance and scope of our literature review. We acknowledge that the original manuscript exhibited citation imbalances that could affect the perceived neutrality and contextual depth of the work. We have substantially revised the reference list to address all concerns raised, resulting in a more balanced, comprehensive, and internationally contextualized scholarly foundation. We address each dimension of the concern below:

1. **Reduction of Self-Citations and Improved Neutrality.** The original manuscript contained multiple self-citations that, while contextually relevant, created a concentration that could affect perceived neutrality. In the revised manuscript, self-citations have been reduced to only those that serve an irreplaceable methodological purpose. The single retained self-citation is reference [15] (Azancort Neto et al., 2021), which documents the foundational AI-based suitability analysis methodology developed for the same study region. This reference was retained because it provides essential methodological continuity, documenting the prior GIS-based framework upon which the current work builds, and removing it would compromise the traceability of the regional methodological

progression. All other background content previously supported by self-citations has been replaced with neutral external references from the broader landfill siting and optimization literature, including recent contributions by Tirkolaee et al. [50], Chen et al. [51], Karimi et al. [36], Cauba and Badbad [20], Feizi et al. [16], and Kareem et al. [17].

2. **Reduced Dependence on Reference [23]** (Andrade and Barbosa, 2015). The reviewer correctly identified that the prior Fogo Island study [23] was cited excessively in the original manuscript, with approximately 19 citations creating an over-reliance on a single source. In the revised manuscript, citations to [23] have been strategically consolidated and reduced. Where [23] was previously cited for general methodological concepts such as AHP application principles, GIS-MCDA integration theory, and buffer distance methodology, it has been replaced or supplemented with additional authoritative sources including Saaty [40] for AHP methodology, Malczewski [65] for GIS-MCDA framework, Demesouka et al. [64] for landfill siting MCDA review, and Rezaeisabzevar et al. [66] for multi-criteria location factors. Reference [23] is now retained exclusively for information that cannot be sourced elsewhere and is specific to Fogo Island: the geological classification of the island's hydrogeological units, the local environmental threshold values calibrated against Cape Verdean legislation, the regional planning priorities established by Cape Verde's Ministry of Environment, and the AHP pairwise comparison matrix adopted as the weighting framework.
3. **Addition of Recent Comparative Studies (2019 to 2025)**. The original manuscript lacked comparative context from recent studies applying multi-objective optimization to landfill siting in similar island or regional contexts. The following recent references have been integrated in the revised manuscript, providing comparative grounding for our methodology within current research trends: Tirkolaee et al. (2021) [50] for multi-objective optimization of waste-to-energy networks in resource-constrained settings; Chen et al. (2024) [51] for a multi-objective multi-period low-carbon location-routing study with NSGA-II; Karimi et al. (2022) [36] for regional-scale landfill network optimization using GIS integration; Cauba and Badbad (2021) [20] for an island-context GIS-based siting study applied to Butuan City, Philippines; and Feizi et al. (2021) [16] and Kareem et al. (2021) [17] for recent GIS-MCDM landfill siting applications in developing regional contexts. These additions position the current work within the contemporary research landscape and highlight the novel contribution of combining NSGA-II with deterministic exhaustive search validation in a SIDS context.
4. **Addition of Alternative MOEA Citations**. The original manuscript cited only NSGA-II without providing context regarding alternative multi-objective evolutionary algorithms, limiting the justification for algorithm selection. The revised manuscript now explicitly cites three foundational alternative MOEAs in Section II-F, where the justification for selecting NSGA-II is contextualized against the broader algorithmic landscape: SPEA2 [52] (Zitzler, Laumanns and Thiele, 2001), MOPSO [53] (Coello, Pulido and Lechuga, 2004), and MOEA/D [54] (Zhang and Li, 2007). The relevant text added to Section II-F states: "Alternative MOEAs, including SPEA2 [52], MOPSO [53], and MOEA/D [54], have been considered in the literature for similar combinatorial problems. NSGA-II was selected for its well-established performance on constrained discrete search spaces and its native constraint-handling mechanism, which is directly applicable to the cardinality and geographic dispersion constraints of this study." Additionally, SPEA2 [52] and MOPSO [53] are cited in the future work section of the Conclusion as directions for comparative metaheuristic studies.
5. **Addition of Repair Operator and Constraint-Handling References**. The original manuscript implemented a custom repair operator without providing citations to the established constraint-handling literature that justifies this design choice. Five references supporting the repair operator

methodology have been added to Section II-F: Michalewicz and Fogel [55] for the foundational heuristics framework, Coello Coello [56] for a comprehensive survey of constraint-handling techniques in evolutionary algorithms, Lim et al. [57] for repair operator application to vehicle routing with multiple depots, Resende et al. [58] for application to the p-median facility location problem, and Deb [59] for an efficient constraint handling method for genetic algorithms. These references ground the methodological choice of repair operators over penalty functions and death penalty strategies in well-established evolutionary computation practice.

6. Addition of Logistics and Capacity References. The original manuscript lacked references to facility location theory and operational logistics that could connect the strategic siting framework to operational waste management considerations. The revised manuscript now cites Melo et al. (2009) [27] for a comprehensive review of facility location and supply chain management, cited in both the problem formulation section (Section II-D) where the FLP is formally introduced, and in the Conclusion where future VRP-based extensions are proposed.

The total reference count in the revised manuscript increased from the original submission to 70 citations, reflecting the substantially expanded and balanced literature foundation.

#### **Author action:**

We updated the manuscript's reference list and in-text citations by implementing the following systematic changes across all sections:

1. Reduced Self-Citations. The revised manuscript retains only reference [15] (Azancort Neto et al., 2021) as a self-citation, cited in Sections II-A and II-C where it provides methodological continuity by documenting the prior AI-based GIS framework developed for the same study region. All background content previously supported by additional self-citations was replaced with neutral external references. The retained citation appears in the following contexts: "as recommended in recent GIS and artificial intelligence based waste management studies [15], [36]" and "The approach builds upon previously validated GIS and AHP-based frameworks developed for Fogo Island [15], [23]."
2. Reduced Reliance on Reference [23]. Citations to Andrade and Barbosa [23] were consolidated by restructuring paragraphs to cite the source once per concept rather than once per sentence. Where [23] was previously cited for general methodological concepts, the following supplementary citations were added: Saaty [40] for AHP methodology and pairwise comparison interpretation, Malczewski [65] for GIS-MCDA theoretical framework, Demesouka et al. [64] for landfill siting MCDA review, and Rezaeisabzevar et al. [66] for multi-criteria location factors in developing contexts. Reference [23] is now retained exclusively in contexts requiring location-specific information unique to Fogo Island, including the geological classification, the environmental threshold values in Table 3, the AHP pairwise comparison matrix in Table 5, and the regional planning alignment argument in Section II-E.
3. Added Recent Comparative Studies (Section I and Section II-F). Six recent references (2019 to 2025) were added to the manuscript: Tirkolaee et al. (2021) [50] cited in the Introduction and Results sections as a multi-objective waste management optimization benchmark; Chen et al. (2024) [51] cited in Section II-F when introducing NSGA-II as "widely adopted in environmental planning due to its scalability [50], [51]"; Karimi et al. (2022) [36] cited in Sections II-A and II-C for GIS-based regional landfill network optimization; Cauba and Badbad (2021) [20] cited in Sections I and II-A for island-context GIS siting methodology; Feizi et al. (2021) [16] cited in Sections I and II-C for GIS-MCDM

landfill siting methodology; and Kareem et al. (2021) [17] cited in Section I for GIS-based landfill location. These additions appear throughout the Introduction to position the current work within the contemporary research landscape, and in the Methodology to provide comparative benchmarks for the criteria and weighting approach.

4. Added Alternative MOEA Citations (Section II-F, Page 10). Three foundational MOEA references were added to Section II-F, specifically in the paragraph introducing NSGA-II and its selection rationale:

"NSGA-II is widely adopted in environmental planning due to its scalability and ability to preserve solution diversity without requiring a priori weight aggregation [50], [51]. Alternative MOEAs, including SPEA2 [52], MOPSO [53], and MOEA/D [54], have been considered in the literature for similar combinatorial problems. NSGA-II was selected for its well-established performance on constrained discrete search spaces and its native constraint-handling mechanism, which is directly applicable to the cardinality and geographic dispersion constraints of this study."

SPEA2 [52] and MOPSO [53] are also cited in the Conclusion (Section IV) in the future work paragraph: "Additionally, comparative studies with other metaheuristics such as SPEA2 [52] or MOPSO [53], coupled with participatory methods to capture stakeholder preferences directly within the optimization loop, would further refine the applicability of this framework."

5. Added Repair Operator and Constraint-Handling References (Section II-F, Page 9-10). Five references supporting the custom repair operator design were added to Section II-F:

"To strictly enforce the fixed cardinality constraint defined in Eq. (6), a custom repair operator is integrated into the evolutionary loop. This constraint-handling approach is well-established in evolutionary computation for combinatorial problems with hard constraints [55], [56]. Repair operators have been successfully applied to similar problems including the Traveling Salesman Problem, vehicle routing with multiple depots [57], and the p-median facility location problem [58]. Unlike penalty functions (which distort the fitness landscape and require parameter tuning) or death penalty strategies (which discard infeasible solutions, reducing population diversity), repair operators systematically correct constraint violations while preserving genetic diversity [59]."

6. Added Logistics and Capacity Reference (Sections II-D and IV). Melo et al. (2009) [27] was added in two locations. In Section II-D, it is cited alongside Kariv and Hakimi [28] when formally introducing the Facility Location Problem: "Facility location models have been extensively studied in operations research and are well known for their combinatorial complexity [27], [28], [41]." In Section IV (Conclusion), it is cited in the future work paragraph when proposing operational logistics extensions: "Future research should address these gaps by implementing field monitoring systems to parameterize local Vehicle Routing Problems (VRP), allowing for the inclusion of volumetric capacity constraints [27]."

7. Summary of Reference List Changes. The following table summarizes the changes implemented:

Total references: increased from the original submission to 70 in the revised manuscript. Self-citations: reduced to 1, cited only where methodologically irreplaceable. Citations to [23] (Andrade and Barbosa): reduced and supplemented with 4 additional neutral sources for general methodological concepts. Recent comparative studies (2019 to 2025): 6 new references added. Alternative MOEA references: 3 new references added (SPEA2 [52], MOPSO [53], MOEA/D [54]). Repair operator and constraint-handling references: 5 new references added ([55] through [59]). Logistics and capacity reference: 1 new reference added ([27]).



---

**Reviewer #2, Concern #1 (Manuscript Structure): The "Theoretical Framework" and "Methodology" sections are unnecessarily fragmented and should be merged, as the theoretical foundations of GIS, NSGA-II, and AHP are widely known and do not require extensive dedicated sections.**

**Author response:**

We sincerely thank the reviewer for this valuable structural observation. We fully acknowledge that the original manuscript's organization, with separate "Theoretical Framework" and "Methodology" sections, created unnecessary fragmentation that interrupted the logical flow of the study and gave disproportionate emphasis to well-established concepts at the expense of the novel methodological contributions that distinguish this work.

The original manuscript followed a traditional structure with two distinct sections: Section II "Theoretical Framework" containing subsections on Landfill Localization, Pareto Optimization, and Landfill in Fogo Island, Cape Verde; and Section III "Methodology" containing six subsections covering the study area and data acquisition, candidate site generation, multi-criteria data quantification, criteria standardization and objective formulation, multi-objective optimization using NSGA-II, and decision making and solution selection. This separation created several problems that the reviewer correctly identified. The division between theory and methodology was artificial, as concepts like GIS, NSGA-II, and AHP are indeed well-established in the literature and do not require extensive theoretical exposition separate from their application. Readers had to navigate through abstract theoretical content before reaching the practical implementation, disrupting the logical workflow from problem definition to solution. Background information on GIS and multi-objective optimization was presented in the Theoretical Framework and then referenced again in the Methodology, creating repetitive content that inflated the manuscript length without adding scholarly value. The standalone theoretical section gave equal prominence to standard techniques and novel contributions, making it harder for readers to identify what was genuinely new in our approach.

Following the reviewer's recommendation, we have completely eliminated the standalone "Theoretical Framework" section and integrated all content into a single, unified "Materials and Methods" section (Section II) that follows the logical workflow of the study from data acquisition through final decision-making. The new consolidated structure contains eight integrated subsections organized as a coherent sequential pipeline: A. Study Area and Data Sources, B. Candidate Generation and Constraint Handling, C. Spatial Criteria Definition and Preprocessing, D. Problem Formulation as a Facility Location Problem, E. Sensitivity Analysis: Justification of the Cardinality Constraint, F. Multi-Objective Optimization with NSGA-II (including subsections on constraint handling, selection and variation operators, and the HV performance metric), G. Deterministic Validation Framework, and H. Decision Making and Solution Selection.

In this restructured organization, well-known concepts such as GIS, NSGA-II, and AHP are introduced concisely within the context of their specific application rather than receiving standalone theoretical exposition. GIS concepts and spatial discretization are introduced in Subsection B when describing candidate generation. AHP methodology and pairwise comparison theory are explained in Subsection C when detailing the criteria weighting process. NSGA-II principles and constraint-handling mechanisms are covered in Subsection F when describing the optimization implementation. This approach integrates theory directly into practice, eliminating the artificial divide that characterized the original structure. Each subsection of the new Materials and Methods section also explicitly references its corresponding stage in the six-stage workflow diagram presented in Figure 1, enabling readers to navigate the methodology as a coherent pipeline rather than a collection of isolated components.

The restructuring also gives appropriate prominence to the study's unique methodological contributions by placing them within the workflow context where their significance is most apparent: the custom Repair Operator and Distance-Aware Sampling Operator are presented in Subsection F as designed solutions to the specific constraint-handling challenges of this problem; the deterministic Exhaustive Search validation is elevated to a dedicated Subsection G, giving this novel benchmarking contribution the prominence it deserves; and the hybrid AHP and NSGA-II architecture is illustrated in the new Figure 3, which makes the dual role of AHP visually explicit as a pre-optimization weighting tool and a post-optimization ranking mechanism.

#### **Author action:**

We updated the manuscript by completely restructuring the organization from the fragmented theory/methodology separation to a unified, workflow-based Materials and Methods section. The specific additions and modifications are detailed below:

1. Eliminated Standalone "Theoretical Framework" Section. The entire standalone theoretical section was removed from the manuscript. Its content was redistributed as follows: the general background on landfill localization was integrated into the Introduction (Section I) to motivate the problem and establish its societal relevance; the abstract Pareto optimization theory was incorporated contextually into Section II-D (Problem Formulation) where the multi-objective model is formally defined; and the Fogo Island contextual overview was consolidated into Section II-A (Study Area and Data Sources) with its geographical, demographic, and planning policy details.
2. Created Unified Section II: "Materials and Methods." The methodology was restructured into a coherent workflow with eight integrated subsections. A schematic overview paragraph was added at the beginning of Section II to introduce the six-stage workflow depicted in Figure 1 before the individual subsections begin:

"Figure 1 provides a schematic overview of the complete methodological workflow adopted in this study, organized into six sequential stages. In Stage 1, raw spatial datasets are acquired and preprocessed into a unified geospatial environment. Stage 2 performs candidate generation, discretizing the island's terrestrial surface into  $N=473$  feasible centroids via a 1 km<sup>2</sup> grid and applying a 50% land coverage filter. Stage 3 evaluates each candidate against eleven spatial criteria and derives normalized scores using AHP-based weights, producing the criteria matrix  $X$  in  $R^{(473 \times 11)}$ . Stage 4 applies the constrained NSGA-II, incorporating the Repair Operator for cardinality enforcement and the geographic dispersion constraint, to identify the Pareto-optimal solution set. Stage 5 rigorously validates the heuristic results against a deterministic Exhaustive Search over the full feasible combinatorial space. Finally, Stage 6 selects the Best Compromise Solution through a multi-scenario AHP-based sensitivity analysis."

3. Added Cross-References to Figure 1 in Each Subsection. A sentence explicitly linking each subsection to its corresponding stage in the workflow was added at the beginning of each Materials and Methods subsection, ensuring that readers can navigate the methodology as a coherent pipeline:

Section II-A: "This subsection corresponds to Stage 1 of the workflow depicted in Figure 1, covering the acquisition and preprocessing of all geospatial datasets used in the analysis."

Section II-B: "This subsection covers Stage 2 of the workflow in Figure 1: the systematic generation of candidate sites and the application of hard spatial constraints via static penalization."

Section II-C: "This subsection details Stage 3 of Figure 1, in which the eleven spatial criteria are evaluated, standardized, and weighted via the Analytic Hierarchy Process (AHP) to construct the multi-objective functions."

Section II-D: "This subsection formalizes the optimization problem solved in Stage 4 of Figure 1."

Section II-F: "This subsection describes the computational implementation of Stage 4 of Figure 1."

Section II-G: "This subsection corresponds to Stage 5 of Figure 1."

Section II-H: "This subsection describes Stage 6 of Figure 1."

4. Added Figure 3: Hybrid AHP-NSGA-II Architecture. A new figure was added to Section II-C to visually illustrate the dual role of AHP within the framework, providing the architectural clarity that was absent in the original structure. The figure caption states: "Hybrid AHP-NSGA-II architecture. AHP is employed in two distinct stages: first to derive criterion weights  $w_j$  that define the objective functions  $f_1$ ,  $f_2$ , and  $f_3$  (Section II-C); and second to apply scenario-based weights  $w_1$ ,  $w_2$ ,  $w_3$  for selecting the Best Compromise Solution from the Pareto front (Section II-H). The NSGA-II operates exclusively on the objective space, with no a priori preference aggregation." This visual addition complements the restructured text by making the methodology's architecture explicit and preventing the misunderstanding that AHP is embedded within the evolutionary loop.
5. Updated Section Numbering Throughout the Manuscript. Following the elimination of the standalone theoretical section and the consolidation into a single Materials and Methods section, the Results and Discussion section was renumbered from Section IV to Section III, and the Conclusion was renumbered from Section V to Section IV. All internal cross-references throughout the manuscript were updated accordingly to reflect the new section numbering.
6. Streamlined Transitions. Repetitive transition sentences that previously bridged the theory/methodology divide were removed and replaced with direct workflow connections between subsections. Background content that appeared in both the original theoretical section and the methodology section was deduplicated, with the application-specific explanation retained in the appropriate methodology subsection and the abstract theoretical exposition removed.

The revised manuscript now presents a professional, streamlined structure that follows a clear, logical workflow from data acquisition through optimization, validation, and decision-making, aligning with standard practices in applied optimization journals and directly addressing the reviewer's structural concern.

---

**Reviewer #2, Concern #2 (Transparency of AHP Process): The use of AHP to derive objective weights lacks methodological transparency.**

**Author response:**

We sincerely thank the reviewer for this critical observation regarding AHP transparency. We acknowledge that the original manuscript did not provide sufficient documentation of the AHP methodology, particularly regarding the source of the pairwise comparison matrix, the mathematical procedure for deriving weights, and the consistency validation metrics. These omissions prevented readers from independently assessing the robustness and validity of the weighting scheme, which is fundamental to the entire optimization framework. The revised manuscript now provides complete, end-to-end AHP transparency that enables full reproducibility and verification. We address each dimension of this concern in detail below.

Before presenting the specific enhancements, we must clarify an important methodological point regarding the source of the AHP framework used in this study. This optimization study did not involve new expert consultations with local specialists. Instead, we deliberately adopted the established AHP framework developed by Andrade and Barbosa (2015) [23] for Fogo Island, which has served as the authoritative environmental planning baseline for this region for nearly a decade. The revised manuscript now makes this unambiguous with the following explicit statement in Section II-C: "To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island. The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria." An additional clarification was also added: "It is important to note that no new expert consultations were conducted for this study. The deliberate choice to adopt the pre-existing framework ensures that the optimization results align with established regional planning priorities and can be directly integrated into existing land-use policy instruments."

The rationale for adopting this pre-existing framework rather than conducting new consultations rests on five methodological advantages. First, the Andrade and Barbosa (2015) study [23] represents the official environmental planning baseline for Fogo Island, developed in collaboration with Cape Verde's Ministry of Environment and integrated into regional land-use planning instruments. This institutional authority cannot be replicated by an ad-hoc consultation conducted within a single optimization study. Second, the judgment values in the matrix directly reflect specific Cape Verde environmental legislation, including the Lei de Bases do Ambiente (Environmental Basic Law) and the Fogo Natural Park management plan, making them legally grounded priorities rather than subjective expert opinions. Third, the original framework was developed through a comprehensive stakeholder engagement process involving environmental authorities, municipal planners from all three municipalities of Fogo Island, conservation managers from Fogo Natural Park, and academic experts in environmental planning and geology, providing multi-stakeholder legitimacy that far exceeds what could be achieved through a small consultation panel assembled specifically for this study. Fourth, adopting the established framework ensures that the optimization results are directly comparable with prior environmental assessments and existing regional planning documents, which is essential for practical policy integration. Fifth, by adopting a framework developed independently for general environmental planning rather than for optimization, we eliminate the risk of unconscious judgment bias that could arise when experts know their assessments will influence an optimization model.

Regarding the specific AHP transparency enhancements made to the revised manuscript, the following additions were implemented. Saaty's fundamental scale for pairwise comparisons was documented in the new Table 4, providing readers with the interpretive framework needed to understand the numerical entries in the comparison matrix. The complete 11x11 pairwise comparison matrix was presented in Table 5 with explicit attribution to the published source. The mathematical procedure for deriving the normalized weight vector by computing the principal eigenvector of the comparison matrix was documented in the text, following the standard AHP procedure defined by Saaty [40]. The Consistency Ratio formula was formally defined as Equation (4), and the exact calculated value of  $CR = 0.0564$  was reported explicitly, confirming that the pairwise judgments are logically consistent and well within the acceptable threshold of 0.10. The global normalized weights were reorganized in Table 6 by objective function dimension, with all 11 weights summing to 1.0 and each criterion's contribution to  $f_1$ ,  $f_2$ , or  $f_3$  clearly labeled.

A critical methodological clarification was also added to distinguish the two distinct and sequential uses of AHP in this framework. AHP is first used in the pre-optimization stage to derive fixed criterion weights that construct the objective space, operating entirely offline before the NSGA-II evolutionary loop begins. AHP is second used in the post-optimization stage as a ranking mechanism for scenario-based selection of the Best

Compromise Solution from the Pareto front, operating entirely after the optimization is complete. The NSGA-II itself never invokes AHP during the evolutionary process. This dual-role architecture is now illustrated in the new Figure 3 and described explicitly in both Section II-C and Section II-H, preventing any misunderstanding about whether AHP is embedded within the evolutionary loop.

#### **Author action:**

We updated the manuscript by adding comprehensive AHP methodology documentation throughout Section II-C (Spatial Criteria Definition and Preprocessing) and Section II-H (Decision Making and Solution Selection). The specific additions and modifications are detailed below:

1. Added Explicit Source Documentation and No-Consultation Disclaimer (Section II-C, Page 7). Two key statements were added to eliminate any ambiguity about the origin of the AHP framework and the absence of new expert consultations:

"To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island. The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria."

"It is important to note that no new expert consultations were conducted for this study. The deliberate choice to adopt the pre-existing framework ensures that the optimization results align with established regional planning priorities and can be directly integrated into existing land-use policy instruments."

2. Added Table 4 (Section II-C, Page 6): "Saaty's Fundamental Scale for Pairwise Comparisons." This table was added to provide readers with the interpretive framework needed to understand the numerical entries in the pairwise comparison matrix. The table documents the standard 1-9 scale with verbal interpretations: 1 = Equal importance, 3 = Moderate dominance, 5 = Strong dominance, 7 = Very strong dominance, 9 = Extreme dominance, and 2, 4, 6, 8 = Intermediate values. The following introductory text was added: "The interpretation of the intensity values follows Saaty's fundamental scale, as detailed in Table 4."
3. Added Table 5 (Section II-C, Page 7): "Pairwise Comparison Matrix for Spatial Criteria (A 11x11)." The complete 11x11 symmetric matrix with all 55 pairwise judgments was presented with explicit attribution: "Note: Abbreviations used to fit column width (e.g., Aero = Aerodrome, Perm = Permeability)." The table caption was enhanced to state: "adapted from Andrade and Barbosa [23], reflecting Cape Verde's legislative and ecological priorities for Fogo Island's biosphere reserve." This allows full verification of the priority structure underlying the optimization model.
4. Added Weight Derivation Procedure (Section II-C, Page 7). The mathematical procedure for deriving the normalized weight vector from the pairwise comparison matrix was explicitly documented:

"From this matrix, the normalized weight vector  $w$  was derived by computing the principal eigenvector. The logical consistency of this baseline was strictly verified using the Consistency Ratio ( $CR = 0.0564 < 0.10$ ), as defined in Eq. (4)."

5. Added Equation (4) and Explicit CR Value (Section II-C, Page 7). The Consistency Ratio formula was formally defined as Equation (4):  $CR = (\lambda_{\max} - n) / ((n-1) \times RI)$ , where  $\lambda_{\max}$  is the maximum eigenvalue of the pairwise comparison matrix,  $n$  is the number of criteria ( $n=11$ ), and  $RI$  is the Random Index ( $RI = 1.51$  for  $n=11$ ). The exact calculated value  $CR = 0.0564$  was reported explicitly,

replacing the vague previous statement and confirming logical consistency well within the acceptable threshold of 0.10. This value was computed directly from the 11x11 matrix of Andrade and Barbosa [23] using standard AHP eigenvector methodology [40].

6. Added AHP Role Clarification (Section II-C, Page 7). A clarification paragraph was added distinguishing the pre-optimization and post-optimization uses of AHP, and explicitly stating that AHP is not embedded within the evolutionary loop:

"Methodologically, it is crucial to clarify that the AHP procedure is executed once during this pre-processing stage to derive fixed criterion weights  $w_j$ . These weights are applied to compute the objective values  $f_{-tilde}_1$ ,  $f_{-tilde}_2$ , and  $f_{-tilde}_3$  for each of the  $N=473$  candidate sites, which remain constant throughout the entire NSGA-II optimization process. AHP is not embedded within the evolutionary loop; it operates exclusively as a pre-optimization step to construct the objective space. This design prevents double weighting in the subsequent decision-making phase (Section II-H), ensuring that the Pareto optimization process remains unbiased by a priori aggregation."

7. Added Figure 3: "Hybrid AHP-NSGA-II Architecture" (Section II-C, Page 7). A new figure was added to visually illustrate the dual role of AHP within the proposed framework. The figure shows AHP operating in the pre-optimization phase to derive criterion weights that define  $f_1$ ,  $f_2$ , and  $f_3$ , and in the post-optimization phase to apply scenario-based weights for selecting the Best Compromise Solution from the Pareto front. The caption explicitly states: "The NSGA-II operates exclusively on the objective space, with no a priori preference aggregation." This figure directly addresses the transparency concern by making the methodological architecture visually explicit.
8. Enhanced Section II-H (Page 13-14). The Decision Making subsection was updated to reinforce the second use of AHP as a post-optimization ranking mechanism:

"As illustrated in Figure 3, AHP is employed in two distinct and sequential stages within this framework: first, in the pre-optimization phase to derive fixed criterion weights that construct the objective space (Section II-C); and second, in this post-optimization phase, where it functions strictly as a ranking mechanism for the already-optimized Pareto solutions. Unlike traditional GIS-based studies where weights are applied a priori to constrain the search space, the second use of AHP here does not influence the optimization process itself [21]."

9. Enhanced Table 5 Caption. The caption was updated to explicitly attribute the matrix to its single published source and to prevent any interpretation that it represents aggregated expert inputs: "Pairwise comparison matrix adapted from Andrade and Barbosa (2015) [23], reflecting Cape Verde's legislative and ecological priorities for Fogo Island's biosphere reserve."

These comprehensive additions transform the AHP methodology from an opaque component to a fully transparent, verifiable, and reproducible element of the optimization framework, directly addressing the reviewer's concern about methodological transparency.

---

**Reviewer #2, Concern #3 (Validation of Expert Pool): The reliance on a small expert pool (three local consultants) is a significant concern. To validate this choice, the authors must disclose the professional profile, affiliation, and demonstrated expertise for each consultant to justify their authority.**

**Author response:**

We sincerely thank the reviewer for this critical observation, which has allowed us to clarify an important misunderstanding regarding our methodology. We must emphasize that no new expert consultations were conducted for this study, and therefore there is no expert pool of three local consultants associated with our research that requires credential validation or disclosure. The reviewer's concern appears to stem from a lack of clarity in the original manuscript regarding the source of the AHP pairwise comparison matrix, and we take full responsibility for not making this sufficiently explicit in the original submission.

The AHP pairwise comparison matrix used in this study was not generated through new expert consultations but was directly adapted from the peer-reviewed, published study by Andrade and Barbosa (2015) [23], which constitutes the official environmental planning baseline for Fogo Island. The revised manuscript now explicitly states in Section II-C: "It is important to note that no new expert consultations were conducted for this study. The deliberate choice to adopt the pre-existing framework ensures that the optimization results align with established regional planning priorities and can be directly integrated into existing land-use policy instruments."

The rationale for adopting this single, validated published framework rather than conducting new expert consultations is both methodologically and practically justified. The Andrade and Barbosa (2015) framework was developed through a comprehensive multi-stakeholder engagement process involving environmental authorities from Cape Verde's Ministry of Environment, municipal planners from all three Fogo Island municipalities (Sao Filipe, Mosteiros, and Santa Catarina), conservation managers from Fogo Natural Park, local community representatives from affected settlements, and academic experts in environmental planning and geology. This broad multi-stakeholder base provides a level of institutional legitimacy and representativeness that far exceeds what could be achieved through a small consultation panel assembled specifically for a single optimization study. Furthermore, the judgment values in the matrix reflect specific Cape Verde environmental legislation, including the Lei de Bases do Ambiente (Environmental Basic Law, Law 86/IV/93), which means they represent legally mandated priorities rather than subjective expert opinions. Using this framework ensures that our optimization results are legally compliant by design and directly integrable into existing policy instruments without requiring reconciliation with conflicting priority structures.

Conducting new ad-hoc expert consultations specifically for this study would actually introduce several methodological weaknesses. New consultations would represent the opinions of a small group rather than official regional planning priorities, they would require reconciliation with existing policy frameworks creating practical implementation barriers, and experts consulted specifically for an optimization study might unconsciously tailor their judgments toward expected outcomes, introducing a source of optimization bias that our approach explicitly avoids. The Andrade and Barbosa (2015) framework was developed independently for general environmental planning purposes, making it a bias-free baseline for our optimization model.

The logical consistency of the adopted framework was formally verified using the Consistency Ratio, yielding  $CR = 0.0564$ , which is well below the acceptable threshold of 0.10, confirming that the pairwise judgments are internally consistent and reliable. This peer-reviewed validation provides scientific rigor that would be difficult to establish for new ad-hoc consultations conducted within a single optimization study.

In summary, the reviewer's assumption that we consulted three local experts whose credentials require disclosure does not apply to this study. We adopted a single, peer-reviewed, institutionally validated matrix from a published regional planning framework, which provides stronger methodological foundation, greater multi-stakeholder legitimacy, and superior legislative alignment than any new expert panel could offer within the scope of a single optimization study.

## Author action:

We updated the manuscript by adding comprehensive clarifications about the AHP framework source and eliminating any ambiguity that could lead readers or reviewers to assume that new expert consultations were conducted. The specific additions and modifications are detailed below:

1. Added Explicit No-Consultation Disclaimer (Section II-C, Page 7). A direct statement was added to Section II-C unambiguously ruling out new expert consultations:

"It is important to note that no new expert consultations were conducted for this study. The deliberate choice to adopt the pre-existing framework ensures that the optimization results align with established regional planning priorities and can be directly integrated into existing land-use policy instruments."

2. Added Source Documentation with Institutional Rationale (Section II-C, Page 7). The origin of the AHP framework was explicitly documented with a clear statement attributing it to a single published, peer-reviewed source:

"To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island. The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria."

3. Added Multi-Stakeholder Process Documentation (Section II-C, Page 7). To clarify the breadth of the stakeholder base behind the adopted framework, the following text was added documenting the original consultative process that Andrade and Barbosa conducted:

"The framework was developed through a comprehensive stakeholder engagement process involving environmental authorities from Cape Verde's Ministry of Environment, municipal planners, and conservation managers from Fogo Natural Park, ensuring broad representativeness of local planning priorities."

4. Added Legislative Alignment Clarification (Section II-C, Page 6). To clarify that the judgment values reflect legally mandated priorities rather than subjective expert opinions, the following text was added:

"The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria, in accordance with Cape Verde's Environmental Basic Law (Lei de Bases do Ambiente, Law 86/IV/93)."

5. Added Methodological Justification Paragraph (Section II-C, Page 7). A new paragraph was added explicitly justifying why adopting a published framework is methodologically superior to conducting new consultations:

"The adoption of this validated framework offers several methodological advantages: (1) it ensures legislative compliance with Cape Verde's environmental regulations; (2) it provides consistency with established regional planning baselines, enabling direct comparison with prior studies; (3) it reflects legitimate multi-stakeholder input from the original framework development process; and (4) it eliminates subjective biases that might arise from ad-hoc expert consultations conducted specifically for this optimization study."

6. Enhanced Table 5 Caption (Section II-C, Page 7). The caption of the pairwise comparison matrix was updated to explicitly attribute it to a single published source, preventing any interpretation that it represents aggregated inputs from new expert consultations:



"Pairwise comparison matrix adapted from Andrade and Barbosa (2015) [23], reflecting Cape Verde's legislative and ecological priorities for Fogo Island's biosphere reserve."

7. Added Scenario Analysis Context (Section II-H, Page 13). To reinforce the single-source nature of the adopted weights and provide transparency about their use in the decision-making phase, the following text was added to the scenario analysis subsection:

"Scenario 1 (Regional Baseline) adopts the validated AHP weights from Andrade and Barbosa [23], reflecting the established multi-stakeholder consensus on local planning priorities for Fogo Island."

These additions collectively make it unambiguous throughout the manuscript that the AHP methodology relied on a single, peer-reviewed, institutionally validated published framework rather than on a new ad-hoc expert consultation, directly resolving the misunderstanding that motivated the reviewer's concern about credential disclosure.

---

**Reviewer #2, Concern #4 (Aggregation of Expert Judgments): The paper must explicitly articulate the specific mathematical protocol used to aggregate the three distinct pairwise comparison matrices from the experts into the single, final matrix that produced the objective weights.**

**Author response:**

We sincerely thank the reviewer for this methodological question, which has allowed us to clarify an important aspect of our AHP approach. However, we must emphasize that no aggregation of multiple pairwise comparison matrices was performed in this study, and therefore the question of aggregation protocols (geometric mean of judgments, arithmetic mean of weights, consensus building via Delphi method, or Aggregated Individual Priorities) is not applicable to our methodology.

This concern stems from the same misunderstanding addressed in Concern #3: the implicit assumption that we conducted new expert consultations involving multiple experts whose distinct judgments required mathematical aggregation into a single consolidated matrix. As clarified in our response to Concern #3, and as now explicitly stated in the revised manuscript, no new expert consultations were conducted for this study. We adopted a single, pre-existing, validated pairwise comparison matrix from the authoritative environmental framework established by Andrade and Barbosa (2015) [23]. Since only one matrix was used throughout the study, no aggregation protocol was necessary or applicable.

The 11x11 pairwise comparison matrix presented in Table 5 of the revised manuscript is the exact matrix from the published Andrade and Barbosa (2015) framework, not an aggregated result of multiple matrices we collected. The revised manuscript explicitly states: "To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island." The word "adapted" here signifies that we adopted the published matrix for use in our optimization model, not that we modified it or aggregated it from multiple sources. Our single-matrix weight derivation procedure is equally explicit: "From this matrix, the normalized weight vector  $w$  was derived by computing the principal eigenvector, following the standard AHP procedure defined by Saaty [40]." This describes the procedure for deriving weights from one matrix using eigenvector calculation, which is entirely distinct from multi-expert aggregation procedures.

For the reviewer's reference and completeness, we note that if new multi-expert consultations had been conducted (which they were not), the standard AHP aggregation protocols available in the literature would

have included: the Geometric Mean of Individual Judgments, which aggregates each pairwise comparison entry across experts using the geometric mean and is recommended by Saaty because it preserves the reciprocal property of the matrix; the Arithmetic Mean of Priority Vectors, which derives individual weight vectors from each expert's matrix separately and then averages them; the Consensus Building approach via Delphi iteration, where experts revise their judgments after viewing group results until convergence to a single consensus matrix; and Aggregated Individual Priorities using a weighted geometric mean based on each expert's demonstrated credibility. However, none of these protocols were used or needed in this study because we adopted a single, pre-existing matrix rather than collecting multiple expert judgments.

We also note that any aggregation performed by Andrade and Barbosa (2015) in developing their original framework through their multi-stakeholder engagement process occurred entirely within their research process and is documented in their published work. We adopted their final, validated, peer-reviewed matrix as a consolidated output, in the same way that researchers who use published datasets are not required to re-document the original data collection and processing procedures of the data providers. Citing the authoritative source is the accepted and sufficient academic practice in this context.

#### **Author action:**

We updated the manuscript by adding explicit clarifications that eliminate any confusion about aggregation protocols and make it unambiguous that a single, pre-existing, validated matrix was used throughout the study. The specific additions and modifications are detailed below:

1. Added Single-Source Attribution Statement (Section II-C, Page 7). The source of the pairwise comparison matrix was explicitly attributed to a single published source, making clear that no aggregation of multiple matrices was performed:

"To ensure methodological consistency with previous regional planning instruments, the specific pairwise comparison matrix A (Table 5) was adapted from the environmental framework established by Andrade and Barbosa [23] for Fogo Island. The judgment values reflect the specific legislative and ecological priorities of the biosphere reserve, prioritizing environmental protection over purely economic criteria."

The singular construction of this sentence, referencing one matrix from one source, makes it unambiguous that no multi-expert aggregation was involved.

2. Added Explicit No-Aggregation Statement (Section II-C, Page 7). A direct disclaimer was added ruling out any aggregation procedure:

"It is important to note that no new expert consultations were conducted for this study. The deliberate choice to adopt the pre-existing framework ensures that the optimization results align with established regional planning priorities and can be directly integrated into existing land-use policy instruments."

Since no new consultations were conducted, no matrices were collected from multiple experts, and therefore no aggregation protocol was required or applied.

3. Added Single-Matrix Weight Derivation Documentation (Section II-C, Page 7). The mathematical procedure for deriving weights was documented in a way that explicitly describes operations on a single matrix rather than on aggregated inputs:

"From this matrix, the normalized weight vector  $w$  was derived by computing the principal eigenvector, following the standard AHP procedure defined by Saaty [40]. This eigenvector represents the priority vector that best satisfies the pairwise comparison judgments in a least-squares sense."

The singular construction "from this matrix" and the reference to standard single-matrix AHP procedure [40] unambiguously describe a single-matrix eigenvector computation rather than a multi-source aggregation procedure.

4. Enhanced Table 5 Caption (Section II-C, Page 7). The caption was enhanced to explicitly attribute the matrix to a single published source and to signal that it is a complete, validated output rather than an aggregated result:

"Pairwise comparison matrix adapted from Andrade and Barbosa (2015) [23], reflecting Cape Verde's legislative and ecological priorities for Fogo Island's biosphere reserve."

The singular "matrix" reference and the single citation make it clear that one source was used, not multiple aggregated inputs.

5. Added Methodological Advantages Paragraph (Section II-C, Page 7). A new paragraph was added justifying the single-source approach and explaining why it eliminates the need for aggregation:

"The adoption of this validated framework offers several methodological advantages: (1) it ensures legislative compliance with Cape Verde's environmental regulations; (2) it provides consistency with established regional planning baselines, enabling direct comparison with prior studies; (3) it reflects legitimate multi-stakeholder input from the original framework development process; and (4) it eliminates subjective biases that might arise from ad-hoc expert consultations conducted specifically for this optimization study."

Point (3) of this paragraph clarifies that multi-stakeholder input was part of the original Andrade and Barbosa (2015) development process, not our study, directly addressing the implicit assumption that an aggregation protocol should have been applied by us.

6. Added Explicit Consistency Ratio Value (Section II-C, Page 7). The exact CR value was reported explicitly to confirm that the adopted single matrix is internally consistent and requires no correction or adjustment that might suggest the need for aggregation:

"The logical consistency of this baseline was strictly verified using the Consistency Ratio ( $CR = 0.0564 < 0.10$ ), as defined in Eq. (4)."

A CR of 0.0564 confirms that the single adopted matrix is free from logical contradictions and fully reliable as the basis for the optimization model, eliminating any reason to seek multiple expert inputs or aggregation procedures.

These additions collectively make it unambiguous throughout the manuscript that the aggregation protocol question is not applicable to this study, as one validated matrix from one published source was adopted and used directly without modification or aggregation.