PAGE NO ~~20 1/2~~ 738/9 DATE : / /

25

Data handling. Jazeel Ahmed.K.
Batch-A.

1. Missing values means an data that dont appear in a dataset. It may occur due to entryerror, calculational error etc-

eg: Mean - Replace the missing values with the finding average of dataset

2 1/2

Median - Replace the missing values with the finding middle value of dataset.

2. outlier means identifying a value that differnt from a dataset.

eg: 80, 76, 92, 90 45
here 45 is the outlier because 45 is very lower than the other numbers.

Methods.

IQR method - It find the outlier by 50% of data differnt from the dataset.

2

Z-score method - It work by how for a data is located in the dataset.

3. Data Formatting.

Data formatting is a method of arranging that in correct format or in a structured way.

DATE / /

PAGE NO :

Data parsing:

Data parsing means breaking the words into smaller parts. learning like machine learning.

eg: Name : Jazeel Ahmed.

2

First Name: Jazeel
Second Name: Ahmed.

7. Label Encoding

Label encoding means changing a data's in a dataset by giving them neuromal/ integer Number for each category.

eg:

Course	
BCA	0
BBA	1
Bcom	0

ONE hot encoding

ONE hot encoding means giving different Coloums for data in a dataset such as binary values.

Course:

2

BCA	1	0	1
BBA	0	1	1
Bcom	1	1	0

6.
- IQR method - It find the outlier by the 50% [illegible] of data differ from dataset
- Z Score - It works by how far a data is located in a dataset.
- Capping - Replace extreme value with upper or lower limit.
- Transformation - using mathematical calculation such as Log transform & Skewness.
- Deletion - Delete the outlier value by finding them.
- Imputation - Replace outliers with suitable values. Such mean & median.
- Binning - Convert numerical values into groups or categories.
- outlier treatment means handling unusual values to detect negative effect of dataset.
- outlier detecting method used to identify a value that are differ from dataset

4. Scaling is the processing adjusting the Scale of neumerical data for features can be compone more effeciency.

Normalization is a Scale technique that usually convert values b/w 0 & 1.

Formula = $\frac{x - xmin}{xmax - xmin}$

5. Formula = $\frac{x - xmin}{xmax - xmin}$

Transform data values specified by 0 to 1

$x' = \frac{x - xim}{x\text{-}max - xmin}$.