Capacitance	Resistance	Comment	Description	Designator	Footprint	LibRef	Quantity
			C&k Components			CMD	
			JS202011SCQN / Switch Slide DPDT		PCB- z2mqghhu0j8lc0ki	CMP- 94a55dc393914b6	
		2 way switch	6VDC 0.3A SMT	J3	x43w-1	2-14	1
			USB 3.1 Gen 2 Type C Receptacle				
			Right Angle Top				
		Amphenol	Mount Dual SMT 2.1mm Shell Tab		PCB- o51ryed2xyiiyzdqu	CMP- 1e79d211525dc1b	
		12401598E4#2A	Black Bulk	J1	kpx-1	e-1	1
			Battery Holder CR2025/2032			CMP-	
			Through Hole		PCBComponent_1 -	c866003ddb1617a	
		BAT-HLD-001-THM	Mount CMR200T Series	BT1	duplicate	1-7	1
			32.768 kHz ±20				
		Citizen Finetech	ppm 6 pF -40 to		PCB-	CMP-	
		Miyota CMR200T32768DZ	+85 °C SMT Tuning Fork		82rgjdkj2ta51ccq5	88ce42ed91805709	
		BT	Crystal	X1	5iy-1	1	1
			Header; Pin; Vertical; Copper				
			Alloy;				
		Connecteur_HE10_	Thermoplastic; 10; 0.100 x 0.100 in.: 1		PCB- vpkch8h1uqdxqvy	CMP- 1d55d605c481c292	
		2X5	Α	J2	nfy4j-1	6	1
			IN-S63AT Series White 0603 120°		_		
			900 mcd 3.9 V		PCB-	CMP-	
		Diode	Surface Mount Top View LED	D1	6c3zjm4k1kvwna5x zjsx-1	8bcb47e0445b540 c-1	1
		Diode	800mA Low-	D1	2,3%-1	C-1	'
		L	Dropout Linear				
		LM1117MPX- 3.3/NOPB	Regulator, 4-pin SOT-223, Pb-Free	U4	MP04A_L	CMP-0062-01639-6	1
			I2C Real-Time Clock with 56-Byte				
			NV RAM, 1.8V, 8-				
		MAX-RTC-8- DS1338U-U8+1	Pin uSOP, -40 to 85 degC, Pb-Free	U2	U8+1_N	CMP-1020999-3	1
			MCU 8-bit ATtiny				
		Microchip	AVR RISC 8KB Flash 3V/5V 20-Pin		PCBComponent_1 -	CMP- 1299df31b8dbcd5	
		ATTINY85V-15MT	VQFN Tube	U3	duplicate	e-1	1
			MCP73831 Series Single-Cell Li-				
		Microchip	Ion/Li-Polymer				
		Technology MCP73831T-	Battery Charge Controller SOT-23-				
		2ACI/OT	5	U1	SOT23-5_D	CMP-961385-12	1
			TUTY C I D				
			THT Vertical Pin Header WR-PHD,		PCB-	CMP-	
		Würth Elektronik	Pitch 2.54 mm,	No and out	s0hfil65plaomi4ibv		
		61300311121	Single Row, 3 pins	Neopixei Out	cw-1	31	1
			Multilayer Ceramic				
			Capacitors MLCC - SMD/SMT 0603				
			10uF 10volts			CMP-	
10.0 μF		10uF	*Derate Voltage/Temp	C2, C3	C0603	2000ea615e44ffc7- 5	2
P.		1				-	
			Cap Ceramic 0.1uF 16V Y5V -20% to		PCB-	CMP-	
		CL05F104ZO5NNN	80% SMD 0402		eewx94glvk4bhx4	7737beb0b932a8f	
100 nF		С	85°C Paper T/R Res Thick Film	C1, C4, C5	pifal-1	0-3	3
			0603 8.66K Ohm		1		
		Stackpole	1% 1/10W		1	CMP-	
		Stackpole Electronics	±100ppm/°C Molded SMD SMD		1	2e03e62c2885f1c4-	
	8.66 k?	RMCF0603FT8K66	Paper T/R	R1	CAPC1708X06N	1	1
			Res Thick Film 0603 10K Ohm 5%				
			1/10W		ncn.	CMD	
			±100ppm/°C Molded SMD SMD		PCB- c90638nymr1sxtgb	CMP- 494d8056daa7968	
	10.0 kO	Res2	Paper T/R	R3, R4, R5	7n4t-1	a-26	3
	510.0 O	Susumu RR0816P-5	RES SMD 510 OHM	R2	RESC1608X50X30LL	CMP-1864586-2	1





