

# Laboratorio de Programación

## 2016 -2

Juan Camilo Rada<sup>1</sup>

<sup>1</sup>Departamento de Electronica y ciencias de la computación

Octubre de 2016

# Outline

- 1 Function Pointers
  - Basics
  - Functions in structures

# Outline

- 1 Function Pointers
  - Basics
  - Functions in structures

# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)

# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)
- The pointer points to executable code within memory

# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)
- The pointer points to executable code within memory
- The function can be executed just by calling the pointer as a normal function

# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)
- The pointer points to executable code within memory
- The function can be executed just by calling the pointer as a normal function
- Invocation is known as *Indirect Call*

# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)
- The pointer points to executable code within memory
- The function can be executed just by calling the pointer as a normal function
- Invocation is known as *Indirect Call*
- Functions passed as an argument are widely known as *Callbacks*



# Function Pointers

## Basics

- Is a characteristic of the *Third Generation* of programming languages [▶ Read More!](#)
- The pointer points to executable code within memory
- The function can be executed just by calling the pointer as a normal function
- Invocation is known as *Indirect Call*
- Functions passed as an argument are widely known as *Callbacks*
- The function is expected to be called back at some convenient time

# Function Pointers

```
int myFunction(double a, char b)
```

# Function Pointers

```
int myFunction(double a, char b)
int (*pointer) (double, char)
```

## Declaring a pointer

- `int (*pointer) → int myFunction`

The pointer type has to be equal to the function return type

# Function Pointers

```
int myFunction(double a, char b)
int (*pointer) (double, char)
```

## Declaring a pointer

- `int (*pointer) → int myFunction`  
The pointer type has to be equal to the function return type
- `(double, char) → (double a, double b)`  
Types of the function members

# Function Pointers

```
int myFunction(double a, char b)
int (*pointer) (double, char)
```

## Declaring a pointer

- `int (*pointer) → int myFunction`  
The pointer type has to be equal to the function return type
- `(double, char) → (double a, double b)`  
Types of the function members
- `int (*pointer) (double, char) = myFunction`  
The pointer points to myFunction

# Function Pointers

```
int myFunction(double a, char b)
int (*pointer) (double, char)
```

## Declaring a pointer

- `int (*pointer) → int myFunction`  
The pointer type has to be equal to the function return type
- `(double, char) → (double a, double b)`  
Types of the function members
- `int (*pointer) (double, char) = myFunction`  
The pointer points to myFunction
- `void process(void (*funcp)(int), int a, int b)`  
A function which receives a function as a parameter

# Function Pointers

## Test the code

```
#include <stdio.h>

void callback(int value)
{
    printf("This Callback function prints the value = %i", value);
}

void process(void (*funcp)(int), int a, int b)
{
    int c = a + b;
    funcp(c);
}

int main()
{
    void (*functionPointer)(int);
    functionPointer = callback;
    process(functionPointer, 2, 3);
}
```

# Function Pointers

## Test the code

```
#include <stdio.h>
void callback()
{
    printf("The process has finished!!!\n");
}
void process(void (*funcp)(), int *a, int b)
{
    *a = (*a * *a) + b;
    funcp();
}
int main()
{
    int var = 5;
    void (*functionPointer)();
    functionPointer = callback;
    process(functionPointer, &var, 3);
    printf("a = %d", var);
}
```



# Function Pointers

## Test the code

```
#include <stdio.h>
int sumCallback(int a, int b)
{
    return a + b;
}
void process(int (*funcp)(int, int), int a, int b)
{
    printf("a = %d, b = %d, res = %d", a, b, funcp(a, b));
}
int main()
{
    int (*functionPointer)(int, int);
    functionPointer = sumCallback;
    process(functionPointer, 5, 3);
}
```

# Function Pointers

```
int* map(int (*fun)(int value), int *array, int size)
```

## The map function

- Is a *High-order* function

# Function Pointers

```
int* map(int (*fun)(int value), int *array, int size)
```

## The map function

- Is a *High-order* function
- A high-order function is the one who takes functions as arguments

# Function Pointers

```
int* map(int (*fun)(int value), int *array, int size)
```

## The map function

- Is a *High-order* function
- A high-order function is the one who takes functions as arguments
- The map function applies the input function over all the elements in an array

# Function Pointers

```
int* map(int (*fun)(int value), int *array, int size)
```

## The map function

- Is a *High-order* function
- A high-order function is the one who takes functions as arguments
- The map function applies the input function over all the elements in an array
- *Keep in mind:* It works also for sequential *containers*

# Function Pointers


The `map` function - How it works?

9	3	31	10	7	4
---	---	----	----	---	---

$$f(x) = x * 2$$

# Function Pointers

## The map function - How it works?



# Function Pointers

## The map function - How it works?

$$f(x) = x * 2$$

9	3	31	10	7	4
---	---	----	----	---	---



18	6				
----	---	--	--	--	--



# Function Pointers

## The map function - How it works?

$$f(x) = x * 2$$

9	3	31	10	7	4
---	---	----	----	---	---



18	6	62	20	14	8
----	---	----	----	----	---

# Function Pointers

## The map function - Implementation

```
int* map(int (*funPtr)(int), int* ptr, int size)
{
    int* ptrRes = calloc(size, sizeof(int));
    for (int i=0; i<size; i++)
    {
        *(ptrRes+i) = funPtr(ptr[i]);
    }
    return ptrRes;
}
```

# Function Pointers - Test the code with the map function

```
#include <stdio.h>
#include <stdlib.h>

int getDouble(int a)
{
    return a*2;
}

int main()
{
    int *a = calloc(2, sizeof(int));
    int (*fun)(int) = getDouble;
    a[0] = 5;
    a[1] = 9;

    int* array = map(fun, a, 2);

    printf("%d, %d", array[0], array[1]);
}
```

# Outline

- 1 Function Pointers
  - Basics
  - Functions in structures

# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;
};
```

# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;
};
```

The basic structure contains:

- A pointer to the head of the queue

# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;
};
```

The basic structure contains:

- A pointer to the head of the queue
- A pointer to the tail of the queue

# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;
};
```

- What if we want to *encapsulate* all the queue functions inside the structure?



# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;
};
```

- What if we want to *encapsulate* all the queue functions inside the structure?
- We can use pointers to functions

# Functions in structures

## The Queue structure

```
struct queue
{
    Node * head;
    Node * tail;

    void (*enqueue)(struct queue *, int);
    int (*dequeue)(struct queue *);
    void (*print)(struct queue *);
};
```

- `void (*enqueue)(struct queue *, int);`

# Functions in structures

## The Queue structure


```
struct queue
{
    Node * head;
    Node * tail;

    void (*enqueue)(struct queue *, int);
    int (*dequeue)(struct queue *);
    void (*print)(struct queue *);
};
```

- `void (*enqueue)(struct queue *, int);`
- We create three new pointers to every handled operation

# Functions in structures

Queue



# Functions in structures

## The Queue structure - The Constructor function

```
Queue * constructor()  
{  
    Queue * myQueue = (Queue*)malloc(sizeof(Queue));  
    myQueue->enqueue = enqueue;  
    myQueue->dequeue = dequeue;  
    myQueue->print = print;  
    return myQueue;  
}
```

- The constructor will provide us an instance of a Queue

# Functions in structures

## The Queue structure - The Constructor function

```
Queue * constructor()  
{  
    Queue * myQueue = (Queue*)malloc(sizeof(Queue));  
    myQueue->enqueue = enqueue;  
    myQueue->dequeue = dequeue;  
    myQueue->print = print;  
    return myQueue;  
}
```

- The constructor will provide us an instance of a Queue
- We must associate every pointer to its respective function

# Functions in structures

## The Queue structure - The Constructor function

```
Queue * myQueue = constructor();  
myQueue->enqueue(myQueue, 5);
```

# Functions in structures

## The Queue structure - The Constructor function

```
Queue * myQueue = constructor();  
myQueue->enqueue(myQueue, 5);
```

- We have to call `constructor()` every time we need a new instance of Queue



# Functions in structures

## The Queue structure - The Constructor function

```
Queue * myQueue = constructor();  
myQueue->enqueue(myQueue, 5);
```

- We have to call `constructor()` every time we need a new instance of Queue
- All the functions has to be called with the `->` operator

# Functions in structures

## The Queue structure - The Constructor function

```
Queue * myQueue = constructor();  
myQueue->enqueue(myQueue, 5);
```

- We have to call `constructor()` every time we need a new instance of Queue
- All the functions has to be called with the `->` operator

# Functions in structures

## The Queue structure - The Constructor function

```
Queue * myQueue = constructor();  
myQueue->enqueue(myQueue, 5);
```

Be careful!. The pointer to every function can be modified so, it can be unsafe!!!