CS 305: Computer Networks
Fall 2022

Lecture 10：Network Layer – The Data Plane

Ming Tang

Department of Computer Science and Engineering
Southern University of Science and Technology (SUSTech)

Chapter 4: outline

4.1 Overview of Network layer
- data plane
- control plane

4.2 What' s inside a router

4.3 IP: Internet Protocol
- datagram format
- fragmentation
- IPv4 addressing
- network address translation
- IPv6

4.4 Generalized Forward and SDN
- match
- action
- OpenFlow examples of match-plus-action in action

Obtaining a Block of Address

Q: how does *network* get subnet part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 00010000	00000000	200.23.16.0/20
Organization 0	11001000 00010111 00010000	00000000	200.23.16.0/23
Organization 1	11001000 00010111 00010010	00000000	200.23.18.0/23
Organization 2	11001000 00010111 00010100	00000000	200.23.20.0/23
...	…..	….	….
Organization 7	11001000 00010111 00011110	00000000	200.23.30.0/23

Obtaining a Host Address

Once obtained a block of addresses:

- manually configure the IP addresses into the router

Q: How does a *host* get IP address?

- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"
  - Same IP each time, or temporary IP addresses

DHCP client-server scenario



(Might be multiple DHCP servers who replies)

DHCP: more than IP addresses

DHCP can return more than just allocated IP address on subnet:

- address of first-hop router for client
- name and IP address of DNS sever
- network mask (indicating network versus host portion of address)

DHCP drawback:

- A new IP address is obtained each time a node connects to a new subnet
- Mobile devices

Chapter 4: outline

4.1 Overview of Network layer
- data plane
- control plane

4.2 What's inside a router

4.3 IP: Internet Protocol
- datagram format
- fragmentation
- IPv4 addressing
- network address translation
- IPv6

4.4 Generalized Forward and SDN
- match
- action
- OpenFlow examples of match-plus-action in action

NAT: network address translation

Local area networks (LANs):

- E.g., a residence, school, laboratory, university campus or office building
- a range of addresses would need to be allocated by the ISP to cover all of the LAN's IP devices
- If the subnet grew bigger, a larger block of addresses would have to be allocated.
- Huge number of LAN …

NAT: network address translation

NAT: reserve blocks of IP addresses for LANs

- Private network; private IP address

RFC 1918 name	IP address range	Number of addresses	Largest CIDR block (subnet mask)	Host ID size	Mask bits	*Classful* description[Note 1]
24-bit block	10.0.0.0 – 10.255.255.255	16 777 216	10.0.0.0/8 (255.0.0.0)	24 bits	8 bits	single class A network
20-bit block	172.16.0.0 – 172.31.255.255	1 048 576	172.16.0.0/12 (255.240.0.0)	20 bits	12 bits	16 contiguous class B networks
16-bit block	192.168.0.0 – 192.168.255.255	65 536	192.168.0.0/16 (255.255.0.0)	16 bits	16 bits	256 contiguous class C networks

NAT: network address translation



all datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7,different source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

motivation: local network uses just one IP address (e.g., 138.76.29.7 in the example) as far as outside world is concerned:

- range of addresses not needed from ISP: just one IP address for all devices
- can change addresses of devices in local network without notifying outside world
- can change ISP without changing addresses of devices in local network
- devices inside local net not explicitly addressable, visible by outside world (a security plus)

NAT: network address translation

implementation: NAT router must:

- *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)

  . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr

- *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair

- *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation



NAT translation table

WAN side addr	LAN side addr
138.76.29.7, 5001	10.0.0.1, 3345
……	……

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

NAT: network address translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, e.g., P2P applications, server processes
    - Well-known port number

Chapter 4: outline

4.1 Overview of Network layer
- data plane
- control plane

4.2 What's inside a router

4.3 IP: Internet Protocol
- datagram format
- fragmentation
- IPv4 addressing
- network address translation
- IPv6

4.4 Generalized Forward and SDN
- match
- action
- OpenFlow examples of match-plus-action in action

IPv6: motivation

- *initial motivation:* 32-bit address space soon to be completely allocated.
- additional motivation:
  - header format helps speed processing/forwarding
  - header changes to facilitate QoS

IPv6 datagram format:

- 128-bit address space: why?
- fixed-length 40 byte header; why?
- no fragmentation allowed ; why?

IPv6 datagram format

priority: identify priority among datagrams in flow

flow Label: identify datagrams in same "flow."
(concept of "flow" not well defined).

next header: identify upper layer protocol for data (for example, to TCP or UDP).



decremented by one by each router that forwards the Datagram; if reaches zero, the datagram is discarded.

Other changes from IPv4

- *checksum*: removed entirely to reduce processing time at each hop; why?
- *options:* allowed, but outside of header, indicated by "Next Header" field
- *no fragmentation:*
  - too large to be forwarded over the outgoing link
  - the router simply drops the datagram and sends a "Packet Too Big" ICMP error message

Transition from IPv4 to IPv6

- not all routers can be upgraded simultaneously
  - no "flag days"
  - how will network operate with mixed IPv4 and IPv6 routers?
- *tunneling:* IPv6 datagram carried as *payload* in IPv4 datagram among IPv4 routers



Tunneling



IPv6 tunneling - IBM Documentation

IPv6: adoption

- Google: 8% of clients access services via IPv6
- NIST: 1/3 of all US government domains are IPv6 capable

- *Long (long!) time for deployment, use*
  - 20 years and counting!
  - think of application-level changes in last 20 years: WWW, Facebook, streaming media, Skype, …
  - *Why?*

Chapter 4: outline

4.1 Overview of Network layer
- data plane
- control plane

4.2 What's inside a router

4.3 IP: Internet Protocol
- datagram format
- fragmentation
- IPv4 addressing
- network address translation
- IPv6

4.4 Generalized Forward and SDN
- match
- action
- OpenFlow examples of match-plus-action in action

Generalized Forwarding and SDN

Each router contains a *flow table* that is computed and distributed by a *logically centralized* routing controller



OpenFlow data plane abstraction

Generalized forwarding: simple packet-handling rules

- *Pattern:* match values in packet header fields
- *Actions: for matched packet:* drop, forward, modify, matched packet or send matched packet to controller
- *Priority*: disambiguate overlapping patterns
- *Counters:* #packets; time last updated



Flow table in a router (computed and distributed by controller) define router's match+action rules

OpenFlow data plane abstraction

Generalized forwarding: simple packet-handling rules

- *Pattern:* match values in packet header fields
- *Actions: for matched packet:* drop, forward, modify, matched packet or send matched packet to controller
- *Priority*: disambiguate overlapping patterns
- *Counters:* #packets; time last updated



* : wildcard

1. src=1.2.*.*, dest=3.4.5.* → drop
2. src = *.*.*.*, dest=3.4.*.* → forward(2)
3. src=10.1.2.3, dest=*.*.*.* → send to controller

OpenFlow: Flow Table Entries



Destination-based forwarding:

Destination-based forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Action
*	*	*	*	*	*	51.6.0.8	*	*	*	port6

IP datagrams destined to IP address 51.6.0.8 should be forwarded to router output port 6

Destination-based layer 2 (switch) forwarding:

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Action
*	22:A7:23: 11:E1:02	*	*	*	*	*	*	*	*	port3

layer 2 frames from MAC address 22:A7:23:11:E1:02 should be forwarded to output port 6

OpenFlow example

Example: datagrams from hosts h5 and h6 should be sent to h3 or h4, via s1 and from there to s2

match	action
IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(3)



match	action
ingress port = 1 IP Src = 10.3.*.* IP Dst = 10.2.*.*	forward(4)

match	action
ingress port = 2 IP Dst = 10.2.0.3	forward(3)
ingress port = 2 IP Dst = 10.2.0.4	forward(4)

Firewall

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Forward
*	*	*	*	*	*	*	*	*	22	drop

do not forward (block) all datagrams destined to TCP port 22

Switch Port	MAC src	MAC dst	Eth type	VLAN ID	IP Src	IP Dst	IP Prot	TCP sport	TCP dport	Forward
*	*	*	*	*	128.119.1.1	*	*	*	*	drop

do not forward (block) all datagrams sent by host 128.119.1.1

Firewall



s2 Flow Table (Example 3)	
Match	Action
IP Src = 10.3.*.* IP Dst = 10.2.0.3	Forward(3)
IP Src = 10.3.*.* IP Dst = 10.2.0.4	Forward(4)

there were no other entries in s2's flow table

Load Balancing



s2 Flow Table (Example 2)	
Match	Action
Ingress port = 3; IP Dst = 10.1.*.*	Forward(2)
Ingress port = 4; IP Dst = 10.1.*.*	Forward(1)
…	…

OpenFlow abstraction

- *match+action:* unifies different kinds of devices

- Router
  - *match:* longest destination IP prefix
  - *action:* forward out a link
- Switch
  - *match:* destination MAC address
  - *action:* forward or flood
- Firewall
  - *match*: IP addresses and TCP/UDP port numbers
  - *action:* permit or deny
- NAT
  - *match:* IP address and port
  - *action:* rewrite address and port

Chapter 4: *done!*

4.1 Overview of Network layer: data plane and control plane

4.2 What's inside a router

4.3 IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- NAT
- IPv6

4.4 Generalized Forward and SDN

- match plus action
- OpenFlow example

Question: how do forwarding tables (destination-based forwarding) or flow tables (generalized forwarding) computed?

Answer: by the control plane (next chapter)

CS 305: Computer Networks
Fall 2022

Network Layer – The Control Plane

Ming Tang

Department of Computer Science and Engineering
Southern University of Science and Technology (SUSTech)

Chapter 5: network layer control plane

chapter goals: understand principles behind network control plane

- traditional routing algorithms
- SDN controllers
- Internet Control Message Protocol
- network management

and their instantiation, implementation in the Internet:

- OSPF, BGP, OpenFlow, ODL and ONOS controllers, ICMP, SNMP

Chapter 5: outline

5.1 introduction

5.2 routing protocols

- link state
- distance vector

5.3 intra-AS routing in the Internet: OSPF

5.4 routing among the ISPs: BGP

5.5 The SDN control plane

5.6 ICMP: The Internet Control Message Protocol

5.7 Network management and SNMP

Network-layer functions

Recall: two network-layer functions:

- *forwarding:* move packets from router's input to appropriate router output — *data plane*
- *routing:* determine route taken by packets from source to destination — *control plane*

Two approaches to structuring network control plane:

- per-router control (traditional)
- logically centralized control (software defined networking)

Per-router control plane

Individual routing algorithm components *in each and every router* interact with each other in control plane to compute forwarding tables



Logically centralized control plane

A distinct (typically remote) controller interacts with local control agents (CAs) in routers to compute forwarding tables



Chapter 5: outline

Routing protocols

Routing protocol goal: determine "good" paths (equivalently, routes), from sending hosts to receiving host, through network of routers

- path: sequence of routers packets will traverse in going from given initial source host to given final destination host
- "good": least "cost", "fastest", "least congested"
- routing: a "top-10" networking challenge!

Graph abstraction of the network



graph: G = (N,E)

N = set of routers = { u, v, w, x, y, z }

E = set of links ={ (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) }

aside: graph abstraction is useful in other network contexts, e.g., P2P, where *N* is set of peers and *E* is set of TCP connections

Graph abstraction: costs



$c(x,x') = \text{cost of link } (x,x')$

e.g., $c(w,z) = 5$

cost could always be 1, or inversely related to bandwidth, or inversely related to congestion

cost of path $(x_1, x_2, x_3, \ldots, x_p) = c(x_1,x_2) + c(x_2,x_3) + \ldots + c(x_{p-1},x_p)$

key question: what is the least-cost path between u and z ?

routing algorithm: algorithm that finds that least cost path

Routing algorithm classification

Q: global or decentralized information?

global:

- all routers have complete topology, link cost info
- "link state" algorithms

decentralized:

- router knows physically-connected neighbors, link costs to neighbors
- iterative process of computation, exchange of info with neighbors
- "distance vector" algorithms

Q: static or dynamic?

static:

- routes change slowly over time

dynamic:

- routes change more quickly
  - periodic update
  - in response to link cost changes

Routing algorithm classification

Q: load-sensitive or load insensitive?

Load-sensitive:

- Link costs vary dynamically to reflect the current level of congestion

Load-insensitive

- A link's cost does not explicitly reflect its current level of congestion

Chapter 5: outline

A link-state routing algorithm

Dijkstra's algorithm

- net topology, link costs known to all nodes
  - accomplished via "link state broadcast"
  - all nodes have same info
- computes least cost paths from one node ('source") to all other nodes
  - gives *forwarding table* for that node
- iterative: after k iterations, know least cost path to k dest.'s

notation:

- c(x,y): link cost from node x to y; $= \infty$ if not direct neighbors
- D(v): current value of cost of path from source to dest. v
- p(v): predecessor node along path from source to v
- N': set of nodes whose least cost path definitively known

Dijsktra’s algorithm

```
Initialization:
  N' = {u}
  for all nodes v
    if v adjacent to u
        then D(v) = c(u,v)
    else D(v) = ∞

Loop
   find w not in N' such that D(w) is a minimum
   add w to N'
   update D(v) for all v adjacent to w and not in N' :
       D(v) = min( D(v), D(w) + c(w,v) )
   /* new cost to v is either old cost to v or known
    shortest path cost to w plus cost from w to v */
until all nodes in N'
```

Dijkstra's algorithm: example

Step	N'	D(v) p(v)	D(w) p(w)	D(x) p(x)	D(y) p(y)	D(z) p(z)
0	u	7,u	3,u	5,u	∞	∞
1	uw	6,w		5,u	11,w	∞
2	uwx	6,w			11,w	14,x
3	uwxv				10,v	14,x
4	uwxvy					12,y
5	uwxvyz					

notes:

- construct shortest path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)



Dijkstra's algorithm: another example

Step	N'	D(v),p(v)	D(w),p(w)	D(x),p(x)	D(y),p(y)	D(z),p(z)
0	u	2,u	5,u	1,u	∞	∞
1	ux	2,u	4,x		2,x	∞
2	uxy	2,u	3,y			4,y
3	uxyv		3,y			4,y
4	uxyvw					4,y
5	uxyvwz					



* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Dijkstra's algorithm: example (2)

resulting shortest-path tree from u:



resulting forwarding table in u:

destination	link
v	(u,v)
x	(u,x)
y	(u,x)
w	(u,x)
z	(u,x)

Dijkstra's algorithm, discussion

algorithm complexity: n nodes

- each iteration: need to check all nodes not in N'
- n(n+1)/2 comparisons: $O(n^2)$
- more efficient implementations possible: O(nlogn)

oscillations possible:

- e.g., support link cost equals amount of carried traffic:



initially



given these costs,
find new routing….
resulting in new costs



given these costs,
find new routing….
resulting in new costs



given these costs,
find new routing….
resulting in new costs

Chapter 5: outline

5.1 introduction

5.2 routing protocols

- link state
- distance vector

5.3 intra-AS routing in the Internet: OSPF

5.4 routing among the ISPs: BGP

5.5 The SDN control plane

5.6 ICMP: The Internet Control Message Protocol

5.7 Network management and SNMP