

	CRS	P&O	44W	SS304-2B SS304-#4	SS304-MF	Alu 5052-H32 Ali 6061-T6	Trou minimum	Tolérance sur découpe
26ga	0.018"			0.018"			0,020	±0.005"
24ga	0.024"			0.025"		0.020"	0,020	±0.005"
22ga	0.030"			0.0312"		0.025"	0,025	±0.005"
20ga	0.036"			0.0375"		0.032"	0,030	±0.005"
18ga	0.048"			0.050"		0.040"	0,035	±0.005"
16ga	0.059"			0.625"		0.051"	0,040	±0.005"
14ga	0.074"			0.0781"		0.064"	0,050	±0.005"
12ga	0.104"			0.109"		0.081"	0,070	±0.005"
11ga	0.119"			0.125"		0.091"	0,080	±0.005"
10ga		0.134"		0.140"		0.102"	0,080	±0.005"
	0.125"					0.125"	0,080	±0.005"
		0.1875"			0.1875"	0.1875"	0,125	±0.005"
		0.250"			0.250"	0.250"	0,187	±0.005"
			0.3125"		0.3125"	0.3125"	0,250	±0.005"
		0.375"			0.375"	0.375"	0,250	±0.008"
			0.500"		0.500"	0.500"	0,375	±0.012"
			0.625"		0.625"	0.625"	0,437	±0.015"
			0.750"		0.750"	0.750"	0,563	±0.015"
			1.000"		1.000"	1.000"	0,750	±0.020"