COMP2602 Chapter Network Layer



A note on the use of these ppt slides:

We're making these slides freely available to all (faculty, students, readers). They're in powerpoint form so you can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) in substantially unaltered form, that you mention their source (after all, we'd like people to use our book!)
- If you post any slides in substantially unaltered form on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

Computer Networking: A Top Down Approach Featuring the Internet,
Jim Kurose, Keith Ross
Addison-Wesley, 2012

Chapter 4: Network Layer

Chapter goals:

- understand principles behind network layer services:
  - routing (path selection)
  - dealing with scale
  - how a router works
  - advanced topics: IPv6, mobility
- instantiation and implementation in the Internet

Overview:

- network layer services
- routing principles: path selection
- Link state and Distance Vector Routing
- IP
- Internet routing protocols
  - intra-domain (at end of slides)
  - inter-domain
- what's inside a router?
- IPv6

Network layer functions

- transport packet from sending to receiving hosts
- network layer protocols in *every* host, router

three important functions:

- *path determination:* route taken by packets from source to dest. *Routing algorithms*
- *forwarding:* move packets from router's input to appropriate router output
- *call setup:* some network architectures require router call setup along path before data flows



Network service model

Q: What *service model* for "channel" transporting packets from sender to receiver?

service abstraction

- guaranteed bandwidth?
- preservation of inter-packet timing (no jitter {jitter=inter-packet delay})?
- loss-free delivery?
- in-order delivery?
- congestion feedback to sender?

The most important abstraction provided by network layer:



Virtual circuits

"source-to-dest path behaves much like telephone circuit"

- performance-wise
- network actions along source-to-dest path

- call setup, teardown for each call *before* data can flow
- each packet carries short VC identifier (not destination host ID)
- *every* router on source-dest path maintains "state" for each passing connection
  - transport-layer connection only involved two end systems
- link, router resources (bandwidth, buffers) may be *allocated* to VC
  - to get circuit-like perf.

Virtual circuits: signaling protocols

Circuit-switched, X.25-packet, frame relay and ATM networks are connection-oriented data networks!

- used to setup, maintain, teardown VC
- used in ATM, frame-relay, X.25 (The most common form of virtual circuit network were ATM and X.25, which for a while were commonly used for public packet data networks.)
-



Datagram networks: the Internet model

- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of "connection"
- packets forwarded using destination host address
  - packets between same source-dest pair may take different paths



Network layer service models:

Network Architecture	Service Model	Guarantees ?				Congestion feedback
		Bandwidth	Loss	Order	Timing	
Internet	best effort	none	no	no	no	no (inferred via loss)
ATM	CBR	constant rate	yes	yes	yes	no congestion
ATM	VBR	guaranteed rate	yes	yes	yes	no congestion
ATM	ABR	guaranteed minimum	no	yes	no	yes
ATM	UBR	none	no	yes	no	no

No spikes

Bursty data

timing of delivered data is not critical

C-Constant;V- Variable; A- Available;U-Unspecified

- Internet model being extended: Intserv, Diffserv (QOS)
  - Chapter 6

Datagram or VC network: why?

Internet

- data exchange among computers
  - "elastic" service, no strict timing req.
- "smart" end systems (computers)
  - can adapt, perform control, error recovery
  - simple inside network, complexity at "edge"
- many link types
  - different characteristics
  - uniform service difficult

ATM

- evolved from telephony
- human conversation:
  - strict timing, reliability requirements
  - need for guaranteed service
- "dumb" end systems
  - telephones
  - complexity inside network

Routing

Routing protocol

Goal: determine "good" path (sequence of routers) thru network from source to dest.



Graph abstraction for routing algorithms:

- graph nodes are routers
- graph edges are physical links
  - link cost: delay, $ cost, or congestion level

- "good" path:
  - typically means minimum cost path
  - other def's possible

Routing Algorithm classification

Global or decentralized information?

Global:

- all routers have complete topology, link cost info
- "link state" algorithms

Decentralized:

- router knows physically-connected neighbors, link costs to neighbors
- iterative process of computation, exchange of info with neighbors
- "distance vector" algorithms

Static or dynamic?

Static:

- routes change slowly over time

Dynamic:

- routes change more quickly
  - periodic update
  - in response to link cost changes

Distance Vector Routing (Decentralised)



Sample calculation, J to F (J->neighb->F)
Via A(8+23=31), I (10+20=30), H (12+19=31), K(6+40=46)
Min = 30 via I

Delay to neighbours of j



(a)



(b)

Routing table calculated using distance via neighbors

Intra-domain and Inter-Domain Routing

- **Intra-domain routing**

-->routing within an AS(Autonomous System).
-->ignores the internet outside the autonomous system.
-->protocols for intra domain routing are also called **interior gateway** protocols.
-->popular protocols are **RIP** and **OSPF**.
(RIP-Routing Information Protocol-Distance vector
OSPF-Open Shortest Path First)-Link state

Intra-domain and Inter-Domain Routing

On the Internet, an autonomous system (AS) is the unit of router policy, either a single network or a group of networks that is controlled by a common network administrator (or group of administrators) on behalf of a single administrative entity (such as a university, a business enterprise, or a business division). An autonomous system is also sometimes referred to as a routing domain. Whatis.com

- **Inter-domain routing**

-->routing between AS's.
-->assumes that the internet consists of a collection of interconnected AS's.
-->protocol for inter domain routing are also called **exterior gateway** protocols.
-->routing protocol e.g. **BGP.** (border gateway protocol)

The Internet Network layer

Kurose and Ross
2012

Host, router network layer functions:



IP Addressing: introduction

- IP address: 32-bit identifier for host, router *interface*
- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host may have multiple interfaces
  - IP addresses associated with each interface



223.1.1.1 = 11011111 00000001 00000001 00000001

223 1 1 1

IP Addressing

- IP address:
  - network part (high order bits)
  - host part (low order bits)
- *What's a network ?* (from IP address perspective)
  - device interfaces with same network part of IP address
  - can physically reach each other without intervening router



network consisting of 3 IP networks (for IP addresses starting with 223, first 24 bits are network address)

223.1.1, 223.1.2, 223.1.3

Net=24, H=8 C | 110 | network | host | 192.0.0.0 to 223.255.255.255

IP Addressing

How to find the networks?

- Detach each interface from router, host
- create "islands of isolated networks



Interconnected system consisting of six networks

IP Addresses

given notion of "network",
let's re-examine IP addresses:
"class-full" addressing:

	Number of Networks	Hosts per Network (Usable Addresses)
A	126 ($2^7 - 2$)	16,777,214 ($2^{24} - 2$)
B	16,382 ($2^{14} - 2$)	65,534 ($2^{16} - 2$)
C	2,097,150 ($2^{21} - 2$)	254 ($2^8 - 2$)



IP addressing: CIDR

- Classful addressing:
  - inefficient use of address space, address space exhaustion
  - e.g., class B net allocated enough addresses for 65K hosts, even if only 2K hosts in that network
- CIDR: Classless InterDomain Routing
  - network portion of address of arbitrary length
  - address format: a.b.c.d/x, where x is # bits in network portion of address



IP addresses: how to get one?

Q: How does *host* get IP address?

- hard-coded by system admin in a file
  - Wintel: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

  (more shortly)

IP addresses: how to get one?

Q: How does *network* get network part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 00010000	00000000	200.23.16.0/20
Organization 0	11001000 00010111 0001000**0**	00000000	200.23.16.0/23
Organization 1	11001000 00010111 0001001**0**	00000000	200.23.18.0/23
Organization 2	11001000 00010111 0001010**0**	00000000	200.23.20.0/23
...	.....	....	....
Organization 7	11001000 00010111 0001111**0**	00000000	200.23.30.0/23

IP addressing: the last word...

Q: How does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

Getting a datagram from source to dest.

IP datagram:

misc fields	source IP addr	dest IP addr	data

- datagram remains unchanged, as it travels source to destination
- addr fields of interest here

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2



Getting a datagram from source to dest.

misc fields	223.1.1.1	223.1.1.3	data

Starting at A, send IP datagram addressed to B:

- look up net. address of B in forwarding table
- find B is on same net. as A
- link layer will send datagram directly to B inside link-layer frame
  - B and A are directly connected

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2



Getting a datagram from source to dest.

misc fields	223.1.1.1	223.1.2.2	data

Starting at A, dest. E:

- look up network address of E in forwarding table
- E on *different* network
  - A, E not directly attached
- routing table: next hop router to E is 223.1.1.4
- link layer sends datagram to router 223.1.1.4 inside link-layer frame
- datagram arrives at 223.1.1.4
- continued…..

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2



Getting a datagram from source to dest.

misc fields	223.1.1.1	223.1.2.2	data

forwarding table in router

Dest. Net	router	Nhops	interface
223.1.1	-	1	223.1.1.4
223.1.2	-	1	223.1.2.9
223.1.3	-	1	223.1.3.27

Arriving at 223.1.1.4, destined for 223.1.2.2

- look up network address of E in router's forwarding table
- E on *same* network as router's interface 223.1.2.9
  - router, E directly attached
- link layer sends datagram to 223.1.2.2 inside link-layer frame via interface 223.1.2.9
- datagram arrives at 223.1.2.2!!! (hooray!)



IP datagram format



IP protocol version Number e.g. IPV4

header length (bytes)

"type" of data (speed, reliability)

max number remaining hops (decremented at each router)

upper layer protocol to deliver payload to, eg UDP

total datagram Length (header+data) (bytes)

for fragmentation/ reassembly

Header checksum only

E.g. timestamp, record route taken, specify list of routers to visit.

Flags
--X More
-X- Don't Fragment
X-- Unused

how much overhead with TCP?

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP Fragmentation & Reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame.
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at final destination
  - IP header bits used to identify, order related fragments



IP Fragmentation and Reassembly



Example

- 4000 byte datagram
- MTU = 1500 bytes

One large datagram becomes several smaller datagrams



1480

1480

1020

3980 of data

So original 4000 byte packet has 20 bytes overhead so data = 3980

ICMP: Internet Control Message Protocol

- used by hosts, routers, gateways to communication network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- ICMP message: type, code plus first 8 bytes of IP datagram causing error

Type	Code	description
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

DHCP: Dynamic Host Configuration Protocol

Goal: allow host to *dynamically* obtain its IP address from network server when it joins network

- Can renew its lease on address in use
- Allows reuse of addresses (only hold address while connected an "on"
- Support for mobile users who want to join network (more shortly)

DHCP overview:

- host broadcasts "DHCP discover" msg
- DHCP server responds with "DHCP offer" msg
- host requests IP address: "DHCP request" msg
- DHCP server sends address: "DHCP ack" msg

NAT: Network Address Translation



All datagrams *leaving* local network have same single source NAT IP address: 138.76.29.7, different source port numbers

Datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: Network Address Translation

- Motivation: local network uses just one IP address as far as outside word is concerned:
  - no need to be allocated range of addresses from ISP: - just one IP address is used for all devices
  - can change addresses of devices in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - devices inside local net not explicitly addressable, visible by outside world (a security plus).

NAT: Network Address Translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
    layer-3(network layer=IP addr, layer-4(transport=port numbers)
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, eg, P2P applications
  - address shortage should instead be solved by IPv6

IPv6

- Initial motivation: 32-bit address space completely allocated by 2008.
- Additional motivation:
  - header format helps speed processing/forwarding
  - header changes to facilitate QoS
  - new "anycast" address: route to "best" of several replicated servers
- IPv6 datagram format:
  - fixed-length 40 byte header
  - no fragmentation allowed at intermediate routers

IPv6 Header (Cont)

Priority: identify priority among datagrams in flow
Flow Label: identify datagrams in same "flow."
(concept of"flow" not well defined).
Next header: identify upper layer protocol for data



Other Changes from IPv4

- *Checksum:* removed entirely to reduce processing time at each hop
- *Options:* allowed, but outside of header, indicated by "Next Header" field
- *ICMPv6:* new version of ICMP
  - additional message types, e.g. "Packet Too Big"
  - multicast group management functions

Transition From IPv4 To IPv6

- Not all routers can be upgraded simultaneous
  - no "flag days"
  - How will the network operate with mixed IPv4 and IPv6 routers?
- Two proposed approaches:
  - *Dual Stack*: some routers with dual stack (v6, v4) can "translate" between formats
  - *Tunneling*: IPv6 carried as payload in IPv4 datagram among IPv4 routers

Dual Stack Approach



Tunneling


Logical view:
A
B
tunnel
E
F
IPv6
IPv6
IPv6
IPv6
Physical view:
A
B
C
D
E
F
IPv6
IPv6
IPv4
IPv4
IPv6
IPv6
Flow: X
Src: A
Dest: F
data
Src:B
Dest: E
Flow: X
Src: A
Dest: F
data
Src:B
Dest: E
Flow: X
Src: A
Dest: F
data
Flow: X
Src: A
Dest: F
data
A-to-B:
IPv6
B-to-C:
IPv6 inside
IPv4
D-to-E:
IPv6 inside
IPv4
E-to-F:
IPv6

Review

1. What is purpose of NAT? How does IPV6 affect NAT?
2. When is fragmentation used?
3. What is an advantage of subnetting?
4. What happened with the early IP address classes as persons tried to obtain them?
5. What does CIDR do?
6. Give an example of how ICMP is used.