



The Salesman

locked

by kevinso

Problem

Submissions

Leaderboard


Discussions

Editorial

You are a salesman and your goal is to visit all the houses along a certain street.

You walk at a constant rate and can start and end at any location. You may visit the houses in any order you wish. Given the locations of the houses along the street, what is the minimum amount of time needed for you to visit all the houses?

Formally, we represent the street as a number line and the positions of the houses as numbers along this line.



There are n houses numbered $1, 2, \dots, n$, and they are located at x_1, x_2, \dots, x_n , respectively. Assume that it takes 0 (negligible) time to visit a house, and walking from house i to house j takes $|x_i - x_j|$ minutes.

Complete the function `minimumTime` which takes an integer array x , denoting the locations of the houses as input. Return an integer denoting the minimum amount of time, in minutes, needed to visit all the houses.

Input Format

The first line contains a single integer t denoting the number of streets. The description of t streets follow.

Each street is described by two lines. The first line contains a single integer n denoting the number of houses in that street. The second line contains n integers x_1, x_2, \dots, x_n denoting the locations of the houses along the street.

Constraints

- $1 \leq t \leq 500$
- $1 \leq n \leq 50$ (So there may be only one house)
- $1 \leq x_i \leq 1000$
- The houses' locations are distinct

Subtasks

- For 20% of the maximum score, $n \leq 3$
- For 50% of the maximum score, $n \leq 6$

Output Format

For each street, print a single line containing a single integer denoting the minimum amount of time, in minutes, needed to visit all the houses.

Sample Input 0

```
1
3
11 6 9
```

Sample Output 0

```
5
```

Explanation 0

In this case, there are $n = 3$ houses at locations $x_1 = 11$, $x_2 = 6$ and $x_3 = 9$.

We can consider 6 possible orders to visit the houses.

1. $1 \rightarrow 2 \rightarrow 3$. This will take $|11 - 6| + |6 - 9| = 8$ minutes.
2. $1 \rightarrow 3 \rightarrow 2$. This will take $|11 - 9| + |9 - 6| = 5$ minutes.
3. $2 \rightarrow 1 \rightarrow 3$. This will take $|6 - 11| + |11 - 9| = 7$ minutes.
4. $2 \rightarrow 3 \rightarrow 1$. This will take $|6 - 9| + |9 - 11| = 5$ minutes.
5. $3 \rightarrow 1 \rightarrow 2$. This will take $|9 - 11| + |11 - 6| = 7$ minutes.
6. $3 \rightarrow 2 \rightarrow 1$. This will take $|9 - 6| + |6 - 11| = 8$ minutes.

Thus, the minimum amount of time is 5 minutes.

The following illustrates this case:



[f](#) [t](#) [in](#)

Submissions: [6871](#)

Max Score: 20

Difficulty: Easy

Rate This Challenge:



[More](#)

Current Buffer (saved locally, editable)  

C++14  

```
1 #include <cmath>
2 #include <cstdio>
3 #include <vector>
4 #include <iostream>
5 #include <algorithm>
6 using namespace std;
7
8
9 int main() {
10     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
11     return 0;
12 }
13
```

Line: 1 Col: 1

 [Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code