

Your Deque-STL submission got 0.00 points. :([Try Again](#)

Deque-STL

by [pratyush](#)

Problem

Submissions

Leaderboard

Discussions

Editorial

Double ended queue or Deque(part of C++ STL) are sequence containers with dynamic sizes that can be expanded or contracted on both ends (either its front or its back). The member functions of deque that are mainly used are:

- Deque Template:

```
std::deque<value_type>
```

- Declaration:

```
deque<int> mydeque; //Creates a double ended queue of deque of int type
```

- Size

```
int length = mydeque.size(); //Gives the size of the deque
```

- Push

```
mydeque.push_back(1); //Pushes element at the end  
mydeque.push_front(2); //Pushes element at the beginning
```

- Pop

```
mydeque.pop_back(); //Pops element from the end  
mydeque.pop_front(); //Pops element from the beginning
```

- Empty

```
mydeque.empty() //Returns a boolean value which tells whether the deque is empty or not
```

To know more about deque, [click here](#)

Given a set of arrays of size N and an integer K , you have to find the maximum integer for each and every contiguous subarray of size K for each of the given arrays.

Input Format

First line of input will contain the number of test cases T . For each test case, you will be given the size of array N and the size of subarray to be used K . This will be followed by the elements of the array A_i .

Constraints

 $1 \leq T \leq 1000$ $1 \leq N \leq 10000$

$1 \leq K \leq N$ $1 \leq A_i \leq 10000$, where A_i is the i^{th} element in the array A .

Output Format

For each of the contiguous subarrays of size K of each array, you have to print the maximum integer.

Sample Input

```
2
5 2
3 4 6 3 4
7 4
3 4 5 8 1 4 10
```

Sample Output

```
4 6 6 4
8 8 8 10
```

Explanation

For the first case, the contiguous subarrays of size 2 are {3,4},{4,6},{6,3} and {3,4}. The 4 maximum elements of subarray of size 2 are: 4 6 6 4.

For the second case, the contiguous subarrays of size 4 are {3,4,5,8},{4,5,8,1},{5,8,1,4} and {8,1,4,10}. The 4 maximum element of subarray of size 4 are: 8 8 8 10.

[f](#) [t](#) [in](#)Submissions: [9440](#)



Max Score: 50



Difficulty: Medium

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

C++14  

```
4 #include <iostream>
5 #include <deque>
6 #include <iterator>
7 #include <algorithm>
8 using namespace std;
9
10 int main()
11 {
12     unsigned int T; cin >> T; // number of test cases T
13     if(1<=T && T<=1000)
14     {
15         while(T>0)
16         {
17             unsigned int size, K=0;
18             cin >> size >> K;
19             if( (1<= size && size<=10000) && (1<=K && K<=size) )
20             {
21                 deque<unsigned int> Deq, Ans;
22                 copy_n(istream_iterator<unsigned int>(cin), size, back_inserter(Deq));
23
24                 auto idx=0;
25                 for(auto itr=Deq.cbegin(); itr!=Deq.cend()-K+1; ++itr)
26                 {
27                     cout<<*max_element(Deq.cbegin()+idx, Deq.cbegin()+K+idx) <<" ";
28                     ++idx;
29                 }
30                 cout<<endl;
31                 T--;
32             }
33         }
34     }
35 }
```

```
36     return 0;  
37 }  
38
```

Line: 38 Col: 1

 [Upload Code as File](#)☐ Test against custom input

Run Code

Submit Code

Terminated due to timeout

Ask your friends for help: [f](#) [t](#) [in](#) Test Case #0 Test Case #3 Test Case #6 Test Case #9 Test Case #1 Test Case #4 Test Case #7 Test Case #10 Test Case #2 Test Case #5 Test Case #8

Try Again