



Dashboard > Algorithms > Implementation > Circular Array Rotation

Badge Progress (Details)



Points: 1401 Rank: 23355

Your Circular Array Rotation submission got 20.00 points.

[Share](#)[Tweet](#)[Try the Next Challenge](#) | [Try a Random Challenge](#)

Circular Array Rotation



by darkshadows

Problem

Submissions

Leaderboard

Discussions

Editorial

John Watson knows of an operation called a *right circular rotation* on an array of integers. One rotation operation moves the last array element to the first position and shifts all remaining elements right one. To test Sherlock's abilities, Watson provides Sherlock with an array of integers. Sherlock is to perform the rotation operation a number of times then determine the value of the element at a given position.

For each array, perform a number of right circular rotations and return the value of the element at a given index.

Input Format

The first line contains **3** space-separated integers, n , k , and q .

The second line contains n space-separated integers, where each integer i describes array element a_i (where $0 \leq i < n$).

Each of the q subsequent lines contains a single integer denoting m .

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq a_i \leq 10^5$
- $1 \leq k \leq 10^5$
- $1 \leq q \leq 500$
- $0 \leq m < n$

Output Format

For each query, print the value of the element at index m of the rotated array on a new line.

Sample Input 0

```
3 2 3
1 2 3
0
1
2
```

Sample Output 0

```
2
3
1
```

Explanation 0

After the first rotation, the array becomes $[3, 1, 2]$.

After the second (and final) rotation, the array becomes $[2, 3, 1]$.

Let's refer to the array's final state as array $b = [2, 3, 1]$. For each query, we just have to print the value of b_m on a new line:

- $m = 0, b_0 = 2$.

2. $m = 1, b_1 = 3$.

3. $m = 2, b_2 = 1$.

Easy

Submitted 95987 times
Max Score 20

Need Help?

[View Discussions](#)[View Editorial Solution](#)[View Top Submissions](#)

Rate This Challenge:

[Download problem statement](#)[Download sample test cases](#)[Suggest Edits](#)

Choose a translation

Russian



Current Buffer (saved locally, editable)

C++14



```
1 #include <iostream>
2 #include <vector>
3 #include <algorithm>
4 #include <iterator>
5 #define speed std::ios_base::sync_with_stdio(false); std::cin.tie(nullptr); std::cout.tie(nullptr)
6 int main()
7 {
8     speed;
9     int n; std::cin >> n;
10    int k; std::cin >> k;
11    k %= n;    //std::cout<<k<<std::endl;
12    k = n-k;    //std::cout<<k<<std::endl;
13    int q; std::cin >> q;
14
15    std::vector<int> vec;
16    vec.reserve(n);
17    std::copy_n(std::istream_iterator<int>(std::cin), n, back_inserter(vec));
18
19    std::rotate(vec.begin(), vec.begin()+k, vec.end());
20    /*std::copy(vec.cbegin(), vec.cend(), std::ostream_iterator<int>(std::cout, "\t"));
21    std::cout<<std::endl;*/
22
23    while(q--)
24    {
25        int index; std::cin >> index;
26        std::cout << vec[index] << std::endl;
27    }
28
29    return 0;
30 }
31
32
```




Line: 28 Col: 6

 [Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code

Congrats, you solved this challenge!

Challenge your friends:   

- ✓ Test Case #0

✓ Test Case #3

✓ Test Case #6

✓ Test Case #9

✓ Test Case #12

✓ Test Case #15
- ✓ Test Case #1

✓ Test Case #4

✓ Test Case #7

✓ Test Case #10

✓ Test Case #13
- ✓ Test Case #2

✓ Test Case #5

✓ Test Case #8

✓ Test Case #11

✓ Test Case #14

You've earned 20.00 points.

Next Challenge