



Dashboard > Algorithms > Dynamic Programming > Sherlock and Cost

Badge Progress (Details)



Points: 1101 Rank: 33325

Sherlock and Cost



by darkshadows

Problem

Submissions

Leaderboard

Discussions

Editorial

Русский | 中文

Array A contains the elements, A_1, A_2, \dots, A_N . And array B contains the elements, B_1, B_2, \dots, B_N . There is a relationship between A_i and B_i , $\forall 1 \leq i \leq N$, i.e., any element A_i lies between 1 and B_i .

Let the cost S of an array A be defined as:

$$S = \sum_{i=2}^N |A_i - A_{i-1}|$$

You have to print the largest possible value of S .

Input Format

The first line contains, T , the number of test cases. Each test case contains an integer, N , in first line. The second line of each test case contains N integers that denote the array B .

Constraints

$$1 \leq T \leq 20$$

$$1 \leq N \leq 10^5$$

$$1 \leq B_i \leq 100$$

Output Format

For each test case, print the required answer in one line.

Sample Input

```
1
5
10 1 10 1 10
```

Sample Output

```
36
```

Explanation

The maximum value occurs when $A_1=A_3=A_5=10$ and $A_2=A_4=1$.

Medium

Submitted 13318 times
Max Score 50

Need Help?



View Discussions



View Editorial Solution

[View Top Submissions](#)**Rate This Challenge:**[Download problem statement](#)[Download sample test cases](#)[Suggest Edits](#)

Current Buffer (saved locally, editable)

C++14

```
1 #include <cmath>
2 #include <cstdio>
3 #include <vector>
4 #include <iostream>
5 #include <algorithm>
6 using namespace std;
7
8
9 int main() {
10     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
11     return 0;
12 }
13
```

Line: 1 Col: 1

[Upload Code as File](#)

Test against custom input

[Run Code](#)[Submit Code](#)[Contest Calendar](#)[Blog](#)[Scoring](#)[Environment](#)[FAQ](#)[About Us](#)[Support](#)[Careers](#)[Terms Of Service](#)[Privacy Policy](#)[Request a Feature](#)