



Dashboard > Algorithms > Greedy > Maximum Perimeter Triangle

Badge Progress (Details)



Points: 806 Rank: 48523

Your Maximum Perimeter Triangle submission got 20.00 points.

Share

Tweet

[Try the Next Challenge](#) | [Try a Random Challenge](#)

Maximum Perimeter Triangle

by zemen

Problem

Submissions

Leaderboard

Discussions

Editorial

Given n sticks of lengths l_0, l_1, \dots, l_{n-1} , use 3 of the sticks to construct a non-degenerate triangle with the maximum possible perimeter. Then print the lengths of its sides as 3 space-separated integers in non-decreasing order.

If there are several valid triangles having the maximum perimeter:

1. Choose the one with the *longest maximum side* (i.e., the largest value for the longest side of any valid triangle having the maximum perimeter).
2. If more than one such triangle meets the first criterion, choose the one with the *longest minimum side* (i.e., the largest value for the shortest side of any valid triangle having the maximum perimeter).
3. If more than one such triangle meets the second criterion, print any one of the qualifying triangles.

If no non-degenerate triangle exists, print -1.

Input Format

The first line contains single integer, n , denoting the number of sticks.

The second line contains n space-separated integers, l_0, l_1, \dots, l_{n-1} , describing the respective stick lengths.

Constraints

- $3 \leq n \leq 50$
- $1 \leq l_i \leq 10^9$

Output Format

Print 3 non-decreasing space-separated integers, a , b , and c (where $a \leq b \leq c$) describing the respective lengths of a triangle meeting the criteria in the above *Problem Statement*.

If no non-degenerate triangle can be constructed, print -1.

Sample Input 0

```
5
1 1 1 3 3
```

Sample Output 0

```
1 3 3
```

Sample Input 1

```
3
1 2 3
```

Sample Output 1

-1

Explanation*Sample Case 0:*There are **2** possible unique triangles:

1. **(1, 1, 1)**
2. **(1, 3, 3)**

The second triangle has the largest perimeter, so we print its side lengths on a new line in non-decreasing order.

*Sample Case 1:*The triangle **(1, 2, 3)** is degenerate and thus can't be constructed, so we print **-1** on a new line.[f](#) [t](#) [in](#)Submissions: [11099](#)



Max Score: 20



Difficulty: Easy

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

C++14  

```
1 #include <cmath>
2 #include <limits>
3 #include <set>
4 #include <vector>
5 #include <iostream>
6 #include <algorithm>
7 #include <iterator>
8 using namespace std;
9
10 #define ull unsigned long long int
11 int main()
12 {
13     ios_base::sync_with_stdio(0);
14     cin.tie(0);
15     cout.tie(0);
16
17     ull n, miles=0;
18     cin>>n;
19     multiset<ull> mySet;
20     for(auto i=0; i<n;++i)
21     {
22         ull temp=0;
23         cin>>temp;
24         mySet.insert(temp);
25     }
26
27     ull a,b,c;
28     int idx=0;
29     for(auto itr=mySet.rbegin(); itr!=mySet.rend(); ++itr)
30     {
31         if(idx <= (n-3))
32         {
33             a= *(itr++);
34             b= *(itr++);
35             c= *(itr++);
36
37             if(a < (b+c) )
38                 break;
39
40             itr--; itr--; itr--;
41         }
42         ++idx;
43     }
44     if(a < (b+c) )
```

```
45     cout<<c <<" "<<b <<" "<<a<<endl;
46     else
47         cout<<"-1"<<endl;
48     return 0;
49 }
50
```

Line: 50 Col: 1

☐ Test against custom input

Run Code

Submit Code

 Upload Code as File

```
5
3 9 2 15 3
```

Congrats, you solved this challenge!

Challenge your friends: [f](#) [t](#) [in](#)

✓ Test Case #0
✓ Test Case #3
✓ Test Case #6
✓ Test Case #9

✓ Test Case #1
✓ Test Case #4
✓ Test Case #7
✓ Test Case #10

✓ Test Case #2
✓ Test Case #5
✓ Test Case #8
✓ Test Case #11

You've earned 20.00 points.

Next Challenge