ReSTIR DI

ReSTIR 1 ray per pixel
BRDF: Lambert + GGX (different roughness)
Init samples 5 x MIS(Area Light Importance, GGX)
Temporal accumulation: 4 frames
Spatial accumulation: 12 samples

ReSTIR Lambert spatial join study
*in low res i.e. 512*512*

BRDF: Lambert
Init samples 5 x Area Light Importance
Temporal accumulation: 2 frames
Spatial accumulation: 5 samples radius 10

no restriction on join

nor's cos >= 0.9
fireflies on box edge removed

nor's cos >= 0.9
pos's dist < 0.04
half's cos >= 0.98
better shadow
lower convergence

Blender Cycles with
10 rays per pixel, no
denoise, no indirect

ReSTIR GGX spatial join study



BRDF: GGX (different roughness)
Init samples 5 x MIS(Area Light Importance, GGX)
Temporal accumulation: 2 frames
Spatial accumulation: 5 samples radius 10

nor's cos < 0.9
pos's dist < 0.04
Specular over spreads

nor's cos >= 0.9
pos's dist < 0.04
half's cos >= 0.9
Adding restriction between
half vectors narrows the
specular

nor's cos >= 0.9
pos's dist < 0.04
half's cos >= 0.98
better specular
lower convergence

Blender Cycles with
10 rays per pixel, no
denoise, no indirect

Average numbers of samples merged per pixel using different join restrictions:
73.51 [100%] - no restriction on spatial join
57.97 [78%] - pos's dist < 0.1
35.07 [47%] - pos's dist < 0.04 [good shadows]
33.12 [45%] - pos's dist < 0.1 and nor's cos >= 0.9 [OK shadows, good lambert]
26.35 [35%] - pos's dist < 0.1 and nor's cos >= 0.9 and half's cos >= 0.98 [ok shadows, good lambert, good ggx]
49.41 [67%] - half's cos >= 0.98

Lambert + GGX, 5 x MIS(Area Lights Importance, GGX), Temporal 4, Spatial 12 from radius 10
Visual impact & reservoir join percentage vs join restriction

Start point
No restriction on spatial.
Average join: 13583.87
100%



Visual reference
Blender Cycles with 10
samples, no denoise, no
indirect

Washout specular + Rounded shadows
+ Dark visual artefacts

half's cos >= 0.98
average join: 6768.61
49.82%
+ Good specular

half's cos >= 0.98
nor's cos > 0.9
average join: 6478.03
47.68%

half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.5
average join: 6469.80
47.62%
+ No artefacts

half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.1
average join: 3692.08
27.17%
+ OK shadows

half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.04
average join: 190.19
1.40%
+ Good Shadows

- Artefacts: nor's cos >= 0.9 and pos's dist < 0.5 is needed to remove artefacts
- Lambert: it looks good everywhere (once the artefacts are removed)
- GGX: half's cos >= 0.98 results in good specular but we drop half the spatial samples
- Shadows: best shadows with pos's dist < 0.04 (worse joining 1.4%). Acceptable shadows begin from pos's dist < 0.1, 27.17%

A lower percentage of considered neighbors joining means that convergence will require more frames.

Lambert + GGX, 5 x MIS(Area Lights Importance, GGX), Temporal 4, Spatial 12 samples
no half's restriction

Radius 10 - Area 314 reservoirs

Start point
no restriction on spatial
average join: 13583.87
100%

nor's cos > 0.9
pos's dist < 0.5
average join: 12783.13
47.62%

nor's cos > 0.9
pos's dist < 0.1
average join: 6833.63
27.17%

nor's cos > 0.9
pos's dist < 0.04
average join: 334.35
1.40%

Radius 5 - Area 78.5 reservoirs



Start point
no restriction on spatial
average join: 1452.27
100%

nor's cos > 0.9
pos's dist < 0.5
average join: 14092.63
97.04%

nor's cos > 0.9
pos's dist < 0.1
average join: 13095.53
90.16%

nor's cos > 0.9
pos's dist < 0.04
average join: 5553.23
38.24%

Radius 2.5 - Area 19.625 reservoirs



Start point
no restriction on spatial
average join: 15011.42
100%

nor's cos > 0.9
pos's dist < 0.5
average join: 14743.55
98.21%

nor's cos > 0.9
pos's dist < 0.1
average join: 14098.51
97.91%

nor's cos > 0.9
pos's dist < 0.04
average join: 11608.62
77.33%

Ignoring GGX half's cos and gradually concentrating area results in better joining percentage, better specular and better shadows but it gradually adds fireflies. Oh, boy wouldn't it be nice if we can join shadow separately?

Lambert + GGX, 5 x MIS(Area Lights Importance, GGX), Temporal 4, Spatial 12 samples
small disk area

12 samples uniformly
distributed over radius 10
Occasionally collision.

12 samples uniformly
distributed over radius 5
There's collision.

12 samples uniformly
distributed over radius 2.5
Collision city.

For small disk areas instead of computing the sample using r = √(rand), angle = rand * 2 * π we could accept disk samples based on the probability p=num_samples/disk_area_samples. On average 12 disk samples will be generated without collision. This implementation, while it offered good specular for half's cos > 0.9 still has fireflies.



radius 10
half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.1
average join: 3692.08
27.17%

radius 3 - probabilistic samples
half's cos >= 0.9
nor's cos > 0.9
pos's dist < 0.1
average join: 11420.60
67.68%

radius 3 - probabilistic samples
No collision.
Fireflies.

In the disk sampler instead of using r = √(rand) we could use r = rand ** factor and a factor of 1 or 2 would bias samples closer to the center. Changing the distribution requires integration of pdf in reservoir joining for unbiased results.

With factor 1,2 specular is acceptable even with half's cos >= 0.9, shadows are improved and fireflies have been reduced.

radius 10 factor 2
Collisions.
Reduced fireflies

radius 10 factor 2
half's cos >= 0.9
nor's cos > 0.9
pos's dist < 0.1
average join: 7526.37
52.38%

radius 10 factor 1/2
(uniform reference)
half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.1
average join: 3692.08
27.17%

radius 10 factor 1
half's cos >= 0.9
nor's cos > 0.9
pos's dist < 0.1
average join: 6049.12
42.38%

radius 10 factor 1
Less collisions.
Even less fireflies.

Neural based joining of spatial 10 samples from radius 10

Method:
1. Init reservoirs from 64 MIS (Area, GGX) + shadow pass and output the scene gbuffer & reservoirs into json's.
2. Generate 2.1M training samples in C++ as following:
- record all joins from spatial (2.1M joins)
- for each join, compute the loss with and without it against a reference image (scene rendered with Blender Cycles).
- per sample record:
- d_e - distance between joining reservoirs (normalized in respect to scene).
- n_cos e- cosine between normals.
- n_cos e- cosine between half vectors.
- d_r e- destination reservoir roughness.
- s_r e- source reservoir roughness.
- d_a_r e- destination reservoir albedo.
- s_a_r e- source reservoir albedo.
- delta_loss = (loss_without_join - loss_with_join).
- normalize delta_loss sample.delta_loss /= max(|min_delta_loss|, max_delta_loss) min, max delta loss computed for all samples.
3. Train 2-hidden-layer Multilayer Perceptron (MLP) with 64 neurons per hidden layer and ReLU activations. Data was broken into 3 parts: 80% training data (in batches of 4096), 5% validation and 5% final test.

No overfit was recorded in validation and final test.
Mean absolute value and reciprocal mean squared errors are similar in both cases.

4. Export the model
5. Load the model in C++ and build 3 outputs:
- Naive all reservoirs join.
- Analytic join based on pos's dist < 0.04, nor's cos > 0.9, half's cos > 0.98 (best results formula)
- Neural model.forward(d_r,cos_n,cos_r, s_r, d_a_r, s_a_r) > 0.05

Naive join all
joined: 2,184,960
100%

half's cos >= 0.98
nor's cos > 0.9
pos's dist < 0.04
joined: 387,943
17.75%

Neural join
joined: 337,737
15.45%

The neural model achieves comparable quality to well-tuned analytical heuristics, with the potential to generalise across scenes where fixed thresholds would require manual retuning. TBC.

Visual reference
Blender Cycles with 10
samples, no denoise, no
indirect

Distance reference
blue: pos's dist < 0.5
green: pos's dist < 0.1
red: pos's dist < 0.04
Measured from grid center
gbuffer pos

Reducing the sampling radius/count based on depth wasn't considered due to small scene depth range.