OptiMOS^{TM} Power-MOSFET

Features

• Optimized for high performance Buck converter

• Very low on-resistance $R_{DS(on)}$ @ V_{GS}=4.5 V

• 100% avalanche tested

• Superior thermal resistance

• N-channel

• Qualified according to JEDEC[1] for target applications

• Pb-free lead plating; RoHS compliant

• Halogen-free according to IEC61249-2-21

Product Summary

V_{DS}	30	V
$R_{DS(on),max}$	2.6	mΩ
I_D	100	A
Q_{OSS}	16	nC
Q_G(0V..10V)	26	nC

PG-TDSON-8

Type	Package	Marking
BSC0902NS	PG-TDSON-8	0902NS

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	V_{GS}=10 V, T_C=25 °C	100	A
		V_{GS}=10 V, T_C=100 °C	67	
		V_{GS}=4.5 V, T_C=25 °C	91	
		V_{GS}=4.5 V, T_C=100 °C	58	
		V_{GS}=10 V, T_A=25 °C, R_{thJA}=50 K/W[2]	24	
Pulsed drain current[3]	$I_{D,pulse}$	T_C=25 °C	400	
Avalanche current, single pulse[4]	I_{AS}	T_C=25 °C	50	
Avalanche energy, single pulse	E_{AS}	I_D=40 A, R_{GS}=25 Ω	40	mJ
Gate source voltage	V_{GS}		±20	V

[1] J-STD20 and JESD22

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Power dissipation	P_{tot}	T_C=25 °C	48	W
		T_A=25 °C, R_{thJA}=50 K/W[2]	2.5	
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Thermal characteristics

Parameter	Symbol	Conditions	min.	typ.	max.	Unit
Thermal resistance, junction - case	R_{thJC}		-	-	2.6	K/W
		top	-	-	20	
Device on PCB	R_{thJA}	6 cm^2 cooling area[2]	-	-	50	

Electrical characteristics, at T_j=25 °C, unless otherwise specified

Static characteristics

Parameter	Symbol	Conditions	min.	typ.	max.	Unit
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250 µA	1.2	-	2	
Zero gate voltage drain current	I_{DSS}	V_{DS}=30 V, V_{GS}=0 V, T_j=25 °C	-	0.1	1	µA
		V_{DS}=30 V, V_{GS}=0 V, T_j=125 °C	-	10	100	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5 V, I_D=30 A	-	2.8	3.5	mΩ
		V_{GS}=10 V, I_D=30 A	-	2.2	2.6	
Gate resistance	R_G		0.5	0.9	1.8	Ω
Transconductance	g_{fs}	$\lvert V_{DS}\rvert>2\lvert I_D\rvert R_{DS(on)max}$, I_D=30 A	55	110	-	S

[2] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.
[3] See figure 3 for more detailed information

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=15 V, f=1 MHz	-	1700	2261	pF
Output capacitance	C_{oss}		-	600	798	
Reverse transfer capacitance	C_{rss}		-	88	-	
Turn-on delay time	$t_{d(on)}$	V_{DD}=15 V, V_{GS}=10 V, I_D=30 A, $R_{G,ext}$=1.6 Ω	-	4.2	-	ns
Rise time	t_r		-	5.2	-	
Turn-off delay time	$t_{d(off)}$		-	21	-	
Fall time	t_f		-	3.6	-	
Gate Charge Characteristics[5]						
Gate to source charge	Q_{gs}	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 4.5 V	-	4.4	5.9	nC
Gate charge at threshold	$Q_{g(th)}$		-	2.7	-	
Gate to drain charge	Q_{gd}		-	4.0	5.2	
Switching charge	Q_{sw}		-	5.6	-	
Gate charge total	Q_g		-	13	17	
Gate plateau voltage	$V_{plateau}$		-	2.6	-	V
Gate charge total	Q_g	V_{DD}=15 V, I_D=30 A, V_{GS}=0 to 10 V	-	26	35	nC
Gate charge total, sync. FET	$Q_{g(sync)}$	V_{DS}=0.1 V, V_{GS}=0 to 4.5 V	-	11	-	
Output charge	Q_{oss}	V_{DD}=15 V, V_{GS}=0 V	-	16	21	
Reverse Diode						
Diode continuous forward current	I_S	T_C=25 °C	-	-	44	A
Diode pulse current	$I_{S,pulse}$		-	-	175	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=30 A, T_j=25 °C	-	0.83	1	V
Reverse recovery charge	Q_{rr}	V_R=15 V, I_F=I_S, di_F/dt=400 A/µs	-	15	-	nC

[4] See figure 13 for more detailed information
[5] See figure 16 for gate charge parameter definition

## 1 Power dissipation

P_{tot}=f(T_C)

2 Drain current

I_D=f(T_C); $V_{GS} \geq$10 V

3 Safe operating area

I_D=f(V_{DS}); T_C=25 °C; D=0

parameter: t_p

4 Max. transient thermal impedance

Z_{thJC}=f(t_p)

parameter: D=t_p/T

5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C

parameter: V_{GS}

## 6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C

parameter: V_{GS}

7 Typ. transfer characteristics

I_D=f(V_{GS}); $|V_{DS}|>2|I_D|R_{DS(on)max}$

parameter: T_j

8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C

9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=30 A; V_{GS}=10 V

10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}; I_D=250 µA


11 Typ. capacitances

C=f(V_{DS}); V_{GS}=0 V; f=1 MHz

## 12 Forward characteristics of reverse diode

I_F=f(V_{SD})

parameter: T_j

13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω

parameter: $T_{j(start)}$

14 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=30 A pulsed

parameter: V_{DD}

## 15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=1 mA

16 Gate charge waveforms

Package Outline   **PG-TDSON-8**

PG-TDSON-8: Outline

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	0.90	1.10	0.035	0.043
b	0.34	0.54	0.013	0.021
b1	0.02	0.22	0.001	0.008
c	0.15	0.35	0.006	0.014
D=D1	4.95	5.35	0.195	0.211
D2	4.20	4.40	0.165	0.173
E	5.95	6.35	0.234	0.250
E1	5.70	6.10	0.224	0.240
E2	3.40	3.80	0.134	0.150
e	1.27		0.050	
N	8		8	
L	0.45	0.65	0.018	0.026
□	8.5°	11.5°	8.5°	11.5°
aaa	0.25		0.010	
eee	0.05		0.002	
F1	6.75	6.95	0.266	0.274
F2	4.60	4.80	0.181	0.189
F3	4.36	4.56	0.172	0.180
F4	0.55	0.75	0.022	0.030
F5	0.52	0.72	0.020	0.028
F6	1.10	1.30	0.043	0.051
F7	0.40	0.60	0.016	0.024
F8	0.60	0.80	0.024	0.031
F9	0.53	0.73	0.021	0.029
F10	4.90	5.10	0.193	0.201
F11	0.53	0.73	0.021	0.029

DOCUMENT NO.
Z8B00003332

SCALE

EUROPEAN PROJECTION

ISSUE DATE
08-03-2007

REVISION
03

Package Outline

PG-TDSON-8: Tape

Dimensions in mm

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of
conditions or characteristics. With respect to any examples or hints given herein, any typical
values stated herein and/or any information regarding the application of the device,
Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind,
including without limitation, warranties of non-infringement of intellectual property rights
of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please
contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information
on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with
the express written approval of Infineon Technologies, if a failure of such components can
reasonably be expected to cause the failure of that life-support device or system or to affect
the safety or effectiveness of that device or system. Life support devices or systems are
intended to be implanted in the human body or to support and/or maintain and sustain
and/or protect human life. If they fail, it is reasonable to assume that the health of the user
or other persons may be endangered.