

UNIX Principles 1-2 Pg 13-21

Principle 1: The file system is a tree.

- Tree has a root node/directory
 - ↳ ~~\$~~ Name: /

- - → directory itself
 - → parent directory

- Each user has a home directory.

- ↳ reference using ~

- ~/ my home directory

- Useful commands

- pwd: present working directory

- cd: change directory

- mkdir dirname: make a new directory

- mv oldname newname: rename file/directory

- date: print date

- touch: ~~reset the modi~~ filename: reset the modification date & time to now

cp haha.txt
final/

- cp filename copyoffile: copy a file / copy into a different directory

- rm filename: remove.

- rmdir dirname: remove directory (which must be empty).

- ls: list the contents of a directory

- ls-l: list detailed contents of a directory
(access rights, size, modification date)

→ regular file
d → directory

- ls-a: list all files

- cat filename: concatenate. print out the contents of a file.

- head filename: print out the 1st lines

- tail filename: print out the last lines

- man: manual.

man mkdir (etc.)

Principle 2: Input/output is a character stream.

- wc ^{filename}: word count - of #lines/words/char

- echo hello world > newfile : Echo.

↳ prints whatever you give it

↳ redirects the message to newfile -

So you created a file without having to open a text editor.
with some stuff in it

- < : redirect standard input

↳ cat < filename.

- > : redirect standard output

↳ cat < filename > newfile.

↑ redirects input
↓ directs output here

- >> : append to standard output

cat < filename >> oldfile

- | : Pipe ^{stdout} ~~stdin~~ to of the LHS to the stdin of the RHS.

→ ls | wc.

- * : matches all files

→ wc *

- ? : single character wildcard for commandline.

Match all char at that position.

ls *.htm?

↳ would match cs201.html