

Capteur Réfrigérateur/Congélateur Certifié NIST — Stat Temp 3.0

- **Capteur intégré** — boîtier silicone incassable placé entre les fils des clayettes
- **Journalisation Wi-Fi** — fréquence réglable de 5 à 30 min (réseaux 2,4 GHz uniquement)
- **Connectivité maillée** — extension de couverture entre appareils sans Wi-Fi direct
- **Tableau de bord automatique** — connexion unique au site stat-temp.io
- **Rapports mobiles** — accès via ordinateur, tablette ou téléphone
- **Aucun abonnement** · Stockage illimité · Portails par emplacement
- Alertes configurables par texto, courriel ou appel avec accusé de réception
- Alimentation USB-C · Batterie de secours 3 jours · Journal Min/Max 24 h
- Certificat NIST valable 4 ans inclus

N° Art.	Description	Plage de température	Précision	Dimensions
21266	Capteur simple	-50 °C à 50 °C	±0,2 °C	4"x2½"x1"
21268	Capteur double	-50 °C à 50 °C	±0,2 °C	4"x2½"x1"
21270	Capteur ambiant	-40 °C à 85 °C	±0,2 °C	4"x2½"x1"
21272	Capteur ultra-froid	-100 °C à -50 °C	±0,5 °C	4"x2½"x1"

- Mobile-Friendly Reports - Cloud-based storage allows instant access to reports from a computer, tablet, phone or other connected device for process, compliance or inspection.
- No Fees - There is no subscription fee for Stat Temp.
- No Limits - Users have unlimited cloud storage and can have multiple portals.
- Online Portals - Create portals on the Stat Temp website for locations to view all units being monitored or sort to show less (ex. location only).
- Permissions - Set user-defined permissions based on shifts or roles.
- Alerts - Configure real-time and user-defined alerts via text, email or phone call with forced acknowledgment of solutions. Example: Call Calvin, Fred and Cindy M-F, 8 a.m. – 5 p.m.; email Annie and text Tim M-F, 5 p.m. – 8 a.m.
- Power Source - Uses a standard USB-C plug. No batteries to change out.
- Loss of Power - 3-day battery backup
- Min/Max Log - Provides min/max data for the last 24 hours.
- NIST - Includes a 4-year NIST certificate.

Item #	Description	Temperature Range	Temperature Accuracy	Dimensions (W x H x D)
21266	Single Sensor	-50°C to 50°C (-58°F to 122°F)	±0.2°C	4" x 2½" x 1"
21268	Double Sensor	-50°C to 50°C (-58°F to 122°F)	±0.2°C	4" x 2½" x 1"
21270	Ambient Sensor	-40°C to 85°C (-40°F to 185°F)	±0.2°C	4" x 2½" x 1"
21272	Ultra-Low Sensor	-100°C to -50°C (-148°F to -58°F)	±0.5°C	4" x 2½" x 1"

Sensor

two sensors) is housed inside an refrigerator and freezer shelves to

united readings with user-selected

extend coverage and improve network installed in distant or obstructed

np website, stat-temp.io. The sensor

reports from a computer, tablet,

stat Temp monitors linked to their

view all units being monitored or sort to

one call with forced acknowledgment

