

Stat Temp 3.0 NIST Certified Refrigerator / Freezer Sensor

- Encased Sensor - Sensor (21266 includes one sensor; 21268 includes two sensors) is housed inside an unbreakable silicone case that can be placed within the wires on most refrigerator and freezer shelves to minimize obstructions.
- Data Logging - Wi-Fi-enabled temperature monitor (included) offers unlimited readings with user-selected logging rate from every 5 minutes up to every 30 minutes.
- Note: Monitors work with 2.4GHz Wi-Fi networks only.
- Mesh-Enabled Connectivity - Devices communicate with each other to extend coverage and improve network reliability, even in challenging hospital layouts. This allows sensors to be installed in distant or obstructed areas without requiring direct Wi-Fi access.
- Set-Up - Once connected to Wi-Fi, the unit can be added to the Stat Temp website, stat-temp.io. The sensor will automatically be added to the dashboard.
- Mobile-Friendly Reports - Cloud-based storage allows instant access to reports from a computer, tablet, phone or other connected device for process, compliance or inspection.
- No Fees - There is no subscription fee for Stat Temp.
- No Limits - Users have unlimited cloud storage and can have multiple Stat Temp monitors linked to their portal.
- Online Portals - Create portals on the Stat Temp website for locations; view all units being monitored or sort to show less (ex. location only).
- Permissions - Set user-defined permissions based on shifts or roles.
- Alerts - Configure real-time and user-defined alerts via text, email or phone call with forced acknowledgment of solutions. Example: Call Calvin, Fred and Cindy
M-F, 8 a.m. – 5 p.m.; email Annie and text Tim
M-F, 5 p.m. – 8 a.m.
- Power Source - Uses a standard USB-C plug. No batteries to change out.
- Loss of Power - 3-day battery backup
- Min/Max Log - Provides min/max data for the last 24 hours.
- NIST - Includes a 4-year NIST certificate.

Item #	Description	Temperature Range	Temperature Accuracy	Dimensions (W x H x D)
21266	Single Sensor	-50°C to 50°C (-58°F to 122°F)	+/-0.2°C	4" x 2½" x 1"
21268	Double Sensor	-50°C to 50°C (-58°F to 122°F)	+/-0.2°C	4" x 2½" x 1"
21270	Ambient Sensor	-40°C to 85°C (-40°F to 185°F)	+/-0.2°C	4" x 2½" x 1"
21272	Ultra-Low Sensor	-100°C to -50°C (-148°F to -58°F)	+/- 0.5°C	4" x 2½" x 1"

