Feedback Is All You Need

Research working draft: version 2

25 October 2026 (UTC)

Abstract

Can a small controller acquire high capability by repeatedly incorporating feedback? We test a restricted form of this hypothesis rather than assume that model capacity becomes irrelevant. Across 20 task seeds, four model sizes, and seven feedback conditions in each of two changing classification environments, a 161-parameter learner with accurate feedback outperforms a 2,561-parameter frozen learner by 52.91 percentage points on linear rules and 37.32 points on XOR rules. However, when both receive accurate feedback, the larger model exceeds the smaller by 10.93 points on XOR. A linear model remains near chance on XOR despite repeated correction. Corruption, latency, and replay further condition adaptation. These controlled results support feedback as a mechanism of task adaptation while rejecting an interpretation in which capacity, information, and update rules can be ignored. This version reports Study A only; a prospective pretrained-language-model study is pending. No claim about general intelligence or the origin of human intelligence follows from these experiments.

1 Introduction

The motivating hypothesis is that a compact cognitive core, coupled to an efficient loop of action, outcome observation, correction, and memory, may acquire capabilities disproportionate to its parameter count. Books and other external records suggest an analogy with accumulated human experience. That analogy motivates investigation; it does not establish a mechanism of human intelligence.

The hypothesis must be distinguished from two stronger assertions: that feedback is literally sufficient without representation or inductive bias, and that existing scaling results are wrong. Training already uses feedback through losses, gradients, rewards, and preferences. Scaling-law work measures relationships among loss, capacity, data, and computation [2, 3]; it does not rule out online adaptation. We therefore compare capacity and feedback as interacting resources.

We retain the researcher's chosen title and follow the organizational pattern of *Attention Is All You Need* [1]: background, mechanism, motivation, experimental specification, results, and conclusion. The title is a hypothesis under examination, not an established sufficiency theorem. Chen et al. already used a closely related title in 2023 [4]; we make no priority claim for the phrase or broad feedback-centered framing.

2 Background

Fast adaptation in a recurrent state was studied in RL^2 [5] and in-context reinforcement learning in Algorithm Distillation [6]. Reflexion stores verbal reflections from task feedback [7], while Self-Refine iterates on self-generated critiques [8]. Intrinsic self-correction can also fail [9]. These are different information sources and update mechanisms and should not be conflated.

Test-time compute studies already show that some smaller models can outperform larger models under specific inference allocations [10]. Consequently, a small-versus-large win alone is not a novel account of intelligence. Our current contribution is a reproducible diagnostic comparison, including conditions under which the motivating hypothesis fails. A broader novelty assessment and language-model evidence remain necessary.

3 Agent and Feedback Model

An agent has parameters θ, persistent memory m, and an interaction history h. Its policy selects an action, and an update U incorporates an environmental response f:

$$a_t \sim \pi_{\theta_t}(\cdot \mid o_t, m_t, h_t), \qquad (\theta_{t+1}, m_{t+1}, h_{t+1}) = U(\theta_t, m_t, h_t, o_t, a_t, f_t).$$

An implementation may update parameters, memory, context, or some combination. Its entire system capacity includes external storage and algorithms; a small neural core is not necessarily a small complete system.

Study A instantiates this notation with a binary classifier whose action is a label prediction. Feedback gives the true label after prediction. Inputs are independent of the action, and gradient descent updates the parameters. This is supervised online learning, not active exploration or a new reinforcement learning algorithm. In a binary task, correctness plus the chosen label also determines the target label.

4 What Feedback Can and Cannot Supply

4.1 An information constraint

Let Θ be uniform over $K > 1$ tasks. Assume the complete initial agent state and all side information are independent of Θ. Count every subsequent task-dependent observation as part of the response transcript. If each of n responses has an alphabet of size at most 2^b, then $I(\Theta; F_{1:n} \mid S_0) \leq nb$. Adaptive queries are functions of S_0 and preceding responses, so cannot independently supply missing task information. Fano's inequality gives the exact-task identification bound

$$P_e \geq \max\left\{0, 1 - \frac{nb+1}{\log_2 K}\right\}.$$

Indeed, $H(\Theta \mid F_{1:n}, S_0) \leq 1 + P_e \log_2 K$; subtracting this entropy from $\log_2 K$ yields the result. The bound is about task identification, not every prediction or reward metric. Informative priors or unaccounted observation channels invalidate these assumptions.

For a binary symmetric channel with independent flip probability p, the per-response information is at most $1 - H_2(p)$ bits. At $p = 1/2$, responses carry no information about the true bit. At $p = 1$, inversion is recoverable if the corruption mechanism is known. Learner failure under inverted labels therefore diagnoses a misspecified channel, not destroyed information.

4.2 Representation and transcript constraints

If a successful policy is outside the complete agent's permitted policy class, additional updates within that class cannot express it. External memory or tools may enlarge that class, so this constraint cannot be inferred from neural parameter count alone. In addition, a deterministic updater replaying the same ordered transcript from the same initial state reaches the same final state, by induction. Calling the procedure a loop adds no independent advantage. Active information acquisition or changing observations can matter; these mechanisms require their own tests.

5 Experimental Setup

5.1 Tasks, models, and feedback

Each seed defines an initial and an independently generated post-change rule over eight standard-normal inputs. Linear labels threshold a normalized random projection. XOR labels combine signs of two randomly selected coordinates, with an independent fair complement bit for each rule. Warmup comprises 256 batches of 32 examples; adaptation uses a further 256 batches from the new rule. Evaluation sets of 2,048 examples per rule never enter updates. Separate uniform-input tests preserve each rule and change its input distribution.

The models are logistic regression and one-hidden-layer ReLU networks of widths 16, 64, and 256: 9, 161, 641, and 2,561 parameters. Adam uses learning rate 0.01 and default moments, with fresh moments after warmup. Every arm at the same capacity and seed starts from identical warmed-up parameters and sees the same arriving input stream.

The seven arms are frozen weights, clean labels, 25% flips, 50% flips, inverted labels, clean feedback delayed by 32 batches, and 25% replay. Replay replaces the final eight new examples in every batch with eight warmup examples sampled with replacement, retaining their original labels. It therefore changes both memory use and fresh-example exposure. Delayed feedback has 224 updates at arrival batch 256; a separate flush processes the remaining 32 without new observations.

5.2 Protocol, statistics, and resources

The full grid uses 20 seeds, 4000–4019, and was frozen in repository history before collection. A development run accidentally exposed seeds 1000 and 1001; the seed set was amended before formal collection, without hyperparameter tuning. A subsequent code audit found overlapping PRNG streams in the first full run (seeds 2000–2019). That run is archived with a superseded-inference notice. This version reports a replication on untouched seeds 4000–4019, with streams derived by SHA-256 of environment, family, role, and step or width. A complete-grid collision check passed. The protocol, hyperparameters, and endpoints otherwise remain unchanged. This is repository registration, not external preregistration.

The primary contrast in each family compares width-16 clean to width-256 frozen at arrival batch 256. This deliberately unequal-information comparison tests adaptation, not compute superiority. We report paired seed-level t intervals at 97.5% for each of these two contrasts (Bonferroni familywise 95%). Secondary 95% intervals are descriptive. Seeds, not checkpoints or individual examples, are the replication units; t inference assumes adequate approximation of the seed-mean sampling distribution.

The run used PyTorch 2.8.0 with CUDA 12.6 on one RTX 4090 D and completed 1,120 arms in 109.54 seconds. Code and environment hashes, all 19,200 checkpoint rows, and analysis are retained. For arithmetic-budget comparisons we count $6WN$ multiply-add-related training FLOPs for W matrix weights and N examples. This proxy excludes optimizer, activation, bias, and hardware overhead. Warmup and adaptation are reported separately; it is not lifetime compute or a measured energy budget.

6 Results

6.1 Adaptation and capacity

The small adaptive model exceeds the large frozen model by 52.91 points on linear tasks (97.5% CI [47.62,58.20]) and 37.32 on XOR ([28.85,45.79]). When both receive feedback, small-minus-

Table 1: Mean post-change held-out accuracy (%), 20 seeds. All adaptive columns receive the same 8,192 clean examples; frozen models receive none.

Parameters	Linear frozen	Linear clean	XOR frozen	XOR clean
9	45.61	90.67	50.12	49.87
161	45.56	98.53	47.64	84.97
641	45.64	98.71	47.69	96.14
2,561	45.62	98.53	47.65	95.90

large is 0.00 points for linear (95% CI [-0.22,0.22]) and -10.93 for XOR ([-15.39,-6.46]). The latter comparison shows a substantial remaining capacity effect under the tested update schedule. Logistic regression remains near chance on XOR despite clean feedback. This is a representation boundary, not evidence against all small controllers.




Figure 1: Capacity and feedback jointly determine observed accuracy. Error bars are descriptive 95% t intervals across 20 seeds. The dotted line is chance accuracy; noisy feedback can coexist with information retained from warmup, so individual noisy outcomes need not equal chance.

At an equal adaptation arithmetic proxy, the small model's 256 updates and the largest model's 16 updates both cost 7,077,888 proxy FLOPs. The small model leads by 42.80 points on linear tasks and 34.72 on XOR. However, it receives sixteen times as many new examples, while the large model's warmup cost is sixteen times greater. This is a particular compute/information trade, not an isolated causal effect of feedback-loop efficiency or a scaling law.

6.2 Feedback variations, transfer, and retention

For the 161-parameter model, clean, 25% corruption, and 50% corruption yield 98.53%, 92.05%, and 51.03% accuracy on linear tasks and 84.97%, 71.84%, and 49.92% on XOR. Inverted feedback yields 1.20% and 13.32% respectively. More updates can reinforce the wrong target when the update rule assumes trusted labels.

Delayed feedback reaches 98.28% and 81.87% at the online endpoint. After flushing, its scores and final training losses equal clean feedback for every seed and capacity. This equality is a correctness check for ordered updates, not an additional empirical discovery about latency.




Figure 2: The same 161-parameter learner under six update conditions. Shading shows descriptive 95% seed-level intervals at fixed arrival checkpoints.

Clean small-model uniform-input accuracy is 98.44% for linear rules and 88.19% for XOR. This is distribution transfer within the same known rule family, not transfer to an unrelated task. Old-rule accuracy after clean adaptation is 45.23% and 51.94%. Replay raises these to 54.92% and 64.43% while lowering new-rule accuracy to 89.85% and 76.48%. Because rules may conflict without a task identifier, this is an adaptation– retention tradeoff; perfect performance on both is not always possible.

6.3 Limitations and pending evidence

The data are small, synthetic, and fully specified; labels are free and exact except when deliberately corrupted. We test no autonomous information acquisition, long-horizon reward, natural language, meta-learning, or durable cross-domain skill accumulation. The optimizer schedule is fixed rather than separately optimized by capacity, so its outcomes are conditional on that schedule. A model-size threshold for arbitrary intelligence is not identified.

The prospective Study B compares four released Qwen2.5 model sizes on hidden command mappings, true versus guessed feedback, explicit-rule controls, and parameter updates tested without retained demonstrations. Its results are not yet included here. Even positive results would require broader real-world evaluation before supporting the original expansive hypothesis.

7 Conclusion

Under controlled task changes, feedback lets small neural learners recover capability unavailable to frozen models. Capacity still matters when both models learn, and reliable information and a suitable update mechanism remain necessary. The present evidence supports conditional feedback-driven adaptation. It does not establish that feedback alone explains intelligence or that parameter scaling is an incorrect research direction.

References

[1] A. Vaswani et al. Attention Is All You Need. NeurIPS, 2017. https://arxiv.org/abs/1706.03762.

[2] J. Kaplan et al. Scaling Laws for Neural Language Models. 2020. https://arxiv.org/abs/2001.08361.

[3] J. Hoffmann et al. Training Compute-Optimal Large Language Models. 2022. https://arxiv.org/abs/2203.15556.

[4] H. Chen et al. Feedback is all you need: from ChatGPT to autonomous driving. 2023. https://doi.org/10.1007/s11432-023-3740-x. Bibliographic metadata verified; full-text argument not assessed in this version.

[5] Y. Duan et al. RL^2: Fast Reinforcement Learning via Slow Reinforcement Learning. 2016. https://arxiv.org/abs/1611.02779.

[6] M. Laskin et al. In-context Reinforcement Learning with Algorithm Distillation. 2022. https://arxiv.org/abs/2210.14215.

[7] N. Shinn et al. Reflexion: Language Agents with Verbal Reinforcement Learning. 2023. https://arxiv.org/abs/2303.11366.

[8] A. Madaan et al. Self-Refine: Iterative Refinement with Self-Feedback. 2023. https://arxiv.org/abs/2303.17651.

[9] J. Huang et al. Large Language Models Cannot Self-Correct Reasoning Yet. 2023. https://arxiv.org/abs/2310.01798.

[10] C. Snell et al. Scaling LLM Test-Time Compute Optimally can be More Effective than Scaling Model Parameters. 2024. https://arxiv.org/abs/2408.03314.