# Feedback Is All You Need

Research working draft: version 12

26 October 2026 (UTC)

**Abstract**

Can a small controller acquire high capability by repeatedly incorporating feedback? Nine synthetic studies examine feedback, capacity, response interfaces, parameter updates, and external memory. A 161-parameter classifier with accurate feedback outperforms a 2,561-parameter frozen learner, but the larger learner retains an XOR advantage when both adapt. In pretrained models, extending a fixed 7B continuation budget from 128 to 512 tokens raises example-conditioned composition accuracy from 7.94% to 70.57%, with no additional feedback. Sixteen online parameter updates in 0.5B yield no demonstrated composition gain. Compared with retaining only the latest proposal and check, complete correction history over 16 rule revisions gives a 0.5B direct-accuracy difference of 0.00 points (95% CI [−3.96,3.96]) while using over twice the input tokens. Post-hoc selection recovers exact rules from 17/48 full-history 7B pools rather than 9/48 final proposals; no 0.5B pool contains an exact valid rule. A symbolic study tests cross-task compression without a neural model. At a fixed primitive-execution budget, learned fragments solve 85.16% of new motif-composition tasks, versus 2.34% with whole-program memory and 50.39% without memory. Under a shifted program distribution, fragment memory scores 9.96%, versus 50.00% without memory. The searcher, primitives, compression rule, and favorable shared structure are supplied, and prior experience costs are reported separately. A subsequent study trains a 1,172-parameter recurrent program prior on checked solutions. New-composition success falls to 22.85%, versus 50.00% for uniform search: a paired difference of −27.15 points (95% CI [−32.74,−21.55]). A count-based prior scores 66.02% on compositions but 33.59% on shifted tasks; its balanced score does not exceed uniform search. Post-hoc diagnostics find improved experience fitting alongside worse transfer-program likelihood in the small network. These results distinguish useful structure, neural fitting, search allocation, and supplied algorithms. They support conditional adaptation and transfer, but establish neither feedback sufficiency for general intelligence nor a mechanism by which an arbitrarily small model acquires it.

## 1 Introduction

The motivating hypothesis is that a compact cognitive core, coupled to an efficient loop of action, outcome observation, correction, and memory, may acquire capabilities disproportionate to its parameter count. Books and other external records suggest an analogy with accumulated human experience. That analogy motivates investigation; it does not establish a mechanism of human intelligence.

The hypothesis must be distinguished from two stronger assertions: that feedback is literally sufficient without representation or inductive bias, and that existing scaling results are wrong. Training already uses feedback through losses, gradients, rewards, and preferences. Scaling-law work measures relationships among loss, capacity, data, and computation [4, 5]; it does not rule out online adaptation. We therefore compare capacity and feedback as interacting resources.

We retain the researcher's chosen title and follow the organizational pattern of *Attention Is All You Need* [3]: background, mechanism, motivation, experimental specification, results, and conclusion. The title is a hypothesis under examination, not an established sufficiency theorem. Chen et al. already used a closely related title in 2023 [6]; we make no priority claim for the phrase or broad feedback-centered framing.

## 2 Background

The broad motivating idea has a direct precedent in *Reward is enough* [2]. Silver and colleagues hypothesize that abilities associated with intelligence can arise in service of reward maximization in a rich environment. Their account explicitly includes bounded capacity and real-time computation, and provides no sample-efficiency guarantee. Our experiments examine particular learners and feedback mechanisms; they do not test every agent covered by that conjecture.

The later *Welcome to the Era of Experience* perspective [1] directly advocates sustained interaction, rewards grounded in consequences, continuing adaptation, and revised world models. It also recognizes joint scaling with network size, experience, and thinking time. The broad agenda therefore precedes this work; our short synthetic studies do not instantiate its proposed lifelong learning system.

Fast adaptation in recurrent state was studied in $RL^2$ [7] and in-context reinforcement learning in Algorithm Distillation [8]. $RL^2$ separates a slowly learned update algorithm from fast changes in hidden state. A small runtime controller can therefore embody expensive prior learning. Reflexion combines an evaluator, verbal reflection, and episodic memory [9]; its feedback sources vary across tasks. Self-Refine uses the same model to generate, critique, and revise an answer with task-specific prompts [10], and explicitly requires sufficient instruction-following ability. Our sequential guess condition reproduces neither method.

Huang et al. distinguish intrinsic self-correction from correction supplied with external correctness signals [11]. Their evaluation also stresses inference-cost comparisons and equally informative initial instructions. Test-time compute studies show that some smaller models can outperform larger ones under specific inference allocations [12]. Accordingly, a small-versus-large win alone is not a new account of intelligence. Our current contribution is a reproducible diagnostic comparison of feedback, capacity, and response interfaces, including failed mechanisms and explicit controls. The literature review is targeted rather than exhaustive; exact versions and reading scope are recorded with the repository's source manifests.

Executable and abstract memory have close precedents. Voyager combines Minecraft feedback, execution errors, self-verification, and an executable skill library with GPT-4/GPT-3.5 components and a separate embedding model [13]. Self-Debugging combines execution/test results with generated explanations or simulated traces [14]; its traces are not observed intermediate states, and Spider still supplies executed SQL results without a unit-test correctness oracle. ExpeL appends extracted natural-language insights and retrieves successful trajectories [16]. Its HotpotQA-to- FEVER transfer adapts insights using GPT-4 and target-task examples, without experience-pool retrieval in that transfer setting. These systems precede our external-memory proposal. They motivate controlled tests of verification and representation, not a novelty claim for agent memory itself.

DreamCoder provides an earlier concrete mechanism for experience compression [15]. Its wake phase searches for programs; abstraction sleep refactors solutions into a reusable library; dreaming sleep trains a neural recognition model on replayed and imagined tasks. In the reviewed 2020 preprint, imagined tasks are solved again by search. Both the library and neural search policy change. Held-out-task evaluations and memorization baselines distinguish this from simply retain-

ing transcripts. Supplied primitives, types, search, and synthetic training remain part of the system: typical reported training takes about a day on 20–100 CPUs, and a minimal functional-programming experiment takes about five days on 64 CPUs. Study H isolates a smaller symbolic fragment-reuse mechanism; Study I trains a small program prior from checked solutions, without a task encoder or learned library. Neither replicates DreamCoder or claims novelty for these mechanisms. Inspection of an April 2020 source snapshot finds 64-dimensional recurrent features in its list/text constructors, but cannot establish the checkpoints and configurations used in the reported experiments. Feature width is not a total parameter count; we report no verified published neural count from that inspection. Source versions and the conditional counting audit are archived.

# 3 Agent and Feedback Model

An agent has parameters $\theta$, persistent memory $m$, and an interaction history $h$. Its policy selects an action, and an update $U$ incorporates an environmental response $f$:

$$a_t \sim \pi_{\theta_t}(\cdot \mid o_t, m_t, h_t), \qquad (\theta_{t+1}, m_{t+1}, h_{t+1}) = U(\theta_t, m_t, h_t, o_t, a_t, f_t).$$

An implementation may update parameters, memory, context, or some combination. Its entire system capacity includes external storage and algorithms; a small neural core is not necessarily a small complete system.

Study A instantiates this notation with a binary classifier whose action is a label prediction. Feedback gives the true label after prediction. Inputs are independent of the action, and gradient descent updates the parameters. This is supervised online learning, not active exploration or a new reinforcement learning algorithm. In a binary task, correctness plus the chosen label also determines the target label.

# 4 What Feedback Can and Cannot Supply

## 4.1 An information constraint

Let $\Theta$ be uniform over $K > 1$ tasks. Assume the complete initial agent state and all side information are independent of $\Theta$. Count every subsequent task-dependent observation as part of the response transcript. If each of $n$ responses has an alphabet of size at most $2^b$, then $I(\Theta; F_{1:n} \mid S_0) \le nb$. Adaptive queries are functions of $S_0$ and preceding responses, so cannot independently supply missing task information. Fano's inequality gives the exact-task identification bound

$$P_e \ge \max\left\{0, 1 - \frac{nb+1}{\log_2 K}\right\}.$$

Indeed, $H(\Theta \mid F_{1:n}, S_0) \le 1 + P_e \log_2 K$; subtracting this entropy from $\log_2 K$ yields the result. The bound is about task identification, not every prediction or reward metric. Informative priors or unaccounted observation channels invalidate these assumptions.

For a binary symmetric channel with independent flip probability $p$, the per-response information is at most $1 - H_2(p)$ bits. At $p = 1/2$, responses carry no information about the true bit. At $p = 1$, inversion is recoverable if the corruption mechanism is known. Learner failure under inverted labels therefore diagnoses a misspecified channel, not destroyed information.

### 4.2 Representation and transcript constraints

If a successful policy is outside the complete agent's permitted policy class, additional updates within that class cannot express it. External memory or tools may enlarge that class, so this constraint cannot be inferred from neural parameter count alone. In addition, a deterministic updater replaying the same ordered transcript from the same initial state reaches the same final state, by induction. Calling the procedure a loop adds no independent advantage. Active information acquisition or changing observations can matter; these mechanisms require their own tests.

Under the same independent-prior assumption, suppose the final retained state has at most $2^M$ possible values, with $M$ counting all retained task-dependent bits. Without further task-dependent observations, identification of a uniform task among $K$ possibilities has success probability at most $\min\{1, 2^M/K\}$. For any encoder, the optimal decoder succeeds with probability $K^{-1}\sum_s \max_k P(s \mid \Theta = k) \le 2^M/K$. This bound concerns exact identification, not every prediction metric. External records belong in the retained state; their capacity cannot be omitted simply because neural parameter count is small. It yields no universal threshold in numbers of neural parameters.

## 5 Experimental Setup

### 5.1 Tasks, models, and feedback

Each seed defines an initial and an independently generated post-change rule over eight standard-normal inputs. Linear labels threshold a normalized random projection. XOR labels combine signs of two randomly selected coordinates, with an independent fair complement bit for each rule. Warmup comprises 256 batches of 32 examples; adaptation uses a further 256 batches from the new rule. Evaluation sets of 2,048 examples per rule never enter updates. Separate uniform-input tests preserve each rule and change its input distribution.

The models are logistic regression and one-hidden-layer ReLU networks of widths 16, 64, and 256: 9, 161, 641, and 2,561 parameters. Adam uses learning rate 0.01 and default moments, with fresh moments after warmup. Every arm at the same capacity and seed starts from identical warmed-up parameters and sees the same arriving input stream.

The seven arms are frozen weights, clean labels, 25% flips, 50% flips, inverted labels, clean feedback delayed by 32 batches, and 25% replay. Replay replaces the final eight new examples in every batch with eight warmup examples sampled with replacement, retaining their original labels. It therefore changes both memory use and fresh-example exposure. Delayed feedback has 224 updates at arrival batch 256; a separate flush processes the remaining 32 without new observations.

### 5.2 Protocol, statistics, and resources

The full grid uses 20 seeds, 4000–4019, and was frozen in repository history before collection. A development run accidentally exposed seeds 1000 and 1001; the seed set was amended before formal collection, without hyperparameter tuning. A subsequent code audit found overlapping PRNG streams in the first full run (seeds 2000–2019). That run is archived with a superseded-inference notice. This version reports a replication on untouched seeds 4000–4019, with streams derived by SHA-256 of environment, family, role, and step or width. A complete-grid collision check passed. The protocol, hyperparameters, and endpoints otherwise remain unchanged. This is repository registration, not external preregistration.

The primary contrast in each family compares width-16 clean to width-256 frozen at arrival batch 256. This deliberately unequal-information comparison tests adaptation, not compute superiority.

We report paired seed-level t intervals at 97.5% for each of these two contrasts (Bonferroni familywise 95%). Secondary 95% intervals are descriptive. Seeds, not checkpoints or individual examples, are the replication units; t inference assumes adequate approximation of the seed-mean sampling distribution.

The run used PyTorch 2.8.0 with CUDA 12.6 on one RTX 4090 D and completed 1,120 arms in 109.54 seconds. Code and environment hashes, all 19,200 checkpoint rows, and analysis are retained. For arithmetic-budget comparisons we count $6WN$ multiply-add-related training FLOPs for $W$ matrix weights and $N$ examples. This proxy excludes optimizer, activation, bias, and hardware overhead. Warmup and adaptation are reported separately; it is not lifetime compute or a measured energy budget.

### 5.3 Study B: pretrained language models

We compare Qwen2.5-Instruct models with 0.494, 1.544, 3.086, and 7.616 billion parameters. Exact Hugging Face revisions and package versions are archived. Each of 24 environments (seeds 3000–3023) assigns four named commands distinct hidden offsets modulo eight. A command adds its offset to an integer state; compositions apply two commands. The family is disclosed, while each environment's offsets are withheld except in an oracle control. Train/test inputs are disjoint: 16 single-command feedback examples, 16 held-out single commands, and 32 held-out length-two compositions per environment. These translations commute, so the test does not measure command-order sensitivity.

Frozen-model conditions are no examples, 4/8/16 correct examples, 16 corrupted examples, 16 sequential model guesses, and explicit oracle offsets. Corruption replaces an answer with a uniformly chosen wrong digit with probability 0.5; this channel still conveys information. Self-generated examples use each model's constrained predictions conditioned only on its earlier guesses. All histories share the same demonstration template. Query selection is fixed, so this is passive adaptation rather than action-dependent exploration. Giving the final correct transcript offline produces byte-identical prompts; we do not count duplicate calls as independent evidence of an online effect. A hand-coded modular-offset estimator solves every test after the same clean examples, demonstrating identifiability within the supplied algorithmic family.

We select the most likely first assistant token among digits 0–7 in bfloat16, without sampling or additional reasoning tokens. Each digit is one tokenizer token. We also record unrestricted first-token accuracy, which does not measure full-response validity. This narrow interface can underuse a model's generative reasoning ability and is a central limitation, not an intelligence metric.

For the 0.5B model, rank-8 LoRA updates all query/value projection matrices (alpha 16, zero dropout), using 16 example-free training prompts for 32 passes, batches of four, AdamW at $2 \times 10^{-4}$, and a next-digit cross-entropy loss. Each environment starts from the same base checkpoint and fresh adapters and optimizer. Tests establish exact base-weight equality after two adapter train/unload cycles. Held-out tests use either no examples or the full correct context. There is no checkpoint selection. This measures persistence on one language, not lifelong retention across unrelated tasks.

The primary Study B endpoint is the paired 0.5B clean-16 minus self-generated accuracy on compositions, across 24 environments, with a 95% t interval and 10,000-resample paired bootstrap sensitivity interval. All other intervals are descriptive. Comparing released model sizes confounds parameter count with their different pretraining histories; no causal scaling-law estimate is claimed. All model calls run locally on the same RTX 4090 D, with full query predictions, prompt hashes, token counts, measured times, and peak memory.

### 5.4 Study C: response-interface sensitivity

We freeze 24 additional environments (seeds 5000–5023) before formal inference and evaluate the same pinned 0.5B and 7B checkpoints. Each environment has the same 16 feedback, 16 direct, and 32 composition queries as Study B's design. The four conditions are no examples, 16 correct examples, 16 sequential guesses, and oracle offsets. No weights change in this study.

Each condition is evaluated with Study B's constrained first-token interface and with full generation. In the latter, both digit-only instructions are replaced by a request for brief reasoning followed by a final line `Answer: N`. Decoding is greedy with a 128-new-token cap and inherited checkpoint defaults: repetition penalties are 1.1 for 0.5B and 1.05 for 7B. After tokenizer special tokens are removed, the last nonempty line must match `Answer: [0-7]`, ignoring case and optional whitespace. Invalid formats count as wrong. Self-history stores the parsed digit or the literal string `invalid`. All output tokens through EOS, decoded text, invalid formats, truncations, input/output tokens, and measured time are retained.

The primary endpoint is the paired environment-level interaction for 0.5B composition accuracy,

$$\Delta_{\text{int}} = (A_{\text{clean}} - A_{\text{none}})_{\text{generation}} - (A_{\text{clean}} - A_{\text{none}})_{\text{first token}},$$

with a 95% t interval and a 10,000-resample bootstrap interval. Remaining intervals are descriptive. An interaction must be interpreted with its component means and within-interface feedback effects: it can be positive because the control deteriorates. The intervention changes instructions, output constraints, and compute jointly; it does not isolate the effect of reasoning tokens. Development uses seed 9 only. Prompt and cap remain fixed after its failures. A prose error that described both repetition penalties as 1.1 was corrected after launch; the frozen rule to inherit model defaults and the runner were unchanged. Exact source hashes and this amendment are retained.

### 5.5 Study D: longer generation with fixed instructions

Study C's truncation motivates a separately frozen follow-up on 24 new languages (seeds 6000–6023). Only the pinned 7B model is evaluated, with unchanged instructions, weights, parser, batch size, and generation defaults. The conditions are no examples, clean16, and oracle offsets. Each query has one greedy continuation capped at 512 new tokens. We score both its first 128 tokens and its full continuation. Under this configuration, decoding before the shorter cap is independent of the cap: there is no length-dependent forced EOS, beam search, or minimum-length control. On development seed 11, all 144 prefixes exactly match separately generated 128-token responses. Source hashes, model identity, and settings match the formal runner; every compared pair is retained before formal collection.

The primary endpoint is the environment-paired clean16 composition difference, $A_{512} - A_{128}$, with a 95% t interval and 10,000-resample bootstrap. Other conditions, direct accuracy, feedback effects, format rates, truncation, and correct-to-wrong transitions are descriptive. No monotonic improvement is assumed: later text can revise an answer or invalidate the required final line. There are 1,152 environment/query pairs evaluated in three conditions, giving 3,456 actual continuations in 216 batches. Prefixes do not count as independent replicates or additional model calls, and shorter-budget wall times are not invented. The 0.5B model is excluded because its Study C responses terminated at EOS after two tokens; a higher cap cannot extend those completed responses under identical instructions. This selection is explicit and does not test alternative small-model prompts.

### 5.6 Study E: online outcomes and parameter updates

To test repeated updates explicitly, we freeze 24 further environments (seeds 7000–7023) with the same adaptation, direct, and composition splits. The pinned 0.5B model uses Study B's constrained first-token scoring. Three conditions receive the same ordered 16 adaptation queries. The context condition predicts, observes the true target, and appends the correct pair. The per-outcome LoRA condition predicts without examples, observes the target, and applies one gradient update. The error-only condition applies that update only after an incorrect constrained prediction. Targets enter no prediction prompt, and every pre-update prediction is flushed to an append-only journal before optimization. Feedback inputs are fixed, not actively selected.

LoRA uses the same rank, modules, optimizer, and learning rate as Study B, but one update on the current example per outcome: at most 16 singleton updates. Both adapter conditions start from identical adapter tensors for each environment. All weights and optimizer state reset between conditions and environments. Evaluations after 0, 1, 2, 4, 8, and 16 outcomes use held-out queries; adapters are evaluated without examples, with an additional full- context evaluation only at the final checkpoint. No best checkpoint is chosen. These 16 updates are a smaller optimization dose than Study B's 128 updates.

The primary endpoint is environment-paired per-outcome LoRA composition accuracy at 16 outcomes minus the frozen no-feedback baseline, with a 95% t interval and a 10,000-resample bootstrap (seed 821). Remaining contrasts and learning-curve intervals are descriptive. The error-only arm can use fewer updates; its compute is measured rather than matched. An ordered offline replay of the per-outcome labels and updates would be equivalent. We test this update rule's retained within-environment performance, not an independent benefit of the online presentation or retention after learning another task. The restricted interface also leaves generative ability unmeasured.

Development seed 13 passes the complete audit before formal collection. Exact base-parameter hashes match after each development condition and before and after the formal suite. Zero-feedback predictions agree with the base in every environment. Raw evaluation records, ordered prediction/feedback pairs, all 48 final adapters, provenance, and measured costs are retained.

### 5.7 Study F: checked revision of executable rule memory

We freeze 24 new languages (seeds 8000–8023), with development seed 17, and use the same pinned 0.5B and 7B models. Each model sees the additive family and all 16 single-command examples, and outputs four distinct integer offsets as a JSON object. The exact four command keys and values 0–7 are required; duplicate keys, invalid types, or surrounding prose invalidate the proposal. A single outer code fence is accepted. A supplied modular-addition executor uses only the saved rule to answer the 16 direct and 32 composition queries. No generated code is executed. Neither held-out inputs nor targets enter proposal or revision prompts.

One initial proposal is shared by two branches. Each branch receives exactly two further greedy calls, capped at 512 new tokens each. Self-review repeats the examples and the immediately previous proposal and requests a revision. Checked review adds a deterministic check: format failure, all examples pass, or the first failing example with the proposal's output and the already-known correct output. This supplies computed verification, not new task information or the true offset vector. Both branches run both revisions even after a passing proposal; the final proposal is scored without selecting a better earlier candidate. We retain every intermediate memory and response.

The primary endpoint is 0.5B final checked-minus-self composition accuracy, paired across environments. A positive primary effect requires the 95% t interval's lower bound above zero; a 10,000-resample percentile bootstrap (seed 822) is a sensitivity check. Each branch's final-minus-

initial effect is reported to distinguish improvement from degradation of the control. Exact-rule recovery, direct accuracy, validity, all stages, and 7B are secondary. Binary environment rates use Wilson 95% intervals; query accuracy and transition proportions use t intervals over environment means. In particular, adding four modulo eight to every true offset preserves all two-command outputs while making every direct answer wrong. Perfect composition therefore does not establish correct rule memory.

All examples are available initially. An exact symbolic estimator provides an identifiability control. There is no active exploration, weight update, cross-language accumulation, or test of neural retention after examples are removed. The rule file persists outside the model, and the executor supplies execution competence. Equal call caps are not equal compute: prompt lengths and stopping times differ. Token counts, padding, generation time, checker time, and memory bytes are retained, with the shared initial generation counted once. Only a matching audited development run permits formal inference.

### 5.8 Study G: retaining the correction history

An explicitly post-hoc analysis of Study F's frozen journals motivates the next intervention. In 0.5B, self-review repeats the exact response in 47/48 successive revisions, while checked review repeats it in 26/48 and returns the same final text as its first revision in 16/24 environments. Among 32 valid incorrect rules followed by valid checked proposals, only three repair the first failing command. Across those valid pairs, five offsets become correct and six become wrong. These are descriptive transitions nested within 24 environments, not independent replicates or proof of permanent cycles. They suggest testing earlier correction history rather than assuming that additional repetitions must produce learning.

We freeze 48 further languages (seeds 9000–9047), development seed 19, and the same pinned 0.5B and 7B models. Each branch receives all 16 examples initially and exactly 16 further checked revisions, with the same greedy 512-token cap and inherited defaults as F. The strict rule parser, known additive family, checker, and supplied executor are unchanged. One initial proposal is shared. The `last_only` branch retains only the immediately previous assistant proposal and its check/review message, matching F's checked prompt. The `full_history` branch retains every proposal and its following check/review message, including both failures and successes. Both use the same task/examples and review instruction. Earlier history, including its added context and computation, is the complete intervention.

At the first revision, both branches have identical ordered seed batches, padded input IDs, masks, and generated token IDs. Actual input tensors and raw outputs are preserved; any mismatch fails the suite without retrying until equality. Both models pass matching development audits before formal collection. Revisions continue after successful checks and repeated outputs. No gate retains a better earlier candidate; the last proposal is scored.

The primary endpoint is environment-paired final 0.5B direct accuracy, full history minus last only, with a 95% t interval and a 10,000-resample percentile bootstrap (seed 823). A positive primary claim requires the t lower bound above zero. Direct accuracy replaces composition as primary because of the disclosed two-command alias. Final-minus-initial effects, checkpoints 0, 1, 2, 4, 8, and 16, exact recovery, validity, composition, transitions, and 7B outcomes are descriptive. All intermediate proposals are scored and retained. Repetition is separated into invalid, valid-wrong, and exact states; stable correct behavior is not treated as a failed loop. Marginal binary rates use Wilson intervals. Degenerate t/bootstrap intervals at zero empirical variance would not establish a zero population effect.

Each actual model suite uses 1,584 continuations in 99 batches. A hypothetical standalone branch would require 816 continuations in 51 batches, including its initial proposal. Costs are explicitly recorded for both interpretations; full history can consume substantially more input tokens. No claim of equal compute, neural retention, or cross-language learning follows from retaining these transcripts.

### 5.9 Study H: cross-task fragment compression

Studies F–G do not accumulate reusable knowledge across languages. We next freeze a finite symbolic experiment, development seed 23 and 32 formal seeds 10000–10031. There is no neural model, weight update, or learned search algorithm. Each environment supplies four primitive permutations of 16 states and a left-to-right program interpreter. Four hidden three-operation motifs are sampled from the 64 possible sequences. Six different primitive prefix/ suffix pairs around each motif define 24 length-five experience programs. New tasks concatenate two or three motifs, eight tasks of each length. A shifted family instead draws eight uniform primitive sequences at each of lengths six and nine. Full-function duplicates within or across the experience and evaluation sets are rejected according to the frozen generation rule. The benchmark deliberately supplies recurring structure; arbitrary unrelated experience need not transfer.

Every task discloses eight ordered input/output examples and reserves eight other inputs. Search sees only the primitive tables and disclosed examples; latent motifs, generating programs, and held-out labels are inaccessible to its interface. It enumerates identity and then increasingly long token sequences in fixed lexicographic order, checking examples until the first mismatch and accepting the first complete visible fit. Exact success requires matching the full 16-state function. A false visible fit would still enter experience memory; held-out evaluation cannot reject it or guide a revision.

Experience tasks are first solved with primitives alone. The accepted program multiset $\mathcal{P}$ then defines four frozen evaluation vocabularies: *none* uses only primitives; *whole* adds every distinct accepted program longer than one primitive; *compressed* greedily adds at most four length-two or length-three fragments; and *renamed* applies one random nonidentity permutation of primitive names to the learned fragments. Renaming preserves entry count, lengths, and ordering while changing content; some fragments may survive or help by chance. Compression minimizes the supplied token objective

$$L(\mathcal{L}) = \sum_{f \in \mathcal{L}} (|f| + 1) + \sum_{p \in \mathcal{P}} \ell_{\mathcal{L}}(p),$$

where $\ell_{\mathcal{L}}$ is minimum-token segmentation into primitives and library calls. Definitions pay for their primitive bodies and one name token. Only strict improvements are accepted, with lexicographic ties. This is a flat symbolic compression routine, not hierarchical abstraction discovery; its token counts are not bit lengths. Libraries remain frozen during all evaluation tasks.

Each search has a 65,536 primitive-operation cap. Library calls are expanded and every primitive application to one example input is charged. No macro transition table, semantic cache, or deduplication makes execution free. Completing a fit exactly at the cap is accepted; an interrupted check is not. Failed checks advance the fixed enumeration rather than learning an error-directed search policy. The primitive policy class is unchanged; libraries change enumeration order and branching, with potentially different storage and search costs. Comparisons, expansion overhead, induction, storage, and wall time are reported separately from the cap. Experience collection is shared in actual costs and charged to each standalone memory system; the no-memory system needs none. The renamed control also pays compression cost.

The primary contrast is compressed minus whole-memory exact success on motif compositions, paired over environment means. We use a 95% t interval and 10,000-resample paired percentile

bootstrap (seed 829); a positive primary claim requires the t lower bound above zero. Other arms, shifted tasks, held-out accuracy, and 4,096/16,384/65,536-operation curves are descriptive. The complete fixed grid is audited by replaying full candidate outputs to infer early-rejection costs and by exhaustively checking fragment segmentation. Raw search results are flushed before separate held-out evaluation. No formal outcome changes the design, and all official development evidence is retained.

### 5.10 Study I: sequentially learned program priors

Study H has no neural component. We next freeze a separate comparison using its unchanged task generator, development seed 29, and formal seeds 11000–11031. Every environment supplies 24 length-five experience tasks and the same two 16-task transfer families, with new primitive permutations and hidden motifs. Its outcomes are not paired with Study H's different seeds or search representations. The neural policy sees only program prefixes, not task examples or primitive transition tables; the supplied searcher and checker use those tables and examples.

Primitive-only breadth-first search obtains the first visible fit for each experience task under the same 65,536-operation cap. Accepted nonempty programs enter a replay corpus even if hidden evaluation subsequently finds them wrong. After each attempted task, three persistent neural learners each take 16 full-batch Adam steps on their entire current corpus. Empty corpora produce explicit skipped-update records. We use next-token cross-entropy averaged over real primitive targets, excluding padding. There is no EOS target or learned length distribution. Inputs are five-way one-hot vectors (four primitives and START), followed by a one-layer unidirectional GRU and a four-output linear head. The registered parameter count is

$$P(H) = 3H^2 + 25H + 4,$$

giving 1,172 parameters for $H = 16$ and 13,892 for $H = 64$, including all biases. No pretraining or external embedding model is used. Networks initialize separately in each environment, directly in CPU float64; one PyTorch thread and deterministic algorithms are used. Adam has learning rate 0.01, default momentum coefficients, no weight decay, and gradient-norm clipping at one. We retain optimizer state across experience tasks, for 384 updates per learner in the observed complete corpus.

Six final priors share the same primitive program space. *Uniform* assigns probability 1/4 to each next primitive. *Counts* uses add-one smoothed next-token counts conditioned on the previous two tokens, left-padded with START: a $5 \times 5 \times 4$ integer table with 21 reachable contexts. *Small frozen* retains the initial $H = 16$ network. *Small trained* learns from accepted programs. *Small shuffled* starts from identical small weights but trains on independently permuted tokens within each accepted program, preserving its length and primitive counts. Those shuffled sequences need not solve the original task. *Large trained* uses $H = 64$ and the same fixed schedule. We also save and evaluate the small learner after eight and sixteen experience attempts. All experience and training finish before any transfer evaluation; intermediate outcomes cannot select later weights.

All arms receive the supplied maximum primitive length nine and a uniform prior over lengths zero through nine. For a primitive sequence $p$, its intended prior mass is

$$q(p) = \frac{1}{10} \prod_{i=1}^{|p|} \left[0.9\,\pi(p_i \mid p_{<i}) + 0.025\right].$$

Write $\tilde{\pi} = 0.9\pi + 0.025$; the mixture preserves support for every legal next token. The common $\log 10$ term does not affect ordering. Deterministic ordering sums edge costs $\mathrm{round}[-10^6 \log \tilde{\pi}]$,

with primitive-sequence lexicographic ties; rounding changes the summed token log cost by at most $4.5 \times 10^{-6}$ nats. A minimum heap emits prefixes in ranked order and expands each through length nine. Uniform yields breadth-first lexicographic order. There is no semantic cache, duplicate removal, beam pruning, or task-dependent reranking. Candidate order is shared across an arm's 32 transfer tasks. Storing candidates until their cumulative primitive lengths exceed 65,536 provides a sufficient prefix: each checked nonempty program costs at least its length on the first visible example.

The searcher executes that order, rejects at the first mismatch, and accepts the first full eight-example fit. Interrupted fits cannot be accepted; exact success is scored on all 16 inputs by a separate evaluator. Transfer checks do not update weights. The primitive-execution cap excludes training, ranking, comparisons, storage, and interpreter overhead, which are recorded separately. Standalone trained/count systems pay for experience collection; uniform and frozen priors do not. Intermediate probes add research cost while reusing stored training states. Ranking amortization is explicit, and phase sums reusing shared measurements are not independent wall-time benchmarks.

The primary contrast is small-trained minus uniform composition exact success, paired over 32 environment means, with a two-sided 95% t interval and a 10,000-resample percentile bootstrap (seed 947). The prespecified positive criterion is a t lower bound above zero. All other arms, shifted/balanced scores, intermediate checkpoints, and operation-budget curves are descriptive. An incomplete grid permits no confirmatory conclusion. The complete audit regenerates tasks and initial states, replays every model and optimizer tensor, reconstructs GRU probabilities with independent NumPy gate equations, and infers checking costs from full program functions. Raw searches precede held-out evaluation in the journal; completed phases and failures are retained.

After archiving these outcomes and manuscript v11, we specify a separate post-hoc likelihood analysis of the unchanged checkpoints. It uses all 32 formal environments, six final arms, and two intermediate probes, without training, search, or checkpoint selection. All priors score the same full accepted corpus and all composition/shifted generating programs. Each trained neural checkpoint also scores its actual training corpus, identified by accepted-task IDs and attempt order; the shuffled arm uses its stored shuffled targets for this view. Hidden generating programs enter only this offline diagnostic, after the original learning and searches have finished.

We retain every teacher-forced token log probability, both raw and after the original search smoothing. Losses are natural-log units per real primitive target, excluding EOS and the common length prior. For a corpus with $N$ tokens, the unrestricted empirical prefix predictor has minimum loss

$$H_{\text{emp}} = -\frac{1}{N} \sum_{s,a} n(s,a) \log \frac{n(s,a)}{n(s)},$$

where $s$ is the full preceding primitive prefix and $a$ the next token; only positive counts enter the sum. A separate distribution is allowed at every prefix. This in-sample bound accounts for conflicting continuations without constraining neural capacity or guaranteeing transfer. We report raw loss minus this bound for each learner's actual corpus. Common-set losses are summarized by family, length, and one-based position, averaging the 32 environment means equally. Paired values and sign counts remain descriptive; there is no new primary endpoint or post-hoc hypothesis test.

# 6 Results

## 6.1 Adaptation and capacity

Table 1: Mean post-change held-out accuracy (%), 20 seeds. All adaptive columns receive the same 8,192 clean examples; frozen models receive none.

| Parameters | Linear frozen | Linear clean | XOR frozen | XOR clean |
|---|---|---|---|---|
| 9 | 45.61 | 90.67 | 50.12 | 49.87 |
| 161 | 45.56 | 98.53 | 47.64 | 84.97 |
| 641 | 45.64 | 98.71 | 47.69 | 96.14 |
| 2,561 | 45.62 | 98.53 | 47.65 | 95.90 |

The small adaptive model exceeds the large frozen model by 52.91 points on linear tasks (97.5% CI [47.62,58.20]) and 37.32 on XOR ([28.85,45.79]). When both receive feedback, small-minus-large is 0.00 points for linear (95% CI [-0.22,0.22]) and -10.93 for XOR ([-15.39,-6.46]). The latter comparison shows a substantial remaining capacity effect under the tested update schedule. Logistic regression remains near chance on XOR despite clean feedback. Exact XOR is outside this fixed linear policy class, but observed chance performance also depends on the loss and optimization: a biased linear threshold can exceed chance under a zero-one objective. We do not identify chance as the best attainable linear-classifier accuracy or a limit for all small controllers.





Figure 1: Capacity and feedback jointly determine observed accuracy. Error bars are descriptive 95% t intervals across 20 seeds. The dotted line is chance accuracy; noisy feedback can coexist with information retained from warmup, so individual noisy outcomes need not equal chance.

At an equal adaptation arithmetic proxy, the small model's 256 updates and the largest model's 16 updates both cost 7,077,888 proxy FLOPs. The small model leads by 42.80 points on linear tasks and 34.72 on XOR. However, it receives sixteen times as many new examples, while the large model's warmup cost is sixteen times greater. This is a particular compute/information trade, not an isolated causal effect of feedback-loop efficiency or a scaling law.

### 6.2 Feedback variations, transfer, and retention

For the 161-parameter model, clean, 25% corruption, and 50% corruption yield 98.53%, 92.05%, and 51.03% accuracy on linear tasks and 84.97%, 71.84%, and 49.92% on XOR. Inverted feedback yields 1.20% and 13.32% respectively. More updates can reinforce the wrong target when the update rule assumes trusted labels.

Delayed feedback reaches 98.28% and 81.87% at the online endpoint. After flushing, its scores and final training losses equal clean feedback for every seed and capacity. This equality is a correctness check for ordered updates, not an additional empirical discovery about latency.





Figure 2: The same 161-parameter learner under six update conditions. Shading shows descriptive 95% seed-level intervals at fixed arrival checkpoints.

Clean small-model uniform-input accuracy is 98.44% for linear rules and 88.19% for XOR. This is distribution transfer within the same known rule family, not transfer to an unrelated task. Old-rule accuracy after clean adaptation is 45.23% and 51.94%. Replay raises these to 54.92% and 64.43% while lowering new-rule accuracy to 89.85% and 76.48%. Because rules may conflict without a task identifier, this is an adaptation– retention tradeoff; perfect performance on both is not always possible.

### 6.3 Study B: feedback does not guarantee compositional gains

Table 2: Study B mean constrained first-token accuracy (%), 24 environments. Direct tests use one command; composition tests use two. Chance is 12.5%.

| Model | Direct none | Direct clean | Compose none | Compose clean | Compose oracle |
|---|---|---|---|---|---|
| 0.5B | 13.80 | 12.24 | 11.46 | 11.46 | 11.46 |
| 1.5B | 13.28 | 13.02 | 11.20 | 12.63 | 12.89 |
| 3B | 10.16 | 5.73 | 13.02 | 12.63 | 14.32 |
| 7B | 13.80 | 26.56 | 13.80 | 17.58 | 26.82 |

For the primary 0.5B comparison, clean feedback and self-generated examples both yield 11.46% composition accuracy. The paired difference is 0.00 points (95% t CI [-1.03,1.03]; bootstrap [-

0.78,1.04]). Clean-minus-none is also 0.00 points. This is a failure to demonstrate the hypothesized gain with this mechanism, not proof that every feedback mechanism must fail.

The 7B model reaches 26.56% on direct tasks with clean-16 examples versus 13.80% without examples. Its composition scores are 17.58% and 13.80%, respectively: a descriptive paired difference of 3.78 points (95% CI [0.38,7.17]). With explicit offsets, direct accuracy rises to 75.52%, while composition reaches 26.82%. Representation of the instruction, inference of the latent rule, and execution of compositions are distinct bottlenecks.





Figure 3: Released-model size and the supplied evidence affect direct and compositional performance differently. Error bars are descriptive environment- level 95% t intervals. The oracle provides extra structured information; it is not a cost-matched competitor.

LoRA trains 540,672 parameters in addition to the frozen 0.494B base. Without example context, its direct accuracy is 26.30% versus 13.80% for the base. The paired direct gain is 12.50 points (descriptive 95% t CI [3.76,21.24]). Composition accuracy is 13.15%; its paired improvement over no-feedback base is 1.69 points (95% CI [-2.12,5.50]). Retaining examples at inference yields 13.28% composition accuracy but reduces direct accuracy to 9.90%. Thus the persistent single-command gain is strongly context-dependent: adding the same demonstrations does not preserve it. These results distinguish a gain under the training prompt format from robust compositional transfer.

Each frozen-model suite processes 2,156,304 unpadded input tokens in 888 forward calls, including self-history construction and evaluation. Measured suite times are 21.81, 56.22, 109.02, and 234.69 seconds; peak allocated memory is 1.20, 3.41, 6.41, and 15.29 GiB. These figures are whole-suite accounting, not equal lifetime budgets or per-condition causal estimates. The LoRA suite adds 1,486,848 training input tokens and 86.67 measured update seconds. Its extra optimization is explicitly not cost-matched to frozen inference.

### 6.4 Study C: format and budget limit the generation comparison

All 9,216 held-out predictions and 768 self-history records per model pass source, model-revision, environment, completeness, raw-token decoding, and score checks. Table 3 reports composition accuracy; Figure 4 also shows direct predictions.

The primary 0.5B interaction is −0.52 percentage points (95% t interval [−1.16,0.11]; bootstrap [−1.17,0.00]). Its first-token clean-minus-none effect is 0.52 points, while the generation effect is exactly zero in this sample. Every generated answer is the literal `N` followed by EOS, including the

| Model | Interface | No examples | Clean 16 | Self | Oracle |
|---|---|---|---|---|---|
| 0.5B | First token | 10.68 | 11.20 | 10.68 | 10.68 |
| 0.5B | Generation | 0.00 | 0.00 | 0.00 | 0.00 |
| 7B | First token | 13.15 | 16.15 | 12.24 | 24.74 |
| 7B | Generation | 0.00 | 6.90 | 0.26 | 97.27 |

Table 3: Study C composition accuracy (%). Generation scores include invalid and truncated responses as defined by the frozen parser; they must be read with the format and budget results below.

oracle condition. This is a failure of the tested instructions and output interface; it cannot establish that the model lacks the reasoning capacity measured by a different interface.

For 7B, oracle generation reaches 100% direct and 97.27% composition accuracy, compared with 69.53% and 24.74% under first-token scoring. Thus the narrow first-token interface can substantially understate execution capability when the true rules are supplied. With examples, generation's clean-minus-none composition contrast is 6.90 points (descriptive 95% interval [4.04,9.76]), but absolute clean accuracy falls from 16.15% to 6.90%. Generation improves that contrast partly against a control with zero measured accuracy; it does not establish a superior overall inference method.

The 128-token cap is material. In 7B composition queries, truncation rates are 100%, 88.28%, 95.70%, and 0.26% for no examples, clean examples, self examples, and oracle offsets respectively. Corresponding invalid-format rates are 100%, 88.28%, 95.57%, and 0.26%. A truncated response can still contain a parseable final line, so these quantities need not coincide. Clean-example direct generation scores 24.22%, with 57.55% truncation. These outcomes leave longer-budget example induction unresolved; they are not evidence of an unrestricted inability to infer the offsets.

Self-history also deteriorates under the interface: all 384 generated examples for 0.5B and 354 of 384 for 7B are invalid. The resulting histories contain the literal `invalid`, as specified. They are not 16 valid critiques or error-directed repairs. The contrast measures the complete construction of this self-history under the fixed prompt and budget.

Whole-suite elapsed times, excluding loading, are 28.92 and 1,831.46 seconds. Each model uses 672 calls per interface, including history acquisition. The 7B first-token and generation paths take 133.83 and 1,695.16 measured forward seconds; generation emits 554,021 tokens, or 599,945 token slots with batch padding. Such costs are recorded, not matched. All generation defaults, including the model-specific repetition penalties, remain part of the treatment.

### 6.5 Study D: longer continuations recover example-based performance

All 3,456 continuations and 216 actual generation batches pass the registered integrity checks. Table 4 and Figure 5 compare paired prefixes on the same 24 new environments.

| | Direct | | Composition | |
|---|---|---|---|---|
| Condition | 128 tokens | 512 tokens | 128 tokens | 512 tokens |
| No examples | 3.12 | 11.98 | 0.00 | 14.06 |
| Clean 16 | 20.05 | 59.90 | 7.94 | 70.57 |
| Oracle offsets | 100.00 | 100.00 | 96.61 | 96.88 |

Table 4: Study D accuracy (%) with fixed instructions and model. Shorter scores use prefixes of the same deterministic continuations.





Figure 4: Study C response interfaces. Error bars are descriptive 95% intervals across 24 environment means. Strong oracle execution under generation coexists with pervasive format or token-cap failures in other conditions.

The primary clean composition difference is 62.63 percentage points (95% t interval [56.10,69.16]; bootstrap [56.38,68.75]). The clean-minus-none effect at 512 tokens is 56.51 points (descriptive 95% interval [48.99,64.03]), compared with 7.94 at 128 tokens. The control also improves as its answers become complete. Thus the larger budget reveals a substantial measured benefit from the correct examples under this fixed interface.

Clean composition truncation falls from 87.76% to 3.26%, and invalid-format rate falls from 87.76% to 2.99%. Among 768 clean composition queries, 481 change from wrong to correct and none change in the opposite direction. All 481 gains occur where the shorter prefix was invalid. Accordingly, this result does not show correction of 481 previously valid wrong answers or isolate a reasoning mechanism from completion of the requested answer format. It shows that early evaluation of an unfinished response can seriously understate the model's use of existing information. No additional environmental feedback arrives during these continuations.

Oracle composition changes little, from 96.61% to 96.88%, while clean direct accuracy rises from 20.05% to 59.90%. These separate direct and composition query sets have different input lengths and generated traces; their ordering is not a general statement that composition is easier than direct prediction. The experiment adds no persistence across tasks, active exploration, or new parameter updates. It neither resolves small-model format failures nor establishes an advantage of a small learner over a large one.

The run takes 1,436.61 seconds, including 1,435.81 measured generation seconds, processing 853,632 input tokens and 654,495 output tokens. Output padding raises token slots to 1,044,320. The shorter prefixes have no separately measured wall times, so these records do not support a 128-versus-512 speed ratio.





Figure 5: Study D generation budgets. Error bars are descriptive 95% intervals across 24 environment means. Extending the same continuation substantially changes example-based accuracy; oracle execution is already nearly complete at the shorter budget.

### 6.6 Study E: one-pass updates do not establish retained gains

The complete 24-environment run passes all grid, source, model, prompt, feedback-order, state-reset, and adapter-file checks. Table 5 shows final accuracy; Figure 6 reports the fixed checkpoint curves.

| Condition | Direct | Composition |
|---|---|---|
| No feedback | 14.06 | 14.32 |
| Context after 16 outcomes | 12.50 | 14.45 |
| Per-outcome LoRA | 13.28 | 13.67 |
| Error-only LoRA | 10.68 | 11.98 |
| Per-outcome LoRA with context | 5.47 | 13.54 |
| Error-only LoRA with context | 5.99 | 12.89 |

Table 5: Study E constrained first-token accuracy (%). Adapter-only rows remove the correct transcript at evaluation. Chance is 12.5%.

The primary per-outcome composition change is −0.65 percentage points. Its 95% t interval is [−4.04, 2.74]; the bootstrap interval is [−3.78, 2.47]. Of 768 composition queries, 99 change from wrong to correct and 104 change from correct to wrong. The updates change behavior without demonstrating a net gain. Error-only updating has a descriptive change of −2.34 points (95% interval [−5.53,0.85]), with 86 improvements and 104 regressions. Context alone changes composition accuracy by 0.13 points ([−0.34,0.60]). These intervals describe uncertainty under this protocol; a null result is not a proof of no possible feedback benefit.

Adding the correct transcript to the per-outcome adapter lowers direct accuracy from 13.28% to 5.47%, a descriptive paired difference of −7.81 points (95% interval [−12.16,−3.46]). The error-only adapter falls from 10.68% to 5.99% (−4.69 points; [−8.67,−0.70]). This repeats the qualitative context dependence seen in Study B; it does not establish that context is generally harmful. Neither tested update rule yields a demonstrated composition improvement under this short adaptation schedule and interface.

The suite takes 72.80 seconds after model loading, recording 24,192 evaluation rows in 1,512 batches and 1,152 pre-update prediction calls. Per-outcome LoRA applies 384 updates across environments, processing 46,464 optimization input tokens in 7.82 measured seconds. Error-only LoRA applies 337 updates with 40,777 tokens in 6.82 seconds. Whole-suite peak allocation is 1,305,673,728 bytes. Full per-condition inference, padding, and update costs are archived. These are unequal adaptation costs, not lifetime compute estimates.

### 6.7 Study F: external checks do not establish a reliable gain

Both model suites pass the full audit of 120 proposals, 120 rule files, and 5,760 held-out evaluations each. Table 6 reports the initial and final proposals; Figure 7 includes both fixed revisions. Every proposal terminates at EOS before the 512-token cap.

The primary 0.5B checked-minus-self composition effect is +4.04 percentage points (95% t CI [−2.78,10.85]; bootstrap [−1.56,11.07]). Neither interval demonstrates a positive effect under this protocol. Checked-minus-initial has the same mean and t interval. Self-review has zero net composition change, with two query answers gained and two lost. Against self-review, checked revision gains 60 composition answers and loses 29, while direct accuracy falls by 1.04 points (CI [−10.11,8.02]). No 0.5B proposal recovers all four offsets at any stage; the final 0/24 exact-recovery rate has Wilson 95% CI [0.00%,13.80%]. Thus lack of observed recovery is not a universal zero-rate claim.





Figure 6: Study E fixed checkpoints. Error bars are descriptive 95% t intervals across 24 environments. Repeated verified outcomes do not produce demonstrated final compositional gains with either tested adapter update rule.

| Model | Proposal | Direct | Composition | Valid/24 | Exact/24 |
|---|---|---|---|---|---|
| 0.5B | Initial | 11.46 | 9.38 | 18 | 0 |
| | Self-review final | 11.46 | 9.38 | 18 | 0 |
| | Checked final | 10.42 | 13.41 | 17 | 0 |
| 7B | Initial | 51.04 | 43.23 | 21 | 4 |
| | Self-review final | 52.08 | 42.32 | 22 | 3 |
| | Checked final | 54.17 | 45.44 | 21 | 6 |

Table 6: Study F executor accuracy (%) and rule counts. Invalid rules score zero. The stored rules supply offsets; a human-provided algorithm executes the held-out queries. Results measure the combined system.

For 7B, comparing checked review with self-review gives a composition difference of +3.13 points (CI [−9.32,15.57]). The change from the initial proposal is +2.21 points (CI [−9.93,14.36]). Checked revision recovers two previously incorrect rule vectors and retains all four initially correct vectors. Self-review loses one initially correct vector and gains none. Final exact recovery is 6/24 (25.00%, Wilson CI [12.00%,44.90%]) versus 3/24 (12.50%, CI [4.34%,31.00%]); these are descriptive rates, not a confirmed between-arm effect. Against the initial proposal, checked review gains 81 composition answers and loses 64. Partial rule changes can therefore cause many answer regressions even when exact-vector retention appears stable.

The supplied symbolic estimator identifies all languages and executes all held-out targets correctly. No observed nonexact proposal has perfect composition accuracy, although the algebraic +4 counterexample remains valid. Valid saved rules occupy 34 bytes each, including syntax and newline. This compact representation demonstrates externally supplied persistence and execution, not neural retention or a new memory mechanism.

Validity remains an interface limitation. Across all five stages, all 32 invalid 0.5B proposals contain repeated offsets. Of 12 invalid 7B proposals, nine use negative offsets outside the required 0–7 range, two contain malformed JSON, and one repeats an offset. Seed 8012's final checked rule is semantically exact with $-1 \equiv 7 \pmod 8$, but the frozen interface scores it as invalid. We do not normalize scores after collection. Unlike Study C, most proposals satisfy the new interface, but rule correctness remains weak.

Each model uses ten actual generation batches. Whole-suite unpadded input and output token counts are 51,427/4,680 for 0.5B and 50,283/3,305 for 7B. Generation takes 2.724 and 12.457 seconds, with runner totals of 2.763 and 12.497 seconds after loading; peak allocation is 1.269 and 15.546 GiB. Diagnostic checking of all proposals takes 0.00114 and 0.00123 seconds. These costs count shared initial generation once and exclude offline scoring and plotting. Matching revision counts does not match measured inference cost or the models' pretraining investment.

### 6.8 Study G: longer history does not establish cumulative improvement

Both model suites pass the audit of 1,584 proposals, 1,584 saved rules, and 76,032 held-out evaluations each. All 3,188 transferred manifest entries match. The first-revision inputs and outputs are identical across branches, and every proposal terminates at EOS before the cap. Table 7 reports final outcomes; Figure 8 retains all declared checkpoints.

| Model | Proposal | Direct | Composition | Valid/48 | Exact/48 |
|---|---|---|---|---|---|
| 0.5B | Initial | 13.54 | 13.02 | 44 | 0 |
| | Last only, revision 16 | 10.42 | 7.94 | 32 | 0 |
| | Full history, revision 16 | 10.42 | 7.23 | 30 | 0 |
| 7B | Initial | 53.13 | 39.52 | 45 | 4 |
| | Last only, revision 16 | 47.40 | 34.51 | 44 | 5 |
| | Full history, revision 16 | 47.92 | 36.65 | 41 | 9 |

Table 7: Study G executor accuracy (%) and rule counts over 48 environments. Each branch makes 16 checked revisions from a shared initial proposal. Invalid rules score zero; no earlier candidate replaces the final proposal.

The primary 0.5B full-history-minus-last-only direct effect is 0.00 percentage points (95% t CI [−3.96,3.96]; bootstrap [−3.65,3.65]). The zero mean combines 20 wrong-to-correct and 20 correct-to-wrong answer differences; it does not mean that the two branches produce identical outcomes. Both finish 3.13 points below initial direct accuracy (last-only CI [−8.01,1.76]; full-history





Figure 7: Study F held-out execution from saved rules. Error bars are descriptive 95% t intervals over 24 environments. The two branches share the initial proposal; all revisions run and the final proposal is scored.

CI [−8.23,1.98]). No small-model proposal recovers an exact rule at any stage; each final 0/48 rate has Wilson CI [0.00%,7.41%]. The secondary composition changes from initial are −5.08 points for last only (CI [−9.22,−0.94]) and −5.79 for full history (CI [−10.04,−1.55]). These descriptive intervals receive no multiplicity adjustment and do not replace the primary endpoint. The between-branch composition difference is −0.72 points (CI [−2.84,1.41]).

For 7B, the descriptive direct contrast is +0.52 points (CI [−11.69,12.73]); composition is +2.15 (CI [−9.55,13.85]). Direct changes from initial are −5.73 points for last only (CI [−13.54,2.09]) and −5.21 for full history (CI [−16.31,5.89]). Final exact recovery is 5/48 (10.42%, Wilson CI [4.53%,22.17%]) versus 9/48 (18.75%, CI [10.19%,31.94%]); these marginal rates do not establish a between-branch effect. Last only gains two exact rules and loses one relative to the four initially exact rules. Full history gains eight but loses three, retaining only one of the four. Higher final exact recovery therefore does not imply stable retention of initial successes. Relative to initial direct answers, last only gains 48 and loses 92; full history gains 88 and loses 128.

Repeated proposals remain common. Each arm has 768 transitions nested in 48 environments. In 0.5B, 483/522 current valid-wrong last-only proposals and 436/485 full-history proposals have appeared earlier in their respective branches. The corresponding invalid-proposal counts are 231/246 and 262/283. Among valid-to-valid pairs, last only gains 11 correct offsets and loses nine; full history gains 37 and loses 32. These component counts exclude invalid transitions and cannot account for complete score changes alone. For 7B, previously seen valid-wrong proposals occur in 525/603 last-only and 425/525 full-history transitions; previously seen exact proposals occur in 98/104 and 146/159. Repetition of correct behavior differs from repeating an error. These nested descriptive counts do not establish permanent cycles or make reduced repetition a proxy for learning.

Actual suite input/output tokens are 1,244,712/61,776 for 0.5B and 1,168,726/44,253 for 7B. Generation takes 41.294 and 227.323 seconds; post-loading runner totals are 42.085 and 228.098 seconds, with peak allocations of 2.380 and 19.485 GiB. Standalone input tokens, initial included, are 367,542 versus 894,642 in 0.5B and 360,150 versus 826,048 in 7B for last only versus full history: ratios of 2.43 and 2.29. Accounted generation times are 15.836 versus 26.315 seconds and 78.413 versus 152.625 seconds. These totals reuse the measured shared-initial cost, not separately timed reruns. Full history increases measured cost without establishing a direct-accuracy benefit in these 16 revisions.

### 6.9 Exploratory selection and uniform-proposal references

After reviewing Study G and freezing manuscript v8, we specify a post-hoc analysis of its fixed candidate pools. At each declared checkpoint, an external selector scores every valid candidate against all 16 disclosed examples and keeps the earliest maximum in the available prefix. Invalid proposals rank below valid ones, including valid zero-score rules; an all-invalid prefix retains its initial invalid proposal. No later candidate, hidden queries or their targets, or true offset vector enters selection. No new model call occurs, and the original final-proposal endpoints remain unchanged.

For this known additive family, each command has four training and four disjoint direct-test inputs. A wrong offset fails every input for its command, so training accuracy equals direct accuracy for every valid rule; both scores are zero for invalid rules. Selection therefore guarantees nondecreasing direct accuracy over prefixes by construction. This is a supplied algorithmic property, not evidence of neural learning or transfer to a different family. Composition has no corresponding guarantee because of the +4-offset alias.

Table 8 distinguishes final proposals from selected candidates. The 7B last-only pools contain exact valid rules in 10 environments and the full-history pools in 17. The final proposals discard five and eight of these exact solutions, respectively. In contrast, none of the 0.5B pools contains an





Figure 8: Study G held-out execution at the prespecified checkpoints. Error bars are descriptive 95% t intervals over 48 environments. Both branches share the initial rule and have identical first-revision computation; all 16 revisions run without an acceptance gate.

exact valid rule for selection to retrieve. Per-environment direct scores improve in 10, 13, 20, and 22 environments in table order, with none decreasing. Individual direct answers can still regress when the retained rule has a different subset of correct offsets: gained/lost counts are 60/4, 76/8, 132/8, and 172/0. Composition scores decrease in 5, 4, 2, and 3 environments despite higher group means. Selection retains existing candidates; it cannot predict what a model would generate if an acceptance gate changed later prompts or feedback.

| | | Direct accuracy (%) | | | Exact count / 48 | | |
|---|---|---|---|---|---|---|---|
| Model | Pool | Final | Selected | Uniform | Final | Selected | Uniform |
| 0.5B | Last only | 10.42 | 17.71 | 48.47 | 0 | 0 | 0.46 |
| | Full history | 10.42 | 19.27 | 48.47 | 0 | 0 | 0.46 |
| 7B | Last only | 47.40 | 63.54 | 63.84 | 5 | 10 | 4.42 |
| | Full history | 47.92 | 70.31 | 63.84 | 9 | 17 | 4.42 |

Table 8: Post-hoc Study G descriptions. Final and selected columns are observed outcomes. Uniform columns are exact expectations for 16 independent uniform legal proposals after the same observed neural initial rule, followed by training-example selection. They are not observed random-agent runs or confidence bounds. All comparisons include supplied grammar and execution.

After viewing these selection outcomes, we specify a second post-hoc reference: independent uniform legal proposals drawn with replacement and the same selector. There are $N = 8 \cdot 7 \cdot 6 \cdot 5 = 1680$ legal offset vectors. Enumeration gives counts $(1001, 536, 126, 16, 1)$ for $M = 0, 1, 2, 3, 4$ correct positions. An injective relabeling of the eight values maps any legal true vector to the canonical $(0, 1, 2, 3)$, preserving this distribution. Let $F(j) = P(M \leq j)$. With $k$ initially correct offsets and $n$ independent uniform proposals, selected direct accuracy has exact expectation

$$\mathbb{E}[A_{\text{direct}}] = \frac{1}{4}\left[k + \sum_{j=k+1}^{4} \{1 - F(j-1)^n\}\right].$$

The selected rule is exact with probability one if $k = 4$, and otherwise with probability $1-(1-1/N)^n$. Invalid initial proposals have zero direct score. We compute exact fractions, using the observed initial training-pass counts for $k$, without Monte Carlo sampling or a significance claim.

Seventeen uniform proposals without a neural initial call have expected direct accuracy 48.71% and exact-rule probability 1.01%. This uses $k = 0$ as a score lower bound and $n = 17$; the lower bound is not an additional candidate. Conditioning instead on each model's shared initial proposal and adding 16 uniform draws gives Table 8. The 0.5B selected pools are 30.76 and 29.20 points below that conditional direct expectation. The 7B last-only pool is 0.30 points below it, while full history is 6.47 points above it. More exact 7B rules coexist with these different direct-score comparisons. Zero observed exact small-model rules does not establish a rate below a reference whose expected exact count is only 0.46. These comparisons describe observed pools relative to policy expectations, not a population effect or an isolated causal contribution of feedback or model size.

The sampler hardcodes the legal action grammar and always emits valid rules; its proposals ignore feedback, while the external selector uses all examples. The conditional reference retains the neural initial call and its prior learning. Equal candidate opportunities do not match validity, dependence, checker executions, or measured compute. Selection from recorded pools adds 9,056, 8,464, 12,032, and 11,664 example executions in table order. The conditional uniform references require 12,992 executions per 0.5B pool group and 13,008 per 7B group, including valid initial rules.

The pure uniform reference requires 13,056 for 48 environments and no neural initial call. The two offline analyses take 0.668 and 0.037 seconds before serialization, excluding imports and original generation. The latter times expectation calculation, not deployment of random agents. All records and exact fractions are archived separately from the original formal results.

### 6.10 Study H: useful compression and distribution-specific search

All 768 experience programs are accepted and match their full functions. The formal suite contains 4,864 searches and separate evaluations, including 4,096 evaluation searches. No accepted evaluation program is a false fit on the held-out inputs, so exact success and held-out accuracy coincide in this sample. Unaccepted tasks score zero. This agreement is an observed property, not a guarantee of the eight-example acceptance rule.

| Memory | Composition exact | Shifted exact | Definition tokens |
|---|---|---|---|
| None | 50.39 (258/512) | 50.00 (256/512) | 0 |
| Whole programs | 2.34 (12/512) | 1.17 (6/512) | 4,608 |
| Compressed fragments | 85.16 (436/512) | 9.96 (51/512) | 473 |
| Renamed fragments | 14.65 (75/512) | 12.11 (62/512) | 473 |

Table 9: Study H exact success (%) at 65,536 primitive operations per task. Each arm has 16 tasks per family in each of 32 environments. Definition-token storage is summed over environments and excludes the shared primitive tables and search implementation. Whole memory has 24 entries per environment; compressed and renamed memory each have four.

The prespecified compressed-minus-whole composition contrast is +82.81 percentage points, with a 95% t interval [77.12,88.51] and percentile bootstrap interval [77.34,88.09]. Both support a positive effect. All environment contrasts are positive. This satisfies the declared primary criterion for this finite intervention. The whole-memory baseline also performs much worse than no memory: adding complete solutions increases the vocabulary from four to 28 entries under the fixed breadth-first enumerator. Compressed memory has eight entries including primitives and exceeds no memory by 34.77 points on compositions, descriptively. The renamed control has the same number and lengths of entries but solves only 14.65%, indicating that entry count and storage alone do not explain the observed composition performance.

Transfer is distribution-specific. On shifted random programs, compressed memory solves 9.96%, compared with 50.00% without memory. Across the fixed balanced mixture of both evaluation families, it solves 487/1,024 tasks versus 514/1,024 without memory. The induced vocabulary changes the search allocation; it does not remove primitive programs from the policy class. Reduced success under the cap therefore need not imply loss of representation or deletion of previously stored knowledge. These are limitations of this fixed enumeration and representation policy, not evidence that memory is generally harmful.

Compression reduces the experience encoding from 3,840 primitive tokens to 2,434 corpus tokens plus 473 definition tokens. Experience collection costs 3,110,069 primitive operations, charged to every standalone memory arm. Including that experience, the aggregate search costs across both evaluation families are 43.49, 69.10, 42.26, and 63.66 million operations for none, whole, compressed, and renamed memory. These totals have different success counts and exclude comparisons, induction, and interpreter overhead; they are not equal lifetime compute. Compression itself takes 0.833 seconds over 32 environments, with 5,048 candidate-library evaluations. The actual shared

experiment takes 127.832 seconds including journaling on an Intel Core i5-1135G7 CPU. No neural training or GPU inference occurs in this study.

### 6.11 Study I: neural fitting without improved search transfer

All 768 experience solutions match their full functions and supply 3,840 primitive tokens. The formal run contains 8,960 searches, including 8,192 transfer searches, and 36,864 gradient updates. All 5,761 nonaccepted searches exhaust their operation cap. No accepted transfer program fails its hidden evaluation. Thus the observed failure concerns finding a fit under the budget, with neither a false-acceptance nor an output-format failure in this sample.

| Prior | Neural parameters | Composition exact | Shifted exact |
|---|---|---|---|
| Uniform | 0 | 50.00 (256/512) | 50.00 (256/512) |
| Counts | 0 | 66.02 (338/512) | 33.59 (172/512) |
| Small frozen | 1,172 | 50.00 (256/512) | 49.80 (255/512) |
| Small trained | 1,172 | 22.85 (117/512) | 10.16 (52/512) |
| Small shuffled | 1,172 | 26.76 (137/512) | 13.67 (70/512) |
| Large trained | 13,892 | 17.58 (90/512) | 9.96 (51/512) |
| Small after 8 attempts | 1,172 | 28.52 (146/512) | 11.91 (61/512) |
| Small after 16 attempts | 1,172 | 23.24 (119/512) | 10.74 (55/512) |

Table 10: Study I exact success (%) under the same 65,536 primitive-operation cap per task, with 32 environments and 16 tasks per family per environment. Parameter counts are per neural model; the count prior instead stores 100 integer cells. Supplied search, verification, tables, and runtime storage are outside those neural counts. Only the small-trained versus uniform composition contrast is primary; other rows/comparisons are descriptive.

The primary contrast is $-27.15$ percentage points. The 95% t interval is $[-32.74, -21.55]$; the bootstrap interval is $[-32.23, -21.68]$. The intervals agree. Differences are negative in 29 environments, positive in two, and zero in one. The declared positive prediction fails, with contrary evidence for this configuration. Identical initial small networks have 50.00% composition success when frozen, versus 22.85% after replay. A larger trained GRU also has a lower observed score under this schedule; this does not establish a general capacity optimum or a result about scaling laws.

The simpler count prior has higher observed composition success than uniform search, 66.02% versus 50.00%, but falls to 33.59% on shifted programs. Across the balanced mixture it solves 510/1,024 tasks, versus uniform's 512/1,024; small trained solves 169/1,024. We therefore claim no overall superiority for the count prior. Its use of local sequential structure differs from both a recurrent learned representation and Study H's callable fragments. Their storage and algorithms are not capacity-matched.

Shared experience costs 3,188,241 primitive operations. Including that cost where applicable, standalone search totals for uniform, counts, small frozen, small trained, small shuffled, and large trained are respectively 44.14, 46.64, 43.86, 63.64, 62.14, and 65.07 million operations. Corresponding reconstructed phase-time sums are 2.739, 2.847, 27.705, 25.907, 25.969, and 29.562 seconds. These sums charge initialization, optimizer setup, training, count construction, ranking, and search as applicable, using shared measured phases; they are not separate wall-time trials or equal total computation.

Actual collection includes the intermediate probes and uses 434,569,422 search operations. It processes 2,304,000 replay target tokens and 9,606,438 neural prefix positions. Training takes 26.203





Figure 9: Study I small-prior transfer at the four prespecified checkpoints. Thin lines show individual environments; the blue line shows their mean. The zero-attempt point is the frozen initial network. The dashed reference uses uniform search without experience. All points are scored on the same fixed transfer tasks after training ends. Means decline in both families, but individual trajectories vary; these descriptive curves do not imply that each update or each environment deteriorates.

seconds, ranking 103.961 seconds, and search 17.751 seconds. Full collection takes 150.076 seconds on the lens AMD Ryzen 9 9950X CPU. Independent audit and analysis take 84.424 seconds. The hidden evaluator adds 302,256 primitive operations outside search. All 352 checkpoint files are retained, including optimizer states, occupying 43,789,664 archive bytes; this is not an inference-RAM measurement. The complete 969-file raw/audit archive matches its originals, and both intervals were independently reproduced. No experiment source, task, seed, budget, or checkpoint selection changed after official development or formal outcomes.

### 6.12 Post-hoc experience fit and transfer likelihood

The small trained prior lowers raw loss on the full accepted corpus relative to its frozen state in all 32 environments. Its mean is 0.662957 nats per token, versus 1.393215 initially: a mean difference of $-0.730258$. The empirical prefix bound is 0.635611, with mean excess 0.027347. This establishes improved fitting of the observed experience under the next-token objective. It does not establish improved task-solving ability.

On composition generating programs, small-trained raw loss exceeds uniform in every environment; its mean excess is 1.210152 nats/token. The original search smoothing reduces absolute loss to 1.824081, still 0.437787 above uniform on average, with positive differences in 31 environments and a negative difference in one. Shifted raw loss is 3.357285 and smoothed loss is 2.144459; both exceed uniform in all 32 environments. Improved experience fitting therefore coexists with unfavorable transfer likelihood and the original lower search success. These are distinct descriptive outcomes, not an estimate that one caused another.

The final larger network has a smaller mean experience excess over the same bound, 0.011663, yet higher transfer loss and lower original search success under the fixed schedule. The count prior fits real experience less closely than the final small and large priors trained on that corpus, while as-

| Prior | Full experience | Composition | Shifted |
|---|---|---|---|
| Uniform | 1.3863 | 1.3863 | 1.3863 |
| Counts | 1.0298 | 1.0913 | 1.5098 |
| Small frozen | 1.3932 | 1.3897 | 1.4000 |
| Small trained | 0.6630 | 2.5964 | 3.3573 |
| Small shuffled | 2.2551 | 2.3209 | 2.9893 |
| Large trained | 0.6473 | 2.9522 | 3.6507 |
| Small after 8 attempts | 1.4153 | 2.1319 | 2.7116 |
| Small after 16 attempts | 0.9803 | 2.4225 | 3.0870 |

Table 11: Post-hoc raw next-token loss, nats per token (lower is better), equally averaged across 32 environments. Full experience uses the same 24 real accepted programs for every row, including the shuffled and early checkpoints. Transfer columns score the original generating sequences, not every semantically equivalent solution. No new training occurs.

signing higher likelihood to composition generating programs. Its shifted loss exceeds uniform. Thus closeness to the in-sample optimum alone does not establish transfer quality; other optimization or regularization interventions remain untested. The shuffled learner's own-corpus loss is 0.703128, with bound 0.630918 and excess 0.072211. This differs from its loss on real experience in Table 11. Intermediate own-corpus losses also concern different datasets and cannot be read as a fixed-corpus learning curve.

Every length/position cell is archived. For the small trained prior, mean loss already exceeds uniform at positions one through five in both transfer families and both lengths, under raw and smoothed scoring. However, content and motif placement also differ between experience and transfer; these cells do not isolate positional overfitting or length extrapolation as a cause. Furthermore, the generating sequence is only one possible solution. Its likelihood does not measure total probability over semantically equivalent programs or exclude shorter successful candidates.

The diagnostic took 4.349 seconds on the lens CPU and retained 17,408 program records, including duplicate views of actual training corpora. All 84,480 neural target probabilities and logs agree with independent NumPy equations at absolute/relative tolerance $10^{-12}$. Standard-library reconstruction on lens and locally agrees on the complete grid, 12,128 environment cells, 379 aggregates, 160 training-corpus summaries, and six paired contrasts. All original file hashes and transferred diagnostic files match their recorded sources. The analysis plan, source freeze, raw scores, and all descriptions are archived separately from the original experiment.

### 6.13 Limitations and interpretation

All nine studies use synthetic tasks with disclosed families and inexpensive feedback. They do not measure autonomous exploration, long-horizon reward, human intelligence, or general cross-domain skill accumulation. Study A's fixed optimization schedule may interact with capacity. Its replay treatment also changes fresh-example exposure. Study B uses only one model family and a first-token response interface. Study C adds full generation but also a strict final-line format and a fixed token cap. Study D shows that extending that cap can materially change accuracy with the same prompt and model. Study E tests only 16 online outcomes and reuses the narrow first-token interface; it is not an optimized learning algorithm or a full-generation test. Low accuracy can reflect the interface, instruction-following ability, prior execution ability, or the specific update schedule. Study F adds error-directed rule revision with equal call caps, but neither equal measured compute nor an open-ended reflection agent. Its executor and disclosed rule family contribute

supplied capability, and its final score does not measure learning across languages. Study G extends revision to 16 rounds and retains complete transcripts, but supplies all task examples from the start and adds no new observations. It tests transcript availability together with increased context and compute, not a fixed-cost memory comparison. Its ungated last-proposal policy can discard earlier success; mechanisms that preserve verified progress require their own prospective comparisons. The 7B and other secondary contrasts are descriptive and do not receive multiplicity adjustment. The subsequent selection and uniform references are explicitly post-hoc. Their known grammar and full-example scorer supply capability, and a conditional policy expectation is not a measured random-agent outcome or an interactive intervention. They do not establish general intelligence through random search or through retaining the best synthetic-task candidate.

Study H deliberately creates shared motifs and tests only one frozen experience-to-transfer cycle. The searcher, primitive tables, flat compression algorithm, task-generation structure, and exact checker are supplied. Whole and compressed memory differ in vocabulary size and storage; the renamed control addresses content at matched entry lengths but does not create a universal memory baseline. The primitive-operation cap excludes other work, and prior experience differs from the no-memory arm. A favorable primary contrast therefore does not establish improved general intelligence, a neural capacity threshold, or overall superiority across the tested distributions. Hierarchical abstraction, evolving neural search policies, noisy feedback, and continual library updates are outside this experiment.

Study I learns an unconditional program prior from length-five solutions obtained by a supplied searcher, then transfers to lengths six and nine. Next-token fitting and successful synthesis are different objectives; the network never receives the task's input/output examples or updates from its failed transfer proposals. The result does not isolate architecture, optimization, positional overfitting, or objective/distribution mismatch as the cause. Those explanations need separate interventions. The two hidden widths and single update schedule do not establish what an optimized or task-conditioned learner could achieve. This is one experience-to-transfer cycle with sequential replay, not lifelong learning or a test of all feedback systems. The subsequent likelihood diagnostics are post-hoc descriptions of fixed checkpoints. Their experience bounds apply in sample, and their transfer scores use single generating sequences rather than semantic solution classes; they identify no causal mechanism. The count comparator has a different representation and storage; none of these comparisons equates neural parameters with total system capacity.

In development, 0.5B answered a simple arithmetic question incorrectly under a one-digit instruction. The official weight SHA-256 matched, and CPU float32, GPU float32/bfloat16, and eager/SDPA paths reproduced it. A subsequent ordinary question produced the correct answer; other ordinary-language responses were coherent. Thus the calibration reveals prompt sensitivity, not general arithmetic incapacity. Model files and device agreement alone cannot certify that a response interface makes full use of the available capability.

The initial Study A random-stream defect and the corrected fresh-seed replication are both disclosed and preserved. A disk-full error occurred only during Study B export; every original run had completion metadata and complete predictions. Export was repeated on a separate filesystem without rerunning models. Study F's first 7B development load failed on a cache metadata write to that full filesystem, before inference; its provenance and traceback are preserved. The same frozen source and cached weights passed after enabling offline cache access. Source hashes and complete outcome grids were checked before analysis.

Prior work already establishes reinforcement learning, external memory, verbal reflection, and test-time computation as relevant mechanisms. Our current evidence is a diagnostic investigation of the stated hypothesis, not a first discovery of feedback-driven intelligence. Targeted review of ten close precedents strengthens the comparison, but a systematic novelty review remains incomplete.

Studies F and G test a small structured external rule. Study H tests one finite experience-to-transfer cycle with supplied symbolic search and compression; Study I adds sequentially learned program priors. Open-ended abstraction learning, active exploration, sustained cross-task retention, and long-horizon reward learning remain untested.

Stability is partially measured by Study A's old-rule retention and F/G's within-language rule regressions. Long-term memory interference across tasks remains untested. Our exact synthetic targets do not reproduce the difficulty of obtaining trustworthy real-world feedback. No study tests reward hacking: optimizing a proxy evaluator can improve its score without improving the intended task, particularly if the agent can influence the feedback source. These mechanisms require separate held-out evaluation and feedback-quality experiments; faster updates alone do not address them.

# 7 Conclusion

Feedback enables substantial adaptation in small neural learners under task change, but capacity remains consequential when both small and large models learn. In the smallest pretrained model, our example-conditioning and limited parameter-update protocols do not establish compositional improvement. Its format failures under Study C's prompt remain unresolved; Study F's new structured interface produces mostly valid rules but no exact 0.5B recovery. In 7B, supplying correct examples yields substantial compositional accuracy once the continuation budget permits most responses to finish. The earlier short-budget failures therefore cannot support a general conclusion that this model cannot learn the disclosed rules in context. An explicit one-pass feedback loop in the 0.5B model yields no demonstrated compositional gain, whether it updates after every outcome or only after an error. Retaining behavior changes therefore cannot be equated with accumulating useful, transferable skill. External rule storage and exact example checks also yield no demonstrated 0.5B composition gain over two self-revisions. The larger model recovers some full rules, while retaining substantial uncertainty and query-level regressions. Extending checked revision to 16 rounds and retaining all earlier corrections does not establish improved 0.5B direct accuracy, despite substantially greater input cost. In 7B, increased final exact-rule counts coexist with losses of initially correct rules. Neither additional iterations nor a complete transcript ensures cumulative improvement under the tested update mechanism.

Post-hoc analysis exposes two distinct limits: exact candidates can appear and then be discarded, or never appear in the recorded pool. A supplied training-example selector recovers 17/48 full-history 7B rules, but none in 0.5B. The smaller model's selected direct score also falls below the exact expectation of a uniform legal-proposal reference under the same supplied selector. This comparison includes an externally specified grammar and unequal checking costs; it does not establish a general model-size threshold. Available candidates, retention, verification, and supplied algorithms must therefore remain separate from claims about neural learning.

The symbolic transfer experiment adds a conditional positive mechanism: compressing accepted solutions into reusable fragments greatly improves search on new compositions of shared motifs, compared with storing entire solutions. The same library reduces success on shifted random programs relative to search without memory. This is experience-derived representation learning implemented by a supplied symbolic algorithm, with no neural update. It shows why external knowledge and task structure belong in a complete account of system capability, while providing no evidence that feedback alone can replace either inductive bias or a capable learning mechanism.

Sequential neural fitting provides a further counterexample to guaranteed cumulative progress under a feedback mechanism: the small program prior's new-composition score falls below uniform search despite exact accepted experience and persistent updates. A simple count rule uses that

experience more successfully on compositions in this grid, yet loses performance after the program distribution changes and does not exceed uniform search on the balanced mixture. The objective, representation, transfer distribution, and supplied search therefore remain central parts of the explanation. This comparison does not rule out more effective small agents or update rules. Post-hoc likelihood diagnostics confirm that improved fitting of accepted experience can coexist with lower likelihood on transfer generating programs. The small and large learned priors approach the unrestricted empirical prefix-loss bound on their training corpus, yet fail to improve the original transfer-search endpoint. These observations motivate interventions on how experience is represented and used; they do not isolate a remedy or imply that a different learning mechanism must fail.

The supported conclusion is conditional: feedback, representation, prior learning, update rules, and response interfaces jointly determine measured adaptation. A strong claim about small agents needs evidence of sustained error-directed updates, retention, and transfer across diverse tasks under comparable resource constraints. The present study establishes neither that feedback alone explains intelligence nor that increasing model capacity is an incorrect research direction.

## References


[1] D. Silver and R. S. Sutton. Welcome to the Era of Experience. Book-chapter preprint, 2025. Author-linked copy: https://www.davidsilver.uk/publications/.

[2] D. Silver, S. Singh, D. Precup, and R. S. Sutton. Reward is enough. Artificial Intelligence, 299:103535, 2021. https://doi.org/10.1016/j.artint.2021.103535.

[3] A. Vaswani et al. Attention Is All You Need. NeurIPS, 2017. https://arxiv.org/abs/1706.03762.

[4] J. Kaplan et al. Scaling Laws for Neural Language Models. 2020. https://arxiv.org/abs/2001.08361.

[5] J. Hoffmann et al. Training Compute-Optimal Large Language Models. 2022. https://arxiv.org/abs/2203.15556.

[6] H. Chen et al. Feedback is all you need: from ChatGPT to autonomous driving. 2023. https://doi.org/10.1007/s11432-023-3740-x. Bibliographic metadata verified; full-text argument not assessed in this version.

[7] Y. Duan et al. $RL^2$: Fast Reinforcement Learning via Slow Reinforcement Learning. 2016. https://arxiv.org/abs/1611.02779v2.

[8] M. Laskin et al. In-context Reinforcement Learning with Algorithm Distillation. 2022. https://arxiv.org/abs/2210.14215.

[9] N. Shinn et al. Reflexion: Language Agents with Verbal Reinforcement Learning. 2023. https://arxiv.org/abs/2303.11366v4.

[10] A. Madaan et al. Self-Refine: Iterative Refinement with Self-Feedback. 2023. https://arxiv.org/abs/2303.17651v2.

[11] J. Huang et al. Large Language Models Cannot Self-Correct Reasoning Yet. ICLR, 2024. https://arxiv.org/abs/2310.01798v2.

[12] C. Snell et al. Scaling LLM Test-Time Compute Optimally can be More Effective than Scaling Model Parameters. 2024. https://arxiv.org/abs/2408.03314.

[13] G. Wang et al. Voyager: An Open-Ended Embodied Agent with Large Language Models. 2023. https://arxiv.org/abs/2305.16291v2.

[14] X. Chen et al. Teaching Large Language Models to Self-Debug. 2023. https://arxiv.org/abs/2304.05128v2.

[15] K. Ellis et al. DreamCoder: Growing generalizable, interpretable knowledge with wake-sleep Bayesian program learning. 2020. https://arxiv.org/abs/2006.08381v1.

[16] A. Zhao et al. ExpeL: LLM Agents Are Experiential Learners. 2024. https://arxiv.org/abs/2308.10144v3.