

Started on	Friday, 24 April 2026, 11:16 AM
State	Finished
Completed on	Friday, 24 April 2026, 11:28 AM
Time taken	12 mins 21 secs
Name	J6BA BLESSYBHA A 2025-BME

Question 1
Correct
Marked out of 1.00
Flag question

Processing of a structure refers to the ways of accessing the members of that structure.

Basically there are two operators available for accessing the members of a structure depending on whether a normal variable or a pointer variable is declared to the structure.

They are:

1. Dot (period) operator
2. Arrow operator

To access a member of a structure using dot (.) operator, the syntax is:
structure_variable.member

Let us consider an example:

```
struct example
{
    int a;
    float b;
    char c;
};
struct example e;
e.a = 25;
e.b = 45.67;
e.c = 'M';
```

In the above code e is a structure variable which has the memory of 3 variables a, b and c. Each member can be accessed by using the operator dot (.) as e.a, e.b and e.c.

Let us consider another example:

```
struct employee
{
    int empId;
    char empName[20];
} emp1;
emp1.empId = 201;
emp1.empName = "APJ.Abdul Kalam"; // Gives an error because a string can not be assigned direct
strcpy(emp1.empName, "APJ.Abdul Kalam"); // Correct way of assigning a string to the array
```

Fill in the missing code in the below program to read three employees data and display it.

For example:

Input	Result		
Einstein 55 34556.45	AGE	Name	SALARY
GrahamBell 46 31252	55	Einstein	34556.449219
Aristotle 30 42345.50	46	GrahamBell	31252.000000
	30	Aristotle	42345.500000

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2
3 struct employee
4 {
5     char name[20];
6     int age;
7     float sal;
8 };
9
10 int main()
11 {
12     struct employee s1, s2, s3;
13     scanf("%s %d %f", s1.name, &s1.age, &s1.sal ); // Write the correct code
14     scanf("%s %d %f", s2.name, &s2.age, &s2.sal ); // Write the correct code
15     scanf("%s %d %f", s3.name, &s3.age, &s3.sal ); // Write the correct code
16     printf("%7s %15s %15s\n", "AGE", "Name", "SALARY");
17     printf("%8d %15s %15f\n", s1.age, s1.name, s1.sal ); // Write the correct code
18     printf("%8d %15s %15f\n", s2.age, s2.name, s2.sal ); // Write the correct code
19     printf("%8d %15s %15f\n", s3.age, s3.name, s3.sal ); // Write the correct code
20     return 0;
21 }
```

	Input	Expected			Get	
✓	Einstein 55 34556.45 GrahamBell 46 31252 Aristotle 30 42345.50	AGE	Name	SALARY	AGE	Name
		55	Einstein	34556.449219	55	Einstein
		46	GrahamBell	31252.000000	46	GrahamBell
		30	Aristotle	42345.500000	30	Aristotle

Passed all tests! ✓

Question 2

Correct

Marked out of 1.00

Flag question

A structure variable can be initialized in its definition itself with a list of initializers enclosed within the braces. The initialization of values will be taken in an order.

Let us consider an example:

```
struct student
{
    int roll_number;
    int total_marks;
    float attendance_percentage;
};
struct student s = {101, 450, 72.45};
```

In the above example 101 is assigned to s.roll_number, 450 is assigned to s.total_marks and 72.45 is assigned to s.attendance_percentage.

See and retype the below code.

```
#include <stdio.h>
```

```
int main()
{
    struct book
    {
        char name[30];
        int pages;
        float price;
    };
    struct book b1 = {"C Programming Language", 350, 425.75};
    struct book b2 = {"How to learn C", 275, 550.25};
    printf("First book information is\nName : %s\nNumber of pages: %d\nPrice of the book : %f\n", b1.name, b1.pages, b1.price);
    printf("Second book information is\nName : %s\nNumber of pages: %d\nPrice of the book : %f\n", b2.name, b2.pages, b2.price);
    return 0;
}
```

For example:

Result
First book information is Name : C Programming Language Number of pages: 350 Price of the book : 425.750000 Second book information is Name : How to learn C Number of pages: 275 Price of the book : 550.250000

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     struct book
5     {
6         char name[30];
7         int pages;
8         float price;
9     };
10    struct book b1 = {"C Programming Language",350,425.75};
11    struct book b2 = {"How to learn C",275,550.25};
12    printf("First book information is\nName : %s\nNumber of pages: %d\nPrice
13    printf("Second book information is\nName : %s\nNumber of pages: %d\nPrice
14    return 0;
15 }
```

Expected	Got	
✓ First book information is Name : C Programming Language Number of pages: 350 Price of the book : 425.750000 Second book information is Name : How to learn C Number of pages: 275 Price of the book : 550.250000	First book information is Name : C Programming Language Number of pages: 350 Price of the book : 425.750000 Second book information is Name : How to learn C Number of pages: 275 Price of the book : 550.250000	✓

Passed all tests! ✓

Started on	Friday, 24 April 2026, 11:30 AM
State	Finished
Completed on	Friday, 24 April 2026, 11:42 AM
Time taken	12 mins 4 secs
Name	JEBA BLESSYBHA A 2025-BME

Question 1

Correct

Marked out of 1.00

Flag question

When the programmer wants to define more number of structure variables, it is better practice to define array of structures rather than individual structure variables.

Creation of array of structures is same as creation of integer arrays, float arrays and so on.

The syntax of defining an array of structure is: Below is an example of array of structure:

`struct tag_name structure_variable[size]; // The size specifies the number of structure variable`

Below is an example of array of structure:

```
struct example
{
    int a;
    float b;
};
struct example e[3];
```

In the above example the definition of a structure will create an array of structures with 3 structure variables of type structure example. An array of structure variables should get a memory of continuous blocks and they can be accessed sequentially.

`e[0].a e[0].b e[1].a e[1].b e[2].a e[2].b`

4724 4726 4730 4732 4736 4738

Understand the below program and then fill in the missing code to read n books data and display it.

For example:

Input	Result
2	Given books details are
C-Language	Book-0 Name : C-Language Price : 235.649994 Pages : 245
245	Book-1 Name : Java-Programming Price : 275.799988 Pages : 350
235.65	
Java-Programming	
350	
275.80	

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2
3 int main()
4 {
5     struct book
6     {
7         char name[30];
8         int pages;
9         float price;
10    };
11    struct book b[5];
12    int i, n;
13    scanf("%d", &n);
14    for (i = 0; i < n; i++)
15    {
16        scanf("%s", b[i].name ); // Write the correct code
17        scanf("%d", &b[i].pages ); // Write the correct code
18        scanf("%f", &b[i].price ); // Write the correct code
19    }
20    printf("Given books details are\n");
21    for (i = 0; i < n; i++)
22    {
```

	Input	Expected	Get
✓	2 C-Language 245 235.65 Java-Programming 350 275.80	Given books details are Book-0 Name : C-Language Price : 235.649994 Pages : 245 Book-1 Name : Java-Programming Price : 275.799988 Pages : 350	Given bo Book-0 N Book-1 N

Passed all tests! ✓

Question 2

Correct

Marked out of 1.00

Flag question

Write a C program to find out the total and average marks gained by the students in a section using array of structures.

Note: Consider that regdno, marks of 3 subjects, total and average are the members of a structure and make sure to provide the int value for number of students which are less than 60

Sample Input and Output:

```
3
101 56 78 76
201 76 89 91
301 46 57 61
Student-0 Regdno = 101 Total marks = 210 Average marks = 70.000000
Student-1 Regdno = 201 Total marks = 256 Average marks = 85.333336
Student-2 Regdno = 301 Total marks = 164 Average marks = 54.666668
```

For example:

Input	Result
3	Student-0 Regdno = 101 Total marks = 210 Average marks = 70.000000
101 56 78 76	Student-1 Regdno = 201 Total marks = 256 Average marks = 85.333336
201 76 89 91	Student-2 Regdno = 301 Total marks = 164 Average marks = 54.666668
301 46 57 61	

Answer: (penalty regime: 0 %)

Reset answer

```
1 #include <stdio.h>
2
3 struct student
4 {
5     int regdno;
6     int marks[3];
7     int total;
8     float average;
9 };
10
11 int main()
12 {
13     struct student s[60];
14     int i, n;
15     scanf("%d", &n);
16     for (i=0;i<n;i++ )
17     {
18         scanf("%d %d %d %d",&s[i].regdno,&s[i].marks[0],&s[i].marks[1],&s[i].marks[2]);
19         // Read regdno and 3 subjects marks
20
21         s[i].total = s[i].marks[0] + s[i].marks[1] + s[i].marks[2];
22         s[i].average = s[i].total/3.0;
```

	Input	Expected	Got
✓	3	Student-0 Regdno = 101 Total marks = 210 Average marks = 70.000000	Student
	101 56 78 76	Student-1 Regdno = 201 Total marks = 256 Average marks = 85.333336	Student
	201 76 89 91	Student-2 Regdno = 301 Total marks = 164 Average marks = 54.666668	Student
	301 46 57 61		

Passed all tests! ✓