

220901035

Question 1

Correct

Mark 1.00 out of
1.00

Flag
question

Write a program to convert strings to an integer and float and display its type.

Sample Input:

10

10.9

Sample Output:

10,<class 'int'>

10.9,<class 'float'>

For example:

Input	Result
10	10,<class 'int'>
10.9	10.9,<class 'float'>

Answer: (penalty regime: 0 %)

```
1 a=int(input())
2 b=float(input())
3 b=round(b,1)
4 print(a,type(a),sep=', ')
5 print(b,type(b),sep=', ')
6
7
```

	Input	Expected	Got
✓	10 10.9	10,<class 'int'> 10.9,<class 'float'>	10,<class 10.9,<clas
✓	12 12.5	12,<class 'int'> 12.5,<class 'float'>	12,<class 12.5,<clas
✓	89 7.56	89,<class 'int'> 7.56,<class 'float'>	89,<class 7.56,<class
✓	55000 56.2	55000,<class 'int'> 56.2,<class 'float'>	55000,<classe 56.2,<classe
✓	2541 2541.679	2541,<class 'int'> 2541.679,<class 'float'>	2541,<classe 2541.679,<classe

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

220901035

Question 2

Correct

Mark 1.00 out of
1.00

 Flag
question

Ramesh's basic salary is input through the keyboard. His dearness allowance is 40% of his basic salary, and his house rent allowance is 20% of his basic salary. Write a program to calculate his gross salary.

Sample Input:

10000

Sample Output:

16000

For example:

Input	Result
10000	16000

Answer: (penalty regime: 0 %)

```
1 a=int(input())
2 da=0.4*a
3 ra=0.2*a
4 g=a+da+ra
5 print(int(g))
```

	Input	Expected	Got	
✓	10000	16000	16000	✓
✓	20000	32000	32000	✓
✓	28000	44800	44800	✓
✓	5000	8000	8000	✓

Passed all tests! ✓

Correct

220901035

Question 3

Correct

Mark 1.00 out of
1.00

Flag
question

Write a simple python program to find the square root of a given floating point number. The output should be displayed with 3 decimal places.

Sample Input:

8.00

Sample Output:

2.828

For example:

Input	Result
14.00	3.742

Answer: (penalty regime: 0 %)

```
1 a=float(input())
2 b=a**0.5
3 b=round(b,3)
4 print(b)
```

	Input	Expected	Got	
✓	8.00	2.828	2.828	✓
✓	14.00	3.742	3.742	✓
✓	4.00	2.000	2.0	✓
✓	487	22.068	22.068	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

220901035**Question 4**

Correct

Mark 1.00 out of
1.00Flag
question

Alfred buys an old scooter for Rs. X and spends Rs. Y on its repairs. If he sells the scooter for Rs. Z ($Z > X + Y$). Write a program to help Alfred to find his gain percent. Get all the above-mentioned values through the keyboard and find the gain percent.

Input Format:

The first line contains the Rs X

The second line contains Rs Y

The third line contains Rs Z

Sample Input:

10000

250

15000

Sample Output:

46.34 is the gain percent.

For example:

Input	Result
45500 500 60000	30.43 is the gain percent.

Answer: (penalty regime: 0 %)

```
1 a=int(input())
2 b=int(input())
3 c=int(input())
4 d=a+b
5 e=c-d
6 f=(e/d)*100
7 print("%.2f"%f,"is the gain percent.")
```

	Input	Expected	Got
✓	10000 250 15000	46.34 is the gain percent.	46.34 is the gain percent.
✓	45500 500 60000	30.43 is the gain percent.	30.43 is the gain percent.
✓	5000 0 7000	40.00 is the gain percent.	40.00 is the gain percent.
✓	12500 5000 18000	2.86 is the gain percent.	2.86 is the gain percent.

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

220901035

Question 5

Correct

Mark 1.00 out of
1.00

Flag
question

In many jurisdictions, a small deposit is added to drink containers to encourage people to recycle them. In one particular jurisdiction, drink containers holding one liter or less have a \$0.10 deposit and drink containers holding more than one liter have a \$0.25 deposit. Write a program that reads the number of containers of each size(less and more) from the user. Your program should continue by computing and displaying the refund that will be received for returning those containers. Format the output so that it includes a dollar sign and always displays exactly two decimal places.

Sample Input

10

20

Sample Output

Your total refund will be \$6.00.

For example:

Input	Result
20	Your total refund will be \$7.00.
20	

Answer: (penalty regime: 0 %)

```
1 a=float(input())
2 b=float(input())
3 c=a*0.10
4 d=b*0.25
5 e=c+d
6 print("Your total refund will be %.2f." %
```

	Input	Expected	Got
✓	20 20	Your total refund will be \$7.00.	You
✓	11 22	Your total refund will be \$6.60.	You
✓	123 200	Your total refund will be \$62.30.	You
✓	76 38	Your total refund will be \$17.10.	You

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

Justin is a carpenter who works on an hourly basis. He works in a company where he is paid Rs 50 for an hour on weekdays and Rs 80 for an hour on weekends. He works 10 hrs more on weekdays than weekends. If the salary paid for him is given, write a program to find the number of hours he has worked on weekdays and weekends.

Hint:

If the final result(hrs) are in -ve convert that to +ve using `abs()` function

The `abs()` function returns the absolute value of the given number.

```
number = -20
absolute_number = abs(number)
print(absolute_number)
# Output: 20
```

Sample Input:

450

Sample Output:

weekdays 10.38

weekend 0.38

For example:

Input	Result
450	weekdays 10.38
	weekend 0.38

Answer: (penalty regime: 0 %)

```
1 | a=int(input())
2 | b=(a-500)/130
3 | b=abs(b)
4 | c=b+10
5 | print("weekdays %.2f"%c)
6 | print("weekend %.2f"%b)
```

	Input	Expected	Got	
✓	450	weekdays 10.38 weekend 0.38	weekdays 10.38 weekend 0.38	✓
✓	500	weekdays 10.00 weekend 0.00	weekdays 10.00 weekend 0.00	✓
✓	10000	weekdays 83.08 weekend 73.08	weekdays 83.08 weekend 73.08	✓
✓	6789	weekdays 58.38 weekend 48.38	weekdays 58.38 weekend 48.38	✓

Passed all tests! ✓

Question 5
Correct
Mark 1.00 out of 1.00
[Flag question](#)

Pretend that you have just opened a new savings account that earns 4 percent interest per year. The interest that you earn is paid at the end of the year, and is added to the balance of the savings account. Write a program that begins by reading the amount of money deposited into the account from the user. Then your program should compute and display the amount in the savings account after 1, 2, and 3 years. Display each amount so that it is rounded to 2 decimal places. Sample Input: 10000 Sample Output: Balance as of end of Year 1: \$10400.00. Balance as of end of Year 2: \$10816.00. Balance as of end of Year 3: \$11248.64.

For example:

Input	Result
10000	Balance as of end of Year 1: \$10400.00. Balance as of end of Year 2: \$10816.00. Balance as of end of Year 3: \$11248.64.

Answer: (penalty regime: 0 %)

```
1 a=float(input())
2 b=0.04
3 y1=a*(1+b)
4 y2=y1*(1+b)
5 y3=y2*(1+b)
6 print("Balance as of end of Year 1: %.2f."%(y1))
7 print("Balance as of end of Year 2: %.2f."%(y2))
8 print("Balance as of end of Year 3: %.2f."%(y3))
```

	Input	Expected	Got	
✓	10000	Balance as of end of Year 1: \$10400.00. Balance as of end of Year 2: \$10816.00. Balance as of end of Year 3: \$11248.64.	Balance as of end of Year 1: \$10400.00. Balance as of end of Year 2: \$10816.00. Balance as of end of Year 3: \$11248.64.	✓
✓	20000	Balance as of end of Year 1: \$20800.00. Balance as of end of Year 2: \$21632.00. Balance as of end of Year 3: \$22497.28.	Balance as of end of Year 1: \$20800.00. Balance as of end of Year 2: \$21632.00. Balance as of end of Year 3: \$22497.28.	✓

Passed all tests! ✓

Question 1

Correct

Mark 1.00 out of
1.00 Flag
question

In London, every year during Dasara there will be a very grand doll show. People try to invent new dolls of different varieties. The best-sold doll's creator will be awarded with a cash prize. So people broke their heads to create dolls innovatively. Knowing this competition, Mr.Lokpaul tried to create a doll that sings only when an even number is pressed and the number should not be zero and greater than 100.

IF Lokpaul wins print true, otherwise false.

Sample Input

10

Sample Output

True

Explanation:

Since 10 is an even number and a number between 0 and 100, True is printed

For example:

Input	Result
101	False

Answer: (penalty regime: 0 %)

```
1 a=int(input())
2 if(a>0 and a<100):
3     if(a%2==0):
4         print("True")
5     else:
6         print("False")
7 else:
8     print("False")
```

	Input	Expected	Got	
✓	56	True	True	✓
✓	101	False	False	✓
✓	-1	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7

Correct

Mark 10.00 out
of 10.00 Flag
question

An online retailer sells two products: widgets and gizmos. Each widget weighs 75 grams. Each gizmo weighs 112 grams. Write a program that reads the number of widgets and the number of gizmos from the user. Then your program should compute and display the total weight of the parts.

Sample Input:

10

20

Sample Output:

The total weight of all these widgets and gizmos is 2990 grams.

Answer: (penalty regime: 0 %)

```
1 w=int(input())
2 g=int(input())
3 a=w*75
4 b=g*112
5 t=a+b
6 print("The total weight of all these widge
```

	Input	Expected
✓	10 20	The total weight of all these widgets

Passed all tests! ✓

Correct

Marks for this submission: 10.00/10.00.

Question 3

Correct

Mark 1.00 out of
1.00[Flag
question](#)**Note:**

Don't use if-else. Operators alone must be used.

A team from the Rotaract club had planned to conduct a rally to create awareness among the Coimbatore people to donate blood. They conducted the rally successfully. Many of the Coimbatore people realized it and came forward to donate their blood to nearby blood banks. The eligibility criteria for donating blood are people should be above or equal to 18 and his/ her weight should be above 40. There was a huge crowd and staff in the blood bank found it difficult to manage the crowd. So they decided to keep a system and ask the people to enter their age and weight in the system. If a person is eligible he/she will be allowed inside.

Write a program and feed it to the system to find whether a person is eligible or not.

Input Format:

Input consists of two integers that correspond to the age and weight of a person respectively.

Output Format:

Display True(IF ELIGIBLE)

Display False (if not eligible)

Sample Input

19

45

Sample Output

True

For example:

Input	Result
18	False
40	

Answer: (penalty regime: 0 %)

```
1 | a=int(input())
2 | w=int(input())
3 | print(a>=18 and w>40)
```

	Input	Expected	Got	
✓	19 45	True	True	✓
✓	18 40	False	False	✓
✓	18 42	True	True	✓
✓	16 45	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of
1.00 Flag
question

Write a python program that takes a integer between 0 and 15 as input and displays the number of '1' s in its binary form.(Hint:use python bitwise operator.

Sample Input

3

Sample Output:

2

Explanation:

The binary representation of 3 is 011, hence there are 2 ones in it. so the output is 2.

For example:

Input	Result
3	2

Answer: (penalty regime: 0 %)

```
1 |n=int(input())
2 |print(n.bit_count())
```

	Input	Expected	Got	
✓	3	2	2	✓
✓	5	2	2	✓
✓	15	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10

Correct

Mark 1.00 out of
1.00Flag
question

Write a program that returns the last digit of the given number. Last digit is being referred to the least significant digit i.e. the digit in the ones (units) place in the given number.

The last digit should be returned as a positive number.

For example,

if the given number is 197, the last digit is 7

if the given number is -197, the last digit is 7

For example:

Input	Result
197	7
-197	7

Answer: (penalty regime: 0 %)

```
1 | import math
2 | x=int(input())
3 | y=math.fmod(x,10)
4 | print(abs(y))
```

	Input	Expected	Got	
✓	197	7	7.0	✓
✓	-197	7	7.0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

Mr. X's birthday is in next month. This time he is planning to invite N of his friends. He wants to distribute some chocolates to all of his friends after the party. He went to a shop to buy a packet of chocolates. At the chocolate shop, 4 packets are there with different numbers of chocolates. He wants to buy such a packet which contains a number of chocolates, which can be distributed equally among all of his friends. Help Mr. X to buy such a packet.

Input Given:

N No of friends

P1,P2,P3 AND P4 No of chocolates

OUTPUT:

"True" if he can buy that packet and "False" if he can't buy that packet.

SAMPLE INPUT AND OUTPUT:

5

25

12

10

9

OUTPUT

True False True False

For example:

Input	Result
5	True False True True
25	
23	
20	
10	

Answer: (penalty regime: 0 %)

```

1 | n=int(input())
2 | a=int(input())
3 | b=int(input())
4 | c=int(input())
5 | d=int(input())
6 | if(a%n==0):
7 |     print("True",end=" ")
8 | else:
9 |     print("False",end=" ")
10 | if(b%n==0):
11 |     print("True",end=" ")
12 | else:
13 |     print("False",end=" ")
14 | if(c%n==0):
15 |     print("True",end=" ")
16 | else:
17 |     print("False",end=" ")
18 | if(d%n==0):
19 |     print("True",end=" ")
20 | else:
21 |     print("False",end=" ")

```

	Input	Expected	Got
✓	5 25 23 20 10	True False True True	True False True
✓	4 23 24 21 12	False True False True	False True Fals
✓	8 64 8 16 32	True True True True	True True True

Passed all tests! ✓

Correct

Question 2

Correct

Mark 1.00 out of
1.00 Flag
question

The program that you create for this exercise will begin by reading the cost of a meal ordered at a restaurant from the user. Then your program will compute the tax and tip for the meal. Use your local tax rate (5 percent) when computing the amount of tax owing. Compute the tip as 18 percent of the meal amount (without the tax). The output from your program should include the tax amount, the tip amount, and the grand total for the meal including both the tax and the tip. Format the output so that all of the values are displayed using two decimal places.

Sample Input

100

Sample Output

The tax is 5.00 and the tip is 18.00, making the total 123.00

For example:

Input	Result
100	The tax is 5.00 and the tip is 18.00, making

Answer: (penalty regime: 0 %)

```
1 c=float(input())
2 t=0.18*c
3 r=0.05*c
4 g=c+t+r
5 print("The tax is %.2f and the tip is %.2f"
```

	Input	Expected
✓	100	The tax is 5.00 and the tip is 18.00,
✓	250	The tax is 12.50 and the tip is 45.00,

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9

Correct

Mark 1.00 out of
1.00 Flag
question

Mr.Ram has been given a problem kindly help him to solve it. The input of the program is either 0 or 1. IF 0 is the input he should display "C" if 1 is the input it should display "D". There is a constraint that Mr. Ram should use either logical operators or arithmetic operators to solve the problem, not anything else.

Hint:

Use ASCII values of C and D.

Input Format:An integer x, $0 \leq x \leq 1$.**Output Format:**

output a single character 'C' or 'D'depending on the value of x.

Input 1:

0

Output 1:

C

Input 2:

1

Output 1:

D

For example:

Input	Result
0	C

Answer: (penalty regime: 0 %)

```

1 | x=int(input())
2 |
3 | a=chr(ord('C')+x)
4 | print(a)
5 |

```

	Input	Expected	Got	
✓	0	C	C	✓
✓	1	D	D	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 8

Correct

Mark 1.00 out of
1.00 Flag
question

In the 1800s, the battle of Troy was led by Hercules. He was a superstitious person. He believed that his crew can win the battle only if the total count of the weapons in hand is in multiple of 3 and the soldiers are in an even number of count. Given the total number of weapons and the soldier's count, Find whether the battle can be won or not according to Hercules's belief. If the battle can be won print True otherwise print False.

Input format:

Line 1 has the total number of weapons

Line 2 has the total number of Soldiers.

Output Format:

If the battle can be won print True otherwise print False.

Sample Input:

32

43

Sample Output:

False

For example:

Input	Result
32	False
43	

Answer: (penalty regime: 0 %)

```

1 | w=int(input())
2 | s=int(input())
3 | wc=w%3
4 | sc=s%2
5 | if(wc==0 and sc==0):
6 |     print("True")
7 | else:
8 |     print("False") ...

```

	Input	Expected	Got	
✓	32 43	False	False	✓
✓	273 7890	True	True	✓
✓	800 4590	False	False	✓
✓	6789 32996	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 2
Correct
Mark 1.00 out of
1.00
Flag
question

Write a program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths ≥ 65

Marks in Physics ≥ 55

Marks in Chemistry ≥ 50

Or

Total in all three subjects ≥ 180

Sample Test Cases

Test Case 1

Input

70

60

80

Output

The candidate is eligible

Test Case 2

Input

50

80

80

Output

The candidate is eligible

Test Case 3

Input

50

60

40

Output

The candidate is not eligible

For example:

Input	Result
70	The candidate is eligible
60	
80	

Answer: (penalty regime: 0 %)

```
1 m=int(input())
2 p=int(input())
3 c=int(input())
4 t=m+p+c
5 if{m>=65 and p>=55 and c>=50 or t>=180}:
6     print("The candidate is eligible")
7 else:
8     print("The candidate is not eligible")
```

	Input	Expected	Got
✓	70 60 80	The candidate is eligible	The can
✓	50 80 80	The candidate is eligible	The can
✓	50 60 40	The candidate is not eligible	The can
✓	20 10 25	The candidate is not eligible	The can

Question 4
Correct
Mark 1.00 out of
1.00
Flag
question

IN / OUT

Ms. Sita, the faculty handling programming lab for you is very strict. Your seniors have told you that she will not allow you to enter the week's lab if you have not completed at least half the number of problems given last week. Many of you didn't understand this statement and so they requested the good programmers from your batch to write a program to find whether a student will be allowed into a week's lab given the number of problems given last week and the number of problems solved by the student in that week.

Input Format:

Input consists of 2 integers

The first integer corresponds to the number of problems given and the second integer corresponds to the number of problems solved.

Output Format:

Output consists of the string "IN" or "OUT".

Sample Input and Output:

Input

8

3

Output

OUT

For example:

Input	Result
8	OUT
3	

Answer: (penalty regime: 0 %)

```
1 h=int(input())
2 m=int(input())
3 a=n/2
4 if(a>=m):
5     print("IN")
6 else:
7     print("OUT")
```

	Input	Expected	Got	
✓	8 3	OUT	OUT	✓
✓	8 5	IN	IN	✓
✓	20 9	OUT	OUT	✓
✓	50 31	IN	IN	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program that returns the second last digit of the given number. Second last digit is being referred to the digit in the tens place in the given number.

For example, if the given number is 197, the second last digit is 9.

Note1 - The second last digit should be returned as a positive number. i.e. If the given number is -197, the second last digit is 9.

Note2 - If the given number is a single digit number, then the second last digit does not exist. In such cases, the program should return -1. i.e. If the given number is 5, the second last digit should be returned as -1

For example:

Input	Result
197	9
5	-1

Answer: (penalty regime: 0 %)

```
1 m=int(input())
2 m=abs(m)
3 if(m<10):
4     print("-1")
5 else:
6     s=int(str(m)[-2])
7     print(s)
```

	Input	Expected	Got	
✓	197	9	9	✓
✓	-197	9	9	✓
✓	5	-1	-1	✓
✓	123456	5	5	✓
✓	8	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of
1.00 Flag
question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third.

For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$

You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print 'yes', otherwise, print 'no'. Please note that the output message is in small letters.

Sample Input

3

5

4

Sample Output

yes

Sample Test Cases**Test Case 1****Input**

3

5

4

Output

yes

Test Case 2**Input**

5

8

2

Output

no

Answer: (penalty regime: 0 %)

```

1 | a=int(input())
2 | b=int(input())
3 | c=int(input())
4 | a=a**2
5 | b=b**2
6 | c=c**2
7 | if(a+b==c or b+c==a or a+c==b):
8 |     print("yes")
9 | else:
10 |     print("no")

```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

In this exercise you will create a program that reads a letter of the alphabet from the user. If the user enters a, e, i, o or u then your program should display a message indicating that the entered letter is a vowel. If the user enters y then your program should display a message indicating that sometimes y is a vowel, and sometimes y is a consonant. Otherwise your program should display a message indicating that the letter is a consonant.

Sample Input 1

i

Sample Output 1

It's a vowel.

Sample Input 2

y

Sample Output 2

Sometimes it's a vowel... Sometimes it's a consonant.

Sample Input3

c

Sample Output 3

It's a consonant.

For example:

Input	Result
y	Sometimes it's a vowel... Sometimes it's a c
c	It's a consonant.

Answer: (penalty regime: 0 %)

```

1 |x=input()
2 |if x in ['a','e','i','o','u']:
3 |    print("It's a vowel.")
4 |elif(x=='y'):
5 |    print("Sometimes it's a vowel... Somet")
6 |else:
7 |    print("It's a consonant.")
```

	Input	Expected
✓	i	It's a vowel.
✓	y	Sometimes it's a vowel... Sometimes it's a consonant.
✓	c	It's a consonant.
✓	e	It's a vowel.
✓	r	It's a consonant.

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10

Correct
Mark 1.00 out of 1.00

Flag question

Write a program to calculate and print the Electricity bill where the unit consumed by the user is given from test case. It prints the total amount the customer has to pay. The charge are as follows:

Unit	Charge / Unit
Upto 199	@1.20
200 and above but less than 400	@1.50
400 and above but less than 600	@1.80
600 and above	@2.00

If bill exceeds Rs.400 then a surcharge of 15% will be charged and the minimum bill should be of Rs.100/-

Sample Test Cases**Test Case 1**

Input

50

Output

100.00

Test Case 2

Input

300

Output

517.50

For example:

Input	Result
100.00	120.00
500	1035.00

Answer: (penalty regime: 0 %)

```

1 u=float(input())
2 if(u<=199):
3     c=1.20
4 elif(u<400):
5     c=1.50
6 elif(u<600):
7     c=1.80
8 elif(u>600):
9     c=2.00
10 b=u*c
11 if(b>400):
12     s=b*0.15
13     b=b+s
14     print("%.2f"%(b))
15 elif(b<100):
16     print("100.00")
17 else:
18     print("%.2f"%(b))

```

	Input	Expected	Got	
✓	50	100.00	100.00	✓
✓	100.00	120.00	120.00	✓
✓	500	1035.00	1035.00	✓
✓	700	1610.00	1610.00	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 7

Comics

Mark 1.00 out of
1.00 Flag
question

A triangle can be classified based on the lengths of its sides as equilateral, isosceles or scalene. All three sides of an equilateral triangle have the same length. An isosceles triangle has two sides that are the same length, and a third side that is a different length. If all of the sides have different lengths then the triangle is scalene.

Write a program that reads the lengths of the three sides of a triangle from the user. Then display a message that states the triangle's type.

Sample Input 1

60
60
60

Sample Output 1

That's a equilateral triangle

Sample Input 2

40
40
80

Sample Output 2

That's a isosceles triangle

Sample Input 3

50
60
70

Sample Output 3

That's a scalene triangle

For example:

Input	Result
60 60 60	That's a equilateral triangle
40 40 80	That's a isosceles triangle

Answer: (penalty regime: 0 %)

```

1 a=int(input())
2 b=int(input())
3 c=int(input())
4 if(a==b==c):
5     print("That's a equilateral triangle")
6 elif(a==b!=c or a==c!=b or c==b!=a):
7     print("That's a isosceles triangle")
8 else:
9     print("That's a scalene triangle")

```

	Input	Expected	Got
✓	60 60 60	That's a equilateral triangle	That's
✓	40 40 80	That's a isosceles triangle	That's
✓	50 60 70	That's a scalene triangle	That's
✓	50 50 60	That's a isosceles triangle	That's
✓	10 10 10	That's a equilateral triangle	That's

Passed all tests! ✓

Question 8

Incorrect

Mark 0.00 out of
1.00 Flag
question

Most years have 365 days. However, the time required for the Earth to orbit the Sun is actually slightly more than that. As a result, an extra day, February 29, is included in some years to correct for this difference. Such years are referred to as leap years. The rules for determining whether or not a year is a leap year follow:

- Any year that is divisible by 400 is a leap year.
- Of the remaining years, any year that is divisible by 100 is not a leap year.
- Of the remaining years, any year that is divisible by 4 is a leap year.
- All other years are not leap years.

Write a program that reads a year from the user and displays a message indicating whether or not it is a leap year.

Sample Input 1

1900

Sample Output 1

1900 is not a leap year.

Sample Input 2

2000

Sample Output 2

2000 is a leap year.

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 a=n%400
3 b=n%4
4 c=n%100
5 if(a==0):
6     print(n,"is a leap year.")
7 elif(c==0):
8     print(n,"is not a leap year.")
9 elif(b==0):
10    print(n,"is a leap year")
11 else:
12    print(n,"is not a leap year.")
```

	Input	Expected	Got
✓	1900	1900 is not a leap year.	1900 is not
✓	2000	2000 is a leap year.	2000 is a le
✓	2100	2100 is not a leap year.	2100 is not
✗	2020	2020 is a leap year.	2020 is a le

Your code must pass all tests to earn any marks. Try again.

Show differences**Incorrect**

Marks for this submission: 0.00/1.00.

Question 9

Correct

Mark 1.00 out of
1.00 Flag
question

The Chinese zodiac assigns animals to years in a 12 year cycle. One 12 year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the dragon, and 1999 being another year of the hare.

Year Animal

2000 Dragon

2001 Snake

2002 Horse

2003 Sheep

2004 Monkey

2005 Rooster

2006 Dog

2007 Pig

2008 Rat

2009 Ox

2010 Tiger

2011 Hare

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

Sample Input 1

2010

Sample Output 1

2010 is the year of the Tiger.

Sample Input 2

2020

Sample Output 2

2020 is the year of the Rat.

Answer: (penalty regime: 0 %)

```
1 | y=int(input())
2 | a=['Dragon','Snake','horse','sheep','Monke
3 | i=(y-2000)%12
4 | print(y,"is the year of the",a[i],end=".")
```

	Input	Expected	Got
✓	2010	2010 is the year of the Tiger.	2010 i
✓	2020	2020 is the year of the Rat.	2020 i

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 1
Correct
Mark 1.00 out
of 1.00
Flag question

The length of a month varies from 28 to 31 days. In this exercise you will create a program that reads the name of a month from the user as a string. Then your program should display the number of days in that month. Display "28 or 29 days" for February so that leap years are addressed.

Sample Input 1
February
Sample Output 1
February has 28 or 29 days in it.
Sample Input 2
March
Sample Output 2
March has 31 days in it.
Sample Input 3
April
Sample Output 3
April has 30 days in it.

For example:

Input	Result
February	February has 28 or 29 days in it.

Answer: (penalty regime: 0 %)

```
1 a=['January','March','May','June','August','October','December']  
2 b=['April','May','July','September','November']  
3 m=input()  
4 if m in a:  
5     print(m,"has 31 days in it.")  
6 elif m in b:  
7     print(m,"has 30 days in it.")  
8 elif m=='February':  
9     print(m,"has 28 or 29 days in it.")
```

	Input	Expected	Got
✓	February	February has 28 or 29 days in it.	✓
✓	March	March has 31 days in it.	✓
✓	April	April has 30 days in it.	✓
✓	May	May has 31 days in it.	✓

Passed all tests! ✓

Question 1

Correct

Mark 1.00 out of
1.00 Flag
question

Given a positive integer N, check whether it can be represented as a product of single digit numbers.

Input Format:

Single Integer input.

Output Format:

Output displays Yes if condition satisfies else prints No.

Example Input:

14

Output:

Yes

Example Input:

13

Output:

No

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 if(n < 10):
3     print("Yes")
4 else:
5     x=False
6     for i in range(2, 10):
7         y=n%i
8         z=n//i
9         if y==0 and z<10:
10            x=True
11            break
12 if x==True:
13     print("Yes")
14 else:
15     print("No")
16
```

	Input	Expected	Got	
✓	14	Yes	Yes	✓
✓	13	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

A Number is said to be Disarium number when the sum of its digit raised to the power of their respective positions becomes equal to the number itself. Write a program to print number is Disarium or not.

Input Format:

Single Integer Input from stdin.

Output Format:

Yes or No.

Example Input:

175

Output:

Yes

Explanation

$$1^1 + 7^2 + 5^3 = 175$$

Example Input:

123

Output:

No

For example:

Input	Result
175	Yes
123	No

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 s=str(n)
3 l=len(s)
4 tot=0
5 for i in range(l):
6     tot=tot+int(s[i])**(i+1)
7 if(n==tot):
8     print("Yes")
9 else:
10    print("No")
11

```

	Input	Expected	Got	
✓	175	Yes	Yes	✓
✓	123	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

In mathematics, the factorial of a non-negative integer n , denoted by $n!$, is the product of all positive integers less than or equal to n . For example,

$$5! = 5 \times 4 \times 3 \times 2 \times 1 = 120$$

$$4! = 4 \times 3 \times 2 \times 1 = 24$$

$$9! = 9 \times 8 \times 7 \times 6 \times 5 \times 4 \times 3 \times 2 \times 1 = 362880$$

Write a program to find the factorial of a given number.

The given number will be passed to the program as an input of type int.

The program is expected to calculate the factorial of the given number and return it as an int type.

Assumptions for this program:

The given input number will always be greater than or equal to 1.

Due to the range supported by int, the input numbers will range from 1 to 12.

For example:

Input	Result
5	120
4	24
9	362880

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 s=1
3 for i in range(1,n+1):
4     s=s*i
5 print(s)

```

	Input	Expected	Got	
✓	5	120	120	✓
✓	4	24	24	✓
✓	9	362880	362880	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program to return the nth number in the fibonacci series.

The value of N will be passed to the program as input.

NOTE: Fibonacci series looks like –

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . and so on.

i.e. Fibonacci series starts with 0 and 1, and continues generating the next number as the sum of the previous two numbers.

- first Fibonacci number is 0,
- second Fibonacci number is 1,
- third Fibonacci number is 1,
- fourth Fibonacci number is 2,
- fifth Fibonacci number is 3,
- sixth Fibonacci number is 5,
- seventh Fibonacci number is 8, and so on.

For example:

Input	Result
1	0
4	2
7	8

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 a=0
3 b=1
4 for i in range(n-1):
5     s=a+b
6     a=b
7     b=s
8     i=i+1
9 print(a)
```

	Input	Expected	Got	
✓	1	0	0	✓
✓	4	2	2	✓
✓	7	8	8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program to find the count of unique digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

For e.g.

If the given number is 292, the program should return 2 because there are only 2 unique digits '2' and '9' in this number

If the given number is 1015, the program should return 3 because there are 3 unique digits in this number, '1', '0', and '5'.

For example:

Input	Result
292	2
1015	3

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 u=[]
3 s=str(n)
4 for i in s:
5     d=int(i)
6     if d not in u:
7         u.append(d)
8 print(len(u))

```

	Input	Expected	Got	
✓	292	2	2	✓
✓	1015	3	3	✓
✓	123	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8

Question 5

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program to find the sum of the series $1 + 11 + 111 + \dots + n$ terms (n will be given as input from the user and sum will be the output)

Sample Test Cases**Test Case 1****Input**

4

Output

1234

Test Case 2**Input**

6

Output

123456

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 s=0
3 t=1
4 for i in range(n):
5     s+=t
6     t=t*10+1
7 print(s)
```

	Input	Expected	Got	
✓	4	1234	1234	✓
✓	6	123456	123456	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program that finds whether the given number N is Prime or not.

If the number is prime, the program should return 2 else it must return 1.

Assumption: $2 \leq N \leq 5000$, where N is the given number.

Example1: if the given number N is 7, the method must return 2

Example2: if the given number N is 10, the method must return 1

For example:

Input	Result
7	2
10	1

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 a=n//2
3 flag=0
4 if(n<=1):
5     print("1")
6 else:
7     for i in range(2,a+1):
8         if(n%i==0):
9             flag=1
10            break
11     if(flag==0):
12         print("2")
13     else:
14         print("1")
15

```

	Input	Expected	Got	
✓	7	2	2	✓
✓	10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8

Correct

Mark 1.00 out of
1.00 Flag
question

Given a number N, find the next perfect square greater than N.

Input Format:Integer input from `stdin`.**Output Format:**

Perfect square greater than N.

Example Input:

10

Output:

16

Answer: (penalty regime: 0 %)

```
1 import math
2 n=int(input())
3 num=math.ceil(math.sqrt(n))
4 while (1):
5     N=num**2
6     if(n<N):
7         print(N)
8         break
9     else:
10        num+=1
```

	Input	Expected	Got	
✓	10	16	16	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10

Correct

Mark 1.00 out of
1.00 Flag
question

Given an Integer N, check whether N the given number can be made a perfect square after adding to it.

Input Format:

Single integer input.

Output Format:

Yes or No.

Example Input:

24

Output:

Yes

Example Input:

26

Output:

No

For example:

Input	Result
24	Yes

Answer: (penalty regime: 0 %)

```
1 import math
2 n=int(input())
3 x=math.sqrt(n)
4
5 for i in range(1,n+1):
6     a=i*i
7     if(a-1==n):
8         print("Yes")
9         break
10    elif(a-1>=n):
11        print("No")
12        break
13    i+=i
14
15
```

	Input	Expected	Got	
✓	24	Yes	Yes	✓
✓	26	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program to find the count of non-repeated digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

Some examples are as below.

If the given number is 292, the program should return 1 because there is only 1 non-repeated digit '9' in this number.

If the given number is 1015, the program should return 2 because there are 2 non-repeated digits in this number, '0', and '5'.

If the given number is 108, the program should return 3 because there are 3 non-repeated digits in this number, '1', '0', and '8'.

If the given number is 22, the function should return 0 because there are NO non-repeated digits in this number.

For example:

Input	Result
292	1
1015	2
108	3
22	0

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 c=0
3 a=[0]*10
4 while n>0:
5     rem=n%10
6     a[rem]=a[rem]+1
7     n=n//10
8 for i in a:
9     if(i==1):
10         c=c+1
11 print(c)
12
13
14

```

	Input	Expected	Got	
✓	292	1	1	✓
✓	1015	2	2	✓
✓	108	3	3	✓
✓	22	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program to check if two strings are balanced. For example, strings s1 and s2 are balanced if all the characters in the s1 are present in s2. The character's position doesn't matter. If balanced display as "true", otherwise "false".

For example:

Input	Result
Yn	True
PYnative	

Answer: (penalty regime: 0 %)

```
1 a=input()
2 b=input()
3 c=len(a)
4 s=0
5 for i in a:
6     if i in b:
7         s+=1
8 if(c==s):
9     print("True")
10 else:
11     print("False")
```

	Input	Expected	Got	
✓	Yn PYnative	True	True	✓
✓	Ynf PYnative	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 1

Correct

Mark 1.00 out of
1.00Flag
question

Write a python program to count all letters, digits, and special symbols respectively from a given string

For example:

Input	Result
rec@123	3
	3
	1

Answer: (penalty regime: 0 %)

```
1 a=input()
2 l=0
3 d=0
4 s=0
5 for i in a:
6     if i.isalpha():
7         l+=1
8     elif i.isdigit():
9         d+=1
10    else:
11        s+=1
12 print(l)
13 print(d)
14 print(s)
```

	Input	Expected	Got	
✓	rec@123	3 3 1	3 3 1	✓
✓	P@#yn26at^&i5ve	8 3 4	8 3 4	✓
✓	abc@12&	3 2 2	3 2 2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

Given a string S which is of the format

USERNAME@DOMAIN.EXTENSION, the program must print
the EXTENSION, DOMAIN, USERNAME in the reverse order.**Input Format:**

The first line contains S.

Output Format:

The first line contains EXTENSION.

The second line contains DOMAIN.

The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

Example Input/Output 1:**Input:**

abcd@gmail.com

Output:

com

gmail

abcd

Answer: (penalty regime: 0 %)

```
1 s=input()
2 at=s.find('@')
3 dot=s.find('.')
4 u=s[:at]
5 d=s[at+1:dot]
6 e=s[dot+1:]
7 print(e)
8 print(d)
9 print(u)
10
11
```

	Input	Expected	Got	
✓	abcd@gmail.com	com gmail abcd	com gmail abcd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10

Correct

Mark 1.00 out of
1.00 Flag
question

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

Input Format:

The first line contains S1.

The second line contains S2.

The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$

$2 \leq \text{Length of } S1, S2 \leq 1000$

Example Input/Output 1:

Input:

abcbde
cdefghbb
3

Output:

bcd

Note:

b occurs twice in common but must be printed only once.

Answer: (penalty regime: 0 %)

```
1 a=input()
2 b=input()
3 n=int(input())
4 c=set()
5 for i in a:
6     if(i in b and i not in c):
7         print(i,end='')
8         c.add(i)
9     if(len(c)==n):
10        break
11 print()
```

	Input	Expected	Got	
✓	abcbde cdefghbb 3	bcd	bcd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

In this exercise, you will create a program that reads words from the user until the user enters a blank line. After the user enters a blank line your program should display each word entered by the user exactly once. The words should be displayed in the same order that they were first entered. For example, if the user enters:

first

second

first

third

second

then your program should display:

first

second

third

Answer: (penalty regime: 0 %)

```
1 a = []
2
3 try:
4     while True:
5         w = input()
6         if w == "":
7             break
8         if w not in a:
9             a.append(w)
10    except EOFError:
11        pass
12
13 for w in a:
14     print(w)
15
```

	Input	Expected	Got	
✓	first second first third second	first second third	first second third	✓
✓	rec cse it rec cse	rec cse it	rec cse it	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of
1.00 Flag
question**Reverse a string without affecting special characters**

Given a string **S**, containing special characters and all the alphabets, reverse the string without affecting the positions of the special characters.

Input:

A&B

Output:

B&A

Explanation: As we ignore '&' and

As we ignore '&' and then reverse, so answer is "B&A".

For example:

Input	Result
A&x#	x&A#

Answer: (penalty regime: 0 %)

```
1 a=input()
2 rev_s=''
3 s=''
4 c=''
5 for i in a:
6     if i.isalpha():
7         s+=i
8     else:
9         c+=i
10    rev=s[::-1]
11    s_i=0
12    c_i=0
13    for i in a:
14        if i.isalpha():
15            rev_s+=rev[s_i]
16            s_i+=1
17        else:
18            rev_s+=c[c_i]
19            c_i+=1
20 print(rev_s)
```

	Input	Expected	Got	
✓	A&B	B&A	B&A	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9

Correct

Mark 1.00 out of
1.00 Flag
question

String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

Answer: (penalty regime: 0 %)

```
1 x=input()
2 y=x.lower()
3 z=y.split()
4 a=[]
5 for i in z:
6     a.append(i)
7     b=i[::-1]
8     if(i==b):
9         a.remove(i)
10    c=" ".join(a)
11    print(c)
```

	Input	Expected
✓	Malayalam is my mother tongue	is my mother

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7**Correct**Mark 1.00 out of
1.00 Flag
question

Assume that the given string has enough memory.

Don't use any extra space(IN-PLACE)

Sample Input 1

a2b4c6

Sample Output 1

aabbbbcccccc

Answer: (penalty regime: 0 %)

```
1 s=input()
2 e_s=""
3 i=0
4 count=0
5 while(i<len(s)):
6     char=s[i]
7     c_s=""
8     i+=1
9     while(i<len(s) and s[i].isdigit()):
10        c_s+=s[i]
11        i+=1
12    count=int(c_s)
13    e_s+=char*count
14 print(e_s)
```

	Input	Expected	Got
✓	a2b4c6	aabbbbcccccc	aabbbbcccccc
✓	a12b3d4	aaaaaaaaaaaabbddddd	aaaaaaaaaaaabb

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of
1.00 Flag
question

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

Sample Input 1experience
enc**Sample Output 1**

xpri

Answer: (penalty regime: 0 %)

```
1 a=input()
2 b=input()
3 s=""
4 for i in a:
5     if i not in b:
6         s+=i
7 print(s)
```

	Input	Expected	Got	
✓	experience enc	xpri	xpri	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8

Correct

Mark 1.00 out of
1.00 Flag
question

Write a program that takes as input a string (sentence), and returns its second word in uppercase.

For example:

If input is "Wipro Technologies Bangalore" the function should return "TECHNOLOGIES"

If input is "Hello World" the function should return "WORLD"

If input is "Hello" the program should return "LESS".

NOTE 1: If input is a sentence with less than 2 words, the program should return the word "LESS".

NOTE 2: The result should have no leading or trailing spaces.

For example:

Input	Result
Wipro Technologies Bangalore	TECHNOLOGIES
Hello World	WORLD
Hello	LESS

Answer: (penalty regime: 0 %)

```

1 a=input()
2 w=a.split()
3 if len(w)>=2:
4     s=w[1].upper()
5     print(s)
6 else:
7     print("LESS")

```

	Input	Expected
✓	Wipro Technologies Bangalore	TECHNOLOGIES
✓	Hello World	WORLD
✓	Hello	LESS

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Write a program to print all the locations at which a particular element (taken as input) is found in a list and also print the total number of times it occurs in the list. The location starts from 1.

For example, if there are 4 elements in the array:

5
6
5
7

If the element to search is 5 then the output will be:

5 is present at location 1.
5 is present at location 3.
5 is present 2 times in the array.

Sample Test Cases

Test Case 1

Input

4
5
6
5
7
5

Output

5 is present at location 1.
5 is present at location 3.
5 is present 2 times in the array.

Test Case 2

Input

5
67
80
45
97
100
50

Output

50 is not present in the array.

Answers: (penalty regime: 0%)

```
1 print(input())
2 l=[int(input()) for i in range(n)]
3 c=int(input())
4 b=1
5 for i in range(len(l)):
6     if l[i]==c:
7         b+=end(i+1)
8 if len(b)==0:
9     for i in b:
10         print("{} is present at location {}".format(i,i))
11     print("{} is present {} times in the array.".format(c,len(b)))
12 else:
13     print("{} is not present in the array.".format(c))
```

	Input	Expected	Got	
✓	5 6 5 7 5	5 is present at location 1. 5 is present at location 3. 5 is present 2 times in the array.	5 is present at location 1. 5 is present at location 3. 5 is present 2 times in the array.	✓
✓	50 67 80 45 97 100 50	50 is not present in the array.	50 is not present in the array.	✓

Passed all tests! ✓

Comments

Score for this submission: 100/100

Question 5
Correct
Mark 1.00 out of
1.00
1st flag
question

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1

2

3

4

Output:

1 2 3 4

Example Input:

6

1

1

2

2

3

3

Output:

1 2 3

For example:

Input	Result
5	1 2 3 4
1	
2	
2	
3	
4	
6	1 2 3
1	
1	
2	
2	
3	
3	

Answer: (penalty regime: 0 %)

```
1 |n=int(input())
2 |a = []
3 |for i in range(n):
4 |    a.append(int(input()))
5 |d = []
6 |    for s in a:
7 |        if s not in d:
8 |            d.append(s)
9 |print(*d)
```

	Input	Expected	Got	
✓	5 1 2 2 3 4	1 2 3 4	1 2 3 4	✓
✓	6 1 1 2 2 3 3	1 2 3	1 2 3	✓

Passed all tests! ✓

Correct

Mark for this submission: 1.00/1.00

Question 7

Correct
Mark 1.00 out of
1.00

[Flag question](#)

Consider a program to insert an element / item in the sorted array. Complete the logic by filling up required code in editable section. Consider an array of size 10. The eleventh item is the data to be inserted.

Sample Test Cases**Test Case 1****Input**

```
1
3
4
5
6
7
8
9
10
11
2
```

Output

ITEM to be inserted 2.
After insertion array is:

```
1
2
3
4
5
6
7
8
9
10
11
```

Test Case 2**Input**

```
11
22
33
55
66
77
88
99
110
120
44
```

Output

ITEM to be inserted 44.
After insertion array is:

```
11
22
33
44
55
66
77
88
99
110
120
```

Answer: (penalty regime 0 %)

```
1 |a=int(input()) for i in range(0,11):
2 |    b=a[10]
3 |    a.sort()
4 |    print("ITEM to be inserted: ",format(b))
5 |    print("After insertion array is:")
6 |    print(a,sep=' ')
```

	Input	Expected	Got
✓	1 3 4 5 6 7 8 9 10 11 2	ITEM to be inserted 2. After insertion array is: 1 2 3 4 5 6 7 8 9 10 11	ITEM to be inserted After insertion array is: 1 2 3 4 5 6 7 8 9 10 11
✓	11 22 33 55 66 77 88 99 110 120 44	ITEM to be inserted 44. After insertion array is: 11 22 33 44 55 66 77 88 99 110 120	ITEM to be inserted After insertion array is: 11 22 33 44 55 66 77 88 99 110 120

Passed all tests! ✓

[Close](#)

Marks for this submission: 1.00/1.00

Question 2

Correct

Mark 1.00 out of

1.00

 Flag question

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- The sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, $\text{arr}[3]=6$ is the pivot between the two subarrays.
- The index of the pivot is 3.

Constraints

- $3 \leq n \leq 10^3$
- $1 \leq \text{arr}[i] \leq 2 \times 10^4$, where $0 \leq i < n$.
- It is guaranteed that a solution always exists.

The first line contains an integer n , the size of the array arr.Each of the next n lines contains an integer, $\text{arr}[i]$, where $0 \leq i < n$.**Sample Case 0****Sample Input 0**

```
4
1
2
3
3
```

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, $\text{arr}[2]=3$ is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1**Sample Input 1**

```
3
1
2
1
```

Sample Output 1

1

Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, $\text{arr}[1]=1$ is the pivot between the two subarrays.
- The index of the pivot is 1.

For example:

Input	Result
4	2
1	
2	
3	
3	1
1	
2	
1	

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2 l=[int(input()) for i in range(n)]
3 for i in range(n):
4     a=l[0:i]
5     b=l[i+1:]
6     if(sum(a)==sum(b)):
7         print(i)
```

Input	Expected	Got
✓ 4	2	2 ✓
1		
2		
3		
3		
✓ 3	1	1 ✓
1		
2		
1		

Passed all tests! ✓

 Submit

Marks for this submission: 1.00/1.00

Question 8

Correct

Mark 1.00 out of
1.00[Flag question](#)

Given an array A of sorted integers and another non-negative integer k, find if there exists 2 indices i and j such that $A[i] + A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain

2. N, followed by N integers of the array

3. The non-negative integer k.

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Example**Input**

1

3

1

3

5

4

Output:

1

Input

1

3

1

3

5

99

Output

0

For example:

Input	Result
1	1
3	
1	
3	
5	
4	
1	0
3	
1	
3	
5	
99	

Answer: (penalty regime: 0 %)

```

1 t=int(input())
2 for k in range(t):
3     n=int(input())
4     l=[int(input()) for y in range(n)]
5     k=int(input())
6     y=0
7     for i in range(n):
8         for j in range(n):
9             if((l[i]-l[j])==k):
10                 y+=1
11                 break
12     print(y)

```

	Input	Expected	Got	
✓	1 3 1 3 5 4	1	1	✓
✓	1 3 1 3 5 99	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 10

Correct

Mark 1.00 out of
1.00[Flag
question](#)

Write a Python program to check if a given list is strictly increasing or not. Moreover, If removing only one element from the list results in a strictly increasing list, we still consider the list true

Input:

n : Number of elements

List1: List of values

Output

Print "True" if list is strictly increasing or decreasing else print "False"

Sample Test Case

Input

7
1
2
3
0
4
5
6

Output

True

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 l=[int(input()) for i in range(0,n)]
3 s=True
4 for i in range(n-1):
5     if(l[i]>l[i+1]):
6         s=False
7         break
8 if s:
9     print("False")
10 else:
11     print("True")

```

	Input	Expected	Got	
✓	7 1 2 3 0 4 5 6	True	True	✓
✓	4 2 1 0 -1	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of
1.00Flag
question

Write a Python program to Zip two given lists of lists.

Input:

m : row size

n: column size

list1 and list2 : Two lists

Output

Zipped List : List which combined both list1 and list2

Sample test case

Sample input

2

2

1

3

5

7

2

4

6

8

Sample Output

[[1, 3, 2, 4], [5, 7, 6, 8]]

Answer: (penalty regime: 0 %)

```
1 m=int(input())
2 n=int(input())
3 l1=[]
4 for i in range(0,2*(m+n)):
5     l1.append(int(input()))
6 a=l1[:m]
7 b=l1[m:2*n]
8 c=l1[2*n:3*n]
9 d=l1[3*n:]
10 x=a+c
11 y=b+d
12 z=[x,y]
13 print(z)
```

	Input	Expected	Got
✓	2 2 1 2 3 4 5 6 7 8	[[1, 3, 2, 4], [5, 7, 6, 8]]	[[1, 2,

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct
Mark 1.00 out of
1.00
1st Flag
question

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the `list`, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are (1, 2, 4, 5, 10, 20). Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Constraints

$1 \leq n \leq 10^{15}$

$1 \leq p \leq 10^9$

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

Sample Case 0**Sample Input 0**

10

3

Sample Output 0

5

Explanation 0

Factoring $n = 10$ results in (1, 2, 5, 10). Return the $p = 3^{\text{rd}}$ factor, 5, as the answer.

Sample Case 1**Sample Input 1**

10

5

Sample Output 1

0

Explanation 1

Factoring $n = 10$ results in (1, 2, 5, 10). There are only 4 factors and $p = 5$, therefore 0 is returned as the answer.

Sample Case 2**Sample Input 2**

1

1

Sample Output 2

1

Explanation 2

Factoring $n = 1$ results in (1). The $p = 1^{\text{st}}$ factor of 1 is returned as the answer.

For example:

Input	Result
10	5
3	
10	0
5	
1	1
1	

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 p=int(input())
3 a=[]
4 for i in range(1,n+1):
5     if(n%==0):
6         a.append(i)
7 if(len(a)>=p):
8     print(a[p-1])
9 else:
10    print(0)

```

Passed all tests! ✓

Correct

Mark for this submission: 1.00/1.00

Question 6

Correct

Mark 1.00 out of
1.00 Flag
question

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

Sample Test Cases**Test Case 1****Input**

7
23
45
23
56
45
23
40

Output

23 occurs 3 times
45 occurs 2 times
56 occurs 1 times
40 occurs 1 times

Answer: (penalty regime: 0 %)

```
1 a=int(input())
2 d=[]
3 for i in range(a):
4     d.append(int(input()))
5 f={}
6 for i in d:
7     if i in f:
8         f[i]+=1
9     else:
10        f[i]=1
11 for i,count in f.items():
12     print(f"{i} occurs {count} times")
```

	Input	Expected	Got
✓	7	23 occurs 3 times	23 occurs 3 times
	23	45 occurs 2 times	45 occurs 2 times
	45	56 occurs 1 times	56 occurs 1 times
	23	40 occurs 1 times	40 occurs 1 times
	56		
	45		
	23		
	40		

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9
Correct
Mark 1.00 out of
1.00
Flag
question

Output is a merged array without duplicates.

Input Format

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

Output Format

Display the merged array

Sample Input 1

5
1
2
3
6
9
4
2
4
5
10

Sample Output 1

1 2 3 4 5 6 9 10

Answer: {penalty regime: 0 %}

```
1 n=int(input())
2 a=[int(input()) for i in range(n)]
3 n1=int(input())
4 b=[int(input()) for i in range(n1)]
5 c=set(a-b)
6 d=sorted(c)
7 print(*d)
```

	Input	Expected	Got
✓	5 1 2 3 6 9 4 2 4 5 10	1 2 3 4 5 6 9 10	1 2
✓	7 4 7 8 10 12 30 35 9 1 3 4 5 7 8 11 13 22	1 3 4 5 7 8 10 11 12 13 22 30 35	1 3

Passed all tests! ✓

Control

Marks for this submission: 1.00/1.00

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1
Faculty Upskilling in Python Programming ak	2

Answer: (penalty regime: 0 %)

```

1 a=input("").lower()
2 b=input("").lower()
3 w=a.split()
4 c=0
5 for i in w:
6     if any(j in b for j in i):
7         continue
8     c += 1
9 print(c)
10

```

	Input	Expected
✓	hello world ad	1
✓	Welcome to REC e	1
✓	Faculty Upskilling in Python Programming ak	2

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 1**Correct**Mark 1.00 out of
1.00 Flag
question

Coders here is a simple task for you. Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:**Input:** str = "01010101010"**Output:** Yes**Input:** str = "REC101"**Output:** No**For example:**

Input	Result
01010101010	Yes
010101 10101	No

Answer: (penalty regime: 0 %)

```
1 n=input()
2 l=[]
3 for i in n:
4     if(i=="0" or i=="1"):
5         l.append(i)
6 if(len(l)==len(n)):
7     print("Yes")
8 else:
9     print("No")
```

	Input	Expected	Got	
✓	01010101010	Yes	Yes	✓
✓	REC123	No	No	✓
✓	010101 10101	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of
1.00 Flag
question

The DNA sequence is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

- For example, "ACGAATTCCG" is a DNA sequence.

When studying DNA, it is useful to identify repeated sequences within the DNA.

Given a string *s* that represents a DNA sequence, return all the 10-letter-long sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in any order.

Example 1:

Input: *s* = "AAAAACCCCCAAAAACCCCCAAAAAGGGTTT"
Output: ["AAAAACCCCC", "CCCCCAAAAA"]

Example 2:

Input: *s* = "AAAAAAAAAAAAAA"
Output: ["AAAAAAAAAA"]

For example:

Input	Result
AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA

Answer: (penalty regime: 0 %)

```

1 s=input().strip()
2 a={}
3 for i in range(len(s) - 9):
4     b=s[i:i+10]
5     if b in a:
6         a[b]+=1
7     else:
8         a[b]=1
9 r=[]
10 for b, c in a.items():
11     if c>1:
12         r.append(b)
13 for b in r:
14     print(b)
15

```

	Input	Expected	Got
✓	AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA	AAAA CCCCAAAAA
✓	AAAAAAAAAAAAAA	AAAAAAAAAA	AAAA

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of
1.00Flag
question

Given a tuple and a positive integer k , the task is to find the count of distinct pairs in the tuple whose sum is equal to K .

Examples:Input: $t = (5, 6, 5, 7, 7, 8)$, $K = 13$

Output: 2

Explanation:Pairs with sum $K(= 13)$ are $\{(5, 8), (6, 7), (6, 7)\}$.Therefore, distinct pairs with sum $K(= 13)$ are $\{(5, 8), (6, 7)\}$.

Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0

Answer: (penalty regime: 0 %)

```

1 | t = tuple(map(int, input().split(',')))
2 | k = int(input())
3 | freq = {}
4 | for n in t:
5 |     freq[n] = freq.get(n,0)+1
6 | c=0
7 | for n in set(t):
8 |     b=k-n
9 |     if b in freq and (b!=n or freq[n]>1):
10 |         c+=1
11 | r=c//2
12 | print(r)
13 |

```

	Input	Expected	Got	
✓	5,6,5,7,7,8 13	2	2	✓
✓	1,2,1,2,5 3	1	1	✓
✓	1,2 0	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out
of 1.00

Flag question

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

Sample Input:

```
5 4
1 2 8 6 5
2 6 8 10
```

Sample Output:

```
1 5 10
3
```

Sample Input:

```
5 5
1 2 3 4 5
1 2 3 4 5
```

Sample Output:

NO SUCH ELEMENTS

For example:

Input	Result
5 4	1 5 10
1 2 8 6 5	3
2 6 8 10	

Answer: (penalty regime: 0 %)

```
1 s1,s2 = map(int,input().split())
2 a1=list(map(int,input().split()))
3 a2=list(map(int,input().split()))
4 nr=[x for x in a1 if x not in a2]+[x for x in a2 if x not in a1]
5 if nr:
6     nr=sorted(set(nr))
7     print(*nr)
8     print(len(nr))
9 else:
10    print("NO SUCH ELEMENTS")
```

	Input	Expected	Got	
✓	5 4 1 2 8 6 5 2 6 8 10	1 5 10 3 3	1 5 10 3 3	✓
✓	3 3 10 10 10 10 11 12	11 12 2 2	11 12 2 2	✓

Passed all tests! ✓



Marks for this submission: 1.00/1.00.

Question 1
Correct
Mark 1.00 out
of 1.00
Flag
question

In the game of Scrabble™, each letter has points associated with it. The total score of a word is the sum of the scores of its letters. More common letters are worth fewer points while less common letters are worth more points. The points associated with each letter are shown below:

- Points Letters
1 A, E, I, L, N, O, R, S, T and U
2 D and G
3 B, C, M and P
4 F, H, V, W and Y
5 K
8 J and X
10 Q and Z

Write a program that computes and displays the Scrabble™ score for a word. Create a dictionary that maps from letters to point values. Then use the dictionary to compute the score.

A Scrabble™ board includes some squares that multiply the value of a letter or the value of an entire word. We will ignore these squares in this exercise.

Sample Input

REC

Sample Output

REC is worth 5 points.

For example:

Input	Result
REC	REC is worth 5 points.

Answer: (penalty regime: 0 %)

```
1+ p={  
2     'A': 1, 'E': 1, 'I': 1, 'L': 1, 'N': 1, 'O': 1, 'R': 1, 'S': 1, 'T': 1, 'U': 1,  
3     'D': 2, 'G': 2,  
4     'B': 3, 'C': 3, 'M': 3, 'P': 3,  
5     'F': 4, 'H': 4, 'V': 4, 'W': 4, 'Y': 4,  
6     'K': 5,  
7     'J': 8, 'X': 8,  
8     'Q': 10, 'Z': 10  
9 }  
10 w=input()  
11 w=w.upper()  
12 s=0  
13 for i in w:  
14     s+=p.get(i, 0)  
15 print(f'{w} is worth {s} points.')  
16 print(w, 'is worth', s, 'points.')  
17 |
```

	Input	Expected	Got	
✓	GOD	GOD is worth 5 points.	GOD is worth 5 points.	✓
✓	REC	REC is worth 5 points.	REC is worth 5 points.	✓

Passed all tests! ✓

Correct
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out
of 1.00
Flag question

A sentence is a string of single-space separated words where each word consists only of lowercase letters. A word is uncommon if it appears exactly once in one of the sentences, and does not appear in the other sentence.

Given two sentences s1 and s2, return a list of all the uncommon words. You may return the answer in any order.

Example 1:

Input: s1 = "this apple is sweet", s2 = "this apple is sour"

Output: ["sweet", "sour"]

Example 2:

Input: s1 = "apple apple", s2 = "banana"

Output: ["banana"]

Constraints:

$1 \leq s1.length, s2.length \leq 200$

s1 and s2 consist of lowercase English letters and spaces.

s1 and s2 do not have leading or trailing spaces.

All the words in s1 and s2 are separated by a single space.

Note:

Use dictionary to solve the problem

For example:

Input	Result
this apple is sweet	sweet sour
this apple is sour	

Answer: (penalty regime: 0 %)

```
1 s1 =input()
2 s2 =input()
3 w= s1.split() + s2.split()
4 c = {}
5 for i in w:
6     if i in c:
7         c[i] += 1
8     else:
9         c[i] = 1
10 u= [i for i in c if c[i] == 1 and (s1.split().count(i) == 1 or s2.split().count(i) == 1)]
11 print(*u)
12
```

	Input	Expected	Got	
✓	this apple is sweet this apple is sour	sweet sour	sweet sour	✓
✓	apple apple banana	banana	banana	✓

Passed all tests! ✓

Question 2 :

Correct

Mark 1.00 out
of 1.00Flag
question

Give a dictionary with value lists, sort the keys by summation of values in value list.

Input : test_dict = {'Gfg': [6, 7, 4], 'best': [7, 6, 5]}

Output : {'Gfg': 17, 'best': 18}

Explanation : Sorted by sum, and replaced.

Input : test_dict = {'Gfg': [8,8], 'best': [5,5]}

Output : {'best': 10, 'Gfg': 16}

Explanation : Sorted by sum, and replaced.

Sample Input:

2

Gfg 6 7 4

Best 7 6 5

Sample Output:

Gfg 17

Best 18

For example:

Input	Result
2	Gfg 17
Gfg 6 7 4	Best 18
Best 7 6 5	

Answer: (penalty regime: 0 %)

```

1 n = int(input())
2 test_dict = {}
3 for i in range(n):
4     line = input()
5     parts = line.split()
6     key = parts[0]
7     values = list(map(int, parts[1:]))
8     test_dict[key] = values
9 sum_list = [(key, sum(values)) for key, values in test_dict.items()]
10 sorted_sum_list = sorted(sum_list, key=lambda x: x[1])
11 for key, total in sorted_sum_list:
12     print(f'{key} {total}')
13

```

	Input	Expected	Got	
✓	2 Gfg 6 7 4 Best 7 6 5	Gfg 17 Best 18	Gfg 17 Best 18	✓
✓	2 Gfg 6 6 Best 5 5	Best 10 Gfg 12	Best 10 Gfg 12	✓

Question 4

Correct

Mark 1.00 out of
1.00

Flag question

Create a student dictionary for n students with the student name as key and their test mark assignment mark and lab mark as values. Do the following computations and display the result.

- 1.Identify the student with the highest average score
- 2.Identify the student who has the highest Assignment marks
- 3.Identify the student with the Lowest lab marks
- 4.Identify the student with the lowest average score

Note:

If more than one student has the same score display all the student names

Sample input:

```
4
James 67 89 56
Lalith 89 45 45
Ram 89 89 89
Sita 70 70 70
```

Sample Output:

```
Ram
James Ram
Lalith
Lalith
```

For example:

Input	Result
4	Ram
James 67 89 56	James Ram
Lalith 89 45 45	Lalith
Ram 89 89 89	Lalith
Sita 70 70 70	

Answer: (penalty regime: 0 %)

```
1 x = int(input())
2 y = {}
3 for i in range(x):
4     d = input().split()
5     n = d[0]
6     t = int(d[1])
7     a = int(d[2])
8     l = int(d[3])
9     y[n] = {'test': t, 'assignment': a, 'lab': l}
10 a = []
11 b = []
12 c = []
13 d = []
14 p = -1
15 q = -1
16 r = 101
17 s = 101
18 for n,m in y.items():
19     z = (m['test'] + m['assignment'] + m['lab']) / 3
20     if z > p:
21         p = z
22         a = [n]
23     elif z == p:
24         a.append(n)
25     if m['assignment'] > q:
26         q = m['assignment']
27         b = [n]
28     elif m['assignment'] == q:
29         b.append(n)
30     if m['lab'] < r:
31         r = m['lab']
32         c = [n]
33     elif m['lab'] == r:
34         c.insert(0,n)
35     if z < s:
36         s = z
37         d = [n]
38     elif z == s:
39         d.append(n)
40 print(" ".join(a))
41 print(" ".join(b))
42 print(" ".join(c))
43 print(" ".join(d))
44
```

220901035

	Input	Expected	Got	
✓	4 James 67 89 56 Lalith 89 45 45 Ram 89 89 89 Sita 70 70 70	Ram James Ram Lalith Lalith	Ram James Ram Lalith Lalith	✓
✓	3 Raja 95 67 90 Aarav 89 98 90	Shadhana Shadhana Aarav Raja	Shadhana Shadhana Aarav Raja	✓

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

Given an array of names of candidates in an election. A candidate name in the array represents a vote cast to the candidate. Print the name of candidates received Max vote. If there is tie, print a lexicographically smaller name.

Examples:

```
Input : votes[] = {"john", "johnny", "jackie",
                   "johnny", "john", "jackie",
                   "jamie", "jamie", "john",
                   "johnny", "jamie", "johnny",
                   "john"},
```

Output : John

We have four Candidates with name as 'John', 'Johnny', 'Jamie', 'Jackie'. The candidates John and Johnny get maximum votes. Since John is alphabetically smaller, we print it. Use [dictionary](#) to solve the above problem

Sample Input:

```
10
John
John
Johny
Jamie
Jamie
Johny
Jack
Johny
Johny
Jackie
```

Sample Output:

Johny

Answer: (penalty regime: 0 %)

```
1 from collections import defaultdict ...
2 n=int(input())
3 v=[input() for i in range(n)]
4 c=defaultdict(int)
5 for i in v:
6     c[i]+=1
7 x=max(c.values())
8 y=[i for i, v in c.items() if v==x]
9 w=min(y)
10 print(w)
11
```

	Input	Expected	Got	
✓	10 John John Johny Jamie Jamie Johny Jack Johny Johny Jackie	Johny	Johny	✓
✓	6 Ida Ida Ida Kiruba Kiruba Kiruba	Ida	Ida	✓

Passed all test! ✓

Correct
Marks for this submission: 1.00/1.00.

Question 1
Correct
Mark 1.00 out
of 1.00
Flag
question

In the game of Scrabble™, each letter has points associated with it. The total score of a word is the sum of the scores of its letters. More common letters are worth fewer points while less common letters are worth more points. The points associated with each letter are shown below:

- Points Letters
1 A, E, I, L, N, O, R, S, T and U
2 D and G
3 B, C, M and P
4 F, H, V, W and Y
5 K
8 J and X
10 Q and Z

Write a program that computes and displays the Scrabble™ score for a word. Create a dictionary that maps from letters to point values. Then use the dictionary to compute the score.

A Scrabble™ board includes some squares that multiply the value of a letter or the value of an entire word. We will ignore these squares in this exercise.

Sample Input

REC

Sample Output

REC is worth 5 points.

For example:

Input	Result
REC	REC is worth 5 points.

Answer: (penalty regime: 0 %)

```
1+ p={  
2     'A': 1, 'E': 1, 'I': 1, 'L': 1, 'N': 1, 'O': 1, 'R': 1, 'S': 1, 'T': 1, 'U': 1,  
3     'D': 2, 'G': 2,  
4     'B': 3, 'C': 3, 'M': 3, 'P': 3,  
5     'F': 4, 'H': 4, 'V': 4, 'W': 4, 'Y': 4,  
6     'K': 5,  
7     'J': 8, 'X': 8,  
8     'Q': 10, 'Z': 10  
9 }  
10 w=input()  
11 w=w.upper()  
12 s=0  
13 for i in w:  
14     s+=p.get(i, 0)  
15 print(f'{w} is worth {s} points.')  
16 print(w, 'is worth', s, 'points.')  
17 |
```

	Input	Expected	Got	
✓	GOD	GOD is worth 5 points.	GOD is worth 5 points.	✓
✓	REC	REC is worth 5 points.	REC is worth 5 points.	✓

Passed all tests! ✓

Correct
Marks for this submission: 1.00/1.00.

Question 3
Correct
Mark 1.00 out
of 1.00
Flag question

A sentence is a string of single-space separated words where each word consists only of lowercase letters. A word is uncommon if it appears exactly once in one of the sentences, and does not appear in the other sentence.

Given two sentences s1 and s2, return a list of all the uncommon words. You may return the answer in any order.

Example 1:

Input: s1 = "this apple is sweet", s2 = "this apple is sour"

Output: ["sweet", "sour"]

Example 2:

Input: s1 = "apple apple", s2 = "banana"

Output: ["banana"]

Constraints:

$1 \leq s1.length, s2.length \leq 200$

s1 and s2 consist of lowercase English letters and spaces.

s1 and s2 do not have leading or trailing spaces.

All the words in s1 and s2 are separated by a single space.

Note:

Use dictionary to solve the problem

For example:

Input	Result
this apple is sweet	sweet sour
this apple is sour	

Answer: (penalty regime: 0 %)

```
1 s1 =input()
2 s2 =input()
3 w= s1.split() + s2.split()
4 c = {}
5 for i in w:
6     if i in c:
7         c[i] += 1
8     else:
9         c[i] = 1
10 u= [i for i in c if c[i] == 1 and (s1.split().count(i) == 1 or s2.split().count(i) == 1)]
11 print(*u)
12
```

	Input	Expected	Got	
✓	this apple is sweet this apple is sour	sweet sour	sweet sour	✓
✓	apple apple banana	banana	banana	✓

Passed all tests! ✓

Question 2 :

Correct

Mark 1.00 out
of 1.00Flag
question

Give a dictionary with value lists, sort the keys by summation of values in value list.

Input : test_dict = {'Gfg': [6, 7, 4], 'best': [7, 6, 5]}

Output : {'Gfg': 17, 'best': 18}

Explanation : Sorted by sum, and replaced.

Input : test_dict = {'Gfg': [8,8], 'best': [5,5]}

Output : {'best': 10, 'Gfg': 16}

Explanation : Sorted by sum, and replaced.

Sample Input:

2

Gfg 6 7 4

Best 7 6 5

Sample Output:

Gfg 17

Best 18

For example:

Input	Result
2	Gfg 17
Gfg 6 7 4	Best 18
Best 7 6 5	

Answer: (penalty regime: 0 %)

```

1 n = int(input())
2 test_dict = {}
3 for i in range(n):
4     line = input()
5     parts = line.split()
6     key = parts[0]
7     values = list(map(int, parts[1:]))
8     test_dict[key] = values
9 sum_list = [(key, sum(values)) for key, values in test_dict.items()]
10 sorted_sum_list = sorted(sum_list, key=lambda x: x[1])
11 for key, total in sorted_sum_list:
12     print(f'{key} {total}')
13

```

	Input	Expected	Got	
✓	2 Gfg 6 7 4 Best 7 6 5	Gfg 17 Best 18	Gfg 17 Best 18	✓
✓	2 Gfg 6 6 Best 5 5	Best 10 Gfg 12	Best 10 Gfg 12	✓

Question 4

Correct

Mark 1.00 out of
1.00

Flag question

Create a student dictionary for n students with the student name as key and their test mark assignment mark and lab mark as values. Do the following computations and display the result.

- 1.Identify the student with the highest average score
- 2.Identify the student who has the highest Assignment marks
- 3.Identify the student with the Lowest lab marks
- 4.Identify the student with the lowest average score

Note:

If more than one student has the same score display all the student names

Sample input:

```
4
James 67 89 56
Lalith 89 45 45
Ram 89 89 89
Sita 70 70 70
```

Sample Output:

```
Ram
James Ram
Lalith
Lalith
```

For example:

Input	Result
4	Ram
James 67 89 56	James Ram
Lalith 89 45 45	Lalith
Ram 89 89 89	Lalith
Sita 70 70 70	

Answer: (penalty regime: 0 %)

```
1 x = int(input())
2 y = {}
3 for i in range(x):
4     d = input().split()
5     n = d[0]
6     t = int(d[1])
7     a = int(d[2])
8     l = int(d[3])
9     y[n] = {'test': t, 'assignment': a, 'lab': l}
10 a = []
11 b = []
12 c = []
13 d = []
14 p = -1
15 q = -1
16 r = 101
17 s = 101
18 for n,m in y.items():
19     z = (m['test'] + m['assignment'] + m['lab']) / 3
20     if z > p:
21         p = z
22         a = [n]
23     elif z == p:
24         a.append(n)
25     if m['assignment'] > q:
26         q = m['assignment']
27         b = [n]
28     elif m['assignment'] == q:
29         b.append(n)
30     if m['lab'] < r:
31         r = m['lab']
32         c = [n]
33     elif m['lab'] == r:
34         c.insert(0,n)
35     if z < s:
36         s = z
37         d = [n]
38     elif z == s:
39         d.append(n)
40 print(" ".join(a))
41 print(" ".join(b))
42 print(" ".join(c))
43 print(" ".join(d))
44
```

220901035

	Input	Expected	Got	
✓	4 James 67 89 56 Lalith 89 45 45 Ram 89 89 89 Sita 70 70 70	Ram James Ram Lalith Lalith	Ram James Ram Lalith Lalith	✓
✓	3 Raja 95 67 90 Aarav 89 98 90	Shadhana Shadhana Aarav Raja	Shadhana Shadhana Aarav Raja	✓

Question 5
Correct
Mark 1.00 out of 1.00
Flag question

Given an array of names of candidates in an election. A candidate name in the array represents a vote cast to the candidate. Print the name of candidates received Max vote. If there is tie, print a lexicographically smaller name.

Examples:

```
Input : votes[] = {"john", "johnny", "jackie",
                   "johnny", "john", "jackie",
                   "jamie", "jamie", "john",
                   "johnny", "jamie", "johnny",
                   "john"},
```

Output : John

We have four Candidates with name as 'John', 'Johnny', 'Jamie', 'Jackie'. The candidates John and Johnny get maximum votes. Since John is alphabetically smaller, we print it. Use [dictionary](#) to solve the above problem

Sample Input:

```
10
John
John
Johny
Jamie
Jamie
Johny
Jack
Johny
Johny
Jackie
```

Sample Output:

Johny

Answer: (penalty regime: 0 %)

```
1 from collections import defaultdict ...
2 n=int(input())
3 v=[input() for i in range(n)]
4 c=defaultdict(int)
5 for i in v:
6     c[i]+=1
7 x=max(c.values())
8 y=[i for i, v in c.items() if v==x]
9 w=min(y)
10 print(w)
11
```

	Input	Expected	Got	
✓	10 John John Johny Jamie Jamie Johny Jack Johny Johny Jackie	Johny	Johny	✓
✓	6 Ida Ida Ida Kiruba Kiruba Kiruba	Ida	Ida	✓

Passed all test! ✓

Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints $1 \leq \text{orderValue} \leq 10e100000$ **Input**

The input consists of an integer `orderValue`, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
<code>print(christmasDiscount(578))</code>	12

Answer: (penalty regime: 0 %)

Reset answer

```
1. def christmasDiscount(n):
2.     prime_digits = {'2', '3', '5', '7'}
3.     discount = 0
4.     for digit in str(n):
5.         if digit in prime_digits:
6.             discount += int(digit)
7.     return discount
```

	Test	Expected	Got	
✓	<code>print(christmasDiscount(578))</code>	12	12	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of
1.00 Flag
questionWrite a code to check whether product of digits at even places is
divisible by sum of digits

at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False

Answer: (penalty regime: 0 %)**Reset answer**

```

1 • def productDigits(n):
2 •     s=str(n)
3 •     e=1
4 •     o=0
5 •     for i in range(len(s)):
6 •         d=int(s[i])
7 •         if (i + 1) % 2 == 0:
8 •             e*=d
9 •         else:
10 •             o+=d
11 •     if o==0:
12 •         return False
13 •     if e%o==0:
14 •         return True
15 •     else:
16 •         return False
17 • try:
18 •     n=int(input().strip())
19 •     if productDigits(n):
20 •         print("TRUE")
21 •     else:
22 •         print("FALSE")
23 • except EOFError:
24 •     pass
25
26
27

```

	Test	Expected	Got	
✓	print(productDigits(1256))	True	True	✓
✓	print(productDigits(1595))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 1

Correct

Mark 1.00 out of
1.00 Flag
question

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly

Answer: (penalty regime: 0 %)

Reset answer

```

1 | def checkUgly(n):
2 |     if n <= 0:
3 |         return "not ugly"
4 |     for prime in [2, 3, 5]:
5 |         while n % prime == 0:
6 |             n //= prime
7 |     return "ugly" if n == 1 else "not ugly"
8 | n=6

```

	Test	Expected	Got	
✓	print(checkUgly(6))	ugly	ugly	✓
✓	print(checkUgly(21))	not ugly	not ugly	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of
1.00
Flag question

An automorphic number is a number whose square ends with the number itself.

For example, 5 is an automorphic number because $5 \times 5 = 25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

Input Format:

Take a Integer from Stdin Output Format: Print Automorphic if given number is Automorphic number,otherwise Not Automorphic Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example input: 7 Output: Not Automorphic

For example:

Test	Result
print(automorphic(5))	Automorphic

Answer: (penalty regime: 0 %)

Reset answer

```
1 | def automorphic(n):
2 |     if n<0:
3 |         return "Invalid input"
4 |     return "Automorphic" if str(n*n).endswith(str(n)) else "Not Automorphic"
5 |
6 | n=5
```

	Test	Expected	Got	
✓	print(automorphic(5))	Automorphic	Automorphic	✓
✓	print(automorphic(7))	Not Automorphic	Not Automorphic	✓

Question 4

Correct

Mark 1.00 out
of 1.00 Flag
question

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1 | def coinChange(n):
2 |     coins=[1,2,3,4]
3 |     count=0
4 |     while n>0:
5 |         max2=max([coin for coin in coins if coin <=n])
6 |         n-=max2
7 |         count+=1
8 |     return count
9 | n=16
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Question 3

Correct

Mark 1.00 out of
1.00 Flag
question

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints $1 \leq \text{orderValue} \leq 10e100000$ **Input**

The input consists of an integer `orderValue`, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
<code>print(christmasDiscount(578))</code>	12

Answer: (penalty regime: 0 %)

Reset answer

```
1. def christmasDiscount(n):
2.     prime_digits = {'2', '3', '5', '7'}
3.     discount = 0
4.     for digit in str(n):
5.         if digit in prime_digits:
6.             discount += int(digit)
7.     return discount
```

	Test	Expected	Got	
✓	<code>print(christmasDiscount(578))</code>	12	12	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of
1.00 Flag
questionWrite a code to check whether product of digits at even places is
divisible by sum of digits

at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False

Answer: (penalty regime: 0 %)**Reset answer**

```

1 • def productDigits(n):
2 •     s=str(n)
3 •     e=1
4 •     o=0
5 •     for i in range(len(s)):
6 •         d=int(s[i])
7 •         if (i + 1) % 2 == 0:
8 •             e*=d
9 •         else:
10 •             o+=d
11 •     if o==0:
12 •         return False
13 •     if e%o==0:
14 •         return True
15 •     else:
16 •         return False
17 • try:
18 •     n=int(input().strip())
19 •     if productDigits(n):
20 •         print("TRUE")
21 •     else:
22 •         print("FALSE")
23 • except EOFError:
24 •     pass
25
26
27

```

	Test	Expected	Got	
✓	print(productDigits(1256))	True	True	✓
✓	print(productDigits(1595))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 1

Correct

Mark 1.00 out of
1.00 Flag
question

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly

Answer: (penalty regime: 0 %)

Reset answer

```

1 | def checkUgly(n):
2 |     if n <= 0:
3 |         return "not ugly"
4 |     for prime in [2, 3, 5]:
5 |         while n % prime == 0:
6 |             n //= prime
7 |     return "ugly" if n == 1 else "not ugly"
8 | n=6

```

	Test	Expected	Got	
✓	print(checkUgly(6))	ugly	ugly	✓
✓	print(checkUgly(21))	not ugly	not ugly	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2
Correct
Mark 1.00 out of
1.00
Flag question

An automorphic number is a number whose square ends with the number itself.

For example, 5 is an automorphic number because $5 \times 5 = 25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

Input Format:

Take a Integer from Stdin Output Format: Print Automorphic if given number is Automorphic number,otherwise Not Automorphic Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example input: 7 Output: Not Automorphic

For example:

Test	Result
print(automorphic(5))	Automorphic

Answer: (penalty regime: 0 %)

Reset answer

```
1 | def automorphic(n):
2 |     if n<0:
3 |         return "Invalid input"
4 |     return "Automorphic" if str(n*n).endswith(str(n)) else "Not Automorphic"
5 |
6 | n=5
```

	Test	Expected	Got	
✓	print(automorphic(5))	Automorphic	Automorphic	✓
✓	print(automorphic(7))	Not Automorphic	Not Automorphic	✓

Question 4

Correct

Mark 1.00 out
of 1.00 Flag
question

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1 | def coinChange(n):
2 |     coins=[1,2,3,4]
3 |     count=0
4 |     while n>0:
5 |         max2=max([coin for coin in coins if coin <=n])
6 |         n-=max2
7 |         count+=1
8 |     return count
9 | n=16
```

	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Question 1
Correct
Mark 1.00 out of 1.00
1st flag question

Given a list of integers, sort the array in ascending order using the Bubble Sort algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps, where numSwaps is the number of swaps that took place.
 2. First Element: firstElement, the first element in the sorted list.
 3. Last Element: lastElement, the last element in the sorted list.
- For example, given a worst-case but small array to sort: $a=[6,4,1]$, it took 3 swaps to sort the array. Output would be
- Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

Input Format

The first line contains an integer, n , the size of the list a .
The second line contains n space-separated integers $a[i]$.

Constraints

- 1 $\leq n \leq 600$
- 1 $\leq a[i] \leq 2 \times 10^6$

Output Format

You must print the following three lines of output:

1. List is sorted in numSwaps swaps, where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the first element in the sorted list.
3. Last Element: lastElement, the last element in the sorted list.

Sample Input 0

3

1 2 3

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0%)

```
1 n = int(input())
2 a = list(map(int, input().split()))
3 s=0
4 for i in range(n):
5     for j in range(n-1):
6         if a[j]>a[j+1]:
7             a[j], a[j+1]=a[j+1], a[j]
8             s+=1
9 print(f"List is sorted in {s} swaps.")
10 print(f"First Element: {a[0]}")
11 print(f"Last Element: {a[-1]}")
```

	Input	Expected	Got
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 2

Correct

Mark 1.00 out of
1.00 Flag
question

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1 <= n, arr[i] <= 100

Input:

1 68 79 4 90 68 1 4 5

Output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2
	4 2
	5 2

Answer: (penalty regime: 0 %)

```

1 arr = list(map(int, input().split()))
2 freq = {}
3 for n in arr:
4     freq[n] = freq.get(n, 0) + 1
5 for k in sorted(freq.keys()):
6     print(k, freq[k])

```

	Input	Expected	Got	
✓	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	✓
✓	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	✓
✓	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00

Question 5

Correct

Mark 1.00 out of
1.00 Flag
question

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read a list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted list.

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

```

1 n = int(input())
2 arr = list(map(int, input().split()))
3 for i in range(n):
4     for j in range(0, n-i-1):
5         if arr[j] > arr[j+1]:
6             arr[j], arr[j+1] = arr[j+1], arr[j]
7 print(*arr)

```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of
1.00Flag
question

Write a Python program for binary search.

For example:

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

Answer: (penalty regime: 0 %)

```
1 def binary_search(arr,x):
2     low=0
3     high=len(arr)-1
4     while low <= high:
5         mid=(low+high)//2
6         if arr[mid]<x:
7             low=mid+1
8         elif arr[mid]>x:
9             high = mid -1
10        else:
11            return True
12    return False
13 e=list(map(int,input().split(",")))
14 ef=int(input())
15 e.sort()
16 f=binary_search(e,ef)
17 print(f)
```

	Input	Expected	Got	
✓	1,2,3,5,8 6	False	False	✓
✓	3,5,9,45,42 42	True	True	✓
✓	52,45,89,43,11 11	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of
1.00 Flag
question

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, $A[i]$.

Output Format

Print peak numbers separated by space.

Sample Input

5

8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4	12 8
12 3 6 8	

Answer: (penalty regime: 0 %)

```

1 |n = int(input())
2 |arr = list(map(int, input().split()))
3 |p = []
4 .if arr[0] >= arr[1]:
5 |    p.append(arr[0])
6 .for i in range(1, n - 1):
7 |    if arr[i - 1] <= arr[i] >= arr[i + 1]:
8 |        p.append(arr[i])
9 .if arr[-1] >= arr[-2]:
10 |       p.append(arr[-1])
11 |print(*p)

```

	Input	Expected	Got	
✓	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	✓
✓	4 12 3 6 8	12 8	12 8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.