

CIAAlign - Clean and Interpret Alignments

Charlotte Tumescheit, Dr. Katherine Brown, Dr. Andrew E. Firth

CIAAlign is a command line tool which performs various functions to clean and analyse a multiple sequence alignment (MSA).

The tool is designed to be highly customisable, allowing users to specify exactly which functions to run and which settings to use. It is also transparent, generating a clear log file and alignment markup showing exactly how the alignment has changed and what has been removed by which function.

This allows the user to:

- Remove sources of noise from their MSA
 - Crop poorly aligned sequence ends
 - Remove insertions which are not present in the majority of sequences
 - Remove sequences below a threshold number of bases or amino acids
 - Remove columns containing only gaps
 - Remove sequences above a threshold level percentage of divergence from the majority
- Generate consensus sequences
- Visualise alignments
 - Generate image files showing the alignment before and after using CIAAlign cleaning functions and showing which columns and rows have been removed
 - Draw sequence logos
 - Visualise coverage at each position in the alignment
- Analyse alignment statistics
 - Generate a similarity matrix showing the percentage identity between each sequence pair
- Unalign the alignment

Requirements

- python \geq 3.6
- matplotlib \geq 2.1.1
- numpy \geq 1.16.3
- scipy \geq 1.3.0

Installation

The easiest way to install CIAAlign is using pip3:

```
pip3 install cialign
```

The current release of CIAAlign can also be downloaded directly using this link

If you download the package directly, you will also need to add the CIAAlign directory to your PATH environment variable as described here

Usage

Basic Usage

`CIAalign --infile INFILE --outfile_stem STEM --inifile my_config.ini`

Parameters

Parameters can be specified in the command line or in a config file using the naming system below.

A template config file is provided in `CIAalign/templates/ini_template.txt` - edit this file and provide the path to the `--inifile` argument. If this argument is not provided command line arguments and defaults will be used.

Parameters passed in the command line will take precedence over config file parameters, which take precedence over defaults.

Command help can be accessed by typing `CIAalign --help`

Parameter	Description	Default
<code>--infile</code>	Path to input alignment FASTA file	None
<code>--inifile</code>	Path to ini file	None
<code>--outfile_stem</code>	Prefix for output files, including the path to the output directory	CIAalign
<code>--silent</code>	Do not print progress to the screen	False

Beside these main parameters, the use of every function and corresponding thresholds can be specified by the user by adding parameters to the command line or by setting them in the configuration file. Available functions and their parameters will be specified in the following section.

Cleaning an MSA

Each of these steps will be performed sequentially in the order specified in the table below.

The “cleaned” alignment after all steps have been performed will be saved as `OUTFILE_STEM_cleaned.fasta`

Parameter	Description	Default Value
<code>--crop_ends</code>	Crop the ends of sequences if they are poorly aligned	False
<code>- -crop_ends_mingap</code>	minimum gap size to consider when classifying a sequence as poorly aligned	30
<code>--remove_divergent</code>	Remove sequences with $\leq N$ proportion of positions at which the most common base / amino acid in the alignment is present	False
<code>- -remove_divergent_minperc</code>	Minimum proportion of positions which should be identical to the most common base / amino acid in order to be preserved	0.75
<code>--remove_insertions</code>	Remove insertions found in $\leq 50\%$ of sequences from the alignment	False
<code>- -insertion_min_size</code>	Only remove insertions \geq this number of residues	3
<code>- -insertion_max_size</code>	Only remove insertions \leq this number of residues	300
<code>- -insertion_min_flank</code>	Minimum number of bases on either side of an insertion to classify it as an insertion	5
<code>--remove_short</code>	Remove sequences $\leq N$ bases / amino acids from the alignment	False
<code>- -remove_minlength</code>	Minimum number of non-gap residues in a sequence to be preserved	50

Parameter	Description	Default Value
<code>--remove_gaponly</code>	Remove gap only columns from the alignment	True
<code>--all</code>	Use all available functions with default parameters	False

Generating a Consensus Sequence

This step generates a consensus sequence based on the cleaned alignment. If no cleaning functions are performed, the consensus will be based on the input alignment.

Output files:

- `OUTFILE_STEM_consensus.fasta` - the consensus sequence only
- `OUTFILE_STEM_with_consensus.fasta` - the cleaned alignment plus the consensus

Parameter	Description	Default
<code>--make_consensus</code>	Make a consensus sequence based on the cleaned alignment	False
<code>- -consensus_type</code>	Type of consensus sequence to make - can be majority, to use the most common character at each position in the consensus, even if this is a gap, or majority_nongap, to use the most common non-gap character at each position	majority
<code>- -consensus_keeppaps</code>	If there are gaps in the consensus (if majority_nongap is used as consensus_type), should these be included in the consensus (True) or should this position in the consensus be deleted (False)	False
<code>- -consensus_name</code>	Name to use for the consensus sequence in the output fasta file	consensus

Unalign Alignment

This function simply removes the gaps from the input or output alignment and creates an unaligned file of the sequences.

Output files:

- `OUTFILE_STEM_unaligned_input.fasta` - unaligned sequences of input alignment
- `OUTFILE_STEM_unaligned_output.fasta` - unaligned sequences of output alignment

Parameter	Description	Default
<code>--unalign_input</code>	Generates a copy of the input alignment with no gaps	False
<code>--unalign_output</code>	Generates a copy of the output alignment with no gaps	False

Visualising Alignments

Each of these functions produces some kind of visualisation of your alignment.

Mini Alignments

These functions produce “mini alignments” - images showing a small representation of your whole alignment, so that gaps and poorly aligned regions are clearly visible.

Output files:

- `OUTFILE_STEM_input.png` (or `svg`, `tiff`, `jpg`) - the input alignment
- `OUTFILE_STEM_output.png` (or `svg`, `tiff`, `jpg`) - the cleaned output alignment
- `OUTFILE_STEM_markup.png` (or `svg`, `tiff`, `jpg`) - the input alignment with deleted rows and columns marked

Parameter	Description	Default
<code>--plot_input</code>	Draws a mini alignment for the input FASTA file	False
<code>--plot_output</code>	Draws a mini alignment for the output FASTA file	False
<code>--plot_markup</code>	Draws the input alignment but with the columns and rows which have been removed by each function marked up in corresponding colours	False
<code>-plot_dpi</code>	DPI for mini alignments	300
<code>-plot_format</code>	Image format for mini alignments - can be <code>png</code> , <code>svg</code> , <code>tiff</code> or <code>jpg</code>	<code>png</code>
<code>-plot_width</code>	Mini alignment width in inches	5
<code>-plot_height</code>	Mini alignment height in inches	3

Sequence logos

These functions draw sequence logos representing your output (cleaned) alignment. If no cleaning functions are specified, the logo will be based on your input alignment.

Output_files:

- `OUTFILE_STEM_logo_bar.png` (or `svg`, `tiff`, `jpg`) - the alignment represented as a bar chart
- `OUTFILE_STEM_logo_text.png` (or `svg`, `tiff`, `jpg`) - the alignment represented as a standard sequence logo using text

Parameter	Description	Default
<code>--make_sequence_logo</code>	Draw a sequence logo	False
<code>-sequence_logo_type</code>	Can be <code>bar</code> , to draw the logo as a bar chart, <code>text</code> , to draw a standard sequence logo using text, or <code>both</code> , to draw both	<code>bar</code>
<code>-sequence_logo_dpi</code>	DPI for sequence logo	300
<code>-sequence_logo_font</code>	font (see NB below) for bases / amino acids in a text based sequence logo	<code>monospace</code>
<code>-sequence_logo_nt_per_row</code>	number of bases / amino acids to show per row in the sequence logo, where the logo is too large to show on a single line	50
<code>-sequence_logo_filetype</code>	Image file type to use for the sequence logo - can be <code>png</code> , <code>svg</code> , <code>tiff</code> or <code>jpg</code>	<code>png</code>

NB: to see available fonts on your system, run `CIAAlign -list_fonts_only` and view `CIAAlign_fonts.png`

Coverage Plots

This function plots the number of non-gap residues at each position in the alignment.

Output file:

- `OUTFILE_STEM_input_coverage.png` (or `svg`, `tiff`, `jpg`) - image showing the input alignment coverage
- `OUTFILE_STEM_output_coverage.png` (or `svg`, `tiff`, `jpg`) - image showing the output alignment coverage

Parameter	Description	Default
<code>--plot_coverage_input</code>	Plot the coverage of the multiple sequence alignment	False

Parameter	Description	Default
<code>--plot_coverage_output</code>	Plot the coverage of the multiple sequence alignment	False
<code>-plot_coverage_dpi</code>	DPI for coverage plot	300
<code>-plot_coverage_height</code>	Height for coverage plot (inches)	3
<code>-plot_coverage_width</code>	Width for coverage plot (inches)	5
<code>-plot_coverage_colour</code>	Colour for coverage plot (hex code or name)	#007bf5
<code>-plot_coverage_filetype</code>	File type for coverage plot (can be png, svg, tiff, jpg)	png

Analysing Alignment Statistics

These functions provide additional analyses you may wish to perform on your alignment.

Similarity Matrices

Generates a matrix showing the proportion of identical bases / amino acids between each pair of sequences in the MSA.

Output file:

- `OUTFILE_STEM_input_similarity.tsv` - similarity matrix for the input file
- `OUTFILE_STEM_output_similarity.tsv` - similarity matrix for the output file

Parameter	Description	Default
<code>--make_similarity_matrix_input</code>	make a similarity matrix for the input alignment	False
<code>--make_similarity_matrix_output</code>	make a similarity matrix for the output alignment	False
<code>-make_simmatrix_keepgaps</code>	Include positions with gaps in either or both sequences in the similarity calculation	False
<code>-make_simmatrix_dp</code>	Number of decimal places to display in the similarity matrix output file	4
<code>-make_simmatrix_minoverlap</code>	Minimum overlap between two sequences to have non-zero similarity in the similarity matrix	1