

# SPIP: Data Source API V2

<https://issues.apache.org/jira/browse/SPARK-15689>

## Background and Motivation

The current Data Source API was released with Spark 1.3. Based on the community feedbacks, it has the following limitations:

1. Since its input arguments include DataFrame/SQLContext, the data source API compatibility depends on the upper level API.
2. The physical storage information (e.g., partitioning and sorting) is not propagated from the data sources, and thus, not used in the Spark optimizer.
3. Extensibility is not good and operator push-down capabilities are limited.
4. Lacking columnar read interface for high performance.
5. The write interface is so general without transaction supports.

Because of the above limitations/issues, the built-in data source implementations (like parquet, json, etc.) inside Spark SQL are not using this public Data Source API. Instead, they use an internal/non-public interface. It is hard (or almost impossible) to make the external data source implementations as fast as the built-in ones. It disappoints some data source developers and sometimes force them to fork Spark to make extensive changes.

While the current Data Source API support is still maintained, it is highly desirable to introduce the Data Source API V2 for facilitating development of high performant, easy-to-maintain, easy-to-extend external data sources.

## Target Persona

Spark developers and data source developers

## Goals

Design a new Data Source API in Scala/Java:

1. Java friendly
2. No dependency on DataFrame, RDD, SparkSession, etc.
3. Support filter pushdown and column pruning. Also, easy to add more operator pushdowns without breaking backward compatibility, e.g. limit, sample, aggregate, etc. Note that, binary operator pushdown, like join pushdown, is out of the scope.
4. Be able to propagate physical partitioning information and the others without breaking backward compatibility. For example, statistics, indices, and orderings. They can be used by Spark to optimize the query.

5. Having both columnar read interface (which requires a public columnar format) and InternalRow read interface (since InternalRow will not be published, this is still an experimental interface)
6. Having a write interface with transaction support. The write interface should be pluggable to allow read-only data sources.
7. Able to replace HadoopFsRelation.
8. Able to replace the internal Hive-specific table read/write plans.

The proposed data source API mainly focuses on read, write and optimization extensions without adding new functionalities like data updating.

## Non-Goals

1. Define data source in languages other than Scala and Java.
2. Columnar write interface (nice to have)
3. Streaming data source (not included in this SPIP but good to design together)
4. New functionalities that currently we do not have for data source, e.g. data updating (for now we only support append and overwrite), supporting catalog other than Hive, customized DDL syntax, etc.

## Proposed API

Some concerns:

- The best way to keep Java compatibility is writing the API in java. It's easy to deal with Java classes/interfaces in Scala, but not vice-versa.
- The read interface returns read tasks that outputs data, instead of a DataFrame/RDD, for minimizing the dependencies.
- Complementary to the read interface, a schema inference interface is also provided. Data source can be implemented: a) the user-specified schema is required, b) a user specified schema is not allowed and the schema is automatically inferred, c) the user-specified schema is respected, and if unavailable, the schema can also be automatically inferred.
- Schema evolution can be supported based on the data source implementations. Spark can still append and read the data that has different schema from the pre-defined/inferred schema of the data source. Not all the data sources support schema evolution. For example, parquet and json support schema evolution, but csv does not.
- All data source optimizations like column pruning, filter pushdown, columnar reader, etc. should be defined as individual java interfaces and users can pick whatever optimization they want to implement.
- Ideally partitioning/bucketing concept should not be exposed in the Data Source API V2, because they are just techniques for data skipping and pre-partitioning. However, these 2 concepts are already widely used in Spark, e.g. `DataFrameWriter.partitionBy` and DDL syntax like `ADD PARTITION`. To be consistent, we need to add

partitioning/bucketing to Data Source V2, so that the implementations can be able to specify partitioning/bucketing for read/write.

- Bucketing may not be the only technique that can do pre-partitioning, hash partitioning push down is included in Data Source V2.
- The write interface follows FileFormatWriter/FileCommitProtocol and introduces task and job level commit and abort. Note that, this only guarantees job-level transaction. If a single query incurs more than one job, this query may not be transactional. This is an existing issue, how to fix it is another topic and is out of the scope of this SPIP.
- Read, write and inferSchema all take a string to string map as options. Each data source implementation is free to define its own options.
- Datasource options should be case insensitive, and CaseInsensitiveMap is picked to represent options, to make it explicit.
- In addition to setting data source options via the string to string map for each read/write operation, users can also set them in the current session, by prefixing the option name with `spark.datasource.SOURCE_NAME`. For example, when users issue the command `spark.conf.set("spark.datasource.json.samplingRatio", "0.5")`, the new option `samplingRatio=0.5` will take effect in the subsequent json data source reads within this session.

## Prototype

Data source main interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-0512fb43101f98452b00381f37b0d011R24>

Data reader interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-f7f970e9684796e2120223d1153302e4R29>

Read task interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-f367559522eb9fe1946ddc1ef94aa9f8R22>

Various reader optimization interfaces:

<https://github.com/cloud-fan/spark/pull/10/files#diff-fb7f253d61c880f6acfaa3548acfa60fR22>

<https://github.com/cloud-fan/spark/pull/10/files#diff-4e39b4f6eb3b538b271f7f13c8e1edeeR24>

<https://github.com/cloud-fan/spark/pull/10/files#diff-c8a46f157575dda85fd61c4150d2f9d0R22>

...

Schema inference interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-13f56558c968f94bfca4e8645f681164R23>

Writable data source interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-8ed8a07f6ad1321e2515754dee0b2f06R24>

Data source writer interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-8d00c33b7bf7bbcb1d7f3aa5b782fb1eR20>

Write task interface:

<https://github.com/cloud-fan/spark/pull/10/files#diff-baeb4c8032f89e4c371a0be8e4b12227R30>

Scala examples:

<https://github.com/cloud-fan/spark/pull/10/files#diff-1cea29fb1d8b19a3e0b33ad4286b7cf0R85>

<https://github.com/cloud-fan/spark/pull/10/files#diff-1cea29fb1d8b19a3e0b33ad4286b7cf0R112>

<https://github.com/cloud-fan/spark/pull/10/files#diff-1cea29fb1d8b19a3e0b33ad4286b7cf0R183>

<https://github.com/cloud-fan/spark/pull/10/files#diff-1cea29fb1d8b19a3e0b33ad4286b7cf0R219>

Java examples:

<https://github.com/cloud-fan/spark/pull/10/files#diff-70b2ada606e532f612e9d4f1b20dda13R31>

<https://github.com/cloud-fan/spark/pull/10/files#diff-3cd83f83487ba1baf5d20b52e8b0ae7fR35>

<https://github.com/cloud-fan/spark/pull/10/files#diff-7a0fc4447ad2eceda24db85b586b8c61R32>

<https://github.com/cloud-fan/spark/pull/10/files#diff-e686ee16d44620d2a1907974c685f224R31>

## Project Plan

1. Finish the read path, schema inference and write path, and support existing query optimizations like column pruning, filter push down, etc. For newly added optimizations like sample push down, sort push down, we can create the interface without implementing them.
2. Port the internal file based data sources to Data Source V2.
3. Port JDBC data source to Data Source V2. (maybe do this before porting file based data sources, as JDBC is much easier to port)
4. Port Hive table to Data Source V2.
5. Implement all the query optimizations that were proposed in step 1.
6. Revisit the interface/framework, and support more optimizations if needed.