

Binary Search Tree

Pohon Biner Terurut

Binary Search Tree is a node-based binary tree data structure which has the following properties:






- The left subtree of a node contains only nodes with keys lesser than the node's key.
- The right subtree of a node contains only nodes with keys greater than the node's key.
- The left and right subtree each must also be a binary search tree.



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit




Tunjukkan mana yang BST dan mana yang bukan, beserta alasannya



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Tunjukkan mana yang BST dan mana yang bukan, beserta alasannya



Algoritma INSERT Rekursif

Insert(X, T)

If T = nil

Then {insert}

new(T); Val(T) = x; left(T) = nil, right(T) = nil

Else

case

x < val(T) : Insert(X, left(T))

x > val(T) : Insert(X, right(T))

x = val(T) : {duplikasi}

endcase

endif



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Algoritma INSERT NON-Rekursif

Insert(X, T)

If T = nil

Then {insert}

new(T); Val(T) = x; left(T) = nil, right(T) = nil

Else

P = T

repeat

father = P

if $x < \text{val}(P)$ then P = left(P) else P = right(P)

until P = nil

new(P); Val(P) = x; left(P) = nil, right(P) = nil

if $x < \text{val}(\text{father})$

then left(father) = P

else right(father) = P

endif

endif



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Latihan INSERT

Diberikan data-data berikut, gambarkan BST yang terbentuk menggunakan algoritme REKURSIF dan NON-REKURSIF :

1. 7,4,8,3,2,1,9
2. 4,8,1,5,9,2,6

Masalah :

1. Apakah BST yang terbentuk sama jika urutan data berbeda?
2. Coba ubah urutannya dan tuliskan urutan yang Anda buat serta gambarkan BST nya

Algoritma SEARCH Rekursif

Search(T,X,found,P)

If T = nil

Then found = false

Else

case

x < val(T) : Search(left(T), X, found, P)

x > val(T) : Search(right(T), X, found, P)

x = val(T) : found = true; P = T

endcase

endif



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Algoritma SEARCH NON-Rekursif

Search(T,X,found,P)

Q = T ; found = false

While (Q <> nil) and (not found)

Do case

 x < val(T) : Q = left(T)

 x > val(T) : Q = right(T)

 x = val(T) : found = true; P = Q

 endcase

endwhile



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Efisiensi

- Similar to binary search in an array, the search speed is proportional to $\log_2(n)$, if the tree contains N node.
- However, if the tree is very skewed (left or right) the efficiency is similar to the efficiency of a sequential search



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit

Data Non Unik

- Bagaimana jika data tidak unik, misal data 5 muncul 2 kali ?



INSTITUT
TEKNOLOGI
HARAPAN
BANGSA

Veritas vos liberabit