

## Practical 5

Aim: Write a program to implement the naïve Bayesian classifier for a sample training data set stored as a .CSV file. Compute the accuracy of the classifier, considering few test data sets.

```
In [1]: # import necessary libarities
import pandas as pd
from sklearn import tree
from sklearn.preprocessing import LabelEncoder
from sklearn.naive_bayes import GaussianNB

# Load data from CSV
data = pd.read_csv('pr5.csv')
print("The first 5 values of data is :\n",data.head())

# obtain Train data and Train output
X = data.iloc[:, :-1]
print("\nThe First 5 values of train data is\n",X.head())

y = data.iloc[:, -1]
print("\nThe first 5 values of Train output is\n",y.head())

# Convert then in numbers
le_outlook = LabelEncoder()
X.Outlook = le_outlook.fit_transform(X.Outlook)

le_Temperature = LabelEncoder()
X.Temperature = le_Temperature.fit_transform(X.Temperature)

le_Humidity = LabelEncoder()
X.Humidity = le_Humidity.fit_transform(X.Humidity)

le_Windy = LabelEncoder()
X.Windy = le_Windy.fit_transform(X.Windy)

print("\nNow the Train data is :\n",X.head())
```

```

le_PlayTennis = LabelEncoder()
y = le_PlayTennis.fit_transform(y)
print("\nNow the Train output is\n",y)

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X,y, test_size=0.20)

classifier = GaussianNB()
classifier.fit(X_train,y_train)

from sklearn.metrics import accuracy_score
print("Accuracy is:",accuracy_score(classifier.predict(X_test),y_test))

```

The first 5 values of data is :

	Outlook	Temperature	Humidity	Windy	PlayTennis
0	Sunny	Hot	High	False	No
1	Sunny	Hot	High	True	No
2	Overcast	Hot	High	False	Yes
3	Rainy	Mild	High	False	Yes
4	Rainy	Cool	Normal	False	Yes

The First 5 values of train data is

	Outlook	Temperature	Humidity	Windy
0	Sunny	Hot	High	False
1	Sunny	Hot	High	True
2	Overcast	Hot	High	False
3	Rainy	Mild	High	False
4	Rainy	Cool	Normal	False

The first 5 values of Train output is

0	No
1	No
2	Yes
3	Yes
4	Yes

Name: PlayTennis, dtype: object

Now the Train data is :

	Outlook	Temperature	Humidity	Windy
0	2	1	0	0
1	2	1	0	1
2	0	1	0	0
3	1	2	0	0
4	1	0	1	0

Now the Train output is

[0 0 1 1 1 0 1 0 1 1 1 1 0]  
Accuracy is: 0.6666666666666666

## Practical : 6

Aim: Assuming a set of documents that need to be classified, use the naïve Bayesian Classifier model to perform this task. Built-in Java classes/API can be used to write the program. Calculate the accuracy, precision, and recall for your data set.

```
[2]: import pandas as pd
msg = pd.read_csv('pr6.csv', names=['message', 'label'])
print("Total Instances of Dataset: ", msg.shape[0])
msg['labelnum'] = msg.label.map({'pos': 1, 'neg': 0})
```

Total Instances of Dataset: 18

```
[3]: X = msg.message
y = msg.labelnum
from sklearn.model_selection import train_test_split
Xtrain, Xtest, ytrain, ytest = train_test_split(X, y)
from sklearn.feature_extraction.text import CountVectorizer

count_v = CountVectorizer()
Xtrain_dm = count_v.fit_transform(Xtrain)
Xtest_dm = count_v.transform(Xtest)
```

```
[5]: df = pd.DataFrame(Xtrain_dm.toarray(), columns=count_v.get_feature_names_out())
print(df[0:5])
```

	about	am	an	and	awesome	bad	beers	best	boss	do	...	to	today	\
0	0	0	0	0	0	0	0	0	0	0	...	0	0	
1	0	0	0	0	0	0	1	0	0	0	...	1	0	
2	1	0	0	0	0	0	0	1	0	0	...	0	0	
3	0	0	0	0	0	0	0	0	0	0	...	0	0	
4	0	1	0	1	0	0	0	0	0	0	...	0	0	

	tomorrow	very	view	we	went	what	will	work
0	1	0	0	1	0	0	1	0
1	0	0	0	0	0	0	0	0
2	0	1	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0

[5 rows x 46 columns]

```
[6]: from sklearn.naive_bayes import MultinomialNB
      clf = MultinomialNB()
      clf.fit(Xtrain_dm, ytrain)
      pred = clf.predict(Xtest_dm)
```

```
[9]: for doc, p in zip(Xtest, pred):
      p = 'pos' if p == 1 else 'neg'
      print("%s -> %s" % (doc, p))
```

I can't deal with this -> neg  
 I do not like the taste of this juice -> neg  
 I love to dance -> neg  
 This is an amazing place -> pos  
 What a great holiday -> pos

```
[10]: from sklearn.metrics import accuracy_score, confusion_matrix, precision_score, recall_score
       print('Accuracy Metrics: \n')
       print('Accuracy: ', accuracy_score(ytest, pred))
       print('Recall: ', recall_score(ytest, pred))
       print('Precision: ', precision_score(ytest, pred))
       print('Confusion Matrix: \n', confusion_matrix(ytest, pred))
```

Accuracy Metrics:

Accuracy: 0.8

Recall: 0.6666666666666666

Precision: 1.0

Confusion Matrix:

[[2 0]

[1 2]]

## Practical : 7

Aim: Write a program to construct a Bayesian network considering medical data. Use this model to demonstrate the diagnosis of heart patients using standard Heart Disease Data Set. You can use Java/Python ML library classes/API

```
import numpy as np
import pandas as pd
import csv
from pgmpy.estimators import MaximumLikelihoodEstimator
from pgmpy.models import BayesianModel
from pgmpy.inference import VariableElimination

heartDisease = pd.read_csv('heart.csv')
heartDisease = heartDisease.replace('?', np.nan)

print('Sample instances from the dataset are given below')
print(heartDisease.head())
```

Sample instances from the dataset are given below

	age	sex	cp	trestbps	chol	fbs	restecg	thalach	exang	oldpeak	slope	\
0	63	1	1	145	233	1	2	150	0	2.3	3	
1	67	1	4	160	286	0	2	108	1	1.5	2	
2	67	1	4	120	229	0	2	129	1	2.6	2	
3	37	1	3	130	250	0	0	187	0	3.5	3	
4	41	0	2	130	204	0	2	172	0	1.4	1	

	ca	thal	heartdisease
0	0	6	0
1	3	3	2
2	2	7	1
3	0	3	0
4	0	3	0

```
print('\n Attributes and datatypes')
print(heartDisease.dtypes)
```

```
Attributes and datatypes
age                int64
sex                int64
cp                int64
trestbps           int64
chol              int64
fbs               int64
restecg           int64
thalach           int64
exang             int64
oldpeak           float64
slope             int64
ca                object
thal              object
heartdisease       int64
dtype: object
```



```

model= BayesianModel([('age','heartdisease'),('sex','heartdisease'),('exang','heartdisease'),('cp','heartdisease'),
 ('heartdisease','restecg'),('heartdisease','chol')])
print('\nLearning CPD using Maximum likelihood estimators')
model.fit(heartDisease,estimator=MaximumLikelihoodEstimator)

print('\n Inferencing with Bayesian Network:')
HeartDiseasetest_infer = VariableElimination(model)

print('\n 1. Probability of HeartDisease given evidence= restecg')
q1=HeartDiseasetest_infer.query(variables=['heartdisease'],evidence={'restecg':1})
print(q1)

```

Learning CPD using Maximum likelihood estimators

Inferencing with Bayesian Network:

1. Probability of HeartDisease given evidence= restecg

heartdisease	phi(heartdisease)
heartdisease(0)	0.1016
heartdisease(1)	0.0000
heartdisease(2)	0.2361
heartdisease(3)	0.2017
heartdisease(4)	0.4605

```

print('\n 2. Probability of HeartDisease given evidence= cp ')
q2=HeartDiseasetest_infer.query(variables=['heartdisease'],evidence={'cp':2})
print(q2)

```

2. Probability of HeartDisease given evidence= cp

heartdisease	phi(heartdisease)
heartdisease(0)	0.3742
heartdisease(1)	0.2018
heartdisease(2)	0.1375
heartdisease(3)	0.1541
heartdisease(4)	0.1323