Quotation No : Q26000500

Date : 16-Sep-2026

Kanworks Engineering Solutions
89, St. No. 5, Jeevan Nagar, Focal Point
LUDHIANA
PUNJAB

Kind Attention : Mr./Ms. Himalaya Kanwar

Dear Sir,

We understand that in industry, reliability is not just a requirement,it is the foundation of success.
That is why Absstem Industrial PSA Generator is more than just a product; it is a commitment to excellence, efficiency, and uninterrupted performance.

Every component is designed with precision and innovation, ensuring that each molecule of oxygen and nitrogen is delivered with the utmost purity.

With fully automated operation, our system seamlessly integrates into your processes, reducing manual intervention and maximizing productivity.

Moreover, our industry-leading air ratio ensures that you achieve the highest efficiency, optimizing energy consumption while maintaining peak performance.
And because we believe in standing by our craftsmanship, we offer an unmatched-10 year warranty on sieves, giving you the peace of mind that your investment is protected for the long run.

We have attached the detailed quotation for your review.

Should you have any questions or require further customization to meet your specific needs, please do not hesitate to reach out.

We are here to provide not just a product but a solution that breathes life into your operations.

We look forward to the opportunity to serve you and build a lasting partnership.

Thanks and Regards,

For Absstem Industrial Solutions Pvt. Ltd.


Arifa Zaidi
Assistant Manager Business Development
9218108184
www.absstem.com

nGENX POWERED BY ABSSTEM INDUSTRIAL

Industrial
PSA Nitrogen Generator



PSA Technology



PSA (PRESSURE SWING ADSORPTION)

Industrial Nitrogen Generator mainly consists of two adsorbers filled with carbon molecular sieves. Pressurized air is passed through one of these adsorbers, carbon having the property to attract oxygen, adsorbs oxygen from air and Nitrogen is allowed to pass through and move into the storage tank as the final product. As the adsorber approaches saturation, the air is allowed to pass through the other adsorber while this adsorber is being regenerated to ensure a continuous supply of Nitrogen. This changeover takes place through a specially designed microcontroller to ensure a hassle-free operation. The quality of Nitrogen produced is monitored by a Nitrogen analyser.

- Shipped ready for installation
- 5 minutes to run and never have to stop it!
- Easy installation
- Low operating expenses compared to gas cylinders/liquid Nitrogen
- Maintenance costs are very less
- Embedded Safety Interlocks
- Space-saving design
- Eliminates all hazards which are there with gas cylinder or liquid Nitrogen
- Longevity: at least 10 years

Description

a.	Product Name	Nitrogen Gas Generator

Absstem Industrial Solutions Pvt. Ltd.
Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122051
Contact - 1800 3010 3394 Email - indsales@absstem.com
CIN: U29256HR2022PTC103387

b. Model Range nGENX
Technology PSA (Pressure Swing Adsorption)

Specifications

a.	Nitrogen Flow Rate	As per Performance Sheet
b.	Nitrogen Purity	As per Performance Sheet
c.	Nitrogen Delivery Pressure	6.5 Barg (Higher Pressure Options Available)
d.	Ambient conditions	
	Temperature	0 to 50 Deg. Celsius
	Relative Humidity	up to 80 % (Max.)
	Altitude	up to 1000 m above Sea level

Scheme Offered – (PSA Only)

This scheme will comprise of

- Air package with inlet air filtration system
  (Air compressor, Air dryer, Water Separator, Oil filters)
- Industrial Nitrogen generator
- Storage Tank
- Nitrogen Analyzer
- Alarm panel

Unique Features of Absstem

a. All the fabricated items are cleaned and degreased following our strict quality policy.
b. All the Instruments are specially manufactured to make them suitable for Nitrogen gas.
c. Guaranteed 10+ years of healthy life.
d. We provide the purest **Nitrogen** in Industry.
e. Data logging and Graphical Reports for all parameters available.
f. Test certificates of all instruments are available on demand.


Onsite Gas Generation vs Liquid Tank/Cylinder Alternative

Non-stop availability: 24 hours a day, 7 days a week
Easy integration within existing installations
Your own independent supply of industrial gas
Significant economies for scale and lower operational costs: no rental charges, logistical expenses and bulk user evaporation losses
No safety hazards when handling high-pressure cylinders

Absstem Industrial Solutions Pvt. Ltd.
Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122051
Contact - 1800 3010 3394 Email - indsales@absstem.com
CIN: U29256HR2022PTC103387

Equipment Description

The Industrial Nitrogen Generator consists of



Air Compressor	An Air compressor is used to compress the atmospheric air to a pressure required for the separation of **Nitrogen** from the air.
Refrigeration dryer	Compressed air then passes through a refrigerated dryer to remove moisture (which is harmful to sieves) from the air.
Air Tank	Dry air is collected in an air tank to remove the pulsations which serve the dynamic (changing) requirement of air by the PSA system.
Multistage Filtration system	Before air enters the PSA system, it is passed through multistage filtration removing moisture, particulates and oil content to the specified levels.
PSA system	Pressurized air is passed through PSA Towers filled with Molecular sieves to separate **Nitrogen** from Air.
Storage Tank	Industrial Grade **Nitrogen** produced from NGEN is stored in this tank to supply a continuous flow of **Nitrogen**.
Nitrogen Analyzer	Nitrogen produced is monitored by a **Nitrogen** analyser. In case, O2 purity goes below the specified level, it gives an alarm and switches it to vent mode.

EYE-SMART Control System

(User-friendly interface for easy operation and maintenance)

Absstem industrial Nitrogen generator complies with all industry standards and regulation

- Alarm management system
- Plug and play
- Fully automatic
- Process data display
- Consumables running hours display
- Data logging



Absstem Industrial Solutions Pvt. Ltd.
Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122051
Contact - 1800 3010 3394 Email - indsales@absstem.com
CIN: U29256HR2022PTC103387

Additional upgrades

- Digital flow meter with totaliser
- High-pressure Nitrogen tank
- Cylinder manifold and alarm management system
- Remote monitoring- IoT Ready

Plant Operation

- Unit operates 24-hrs a day, 7-days a week reliably, automatically & safely

Automation

- The Plant is fully automatic and needs only electrical power for running the Air compressor
- The machine automatically enters into standby mode when the level in the Storage Tank reaches its set limit. This helps to increase the life of the Air compressor.

International Quality standards

A strict quality procedure, following the leading international pharmacopoeia and Industrial directives, is followed in the selection of all mechanical and electrical instruments, vessel fabrication and designing of Industrial Nitrogen generators.

Itemised Supply description

No.	Item description	Make	Qty
a	Air Compressor with Filters	ABSSTEM APPROVED	Client Scope / Quoted Separately
b	Refrigeration Dryer	ABSSTEM APPROVED	Client Scope / Quoted Separately
c	Air Tank	ABSSTEM	Client Scope / Quoted Separately
d	Set of Filters	ABSSTEM	1 no.
e	PSA unit (NGEN)	ABSSTEM	1 no.
f	Electrical Panel	ABSSTEM	1 no.
f	Digital Nitrogen Analyzer	ABSSTEM	1 no.
g	Storage Tank	ABSSTEM	1 no.
h	Outlet product gas Filter	ABSSTEM	1 no.

Absstem Industrial Solutions Pvt. Ltd.
Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122051
Contact - 1800 3010 3394 Email - indsales@absstem.com
CIN: U29256HR2022PTC103387

Electrical Protection

The client should make proper arrangements for earthing/grounding systems for the Industrial **Nitrogen** Generator at their facility.

Enclosure Panel

- Ergonomically designed metal enclosure with powder-coated finish for longer life.
- High-strength IP-rated panel fittings from Germany for a robust enclosure.
- Fan filters IP-55 rated making the electrical enclosure's internal environment dust-free.
- Easy connectivity to any place of installation with req. port connections.
- High-strength base frame designed for higher load and easy transportation.
- Vessels are designed per ASME section VIII DIV I. Vessels are epoxy paint coated which is considered good for longevity and corrosion resistance.
- All electrical items are CE certified with operating voltage at 24 VDC

Annual Maintenance Contract (AMC)

Our in-house support Absstem shield is 24*7 open and we assure a timely service maintenance schedule. Per the schedule mentioned in the operational manual, we suggest the operator change the filters by following a simple protocol.

It is very easy to change or replace as our commissioning engineer plus our commissioning engineer and tech support office will always guide you about the activity.

Best ROI Guaranteed

ROI within 6 to 18 months when compared to conventional methods

Generator performance depends on the component selection. Our processes make this job easier as all equipment is selected based on more than 3 decades of research. NGEN is a fully automatic (operator-free operation) that ensures peace of mind.

We deliver what we commit!!

Thank You

Absstem Industrial Solutions Pvt. Ltd.
Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122051
Contact - 1800 3010 3394 Email - indsales@absstem.com
CIN: U29256HR2022PTC103387

MINIMUM SPECIFICATIONS FOR FOOD GAS APPLICATIONS

Doc 126/18

Revision of Doc 126/11

EUROPEAN INDUSTRIAL GASES ASSOCIATION AISBL

AVENUE DES ARTS 3-5 • B – 1210 BRUSSELS
Tel: +32 2 217 70 98 • Fax: +32 2 219 85 14
E-mail: info@eiga.eu • Internet: www.eiga.eu

Appendix 1 - Summary of Current Gases Specifications in EU Legislation and JECFA


Component / Impurity	Standard	Carbon dioxide E 290	Nitrogen E 941	Oxygen E 948	Argon E 938	Helium E 939	Nitrous oxide E 942	n-/iso-Butane E 943 a/b	Propane E 944	Hydrogen E 949	Sulfur dioxide E 220
Assay (v/v)	EC	>99%	>99%	>99%	>99%	>99%	>99%	>96%/>94%	>95%	>99,9%	>99 %
	JECFA	>99%	>99%	>99%	>99%	>99%	>97%				>99,9 %
Odour	EC										
	JECFA			Free	free	free					
Moisture	EC		<0,05%	<0,05%	<0,05%	<0,05%	<0,05%	<50vppm	<50vppm	<50vppm	<0,05%
	JECFA	<52 vppm									<0,05%
CO_2	EC										
	JECFA			<300 vppm							
CO	EC	<10 vppm	<10 vppm				<30 vppm				
	JECFA	<10 vppm	<10 vppm	<10 vppm		<10 vppm	<10 vppm				
NO/NO_2	EC		<10 vppm				<10 vppm				
	JECFA						<5 vppm				
Total Hydrocarbon	EC		<100 vppm	<100 vppm	<100 vppm	<100 vppm		see *	see **		
	JECFA	<50vppm									
Residual Gases (O_2, N_2, H_2)	EC		< 1 % (O2)							<0.07%	
	JECFA				<1%						
Oil	EC	<5mg/kg									
	JECFA	<10 ppmw									
Acidity & Red. Subst.	EC	pass test									
	JECFA	pass test									
Halogens & H_2S	EC										
	JECFA						<5 vppm				
Other comp. & Heavy metals	EC										see***
	JECFA										see****

* Methane < 0,15%, other hydrocarbons < 5,1%. For E943a the maximum limit of hydrocarbons are:
C_2H_6 < 0,5%;
C_3H_8<1,5%;
i-C_4H_{10}<3%,
1.3-C_4H_6<0,1%

** Methane < 0,15%, other hydrocarbons are < 6,6%. For E943b the maximum limit of hydrocarbons are:
C_2H_6 < 0,5%;
C_3H_8<2,0%;
i-C_4H_{10}<4%,
1.3-C_4H_6<0,1%

*** EC Directive 2008/84 [2]: Non-volatile residue <0.001 %, Sulphur trioxide < 0,1 %, Selenium < 10 mg/kg, Arsenic <3mg/kg, Lead <5mg/kg, Mercury <1mg/kg, Heavy metals (as Pb) <10 mg/kg

**** JECFA (1998) [3]: Non-volatile residue <0,05%, Selenium <20 mg/kg, Lead <5mg/kg ,Other gases not present in air : No trace



HA Series Gas Booster Pump

Air Driven Gas Booster of HA Series

HA series gas booster pump are compressed air single-driven single-acting gas booster pumps with the advantages of high safety, high output pressure, no energy consumption for pressure maintenance and some products are equipped with gas rapid cooing devices.

- Gas drive prevents the medium from generating heat, sparks and flames during transmission, and the pressurization is safe;
- The driving gas does not require lubrication and is completely isolated from the pressurized medium to ensure the cleanliness of the medium;
- The maximum output pressure can reach 830bar;
- Applicable to various media such as oxygen, nitrogen, methane, carbon dioxide, etc.
- The product is reliable, easy to maintain, strong, has a long sealing life, and can be started and stopped continuously.

Main features:

- Based on static pressure, when the driving air pressure is 7 bar, the air consumption is 1.1.5m3 / min Drive pressure 1 bar-8.3 (14.5-120.35psi) HA series is single drive piston (160mm).
- The medium temperature is not higher then 115°C(240°F) and order for extremely low temperature must be specified.
- The high-pressure end material can be customized to 17-4PH 15-5PH, 44 OC, nickel-based alloy, Hastelloy and other materials to meet special medium requirements.
- GB series standrad products are nitrogen boosted, order code such as: HA40 (series + boost ratio)

Special Product Description:

About the medium: HA series can be used for a variety of media, order code such as: HA30-O2 (series code + boost ratio + boost medium) About the interface: If you need a special medium interface, please indicate it when ordering.

Application Scenario:


- HA Series gas Booster Pumps are the suitable for application with high gas source, high output pressure and small flow requirements.
- Air tightness test of various of pressure components;
- Nitrogen filling of high pressure accumulators;
- Filling of diving breathing oxygen cylinders;
- Filling of diving breathing oxygen cylinders;
- Calibration of high pressure safety valves;
- The reaction device is filled with reaction medium;
- Recovery and reuse of spacial gases;


TECHNICAL PARAMETERS (Pa=Driving Air Pressure Pi=Input Air Pressure Po=Output Air Pressure)

Model	Pressure Ratio	Minimum gas inlet pressure Pi (bar)	Maximum allowable outlet pressure Po (bar)	Gas outlet pressure calculation formula Po=	Gas Inlet In	Gas Outlet Out	Max flow rate standard liters per minute (NL/Min)
HA02T	2.5 : 1	0	20.75	2.5Pa+Pi	NPT1/2"	NPT1/2"	522@Pi=7
HA04	4 : 1	1.2	33.2	4Pa	NPT1/2"	NPT1/2"	354@Pi=7
HA05T	5 : 1	1.7	41.5	4Pa+Pi	NPT1/2"	NPT1/2"	572@Pi=7
HA07	7 : 1	3.4	58.1	7Pa	NPT3/8"	NPT3/8"	252@Pi=7
HA08T	8 : 1	3.4	66.4	7Pa+Pi	NPT3/8"	NPT3/8"	362@Pi=7
HA10	10 : 1	6.5	83	10Pa	NPT3/8"	NPT3/8"	196@Pi=7
HA15	15 : 1	8.1	124.5	15Pa	NPT3/8"	NPT3/8"	164@Pi=10
HA30	30 : 1	18	265.6	30Pa	NPT1/4"	NPT1/4"	91@Pi=20
HA40	40 : 1	25	332	40Pa	NPT1/4"	NPT1/4"	156@Pi=40
HA60	60 : 1	32	498	60Pa	NPT1/4"	NPT1/4"	112@Pi=40
HA75	75 : 1	32	622	75Pa	NPT1/4"	NPT1/4"	86@Pi=40
HA100	100 : 1	40	830	100Pa	NPT1/4"	NPT1/4"	65@Pi=40


@ Represents Under Certain Conditions, For Example: 100@pi=7, Which Means That The Flow Rate Is 100nl/min Under The Input Pressure Of 7bar.

Quality | Efficiency | Reliability







HA02T, HA05T, HA08T




HA04, HA07



Working Principle



HA10, HA15, HA30, HA60, HA100



Installation Size/(mm)												
Model	Actuating air connection (AIR IN)	A	B	C	D	E	F	G	H	Mounting Holes	Cooling Function	Weight /kg
HA02T	G1/2"	448.5	218	219.5	94	240	172	100	420	4-φ12*22	/	24
HA04	G1/2"	391	218	161.5	94	240	172	100	180	4-φ12*22	/	15
HA05T	G1/2"	435.5	218	206.5	94	240	172	100	360	4-φ12*22	/	20
HA07	G1/2"	462	258	193	94	240	172	100	/	4-φ12*22	/	14
HA08T	G1/2"	435.5	218	206.5	94	240	172	100	360	4-φ12*22	/	17
HA10	G1/2"	460	258	191	94	240	172	100	/	4-φ12*22	●	14
HA15	G1/2"	460	258	191	94	240	172	100	/	4-φ12*22	●	14
HA30	G1/2"	447	258	178	94	240	172	100	/	4-φ12*22	●	15
HA40	G1/2"	447	258	178	94	240	172	100	/	4-φ12*22	●	15
HA60	G1/2"	447	258	178	94	240	172	100	/	4-φ12*22	●	15
HA75	G1/2"	447	258	178	94	240	172	100	/	4-φ12*22	●	15
HA100	G1/2"	447	258	178	94	240	172	100	/	4-φ12*22	●	17

Product Description

Product	Description	Make	Qty
nGenx Nitrogen Generator	nGenXC Nitrogen		1

Caption	Specification
N2 Flow	2 Nm3/hr
N2 Purity	99.9%
N2 Storage Tank Volume	150 liters
N2 Pressure	5.5 to 6.5 Barg
Dry Air Required	8 CFM at 7 Barg Pressure

Product	Description	Make	Qty
Pneumatic Booster	HB7/32-SS Booster		1

Caption	Specification
Gas Media	Dry Nitrogen Gas
Pressure Boost Ratio	32:1
Max. gas Inlet Pressure	20 Barg
Max. gas Outlet Pressure	259 Barg
Customer Set Pressure	120 Barg
Driven Air Pressure	2-8.3 Barg
Driven Airflow	35-45 CFM
Max. flow at driven air pressure of 7 Barg	118 LPM
Inclusions	a) 304SS Frame work & control panel, 316SS Tubing & Fittings b) Air regulator with filter, Air control valve c) Pressure gauge for air, N2 inlet and outlet and needle valves for smooth operation
Duty Cycle	This equipment is suitable for intermediate duty and 14-18 hours running per day.

Absstem Industrial Solutions Pvt. Ltd.
Ground Floor, Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122052
Contact: 1800 547 0506 | indsales@absstem.com
CIN: U29256HR2022PTC103387

Commercial Offer

S No	Item Code	Item Name	Description	HSN	Qty	Unit Price	Discount	GST(%)	Amount
1	NGN2	nGenXC	nGenx Nitrogen Generator	840510	1	5,25,000.00	1,05,000.00	18.00	4,20,000.00
2	BOS41	HB7/32-SS	Pneumatic Booster		1	5,54,000.00	1,10,800.00	18.00	4,43,200.00

Sub Total	8,63,200.00
GST(%) @18.00	1,55,376.00
Grand Total (INR)	10,18,576.00

Absstem Industrial Solutions Pvt. Ltd.
Ground Floor, Plot No. 591, Sector 8, Phase IV
IMT Manesar, Gurugram, Haryana - 122052
Contact: 1800 547 0506 | indsales@absstem.com
CIN: U29256HR2022PTC103387

Terms And Conditions

1.	EXCLUSIONS & CLIENTS SCOPE	All erection / civil work, All Power Cables & Cabling out of battery limit of PSA Plant, Cable Trenches etc. Unloading / Shifting of Gas Plant at Clients site will be in Client Scope. Additional gas piping, cooling water (if required).
2.	SUPERVISION OF ERECTION & COMMISSIONING	There shall be no commissioning charges, however you shall arrange freeTo & Fro Air Ticket, lodging / boarding, and local conveyance for our Engineers during supervision of Installation of Gas Plant at site on free of cost basis. Our Engineers will be there for Supervision only. Any manpower / fitter required for installation work shall be provided by you.
3.	P&F	3% Extra.
4.	Freight	Extra at Actuals.
5.	Insurance	In your Scope.
6.	Payment Terms	50% Advance with your Prestegious Purchase Order and Balance against PI.
7.	Delivery	6-8 Weeks from the PO and Advance. Rest can be confirmed for Availability.
8.	Warranty	We hereby confirm that, our equipment shall have Suppliers warranty for a period of 12 months from the date of Commissioning or 18 months from date of Dispatch whichever is earlier.
9.	GST	As per the Commercial Table.
10.	Remarks	.

Hope you will find our offer in line with your requirement.

Should you require any further clarification/information, please feel free to contact us.

Thanking you, and assuring you of our best attention at all times.

Very Yours truly,

For Absstem Industrial Solutions Pvt. Ltd.

Arifa Zaidi

Assistant Manager Business Development

9218108184

www.absstem.com