

## Exp No 3

### Map Reduce program to process a weather dataset Aim:

To implement MapReduce program to process a weather dataset.

#### Procedure:

##### Step 1: Create Data File:

Create a file named "word\_count\_data.txt" and populate it with text data that you wish to analyse.

Login with your hadoop user.

description

dataset.txt

X

+

File

Edit

View

<

##### Step 2: Mapper Logic - mapper.py:

Create a file named "mapper.py" to implement the logic for the mapper. The mapper will read input data from STDIN, split lines into words, and output each word with its count.

nano mapper.py

# Copy and paste the mapper.py code

```
#!/usr/bin/env python
import sys

# input comes from STDIN (standard input)

# the mapper will get daily max temperature and group it by month. so output will be
(month,dailymax_temperature)

Download the dataset (weather data) for
line in sys.stdin:

# remove leading and trailing whitespace
line = line.strip() # split the line into
words words = line.split()

#See the README hosted on the weather website which help us understand how each
position represents a column month = line[10:12] daily_max = line[38:45]
daily_max = daily_max.strip() # increase counters for word in words:

# write the results to STDOUT (standard output);

# what we output here will be go through the shuffle process and then

# be the input for the Reduce step, i.e. the input for reducer.py

#

# tab-delimited; month and daily max temperature as output
print ("%s\t%s" % (month ,daily_max))

.
```

### Step 3: Reducer Logic - reducer.py:

Create a file named "reducer.py" to implement the logic for the reducer. The reducer will aggregate the occurrences of each word and generate the final output.

nano reducer.py

# Copy and paste the reducer.py code reducer.py

```
#!/usr/bin/env python from
operator import itemgetter
import sys

#reducer will get the input from stdid which will be a collection of key, value(Key=month ,
value= daily max temperature)

#reducer logic: will get all the daily max temperature for a month and find max temperature
for the month

#shuffle will ensure that key are sorted(month)

current_month = None current_max = 0

month = None

# input comes from STDIN for

line in sys.stdin:

    # remove leading and trailing whitespace

    line = line.strip()

    # parse the input we got from mapper.py

    month, daily_max = line.split('\t', 1)

    # convert daily_max (currently a string) to float

    try:

        daily_max = float(daily_max)

    except ValueError:

        # daily_max was not a number, so silently

        # ignore/discard this line

        continue

    # this IF-switch only works because Hadoop shuffle process sorts map output
```

```
# by key (here: month) before it is passed to the reducer
if current_month == month:    if daily_max >
current_max: current_max = daily_max
else: if current_month: # write result to
STDOUT print ('%s\t%s' % (current_month,
current_max)) current_max = daily_max
current_month = month # output of the last
month if current_month == month: print
('%s\t%s' % (current_month, current_max))
```

**Step**

#### **4: Prepare Hadoop Environment:**

Start the Hadoop daemons and create a directory in HDFS to store your data. start-all.sh

#### **Step 5: Make Python Files Executable:**

Give executable permissions to your mapper.py and reducer.py files. chmod

```
777 mapper.py reducer.py
```

#### **Step 6: Run the program using Hadoop Streaming:**

Download the latest hadoop-streaming jar file and place it in a location you can easily access.

Then run the program using Hadoop Streaming. hadoop fs -mkdir -p /weatherdata

```
hadoop fs -copyFromLocal /home/sx/Downloads/dataset.txt /weatherdata hdfs dfs -ls
```

```
/weatherdata hadoop jar /home/sx/hadoop-3.2.3/share/hadoop/tools/lib/hadoop-
streaming-3.2.3.jar \
```

```
-input /weatherdata/dataset.txt \
```

```
-output /weatherdata/output \
```

```
-file "/home/sx/Downloads/mapper.py" \
```

```
-mapper "python3 mapper.py" \
```

```
-file "/home/sx/Downloads/reducer.py" \ -reducer "python3 reducer.py"
```


```
hdfs dfs -text /weatherdata/output/* > /home/sx/Downloads/outputfile.txt
```

### Step 7: Check Output:

Check the output of the program in the specified HDFS output directory. hdfs

```
dfs -text /weatherdata/output/* > /home/sx/Downloads/output/
```

```
/part-00000
```

A terminal window with a dark background. The prompt is 'osboxes@fedora:~\$'. The command entered is 'hdfs dfs -cat /exp3/output/\*'. The output is a list of 12 lines, each with an index and a temperature value. The prompt is followed by a cursor.

```
osboxes@fedora:~$ hdfs dfs -cat /exp3/output/*
01      26.5
02      26.6
03      29.1
04      30.8
05      31.1
06      33.6
07      38.5
08      40.2
09      36.5
10      36.9
11      27.6
12      25.9
osboxes@fedora:~$
```

After copy and paste the above output in your local file give the below command to

remove the directory from hdfs : `hadoop fs -rm -r /weatherdata/output` **Result:**

Thus, the program for weather dataset using Map Reduce has been executed successfully.