

Rajalakshmi Engineering College

Name: Jeevaveni S
Email: 241501076@rajalakshmi.edu.in
Roll no: 241501076
Phone: 9342214985
Branch: REC
Department: I AIML AD
Batch: 2028
Degree: B.E - AI & ML

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
#include<stdio.h>
```

```
#include<string.h>
```

```
#define MAX_CONTACTS 50
```

```
#define MAX_NAME_LEN 11
```

```
#define MAX_PHONE_LEN 15
```

```

typedef struct{
    char name[MAX_NAME_LEN];
    char phone[MAX_PHONE_LEN];
}Contact;

int main(){
    int n,i,j,found=0;
    char key[MAX_CONTACTS];
    Contact contacts[MAX_CONTACTS];

    scanf("%d",&n);
    for(i=0;i<n;i++){
        scanf("%s %s",contacts[i].name,contacts[i].phone);
    }
    scanf("%s",key);
    for(i=0;i<n;i++){
        if(strcmp(contacts[i].name,key) == 0){
            found=1;
            printf("The given key is removed!\n");
            for(j=i;j<n-1;j++){
                contacts[j]=contacts[j + 1];
            }
            n--;
            break;
        }
    }
    if(!found){
        printf("The given key is not found!\n");
    }
    for(i=0;i<n;i++){
        printf("Key: %s;Value: %s\n",contacts[i].name,contacts[i].phone);
    }
    return 0;
}

```

Status : Correct

Marks : 10/10