

GFEA0717 - Bloqueio de Faturas de Frete

 Tempo aproximado para leitura: 4 minutos

GFEA0717 - Bloqueio de Faturas de Frete

Características do Requisito

Linha de Produto:	Microsiga Protheus
Segmento:	Supply Chain - Logística
Módulo:	SIGAGFE

Ponto de Entrada:	GFEA0717			
Descrição:	Bloqueia a Fatura de Frete caso os Documentos de Carga de saída estejam com data de entrega vazio			
Localização:	Na hora de aprovar a Fatura de Frete na função GFEA071RA			
Programa Fonte:	GFEA071 - Auditoria de Faturas de Frete			
Parâmetros:	Não se aplica			
Retorno:	Nome	Tipo	Descrição	Obrigatório
	aRet	Array	Retorna se foi bloqueado e o motivo do bloqueio	Sim

Exemplo: GFEA0717

```
1
2 #INCLUDE "PROTHEUS.CH"
3
4 User Function GFEA0717()
5     Local cCTEs := ""
6     Local aOldArea:= GetArea()
7     Local aRet := {.F.,''} //aRet[Bloqueio,Mensagem bloqueio]
8     Local _cParFil := GW6->GW6_FILIAL
9     Local _cEmiFat := GW6->GW6_EMIFAT
10    Local _cSerFat := GW6->GW6_SERFAT
11    Local _cNumFat := GW6->GW6_NRFAT
12    Local _dDtEmis := DTOS(GW6->GW6_DTEMIS)
13
14    cAliasGWU := GetNextAlias()
15    cQuery := " SELECT GWU.GWU_DTENT, GW3.GW3_NRDF, GW1.GW1_NRDC, GV5.GV5_SENTID, GW6.R_E_C_N_O_ AS GW6RI
16    cQuery += "      FROM " + RetSQLName("GW6") + " GW6, " + RetSQLName("GW3") + " GW3, "
17    cQuery += "      RetSQLName("GW4") + " GW4, " + RetSQLName("GW1") + " GW1, "
```

```

18      cQuery += RetSQLName("GWU") + " GWU, " + RetSQLName("GV5") + " GV5 "
19      cQuery += " WHERE "
20      cQuery += " GW6.GW6_FILIAL = GW3.GW3_FILFAT AND "
21      cQuery += " GW6.GW6_EMIFAT = GW3.GW3_EMIFAT AND "
22      cQuery += " GW6.GW6_SERFAT = GW3.GW3_SERFAT AND "
23      cQuery += " GW6.GW6_NRFAT = GW3.GW3_NRFAT AND "
24      cQuery += " GW6.GW6_DTEMIS = GW3.GW3_DTEMFA AND "
25      cQuery += " GW3.GW3_FILIAL = GW4.GW4_FILIAL AND "
26      cQuery += " GW3.GW3_EMISDF = GW4.GW4_EMISDF AND "
27      cQuery += " GW3.GW3_CDESP = GW4.GW4_CDESP AND "
28      cQuery += " GW3.GW3_SERDF = GW4.GW4_SERDF AND "
29      cQuery += " GW3.GW3_NRDF = GW4.GW4_NRDF AND "
30      cQuery += " GW4.GW4_FILIAL = GW1.GW1_FILIAL AND "
31      cQuery += " GW4.GW4_EMISDC = GW1.GW1_EMISDC AND "
32      cQuery += " GW4.GW4_SERDC = GW1.GW1_SERDC AND "
33      cQuery += " GW4.GW4_NRDC = GW1.GW1_NRDC AND "
34      cQuery += " GW4.GW4_TPDC = GW1.GW1_CDTPDC AND "
35      cQuery += " GWU.GWU_FILIAL = GW1.GW1_FILIAL AND "
36      cQuery += " GWU.GWU_CDTPDC = GW1.GW1_CDTPDC AND "
37      cQuery += " GWU.GWU_EMISDC = GW1.GW1_EMISDC AND "
38      cQuery += " GWU.GWU_SERDC = GW1.GW1_SERDC AND "
39      cQuery += " GWU.GWU_NRDC = GW1.GW1_NRDC AND "
40      cQuery += " GWU.GWU_CDTRP = GW6.GW6_EMIFAT AND "
41      cQuery += " GV5_CDTPDC = GW1_CDTPDC AND "
42      cQuery += " GW6.GW6_FILIAL = '" + _cParFil + "' AND "
43      cQuery += " GW6.GW6_EMIFAT = '" + _cEmiFat + "' AND "
44      cQuery += " GW6.GW6_SERFAT = '" + _cSerFat + "' AND "
45      cQuery += " GW6.GW6_NRFAT = '" + _cNumFat + "' AND "
46      cQuery += " GW6.GW6_DTEMIS = '" + _dDtEmis + "' AND "
47      cQuery += " (GW3.GW3_TPDF = '1' OR GW3.GW3_TPDF = '4') AND " //Normal e Reentrega
48      cQuery += " GW6.D_E_L_E_T_ = ' ' AND "
49      cQuery += " GW3.D_E_L_E_T_ = ' ' AND "
50      cQuery += " GW4.D_E_L_E_T_ = ' ' AND "
51      cQuery += " GW1.D_E_L_E_T_ = ' ' AND "
52      cQuery += " GWU.D_E_L_E_T_ = ' ' AND "
53      cQuery += " GV5.D_E_L_E_T_ = ' ' "
54      cQuery := ChangeQuery(cQuery)
55      cAliasGWU := GetNextAlias()
56      dbUseArea( .T., "TOPCONN", TCGENQRY(,cQuery),cAliasGWU, .F., .T.)
57
58      dbSelectArea(cAliasGWU)
59      (cAliasGWU)->( dbGoTop() )
60      While !(cAliasGWU)->(Eof())
61
62          If (cAliasGWU)->GV5_SENTID == '2'
63              If Empty((cAliasGWU)->GWU_DTENT)
64                  aRet[1] := .T.
65                  If Empty(cCTEs)
66                      cCTEs := AllTrim((cAliasGWU)->GW1_NRDC)
67                  Else
68                      If AT(cCTEs, (cAliasGWU)->GW1_NRDC) == 0 //Se não encontrar o Doc de Carga, adiciona
69                          cCTEs += ', ' + AllTrim((cAliasGWU)->GW1_NRDC)
70                      EndIf
71                  EndIf
72              EndIf
73          EndIf
74          (cAliasGWU)->(dbSkip())

```

```
75      EndDo
76      (cAliasGWU)->(dbCloseArea())
77
78      If aRet[1]
79          aRet[2] := "Documento(s) de Carga " + cCTEs + " não possui(em) entrega informada."
80
81          MsgInfo("Documento(s) de Carga " + cCTEs + " não possui(em) entrega informada.")
82      EndIf
83
84      RestArea(aOldArea)
85
      Return aRet
```

[ponto_de_entrada](#) [logistica](#) [protheus](#) [sigagfe](#)
[base_de_conhecimento](#) [bra](#) [mp_gfe_inov](#)
[versao_12_1_17](#) [gfea1158](#)



[Política de
privacidade](#)

[Termos
de uso](#)