Features/Benefits

- Variety of actuators & terminations
- PC and panel mounting
- Shorting or non-shorting contacts
- RoHS compliant
- Halogen free material

Typical Applications

- Test & measurement equipment
- Computer peripherals & network products
- Consumer products



Specifications

CONTACT RATING: See individual parts. MECHANICAL & ELECTRICAL LIFE: 10,000 cycles.

CONTACT RESISTANCE: 20 m Ω or less.

INSULATION RESISTANCE: 100 M Ω min. at 500 VDC. DIELECTRIC STRENGTH: 500 VAC for 1 minute. OPERATING TEMPERATURE: -30°C to +70°C.

PACKAGING: Bulk

Materials

BASE: Phenolic resin.

ACTUATOR: Standard: POM. Black.

High Temperature Option: PA46, Black.

HOUSING PLATE: Non-compatible; SPCC Sn plated.

Compatible; SPCC Ni plated.

MOVABLE CONTACT: Copper alloy, silver plated. STATIONARY CONTACTS: Brass, silver plated.

TERMINALS: Brass, silver plated.

TERMINAL SEALED.

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center


How To Order

Complete part numbers for OS Series Slide Switches are shown on pages I-37 through I-43.

			SWITCH F	UNCTION		
			POS.1	POS.2		
PART NUMBER	RoHS Compliant	RoHS Compatible	4	4		
OS102011MS2QN1 (non-shorting)	YES	NO	ON	ON		
OS102011MS2QN1C* (non-shorting)	YES	YES	ON	ON		
OS102011MS2QS1 (shorting)	YES	NO	ON	ON		
OS102011MS2QS1C* (shorting)	YES	YES	ON	ON		
CONN. TERMINALS			1-2	2-3		
SCHEMATIC C ① ② ③						
SPDT	ļ					


CONTACT RATING: 0.1A @ 12 VDC

^{* &}quot;C" option at the end of part number designates high temperature actuators





-.496 -(12,60)





			SWI	TCH FUNC	TION	
			POS.1	POS.2	POS.3	
PART NUMBER	ROHS Compliant	ROHS Compatible	4	4	1	
OS103011MS8QP1 (Non-specified)	YES	NO	ON	ON	ON	_
OS103011MS8QP1C* (Non-specified)	YES	YES	ON	ON	ON	
CONN. TERMINALS			1-2	2-3	2-4	


SCHEMATIC




SP3T

CONTACT RATING: 0.1A @ 12 VDC

[&]quot;C" option at the end of part number designates high temperature actuators



.240





Dimensions are shown: Inches (mm) Specifications and dimensions subject to change




.079 (2,00)

.079 TRAVEL (2,00)

(4,00)

^{*} For RoHS compatible switches contact customer service.


OS202011MS2QS1 **DPDT**



			SWITCH F	UNCTION		
			POS.1	POS.2		
PART NUMBER	RoHS Compliant	RoHS Compatible				
OS202011MS2QS1 (Shorting)	YES	NO	ON	ON		
OS202011MS2QN1 (Non-shorting)	YES	NO	ON	ON		
CONN. TERMINALS			1-2, 4-5	2-3, 5-6		
SCHEMATIC	0 2 3					
DPDT		4 5 0	6			

CONTACT RATING: 0.1A @ 12 VDC






Actuator shown in pos. 2

			SWI	TCH FUNC	TION
			POS.1	POS.2	POS.3
PART NUMBER	ROHS Compliant	ROHS Compatible	1	1	_
OS203011MS1QP1 (Non-specified)	YES	NO	ON	ON	ON
CONN. TERMINALS			1-3, 5-7	2-3, 6-7	3-4, 7-8
SCHEMATIC			P P C	3 C 4	
DP3T			5 6 0	8	


CONTACT RATING: 0.3A @ 30 VDC



OS202013MT5QN1 **DPDT**



Actuator shown in pos. 1






Dimensions are shown: Inch (mm)
Specifications and dimensions subject to change




.209 (5,30)

OS Series Miniature Slide Switches








Actuator shown in pos. 3

			SWITCH FUNCTION		
			POS.1	POS.2	
PART NUMBER	RoHS Compliant	RoHS Compatible			
OS202013MT8QN1 (Non-shorting)	YES	NO	ON	ON	
CONN. TERMINALS			1-2, 4-5	2-3, 5-6	
SCHEMATIC		9	° 3		
DPDT		4	5 6 0		

CONTACT RATING: 0.3A @ 30 VDC




Actuator shown in pos. 1



			SWITCH FUNCTION		
			POS.1	POS.2	POS.3
PART NUMBER	ROHS Compliant	ROHS Compatible	1	1	1
OS203013MT8QN1 (Non-shorting)	YES	NO	ON	ON	ON
CONN. TERMINALS			1-2, 5-6	2-3, 6-7	3-4, 7-8
SCHEMATIC			1 2	3 4	
			5 6	7 8	
DP3T					

CONTACT RATING: 0.3A @ 30 VDC






Dimensions are shown: Inches (mm) Specifications and dimensions subject to change .118

Actuator shown in pos. 3



OS203013MT6QN1 **DP3T**




			SWITCH FUNCTION			
			POS.1	POS.2	POS.3	
PART NUMBER	ROHS Compliant	ROHS Compatible	1	4	4	
OS203013MT6QN1 (Non-shorting)	YES	NO	ON	ON	ON	
CONN. TERMINALS			1-2, 5-6	2-3, 6-7	3-4, 7-8	



CONTACT RATING: 0.2A @ 30 VDC



OS103012MU1QP1 **SP3T**




			SWI	TCH FUNCTION		
			POS.1	POS.2	POS.3	
PART NUMBER	ROHS Compliant	ROHS Compatible	1	1	_	
OS103012MU1QP1 (Non-shorting)	YES	NO	ON	ON	ON	
CONN. TERMINALS			1-2	2-3	2-4	
SCHEMATIC						
		Ţļ	II.	Ţ		

CONTACT RATING: 0.2A @ 30 VDC


SP3T




OS103012MU2QP1 **SP3T**




Actuator shown in pos. 1



Actuator shown in pos. 1



PC MOUNTING



			SWITCH FUNCTION			
			POS.1	POS.2	POS.3	
PART NUMBER	ROHS Compliant	ROHS Compatible		4	4	
OS103012MU2QP1 (Non-shorting)	YES	NO	ON	ON	ON	
CONN. TERMINALS			1-2	2-3	2-4	
SCHEMATIC						
	Ф <mark>с</mark>					

SCHEMATIC

C 2 3 4


SP3T


CONTACT RATING: 0.2A @ 30 VDC




Dimensions are shown: Inch (mm)
Specifications and dimensions subject to change











POS.1

ON

ROHS

NO

SWITCH FUNCTION

POS.2

ON

POS.3

ON

2-4, 6-8



PART NUMBER

(Non-specified)


SCHEMATIC

DP3T


OS203012MU5QP1

CONN. TERMINALS


ROHS




ACTUATOR SHOWN IN POS. 1










Actuator shown in pos. 1





OS202011MV4QN1 .118 **DPDT** ▼.157 (4,00) .098


ø.031 TYP. (0,80)

.098 (2,50)


			SWI	TCH FUNC	TION
			POS.1	POS.2	POS.3
PART NUMBER	ROHS Compliant	ROHS Compatible	1	1	1
OS203011MV9QS1 (Shorting)	YES	NO	ON	ON	ON
OS203011MV9QN1 (Non-Shorting)	YES	NO	ON	ON	ON
CONN. TERMINALS			1-2-5 6-7-10	1-3-5 6-8-10	1-4-5 6-9-10
SCHEMATIC			c (2)	3 4 5	

CONTACT RATING: 0.1A @ 30 VDC

DP3T



.276 (7,00)	
(12,70)	
.020 (0,50)	.0
os 2(A)	



PC MOUNTING

. 551 (14,00)

.079 TYP

2X Ø.071 (1,80)




Dimensions are shown: Inches (mm) Specifications and dimensions subject to change




OS203011MV9QS1 DP3T

.173 (8,60) (4,40) (4,0) (4,0)

OS102011MA1QN1 SPDT



Actuator shown in pos. 2



PC MOUNTING


			SWITCH F	UNCTION
			POS.1	POS.2
PART NUMBER	RoHS Compliant	RoHS Compatible		
OS102011MA1QN1 (Non-shorting)	YES	NO	ON	ON
OS102011MA1QN1C* (Non-shorting)	YES	YES	ON	ON
OS102011MA1QS1 (Shorting)	YES	NO	ON	ON
OS102011MA1QS1C* (Shorting)	YES	YES	ON	ON
CONN. TERMINALS			1-2	2-3
SCHEMATIC		C	^	
		0 2	3	
SPDT				


CONTACT RATING: 0.1A @ 12 VDC


* "C" option at the end of part number designates high temperature actuators



OS103011MA7QP1 **SP3T**







			SWITCH FUNCTION		
			POS.1	POS.2	POS.3
PART NUMBER	ROHS Compliant	ROHS Compatible	1	Þ	1
OS103011MA7QP1 (Non-specified)	YES	NO	ON	ON	ON
OS103011MA7QP1C* (Non-specified)	YES	YES	ON	ON	ON
CONN. TERMINALS			1-2	2-3	2-4
SCHEMATIC	•				
		C			


CONTACT RATING: 0.1A @ 12 VDC

SP3T


* "C" option at the end of part number designates high temperature actuators



OS203011MA2QP1 **DP3T**



Actuator shown in pos. 3



			SWITCH FUNCTION		
			POS.1	POS.2	POS.3
PART NUMBER	ROHS Compliant	ROHS Compatible	•	4	4
OS203011MA2QP1 (Non-specified)	YES	NO	ON	ON	ON
CONN. TERMINALS			1-2, 5-6	2-3, 6-7	2-4, 6-8
SCHEMATIC		1 °	2 3 4)	
		\$ c	678)	
DP3T					
	OS203011MA2QP1 (Non-specified) CONN. TERMINALS SCHEMATIC	PART NUMBER Compliant OS203011MA2QP1 (Non-specified) CONN. TERMINALS SCHEMATIC	PART NUMBER Compilant Compatible OS203011MA2QP1 (Non-specified) CONN. TERMINALS SCHEMATIC Compilant Compatible VES NO CONS. TERMINALS Compilant Compatible OS203011MA2QP1 (YES) NO CONS. TERMINALS	PART NUMBER ROHS Compliant Compatible OS203011MA2QP1 (Non-specified) CONN. TERMINALS SCHEMATIC POS.1 ROHS Compatible NO ON 1-2, 5-6 SC 2 3 4	PART NUMBER ROHS Compliant Compatible OS203011MA2QP1 (Non-specified) CONN. TERMINALS SCHEMATIC POS.1 POS.2 ROHS Compatible ON ON ON ON ON CON CON CON CON

CONTACT RATING: 0.1A @ 12 VDC




Dimensions are shown: Inch (mm) Specifications and dimensions subject to change



OS Series Miniature Slide Switches

			SWITCH FUNCTION		
			POS.1	POS.2	
PART NUMBER	RoHS Compliant	RoHS Compatible	┡	_	
OS202011MA0QN1 (Non-shorting)	YES	NO	ON	ON	
OS202011MA0QS1 (Shorting)	YES	NO	ON	ON	
CONN. TERMINALS			1-2, 4-5	2-3, 5-6	
SCHEMATIC	999				
4 \$ 6					
CONTACT RATING: 0.1A @ 12 VDC					



Actuator shown in pos. 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Switches:

OS203013MT7QN	1 OS102011MA1QN	1C OS102011MS2Q	N1C OS103011MA7	QP1C OS103011MS8QP1
OS202011MA0QN1	OS202011MS2QS1	OS102011MA1QN1	OS102011MS2QN1	OS103012MU1QP1
OS203011MV9QN1	OS203012MU5QP1	OS203013MT8QN1	OS203013MT6QN1	OS103011MA7QP1
OS203011MS1QP1	OS103012MU2QP1	OS202011MS2QN1	OS202011MV4QN1	OS202013MT5QN1
OS202013MT8QN1	OS203011MA2QP1	OS202011MA0QS1	OS102011MS2QS1	OS203011MV9QS1