

MN3209

256-STAGE LOW VOLTAGE OPERATION LOW NOISE BBD

General description


The MN3209 is a 256-stage low voltage operation ($V_{DD} = 5V$) low noise BBD that provides a signal delay of up to 12.8ms and is particularly suitable as a device for generation of chorus and vibrato effects of audio equipments in low voltage operation portable stereo, radio cassette recorder and electronic musical instruments, etc.

Features


- Variable delay of audio signal: 0.64 ~ 12.8ms.
- Wide supply voltage: 4 ~ 10V.
- No insertion loss: $L_i = 0dB$ typ.
- Wide dynamic range: $S/N = 80dB$ typ.
- Low distortion: $THD = 0.4\%$ typ. ($V_i = 0.25V_{rms}$).
- Clock frequency range: 10KHz ~ 100KHz.
- N-channel silicon gate process.
- 8-lead dual-in-line plastic package.

Applications

- Sound and echo effects of audio equipment such as radio cassette recorder, car radio, portable radio, portable stereo, echo microphone and pre-taped musical accompaniments, etc.
- Sound effect in electronic musical instruments.
- Variable or fixed delay of analog signals.



Block Diagram



Quick Reference Data

Item	Symbol	Value	Unit
Supply Voltage	V_{DD}, V_{GG}	$+5, \frac{1}{18} V_{DD}$	V
Signal Delay Time	t_D	0.64~12.8	ms
Total Harmonic Distortion	THD	0.4	%
Signal to Noise Ratio	S/N	80	dB

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Rating	Unit
Terminal Voltage	$V_{DD}, V_{GG}, V_{CP}, V_i$	-0.3~+11	V
Output Voltage	V_o	-0.3~+11	V
Operating Temperature	T_{opr}	-20~+60	°C
Storage Temperature	T_{stg}	-55~+125	°C


Operating Condition (Ta = 25°C)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Drain Supply Voltage	V_{DD}		+4	+5	+10	V
Gate Supply Voltage	V_{GG}			$\frac{14}{15} V_{DD}$		V
Clock Voltage "H" Level	V_{CPH}			V_{DD}		V
Clock Voltage "L" Level	V_{CPL}		0		+1	V
Clock Frequency	f_{CP}		10		200	kHz
Clock Pulse Width *1	t_{CPW}				0.5T *2	
Clock Rise Time *1	t_{CPR}				500	ns
Clock Fall Time *1	t_{CPF}				500	ns
Clock Input Capacitance	C_{CP}				200	pF
Clock Cross Point *1	V_X		0		0.3V _{CPH}	V

Electrical Characteristics (Ta = 25°C, $V_{DD} = V_{CPH} = 5V$, $V_{CPL} = 0V$, $V_{GG} = 14/15 V$, $R_L = 100k\Omega$)


Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Signal Delay Time	t_D		0.64		12.8	ms
Input Signal Frequency	f_i	$f_{CP} = 40kHz$, Output -3dB down	12			kHz
Input Signal Swing	V_i	THD=2.5%	0.5			Vrms
Insertion Loss	L_i	$f_{CP}=40kHz$, $f_i=1kHz$	-4	0	4	dB
Total Harmonic Distortion	THD	$f_{CP}=40kHz$, $f_i=1kHz$, $V_i=0.25V_{rms}$		0.4	2.5	%
Noise Voltage	V_{no}	$f_{CP} = 100kHz$ Weighted by "A" curve			0.12	mVrms
Signal to Noise Ratio	S/N			80		dB

*1 Clock Pulse Waveforms




*2 $T = 1/f_{CP}$ (Clock Period)










Terminal Assignments






Circuit Diagram



■ Typical Electrical Characteristic Curves





Supply Voltage Characteristics

