

Uncertainty measurements for the reliable classification of mammograms

Paper @ MICCAI 2019

Mickael Tardy ^{1,2} Bruno Scheffer, ³ Diana Mateus, ¹


May 4, 2020

¹Ecole Centrale de Nantes ²Hera-MI, SAS ²Institut de cancérologie de l'Ouest, Nantes

Mickael Tardy

- Ph.D. at Ecole Centrale de Nantes
- Chief Researcher at Hera-MI
- IT Engineer in everyday life
- <https://www.linkedin.com/in/mickael-tardy-54723235/>

Deep learning applied on breast imaging (i.e. mammography)




Deep learning applied on breast imaging (i.e. mammography)

- **Imaging classification (e.g malignant vs. benign)**
- Imaging segmentation (e.g. find pixels from malignant region)
- Object detection (e.g. find coordinates of findings: masses, calcifications, etc.)


Problem

Problem




- The prediction of a model is not always correct
- Safety measures are needed to prevent from wrong decision
- **How to identify, if the deep learning model is wrong?**

Solution highlights




Solution highlights: Latent space

Easy case: Known data (Green-ish): mammography vs.
Unknown data (Blue-ish): natural images




Solution highlights: Latent space

Less obvious: Known data (Green-ish) vs Unknown data (Blue-ish), both are mammographies




Solution



Results

Navigation in measurements space: identifying erroneous data samples in known data (ID) and unknown data (OOD)



- **Improved reliability** of a classifier in a few steps, available **out-of-the box** in any classifier in **a single shot**
- Ability to **identify** both, **uncertain inliers** and unknown **outliers** thanks to **combined threshold**.
- Unlike the state-of-the-art, our method may be used **without retraining** nor **architecture changes**

- Q&A