

ML Week

0x05 K-Means

Jeff Abrahamson

2–5 novembre 2015

Cost function

$$\text{cost} = \sum_i \sum_j |x_j - \mu_i|$$

Silhouette coefficient

Points $d = \{d_1, \dots, d_n\}$

Clusters $K = \{k_1, \dots, k_k\}$.

Cluster k_{d_i} is the cluster of d_i .

Silhouette coefficient

Points $d = \{d_1, \dots, d_n\}$

Clusters $K = \{k_1, \dots, k_k\}$.

Cluster k_{d_i} is the cluster of d_i .

Let a_i be the average dissimilarity of d_i to all points in its cluster.

Let b_i be the least average dissimilarity of d_i to any cluster other than k_{d_i}

Silhouette coefficient

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

Silhouette coefficient

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

$$s_i = \begin{cases} 1 - a_i/b_i & \text{if } a_i < b_i \\ 0 & \text{if } a_i = b_i \\ b_i/a_i - 1 & \text{if } a_i > b_i \end{cases}$$

Silhouette coefficient

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

$$s_i = \begin{cases} 1 - a_i/b_i & \text{if } a_i < b_i \\ 0 & \text{if } a_i = b_i \\ b_i/a_i - 1 & \text{if } a_i > b_i \end{cases}$$

So $s_i \in [-1, 1]$

Silhouette coefficient

s_i near 1 $\iff d_i$ well clustered

s_i near 0 $\iff d_i$ on the border between two clusters

s_i near -1 $\iff d_i$ well clustered

Silhouette coefficient

Consider \overline{s}_i over $i \in k_j$ for cluster k_j

Silhouette coefficient

Consider \overline{s}_j

Questions?

`purple.com/talk-feedback`