

CMPE 152: Compiler Design

September 26 Class Meeting


Department of Computer Engineering
San Jose State University




Fall 2017
Instructor: Ron Mak
www.cs.sjsu.edu/~mak



Type Definition Structures




Type Definition Structures, *cont'd*




When it is **parsing declarations**, the parser builds **type specification structures**.

When it is parsing **executable statements**, the parser builds **parse trees**.



Unnamed type

Type Definition Structures, *cont'd*



TypeDefinitionsParser.parse()


TYPE

```
e = (alpha, beta, gamma); — TypeDefinitionParser::parse()
sr = alpha..beta; — TypeSpecificationParser::parse()
ar = ARRAY [1..10] OF sr;
rec = RECORD
    x, y : integer
END;
```

- Loop to parse each type definition.
 - Parse the type identifier and the = sign.
 - Call the `parse()` method of `TypeSpecificationParser`.
 - Parse the type specification and return a `TypeSpec` object.
 - Cross-link the `SymTabEntry` object of the type identifier with the `TypeSpec` object.

TypeSpecificationParser.parse()


type specification



- Parse an array type.
 - If there is an **ARRAY** reserved word.
 - Call the **parse()** method of **ArrayTypeParser**
- Parse a record type.
 - If there is a **RECORD** reserved word.
 - Call the **parse()** method of **RecordTypeParser**
- Parse a simple type.
 - In all other cases.
 - Call the **parse()** method of **SimpleTypeParser**

SimpleTypeParser.parse()

simple type




□ Method **parse()** parses:


- A previously-defined type identifier.
 - Including **integer**, **real**, etc.
- An enumeration type specification.
 - Call the **parse()** method of **EnumerationTypeParser**.
- A subrange type specification.
 - Call the **parse()** method of **SubrangeTypeParser**.

Pascal Subrange Type

subrange type




`sr = alpha..beta`



SubrangeTypeParser.parse()

- ❑ Call `TypeFactory::create_type(SUBRANGE)` to create a new subrange type specification.
- ❑ Parse the minimum constant value.
 - Call `ConstantDefinitionsParser::parse_constant()`
- ❑ Get and check the data type of the minimum constant value:
 - Call `ConstantDefinitionsParser::get_constant_type()`
 - Call `check_value_type()`
 - ❑ The type must be integer, character, or an enumeration.
- ❑ Consume the `..` token.


sr = alpha..beta



typeSpec
identifier



SUBRANGE_BASE_TYPE




SubrangeTypeParser.parse()

- ❑ Parse the maximum constant value.
- ❑ Check that both minimum and maximum values have the same data type.
- ❑ Check that the minimum value \leq maximum value.
- ❑ Set attributes of the subrange type specification.

- SUBRANGE_BASE_TYPE
- SUBRANGE_MIN_VALUE
- SUBRANGE_MAX_VALUE


sr = alpha..beta



typeSpec

identifier


SUBRANGE_BASE_TYPE



Parsing a Subrange Type

TYPE

```
sr = 1..10;  
enum = (alpha, beta, gamma);  
ar = ARRAY [sr, enum] OF integer;  
rec = RECORD  
    x, y : real  
END;
```




□ Pascal


- ➔ PascalParserTD::parse()
- ➔ BlockParser::parse()
- ➔ DeclarationsParser::parse()
- ➔ TypeDefinitionsParser::parse()
 - ➔ TypeSpecificationParser::parse()
 - ➔ SimpleTypeParser::parse()
 - ➔ SubrangeTypeParser::parse()

Pascal Enumeration Type

enumeration type




`e = (alpha, beta, gamma)`



EnumerationTypeParser.parse()


e = (alpha, beta, gamma)



- Call **TypeFactory::create_type(ENUMERATION)** to create a new enumeration type specification.

EnumerationTypeParser.parse() cont'd


e = (alpha, beta, gamma)



- Loop to parse each enumeration identifier.
 - Call `parse_enumeration_identifier()`
 - Set the definition of the identifier to `ENUMERATION_CONSTANT`.
 - Set the `typeSpec` field of the identifier to the enumeration type specification.
 - Set the `CONSTANT_VALUE` of the identifier to the next integer value (starting with 0).
 - Build a `vector<SymTabEntry *>` of symbol table entries for the enumeration identifiers.

EnumerationTypeParser.parse() *cont'd*

e = (alpha, beta, gamma)




- Set the **ENUMERATION_CONSTANTS** attribute of the enumeration type specification to the array list.

Parsing an Enumeration Type

TYPE


```
sr = 1..10;  
enum = (alpha, beta, gamma);  
ar = ARRAY [sr, enum] OF integer;  
rec = RECORD  
    x, y : real  
END;
```




- **TypeDefinitionsParser::parse()**
 - ➔ **TypeSpecificationParser::parse()**
 - ➔ **SimpleTypeParser::parse()**
 - ➔ **EnumerationTypeParser::parse()**
 - ➔ **parse_enumeration_identifier()**

Pascal Record Type


record type




field declaration



variable or field declaration




rec = RECORD x,y : integer END



RecordTypeParser.parse()


- ❑ Call **TypeFactory::create_type(RECORD)** to create a new record type specification.
- ❑ Create and push a new symbol table onto the symbol table stack.
- Set the **RECORD_SYMTAB** attribute of the record type specification to the new symbol table.



RecordTypeParser.parse() cont'd

- ❑ Call **VariableDeclarationsParser::parse()** to parse the field declarations.
 - Set each field's definition to **FIELD**.
 - Enter each field into the current symbol table (the one just pushed onto the top of the stack).
- ❑ Pop the record type's symbol table off the symbol table stack.


After the record type's symbol table has been popped off the symbol table stack, it's still referenced by the **RECORD_SYMTAB** attribute.



Parsing a Record Type

TYPE



```
sr = 1..10;  
enum = (alpha, beta, gamma);  
ar = ARRAY [sr, enum] OF integer;  
rec = RECORD  
    x, y : real  
END;
```



- **TypeDefinitionsParser::parse()**
 - ➔ **TypeSpecificationParser::parse()**
 - ➔ **RecordTypeParser::parse()**
 - ➔ **VariableDeclarationsParser::parse()**

Pascal Array Type

array type



Pascal Multidimensional Array

- These definitions are all equivalent:

```
dim3 = ARRAY [1..3, 'a'..'z', boolean] OF real;
```

```
dim3 = ARRAY [1..3] OF ARRAY ['a'..'z']  
      OF ARRAY [boolean] OF real;
```

```
dim3 = ARRAY [1..3, 'a'..'z'] OF ARRAY [boolean] OF real;
```

```
dim3 = ARRAY [1..3] OF ARRAY ['a'..'z', boolean] OF real;
```


- Therefore, they must all generate
the **same type specification structure**.

Pascal Multidimensional Array

```
dim3 = ARRAY [1..3, 'a'..'z', boolean] OF real;
dim3 = ARRAY [1..3] OF ARRAY ['a'..'z'] OF ARRAY [boolean] OF real;
```

The **ARRAY_ELEMENT_TYPE** references form the **backbone** of this structure (a linked list).

The first two element types are **arrays**, and the third element type is **real** scalar.



ArrayTypeParser.parse()

- Call `TypeFactory::create_type(ARRAY)` to create a new array type specification.

ArrayTypeParser.parse()

- Call `parse_index_type_list()` to parse the list of index types.
- Set local variable `element_type` to the new array type specification.
- Loop to call `parse_index_type()` to parse each index type.
 - Call `simpleTypeParser::parse()` to parse the index type.
 - Set the attributes for a subrange or enumeration index type specification.
 - Set the `ARRAY_ELEMENT_COUNT` attribute for the current array type spec.

ArrayTypeParser.parse()


- Call `parse_index_type_list()` to parse the list of index types (*cont'd*).
 - For each index type in the list after the first:
 - Call `TypeFactory::create_type(ARRAY)` to create the next `element_type` value.
 - Set the `ARRAY_ELEMENT_TYPE` attribute of the previous `element_type` value to link to the new `element_type` value.
- Call `parse_element_type()` to parse the final element type.
 - Link the previous element type to the final element type.

These
`element_type`
references
create the
backbone.

Parsing an Array Type

TYPE

```
sr = 1..10;  
enum = (alpha, beta, gamma);  
ar = ARRAY [sr, enum] OF integer;  
rec = RECORD  
    x, y : real  
END;
```



- **TypeDefinitionsParser::parse()**
 - ➔ **TypeSpecificationParser::parse()**
 - ➔ **ArrayTypeParser::parse()**
 - ➔ **parse_index_type_list()**
 - ➔ **parse_index_type()**
 - ➔ **parse_element_type()**