
PROJECT: MOBILE COMP. PHOTOGRAPHY // REF: CH.13



Building the HDR Engine

A Deep Dive into Chapter 13: HDR Implementation Strategies & Pipeline Architecture


NotebookLM

Context

The Core Challenge: Dynamic Range Gap


The real world contains luminance ranges that far exceed the "Full Well Capacity" (electron bucket size) of mobile sensors. A single exposure cannot capture both the sun and the shadows.

The Reality: High contrast scenes > 100,000:1 ratio.



The Symptom: Sensor saturation (Clipping).

The Strategy: Multi-Frame Compositing (The Bucket Method).



Visual Diagram




Fig. 1: Dynamic Range Mismatch
Scale: Not to Scale


PROJECT: COMPOSITICNAL PHOTOGRAPHY		
DGC NO: 2401	REV: A	DATE: 2024-65-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Headline

System Architecture: The Processing Pipeline

From RAW burst to final display.



ARCHITECTURE REF: SECTIONS 13.3 - 13.4

	PROJECT: COMPOSITICNAL PHGTOSRAPHY		
	DOC ND: 2401	REV: A	DATE: 2024-65-22
	AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Headline

Pipeline Step 1: Multi-Frame Exposure Capture

The foundation of HDR is 'Exposure Bracketing'. We intentionally capture the scene at different shutter speeds to maximize data collection across the luminance spectrum.

SHORT EXPOSURE




Captures Highlights.
Prevents White Clipping.



Histogram A: Left (Blacks)

NORMAL EXPOSURE




Mid-tone Reference.




Histogram B: Center (Mid-tones)

LONG EXPOSURE



Captures Shadows.
Reduces Noise.



Histogram C: Right (Whites)

Total Data Set

ENGINEERING BLUEPRINT

	PROJECT: COMPOSITIONAL PHOTOGRAPHY	
DOC NO. 2401	REV. A	DATE 2024-05-22
	AUTHOR: TECHNICAL VISUALIZATION UNIT	

NotebookLM

Headline

Pipeline Step 2: Image Alignment


From RAW burst to final display.

The Obstacle: Camera shake and subject motion create misalignments between frames.

The Consequence: ‘Ghosting’ artifacts—double images appearing in the final merge.

The Engineering Fix: Algorithmic registration aligns features across all exposures before merging.

BEFORE & AFTER: IMAGE REGISTRATION




ENGINEERING BLUEPRINT

	PROJECT: COMPOSITIONAL PHOTOGRAPHY	
	DOC NO. 2401	REV. A	DATE 2024-05-22
	AUTHOR: TECHNICAL VISUALIZATION UNIT	

NotebookLM

Pipeline Step 3: Weight Computation

Determining Pixel Quality Programmatically



Logic Gate Criteria:

1. **Saturation:** Discard values at 0 (black) or 255 (white).
2. **Contrast:** Prioritize regions with high variance (detail).
3. **Well-Exposedness:** Favor mean intensity values (Gaussian curve).


ENGINEERING BLUEPRINT

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC NO. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Pipeline Step 4: HDR Fusion

The mathematical merger of aligned frames and computed weights creates the Radiance Map.



OUTPUT: THE RADIANCE MAP

Bit Depth: 32-bit Floating Point
Dynamic Range: Infinite (Theoretical)
Visual State: Linear (Appears dark/flat on standard monitors)


ENGINEERING BLUEPRINT

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC ND. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Pipeline Step 5: Tone Mapping

Fitting the Ocean into a Cup



- **The Problem:** HDR data (32-bit) exceeds the display capability of standard screens (8-bit).
- **The Solution:** Non-linear compression. We compress the global dynamic range while preserving local contrast details.
- **Result:** A natural-looking image that simulates human perception.

ENGINEERING BLUEPRINT

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC NO. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Implementation: The Code Structure

```
class HDR_Fusion_System:
    def __init__(self, image_paths):
        self.images = load_images(image_paths)

    def align_images(self):
        # MTB algorithm for registration
        pass

    def compute_weights(self):
        # Evaluate contrast, saturation, exposure
        pass

    def merge_exposures(self):
        # Create 32-bit radiance map
        pass

    def tone_map(self, radiance_map, gamma=2.2):
        # Drago or Reinhard operator
        pass
```

Core Logic: The implementation encapsulates the 5-step pipeline into a modular class structure, allowing for swappable algorithms (e.g., changing the the alignment method or tone mapper).

ENGINEERING BLUEPRINT

PROJECT: CONPOSITIONAL PHOTOGRAPHY

DOC NO. 24D1 | REV. A | DATE 2024-05-22


AUTHOR: TECHNICAL VISUALIZATION UNIT

NotebookLM

ENGINEERING BLUEPRINT

Usage: Running the System

```
$ python hdr_implementation.py --input ./my_images --output ./result.jpg
```



- ☑ **Prerequisites:** Python 3.x, OpenCV, NumPy.
- ☑ **Input:** Directory of bracketed JPEG/RAW images.
- ☑ **Execution:** Single CLI command.

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC NO. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Advanced Configuration


Fine-tuning the Aesthetic

Control Modules

Tone Map Operator

- ✓ [Drago]
- ✓ [Durand]
- [Reinhard]

Controls how contrast is compressed. Drago preserves naturalness; Reinhard maximizes local detail.




Control Modules

Gamma Correction

2.2

Adjusts luminance curve for display compliance.



Control Modules

Saturation Boost

+1.5

Compensates for color washout during tone mapping.



ENGINEERING BLUEPRINT

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC NO. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

ENGINEERING BLUEPRINT

Future Enhancements: The AI Horizon


Moving from deterministic algorithms to learned representations.

Current State



Fixed Algorithms (MTB Alignment, Reinhard Tone Map).

Future State



Deep Learning (CNNs).

Deep Alignment:
CNNs handle complex non-rigid motion (de-ghosting).

Neural Tone Mapping:
Learning aesthetic preferences rather than mathematical compression.

Mobile Optimization:
Porting logic to DSP/NPU for real-time <10ms execution.

ENGINEERING BLUEPRINT

PROJECT: COMPOSITIONAL PHOTOGRAPHY		
DOC NO. 24D1	REV. A	DATE 2024-05-22
AUTHOR: TECHNICAL VISUALIZATION UNIT		

NotebookLM

Summary & Key Takeaways

- **The Problem:** Sensor hardware cannot match real-world dynamic range.
- **The Solution**: Software-based multi-frame fusion.
- **The Pipeline**: Capture -> Align -> Weight -> Fuse -> Tone Map.
- **The Implementation**: Python-based modular design using OpenCV/NumPy.
- **The Future:** AI-driven alignment and real-time NPU processing.

ENGINEERING BLUEPRINT

SLD98RD		
PROJECT BLOCK		
TLVE		
JetBrains Mono	T9*	DATE

NotebookLM